

Dominick Cole

HUMN-391-02

Dr. Tony Michel

15 June 2026

Literature Review on Morphing Wing Technology

Aircraft control surfaces have not changed much in nearly a hundred years. Modern commercial jets still use the same basic concept as early 20th-century designs: hinged flaps, slats, and ailerons bolted onto a rigid wing structure. These surfaces do their job, but they come with aerodynamic costs and limited use cases. The gaps between hinged surfaces and their external housings create drag, and there is very limited ability to fine-tune the wing's shape beyond a few discrete positions.

Morphing wing technology takes a different approach entirely. Instead of hinged panels, the wing skin itself deforms continuously, allowing the aircraft to dial in exactly the shape it needs for any given flight condition. Researchers have been studying this idea for decades, and the aerodynamic case for it is strong. Wind tunnel testing and computational models consistently show improvements in lift-to-drag ratio and reductions in drag. Despite that, morphing wings have never made it onto a commercial aircraft because the technology keeps running into the same barriers.

This review examines the engineering issues standing between morphing-wing research and commercial implementation. Three problem areas are examined: the materials challenge of building a wing skin that can deform without failing structurally; the challenge of fitting all the actuation hardware inside the wing with no external linkages; and the almost entirely unaddressed problem of storing fuel inside a wing that changes shape. The review concludes by connecting these problems to the regulatory certification barrier, which compounds all three.

Six peer-reviewed sources were reviewed and organized into three thematic categories. The first theme covers structural skin materials. The second covers embedded mechanical

actuation. The third addresses fuel storage inside a morphing wing structure. Several sources touch on more than one theme, and those connections are noted where relevant. The sources range from foundational reviews published in the early 2010s to more recent assessments of the field's current state.

The wing skin is where the morphing-wing concept encounters its first and most basic problem. Any skin used on a morphing wing has to do two things that directly work against each other. It has to be flexible enough to deform when the internal actuators push on it, yet stiff enough to hold its shape under aerodynamic loads without buckling or fatigue. No standard aerospace material does both at once.

Thill, Etches, Bond, Potter, and Weaver (2008) published one of the most widely cited reviews of this problem in *The Aeronautical Journal*. They examined a wide range of morphing skin candidates and found that anisotropic composite structures showed the greatest promise. The key idea is that composites can be designed with different stiffness properties in different directions, so a skin can be made flexible in the chordwise direction while staying stiff enough in the spanwise direction to carry flight loads. Corrugated composite panels emerged as a strong candidate because of this property. The problem is that exposed corrugations create aerodynamic issues, and adding a smooth outer covering to address them adds weight and manufacturing complexity. Thill et al. concluded that no single material had fully solved the tradeoff.

Sofla, Meguid, Tan, and Yeo (2010) examined the same issue from a smart-materials perspective in *Materials and Design*. Their review covered SMA, piezoelectric, and shape-memory polymer approaches and found that flexible smart material skins adequate for small-scale prototype testing do not hold up under the loading conditions of a full-size aircraft. The core dilemma they identified is that stiffer skins require heavier actuation hardware to deform them, while more flexible skins raise concerns about structural performance and durability. Neither direction produces a straightforward solution at a commercial scale.

Majid and Jo (2021) focused specifically on camber morphing in the *International Journal of Aerospace Engineering*. Camber control is probably the most aerodynamically useful morphing mode, so it gets a lot of research attention. Their finding was that the aerodynamic benefits are well established, but the structure needed to deliver them in a real aircraft remains an open problem. Rigid ribs handle flight loads well but limit how much the wing can actually morph. Compliant ribs allow greater shape change but sacrifice too much structural performance. Majid and Jo pointed toward topology-optimized, multi-material internal structures as the most likely path forward. However, they noted that manufacturing those structures at the scale and cost requirements of commercial aerospace is beyond the capabilities of current production lines.

Even if the right skin material existed, the actuation system still has to work inside the wing with no external hardware. On a conventional aircraft, hydraulic actuators are located below the wing and connect to the control surfaces via physical linkages. On a morphing wing, none of that infrastructure exists. Every actuator, sensor, wire, and mechanism must fit within the wing structure and operate reliably across the full range of flight conditions.

Barbarino, Bilgen, Ajaj, Friswell, and Inman (2011) reviewed the full landscape of morphing actuation technologies in the *Journal of Intelligent Material Systems and Structures*. They grouped approaches into three categories: smart material actuators such as shape memory alloys (SMA) and piezoelectrics, scaled-down conventional hydraulic or servo systems, and compliant structures that use geometry to amplify small actuator movements. Smart materials came out looking most practical from a weight and integration standpoint, but each type has real limitations. Piezoelectric actuators are strong but only move a tiny amount, which works for fine control but not for the large shape changes needed in camber morphing. Shape memory alloys can produce much larger strains, but they are thermally activated. The wing heats and cools the material, causing it to contract or relax slowly. For flight control, slow actuation would be an issue.

Sun, Guan, Liu, and Leng (2016) provided a broader state-of-the-art review of smart material actuation in the *Journal of Intelligent Material Systems and Structures*, covering SMAs, piezoelectrics, and shape memory polymers across a range of morphing applications. Their review found that smart materials offer advantages over conventional hydraulic and mechanical systems in terms of weight and integration, but that each material type carries tradeoffs between actuation speed, stroke, force output, and fatigue life that have not been resolved for commercial-scale applications. They also noted that the weight benefit of smart actuators holds only if the morphing system does not require excessive redundancy to meet safety standards, a real tension when commercial certification enters the picture.

Sofla et al. (2010) examined SMA wire configurations in which two sets of wires work in opposition to produce and maintain a deformed shape. This approach is lighter than conventional actuators, and the mechanics are relatively straightforward. The issue they identified is scale. In prototype testing, SMA wire setups work fine. On a full commercial wing under real aerodynamic loads, the forces involved are orders of magnitude higher. Meeting those force requirements with SMA wires means adding a lot more material. At some point, the weight penalty starts canceling out the aerodynamic efficiency the morphing wing is supposed to provide.

Ameduri and Concilio (2020), writing in the *Proceedings of the Institution of Mechanical Engineers*, gave the most up-to-date assessment of where actuation technology actually stands. They concluded that nothing has been validated at a commercial scale. The open issues they flagged include actuator fatigue over tens of thousands of flight cycles, thermal management for SMA systems that deal with temperature swings between ground operations and cruise altitude, and the absence of redundancy in embedded smart material systems. That last point is especially relevant for certification, since aviation regulators require redundant systems for anything involved in flight control. They also noted that actuation and skin problems cannot

really be separated, since the force an actuator needs to produce is directly tied to the skin's stiffness. Fixing one without the other does not get us anywhere useful.

Majid and Jo (2021) added the control system dimension to this discussion. A morphing wing does not just move to one shape and stay there. It has to respond continuously to changing flight conditions, which means closed-loop feedback. That requires sensors embedded in the wing that can accurately measure its actual shape in real time. Getting sensors to work reliably inside a structure that is actively deforming, without those sensors interfering with the structure or degrading under repeated strain cycles, is itself an unsolved problem.

Most of the fuel on a commercial transport aircraft lives inside the wings. The wing box is essentially a sealed structural tank, with fuel stored in bays formed by the spars, ribs, and skin. It is an efficient arrangement. Putting the fuel in the wings keeps the mass close to the aerodynamic center and frees up fuselage space. For a morphing wing, this creates an obvious problem in that the wing structure must hold pressure and stay sealed while continuously flexing and changing shape. Conventional wet-wing fuel tank designs are built around a rigid structure, so there is no existing solution to draw from.

Ameduri and Concilio (2020) noted that fuel storage is one of the most neglected topics in the morphing wing literature. Most research either assumes a fuel-free wing, which is fine for small UAV studies but irrelevant to commercial aviation, or simply pushes the fuel problem to a later phase of development. Barbarino et al. (2011) made the same observation, pointing out that laboratory-scale morphing demonstrations typically use solid or hollow composite wing boxes with no fuel volume. The jump from that to a real commercial wing with thousands of gallons of jet fuel is enormous and largely unexplored in the literature.

Sofla et al. (2010) looked at the internal volume competition between actuation hardware and fuel storage. A conventional wing structure is designed to maximize the sealed volume available for fuel. An embedded actuation system takes up space inside that same structure. Wiring, SMA wire bundles or piezoelectric stacks, thermal management hardware,

and sensors all reduce the net fuel volume. If the fuel capacity drops enough, the aircraft's range suffers, which directly undercuts the efficiency argument for morphing wings in the first place.

The sealing problem may be the hardest part. Standard integral fuel tanks use flexible sealants applied at structural joints to keep the fuel in. Those joints move a little under normal flight loads, and the sealants are designed to handle that. A morphing structure moves a lot more, and moves constantly. No fuel tank sealant currently used in aerospace has been qualified for a structure that undergoes continuous large-amplitude deformation over thousands of flight hours. The sealant would need to stay bonded, stay fuel-resistant, and stay elastic across the temperature range of flight without cracking or peeling. Majid and Jo (2021) identified this as a case where the field needs new primary research, not just engineering refinement of what already exists.

The literature reviewed here points to a consistent conclusion. The aerodynamic case for morphing wings is solid and well-supported by decades of research. Wind tunnel tests and computational studies consistently show the efficiency advantages. The problem is everything that comes after the aerodynamics.

The skin materials problem has gotten the most attention, and corrugated composites and anisotropic laminates have shown real promise, but nothing has cleared the bar of simultaneously handling flexibility, structural load, and long-term fatigue at commercial scale. The actuation problem is tied directly to the skin problem, since stiffer skins demand stronger actuators, and stronger embedded actuators add weight. Smart materials are the most feasible path, but SMAs are slow and piezoelectrics have limited stroke, and neither has been tested at the scale and cycle count that a commercial aircraft would require. Fuel storage has barely been studied in the context of morphing wings at all, and the sealing challenge in particular represents a gap in fundamental materials science rather than just a design question.

All three problems eventually lead to the same final barrier: regulatory certification. Ameduri and Concilio (2020) described airworthiness regulations as a recurring showstopper

for morphing wing development. The FAA's certification framework for transport aircraft is built around a rigid primary structure with discrete, inspectable control surfaces. A wing whose primary structure deforms continuously in service does not fit that framework. A new certification methodology would be needed, and that cannot even be written until there is a real system to certify. The path to commercial morphing wings probably does not run through a single breakthrough. It runs through solving the structural, actuation, and fuel problems well enough to build something that regulators can actually evaluate.

References

- Ameduri, S., & Concilio, A. (2020). Morphing wings review: Aims, challenges, and current open issues of a technology. *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*.
- Barbarino, S., Bilgen, O., Ajaj, R. M., Friswell, M. I., & Inman, D. J. (2011). A review of morphing aircraft. *Journal of Intelligent Material Systems and Structures*.
- Majid, T., & Jo, B. W. (2021). Status and challenges on design and implementation of camber morphing mechanisms. *International Journal of Aerospace Engineering*.
- Sofla, A. Y. N., Meguid, S. A., Tan, K. T., & Yeo, W. K. (2010). Shape morphing of aircraft wing: Status and challenges. *Materials and Design*.
- Sun, J., Guan, Q., Liu, Y., & Leng, J. (2016). Morphing aircraft based on smart materials and structures: A state-of-the-art review. *Journal of Intelligent Material Systems and Structures*.
- Thill, C., Etches, J., Bond, I., Potter, K., & Weaver, P. (2008). Morphing skins. *The Aeronautical Journal*.