
AbstractWarehouse
G : Graph
iterations : int
lotsPerRow : int
nRows : int
randomPositions : list
createGraph(nLots)
edgeListFromState(state)
init_problem(count)
plot(best_state)
solve(count, roulette, max_attempts, NN, V_r, pop_size)
solve_efoa(count, roulette, max_attempts, p, pop_size)
solve_ga(count, roulette, mutation_prob, max_attempts, pop_size)
solve_ifoa(count, roulette)
solve_mip(count)
solve_sa(count, roulette, schedule, max_attempts)
Rack
iterations
createGraph(nLots)
edgeListFromState(state)
init_problem(count, roulette)
plot(best_state, title, show)
Warehouse
iterations
mDist : list
paths : list
Block()
addTargetsToBlock(board)
createGraph(nLots)
edgeListFromState(state)
findShortestPath(nLots)
init_problem(count, roulette)
midpoint(count)
plot(best_state, title, both, show)
plotRoutes(route)
plot_problem(both)
sshape(count)
WarehouseOneDirection
G : DiGraph
iterations
mDist : list
createGraph(nLots)
edgeListFromState(state)
findShortestPath(nLots)
init_problem(count, roulette)
WarehouseWithAisles
aisles : list
Block()
createGraph(nLots)
EFOA
TR(idx1, idx2)
efoa(pop_size, max_attempts, max_iters, p, curve, random_state)
multiplicationOperator(flyB: np.array, problem, G, debug)
plot(flyA, flyB, A1, A2, A3)
reverseOperatorCoords(coords, G, debug)
reverseOperatorDists(dists)
ExactSolver
bruteforce()
mip()
FOA
crossover(fly, V_r, problem)
foa(smellFn, visionFn, pop_size, max_attempts, max_iters, curve, random_state, V_r, NN)
ifoa()
mutate()
s1(fly, NN)
v1(fly, V_r, problem)
v3(fly, V_r, problem)
FOAOpt
probs : ndarray
roulette : bool
random()
Solver
count : int
problemType
results : dict
heuristics()
plotStatistics(rows, x_axis, testCase, show)
simulate(fn, n, debug, name)
solve_for_fn(functions, n)
HyperParameterTuning
results : dict
objective(fn, args)
objective_efoa(args)
objective_foa(args)
objective_ga(args)
objective_sa(args)
tune(n, vec_pop_size, vec_V_r, vec_NN)
tune_efoa(n, vec_pop_size, vec_attempts, vec_p)
tune_ga(n, vec_pop_size, vec_attempts, vec_mutation_prob)
tune_random(alg, debug)
tune_sa(n, vec_attempts, vec_schedule)
TravellingSales
coords : NoneType
dist_list : list
distances : NoneType, list
is_coords : bool
path_lengths : dict
path_list : list
prob_type : str
evaluate(state)
get_path_length(node1, node2)
TravellingSalesDirected
dist_list
distances : NoneType
path_lengths : dict
path_list : list
evaluate(state)
get_path_length(node1, node2)