

Takagi - Framework for CoAP

Dominik Matoulek



Who I am?

- Ruby developer
- Edge computing enthusiast
- Builds sensor boxes

Everyone knows HTTP

- What about IoT?
 - Small devices does not have enough RAM.
 - Headers, parsing
-
- Solution? CoAP! (RFC 7252)

CoAP is totally different, right?

Method	CoAP	HTTP
GET	✓	✓
POST	✓	✓
PUT	✓	✓
DELETE	✓	✓
PATCH	Nope	✓
HEAD	Nope	✓

So I can make a REST?

CoAP	HTTP
2.01	201
4.00	400
4.04	404
5.00	500

How hard it can be?

```
CoapServer server = new CoapServer();
server.add(new CoapResource("hello") {
    public void handleGET(CoapExchange exchange) {
        exchange.respond("Hello world!");
    }
});
server.start();
```

It looks brilliant, but I like this

```
@RestController  
  
public class RestController {  
    @GetMapping(value = "/hello")  
    public Student getTestData() {  
        return "hello";  
    }  
}
```

What else?

Feature	CoAP libraries	“Web” Frameworks
Dynamic routing	DIY	✓
Modular	Just library, other DIY	✓ (usually)
Parameters	Somewhere	✓
Approach	Low-level	High-level

The result is Takagi

- Inspired by Sinatra (That's why Takagi)
- Written in Ruby
- What if CoAP is just HTTP?
- <https://github.com/domitea/takagi>



Little detour: Controllers in Sinatra

```
require 'sinatra'

class FrankApp < Sinatra::Base
  get '/frank-says' do
    'Put this in your pipe & smoke it!'
  end
end

FrankApp.run!
```

In Takagi

```
require 'takagi'

class SensorAPI < Takagi::Base
  get "/sensor/:id" do |params|
    puts params[:id].to_i
  end
end

SensorAPI.run!
```

So we have REST, what next?

- CoAP is not just HTTP
- CoAP is also MQTT
- Meet RFC 7641 - Observing Resources in the Constrained Application Protocol (CoAP)

Wait a minute...

	MQTT	CoAP (RFC 7641)
Subscribe	SUBSCRIBE topic	GET + Observe
Publish	PUBLISH topic	NOTIFY
QoS	defined	CON/NON

And Takagi?

```
reactor do
  observable "/sensors/temp" do # this endpoint can be observed in CoAP way
    { temp: 42.0 }
  end
  observe "coap://temp_server/temp" do |params| # you can also observe another CoAP endpoints
    puts params.inspect
  end
end
end
```

And how I can define...?

- Models? You can use Sequel
- Views? Well, it's CoAP, not HTTP!
- HTTP stuff? You can use... Sinatra!

Why Takagi?

- Human-friendly CoAP
 - Sinatra-like routing
 - MVC like structure (if you add models)
 - Runs where Ruby runs
 - REST and MQTT combo
 - Focus on sensors, not boilerplate
-
- Every Backend developer can do CoAP with Takagi

Questions?

Thank you for your attention