

[illegible][illegible]

The schematic diagram illustrates the power supply and signal connections for the LSM6DSV module (U6).

Power Supply Section:

- A 3V3 supply is connected to a network of capacitors: C21 (0.1uF), C22 (10uF TANT), C23 (0.1uF), and C24 (0.1nF).
- The 3V3 supply is also connected to the FB3 feedback pin of the module.
- The 3V3 supply is connected to the VDDIO pin of the module.
- The 3V3 supply is connected to the 3V3_AL supply pin of the module.

Signal Connections:

- SPI2_MISO (R29) is connected to pin 1 (SDO/SA0).
- SPI2_MOSI is connected to pin 14 (GDA).
- SPI2_SCK is connected to pin 13 (SCL).
- SPI2_CS_LSM is connected to pin 12 (CS).
- INT1 is connected to pin 4 (INT1_LSM).
- INT2 is connected to pin 9 (INT2_LSM).

Module Pinout:

- Pin 1: SDO/SA0
- Pin 2: SDX
- Pin 3: SCX
- Pin 4: INT1
- Pin 5: VDDIO
- Pin 6: GND
- Pin 7: VDD
- Pin 8: 3V3_AL
- Pin 9: INT2
- Pin 10: INT2_LSM
- Pin 11: GND
- Pin 12: CS
- Pin 13: SCL
- Pin 14: GDA