

J1 – System Bus

Pin	Signal	Description
1	GND	Ground
2	+5V	Main power supply
3	+3V3	Logic power supply
4	GND	Ground
5	I2C_SDA	Shared I ² C Data
6	I2C_SCL	Shared I ² C Clock
7	UART0_TX	Primary UART TX
8	UART0_RX	Primary UART RX
9	UART1_TX	Secondary UART TX
10	UART1_RX	Secondary UART RX
11	CAN_TX	FDCAN Controller TX
12	CAN_RX	FDCAN Controller RX
13	IRQ	Shared interrupt (open-drain recommended)
14	RESET	Global reset
15	WAKE	System wake-up
16	GND	Ground

J2 – General Purpose Expansion

Pin	Signal	Description
1	GND	Ground
2	GPIO_A	General-purpose I/O
3	GPIO_B	General-purpose I/O
4	GPIO_C	General-purpose I/O
5	GPIO_D	General-purpose I/O
6	GPIO_E	General-purpose I/O
7	GPIO_F	General-purpose I/O
8	GPIO_G	General-purpose I/O
9	GPIO_H	General-purpose I/O
10	GPIO_I	General-purpose I/O
11	GPIO_J	General-purpose I/O
12	GPIO_K	General-purpose I/O
13	ADC0	Analog input
14	ADC1	Analog input
15	PWM0	PWM output (or timer output)
16	GND	Ground