

Virtual Teammate — Marketing Site Developer Reference

Architecture, conventions, and internals of the `vtnew` marketing site. For content-level edits, see `marketing-site-guide.md`. For the staff portal, see the portal docs.

1. Stack & serving

- **Language:** PHP 8.2 (server-rendered, no framework).
- **Server:** Apache, with the repository as the document root.
- **No build step.** Edit a file, save, refresh. PHP renders the shared includes server-side.
- **External runtime dependencies (CDN/remote):**
 - Font Awesome 6.5.2 (icons).
 - HubSpot (chat widget, meetings embed, forms/CRM API).
 - Manrope is self-hosted (woff2 in the site), not loaded from Google Fonts.

Useful commands

Lint a single PHP file:

```
php -l includes/head.php
```

Full render to stdout (end-to-end smoke test):

```
php index.php > out.html
```

2. Project layout

```
.
├─ index.php                # homepage
├─ 404.php / 403.php / 500.php # error pages (route via includes/error-page.php)
├─ lead.php                 # form lead-capture endpoint (POST)
├─ track.php                # pageview beacon receiver
├─ vt-link.php              # public VT profile viewer (token-gated)
├─ talent-photo.php         # public talent photo server
├─ talent-media.php         # public talent media (photo/resume/video) by token
├─ installer.php            # forwards to portal/install.php
├─ llms.txt                 # plain-text company summary for LLM crawlers
├─ robots.txt / sitemap.xml # crawl directives
├─ .htaccess                # Apache: index, security, gzip/brotli, cache, redirects
├─ deploy.sh                # FTP deploy (sources .ftp.local)
├─ includes/                # shared PHP partials (direct access denied)
├─ css/style.css            # all styles
├─ js/main.js               # all behavior
├─ images/                  # logos, photos, client/press logos, pdf
├─ services/ business/ about/ careers/ case-studies/ contact/ guarantee/
├─ healthcare-landing/ dental-landing/ business-landing/
├─ terms/ privacy-policy/ virtual-teammates/
├─ portal/                  # staff portal (separate app – see portal docs)
└─ data/                    # runtime SQLite + media (web-blocked, not deployed)
```

3. Page composition pattern

A page sets SEO variables, includes the head and nav, writes its content inside `<main>`, then includes the footer:

```
<?php
$page_title      = 'About Virtual Teammate';
$page_description = '...';
$canonical       = 'https://virtualteammate.com/about/';
$is_homepage     = false;
$home_base       = '../';           // relative prefix from this page to site root
$breadcrumbs     = [
    ['name' => 'Home', 'url' => '/'],
    ['name' => 'About', 'url' => '/about/'],
];
include 'includes/head.php';        // (or '../includes/head.php' on inner pages)
include 'includes/nav.php';
?>

<main>
    <!-- page sections -->
</main>

<?php include 'includes/footer.php'; ?>
```

`includes/head.php` parameters

Variable	Type	Purpose
<code>\$page_title</code>	string	<code>&lt;title&gt;</code> and default OG title
<code>\$page_description</code>	string	meta description and default OG description
<code>\$canonical</code>	string	absolute canonical URL
<code>\$og_title</code> , <code>\$og_description</code>	string	social overrides (default to the page vars)
<code>\$is_homepage</code>	bool	when true, emits Organization + Service + FAQ + WebSite JSON-LD
<code>\$breadcrumbs</code>	array	<code>[['name'=&gt;..., 'url'=&gt;...], ...]</code> → BreadcrumbList JSON-LD on inner pages
<code>\$faqs</code>	array	<code>[['q'=&gt;..., 'a'=&gt;...], ...]</code> → FAQPage JSON-LD (ignored on the homepage)
<code>\$robots</code>	string	override the default robots directive (e.g. <code>'noindex,nofollow'</code>)
<code>\$body_class</code>	string	extra classes on <code>&lt;body&gt;</code>
<code>\$home_base</code>	string	relative path prefix to site root (<code>./</code> on homepage, <code>../..</code> on <code>/services/&lt;slug&gt;/</code>)

`head.php` also emits GA4 (production only), no-cache headers for HTML, and versioned CSS/JS URLs via `vt_asset_ver()` (see §6).

4. includes/ reference

File	Role
<code>head.php</code>	<code><head></code> : meta, JSON-LD schema, fonts, versioned CSS/JS, GA4. Parameters above.
<code>nav.php</code>	Sticky topbar + nav, Healthcare mega-menu (medical + dental), mobile hamburger.
<code>footer.php</code>	Footer grid, scroll-to-top button (<code>#scrollTop</code>), CTA modals include, <code>main.js</code> load. Honors <code>\$hide_footer</code> , <code>\$home_base</code> .
<code>cta-modals.php</code>	Hub that includes the modal set on non-homepage pages (guards against double-render).
<code>book-modal.php</code>	<code>#cta-book</code> — HubSpot Meetings scheduler modal.
<code>jumpstart-modal.php</code>	<code>#cta-strategy-call</code> — strategy-call modal (reuses the meetings loader).
<code>checklist-modal.php</code>	<code>#cta-buyers-checklist</code> — email-capture modal posting to <code>lead.php</code> .
<code>request-modal.php</code>	<code>#cta-request</code> — generic request modal; wires modal scroll-lock/ESC/autofocus.
<code>lead-form.php</code>	Reusable lead band. Two modes: <code>'book'</code> (modal link) or <code>'form'</code> (full form). Customizable via <code>\$lf_*</code> vars (title, sub, thanks, cta, placeholders, roles, source, form). Posts to <code>/lead.php</code> .
<code>force-ssl.php</code>	HTTPS-enforcement guard (included at the top of <code>head.php</code>). Toggled by <code>data/force_ssl.on</code> . Skips CLI requests; respects <code>X-Forwarded-Proto</code> / Cloudflare.
<code>cache.php</code>	Asset cache control: <code>vt_cache_state()</code> , <code>vt_asset_ver()</code> . See §6.
<code>hubspot-config.php</code>	Returns <code>hub_id</code> , <code>pipeline_id</code> , <code>forms</code> (intent→GUID), <code>form_fields</code> (intent→allowed fields). Used by <code>lead.php</code> and modals.
<code>hubspot-chat.php</code>	HubSpot live-chat embed (loaded by footer).
<code>hubspot-loader.php</code>	HubSpot Meetings embed loader (used by scheduler modals).
<code>error-page.php</code>	Shared error template (reads <code>\$err_code</code> , <code>\$err_eyebrow</code> , <code>\$err_head</code> , <code>\$err_msg</code>).
<code>service-cta.php</code> , <code>cta-stages.php</code> , <code>vt-cards.php</code>	Service-page CTA sections, funnel-stage definitions, VA profile card component.

`includes/.htaccess` denies direct web access to the partials.

5. CSS architecture — `css/style.css`

Single stylesheet (~10k lines). Desktop rule first, then down-breakpoint overrides.

Design tokens (CSS custom properties at the top)

Reuse these instead of hard-coding hex/rgba:

```
--gold #dfa949    --gold-dk #b8882e    --gold-lt #f5e4b8
--violet #8582c3  --violet-dk #3919ba  --violet-deep #2a1290
--dark #1a1535    --body #3d3860      --white #ffffff
--glass-bg  rgba(255,255,255,.10)    --glass-bg2 rgba(255,255,255,.16)
--glass-border rgba(255,255,255,.28) --glass-border-strong rgba(255,255,255,.45)
--glass-blur blur(18px)              --glass-blur-sm blur(10px)
```

Manrope is self-hosted (variable 300–800, woff2). The page uses a dark violet→dark gradient background; `body` is `max-width:1980px; width:100%; margin:0 auto` with horizontal overflow clipped.

Class-prefix naming (scope per section)

`hero-`, `spec-` (specialties), `biz-` (*business*), `roi-` / `calc-` (*ROI + calculator*), `pstep-` / `proc-` (*process*), `test-` (testimonials), `hw-` (*how we work*), `prof-` (profiles), `faq-`, `cf-` (CTA form), `ft-` (*footer*), `mq-` / `marquee-` (*client marquee*), `news-` (press marquee), `world-` / `gLocal-` (world map), `hv-` (*hero visual collage*), `svc-` (service pages), `nav-*`, `scroll-top`. Buttons: `.btn-primary`, `.btn-glass`.

Responsive breakpoints

Two **down** breakpoints:

- `@media (max-width:1280px)` — tablet / small laptop (nav → hamburger, grids stack).
- `@media (max-width:768px)` — mobile.

Ultra-wide / high-res: at the very end of the file, a ladder of `@media (min-width:...)` tiers steps `body { zoom: ... }` from 1.11× up to a 2.6× cap (for displays up to ~6016×3384). Because the layout is in px, `zoom` is the single lever that scales layout, type, and spacing together while preserving tuned ratios. Content stays centered via `body{margin:0 auto}`; the html gradient fills any gutter past the cap.

Animation utilities

`.reveal` (fade-in + slide-up on scroll; stagger via `.d1` – `.d6`), keyframes `floatOrb`, `orbPulse`, `shimmer`, `pulseGlow`, `marqueeLeft`, `spinSlow`. All wrapped by `@media (prefers-reduced-motion: reduce)` which disables motion.

6. Asset versioning & caching — `includes/cache.php`

- `vt_cache_state()` reads `data/cache-state.php` (toggled from the portal's cache control).
- `vt_asset_ver()` returns `?v={filemtime}` when caching is **on** (stable, cache-friendly URLs

that bust only when the file changes), or a unique per-load token when caching is **off** (forces fresh fetches during active development).

`head.php` appends `vt_asset_ver()` to the CSS and JS URLs so a deploy invalidates the browser cache automatically.

7. JavaScript behavior — `js/main.js`

Single file (~1.4k lines), no framework. Behaviors:

1. **Nav / mega-menu** — `.nav-toggle` opens `#primaryNav`; `.nav-drop-trigger` accordion on mobile via `matchMedia('(max-width:1280px)')` (desktop dropdown is pure CSS hover). Closes on link follow, outside click, or breakpoint change.

1. **Scroll reveal** — `IntersectionObserver` on `.reveal` (threshold 0.12, rootMargin -8%) adds `.in`. Falls back to immediate reveal if unsupported; respects reduced-motion.

1. **Count-up** — `[data-count]` eases 0→target over ~1400ms (easeOutCubic); supports `data-decimals` and `data-suffix`. Hero stats replay periodically while visible.

1. **Client marquee** — track populated from `window.VT_MARQUEE` (filled server-side by a PHP glob of `images/clients/marquee/*`); the track is duplicated for seamless infinite scroll, paused on hover.

1. **Press marquee** — built from the hardcoded `press` array (name, `src` under `images/press/`, `href` to the release). Toned down by default, full color on hover.

1. **ROI calculator** — flat bi-weekly rates (VT full-time / part-time vs. US in-house full-time / part-time) as constants. Slider sets the count; buttons toggle the schedule. Recomputes annual / monthly / 3-year savings, savings %, per-VA savings, then tweens the numbers (token-cancelled to avoid overlap) and updates a donut gauge (stroke-dasharray) and a comparison bar chart.

1. **Scroll-to-top** — `#scrollTop` shows past 600px scroll, fades to 50% when idle, smooth-scrolls to top (respects reduced-motion).

CTA modals need no JS wiring — they open via anchor `href` + CSS `:target`; `data-cta-intent` attributes are retained for analytics only.

8. Lead capture — `lead.php`

Single POST endpoint behind every form on the site (~480 lines).

Flow:

1. **Method guard** — 405 unless POST.

2. **Honeypot** — if `vt_hp` (or legacy `company_site`) is filled, return `{"ok":true}` without

storing (bots think they succeeded).

1. **Field collection** — generic sweep of `$_POST` (skips control fields `vt_hp`, `company_site`, `_csrf`; truncates values to ~2000 chars).

1. **Field mapping** — name (`first_name` / `firstname` + `last_name` / `lastname` , or `name` / `full_name`), `email` (required, validated), phone, company (`company` / `practice` / `clinic` / `organization` /...), message (`message` / `notes` / `comments`), `source` (default `website`), `form` , `intent` (funnel stage: buyers-checklist, practice-audit, strategy-call, contact, careers, vt-request, roi), `vt_interest` .

1. **Persist** — insert into the `leads` table in `data/portal.sqlite` (table auto-created if missing): name, email, phone, company, message, source, form, vt_id, vt_interest, details (full dump), ip, created_at.

1. **Respond** — buffered JSON `{"ok":true}` / `{"ok":false,"error":...}` , returned immediately.

2. **After response** (via `fastcgi_finish_request()` or buffered background work):

- **Team email** — branded HTML + text to the `lead_notify_email` app setting.
- **HubSpot contact upsert** — PATCH/POST to the CRM contacts API by email, with custom properties (`lead_intent` , `lead_source_form`).
- **HubSpot Forms submit** — POST to the public Forms API, mapping intent → form GUID (records a real form submission for HubSpot workflows).

Mail transport: reads `portal/smtp.local.php` (shared with the portal mailer) for a minimal STARTTLS + AUTH LOGIN client; falls back to native `mail()` . **Validation:** email only; the honeypot + server-side validation stand in for CSRF on these public forms.

This `leads` table is the **same table** read by the portal's **Leads** page — see the portal docs.

9. Other endpoints & files

- `track.php` — pageview beacon. Logs path, IP, geo (via ip-api.com, cached per IP in

`geo_cache`), user agent, referrer into the `traffic` table; returns a non-blocking 204.

- `vt-link.php` / `talent-photo.php` / `talent-media.php` — public, token-gated views of VT

talent profiles, photos, resumes, and videos (validated against `vt_special_links`); `talent-photo` serves only `vt_hired` / `vt_onpool` photos with a placeholder fallback.

- `llms.txt` — plain-text summary of the company (facts, services, pages, FAQs) for LLM crawlers.
- `.htaccess` — `DirectoryIndex index.php`; custom 403/404/500; denies sensitive files

(`.ftp.local`, `.env`, `deploy.sh`, `smtp.local.php`, `.md/.sql/.sqlite*/.log/.local/.bak/.ini/.sh`); 301s `/index.php` and `/index.html` → `/`; Options `-Indexes` / `-MultiViews`; gzip + brotli; cache (HTML no-cache, CSS/JS/img/fonts 1yr immutable, PDF 1mo); security headers (nosniff, SAMEORIGIN, Referrer-Policy, Permissions-Policy).

- `robots.txt` — allows general + named AI crawlers; disallows `/includes/`, `/portal/`,

`/data/`; points to the sitemap.

- `sitemap.xml` — homepage (1.0), services (0.9), marketing pages (0.8), legal (0.3).

10. Deployment

`deploy.sh` uploads over **plain FTP** (port 21 — FTPS fails on a cert principal mismatch) using credentials from the gitignored `.ftp.local` (`FTP_USER`, `FTP_PASS`, `FTP_HOST`).

- **Ships:** the top-level production PHP files (index, error pages, `lead.php`, `track.php`,

talent endpoints, installer), `.htaccess`, `robots.txt`, `llms.txt`, `sitemap.xml`, `favicon.ico`, and the production directories (`css`, `js`, `images`, `fonts`, `includes`, `services`, `business`, landing pages, `about`, `careers`, `case-studies`, `contact`, `guarantee`, `virtual-teammates`, `terms`, `privacy-policy`, `portal`, `hubapi`).

- **Selectively ships from** `data/`: only `data/.htaccess` and `data/.gitkeep` — never the

SQLite DB, sync state, credentials, or media.

- **Never ships:** `.git/`, `.ftp.local`, `*.md` (so `docs/` stays internal), `.gitignore`,

`deploy.sh` itself, `portal/smtp.local.php`.

- **Parallelism:** `FTP_PARALLEL` (default 8). `curl --ftp-create-dirs` handles directory creation.

Triggers: runs automatically on `git push` via `.git/hooks/pre-push` (non-blocking — the push proceeds even if FTP fails). Manual deploy without pushing: `./deploy.sh`. Push without deploying: `git push --no-verify`.