

0.5

hoard

A Collections Library for Bigloo scheme
User manual for version 0.5
May

Joseph Donaldson

Copyright © 2016-17 Joseph Donaldson

hoard is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

hoard is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with collections. If not, see [<http://www.gnu.org/licenses/>](http://www.gnu.org/licenses/).

1 Overview of hoard

hoard is a collections library for Bigloo. It consists of a number of generic protocols and corresponding concrete implementations. Currently, it supports generic protocols for abstract collections, dictionaries, sets, queues, stacks, and priority queues as well as generic protocols for enumeration (i.e., iteration) and comparison. Multiple concrete implementations of each protocol are provided. For example, there are both sorted/tree and hash based versions of sets and dictionaries.

Note: hoard heavily leverages bigloo-specific functionality, such as the object system, modules, and keyword arguments. Porting to other scheme systems would require significant effort.

2 Protocols

This chapter documents the protocols provided by hoard. Each protocol is described, the api documented, and examples given.

2.1 collection

2.1.1 Overview

The collection protocol provides the operations expected of an entity that represents an aggregate or container of other entities.

2.1.2 API Reference

`collection?` *object* [generic]
returns a boolean indicating whether or not `object` supports the collection protocol.

`collection-length` *object* [generic]
requires `object` support the collection protocol

returns the length of the `collection` `object`

`collection-empty?` *object* [generic]
requires `object` support the collection protocol

returns a boolean indicating whether the `collection` `object` is empty or not

`collection-contains?` *object itm* [generic]
requires `object` support the collection protocol and `itm` be an arbitrary value

returns a boolean indicating whether or not `itm` is in `object`

Note `collection-contains?` uses `equal?` for comparison, and for dictionary-like entities such as a hashtable or sorted-dictionary, it determines whether `itm` is a value in the collection, not whether it is a key in the collection. If you want to check to see if a key exists in such a collection, use `dictionary-contains?`

`collection-enumerator` *object* [generic]
requires `object` support the collection protocol

returns an `enumerator`

note an `enumerator` provides the ability to enumerate or iterate through the items in a collection.

`collection-copy` *object* [generic]
requires `object` support the collection protocol

returns a shallow copy of `object`

2.1.3 Examples

The standard Bigloo lists, vectors, strings, and hashtables are collections.

```
(collection? (list 1 2 3))
⇒ #t

(collection? (vector 1 2 3))
⇒ #t

(collection? (create-hashtable))
⇒ #t

(collection? "example")
⇒ #t
```

We can check to see if a collection is empty, obtain its length, and check to see if an item is contained within it.

```
(collection-length (list 1 2 3))
⇒ 3

(collection-empty? '())
⇒ #t

(collection-empty? (list 1 2 3))
⇒ #f

(collection-contains? (list 1 2 3) 3)
⇒ #t
```

When needed, we can also obtain a shallow copy of a collection.

```
(let* ((vec1 (vector 1 2 3))
      (vec2 (collection-copy vec1)))
  (and (equal? vec1 vec2)
       (not (eq? vec1 vec2))))
⇒ #t
```

The `collection-enumerator` function is used to implement the `enumerable` functionality. See Section 2.6 [enumerable], page 9,

2.2 indexable

2.2.1 Overview

The indexable protocol specifies the operations expected of an indexable collection. An indexable collection is a collection which individual items can be referenced and potentially set via a key of some sort. This key can be an integer as is the case of lists, vectors, and strings, or arbitrary objects in the case of dictionary types.

2.2.2 API Reference

`collection-indexable? object` [generic]
returns a boolean indicating whether or not *object* supports the `indexable` protocol

`collection-ref object key [default-if-not-found]` [generic]
requires *object* support the `indexable` protocol, *key* be an arbitrary value, and optionally, `default-if-not-found` be an arbitrary value

returns the value at the given **key** or throws `&invalid-index-exception` unless `default-if-not-found` is provided in which case `default-if-not-found` is returned

note For vectors, lists, and their ilk, **key** is an integer value representing the position in the collection. For dictionaries, **key** is the traditional key associated with such types.

`collection-set!` *object key value* [generic]

requires `object` support the `indexable` protocol and both **key** and **value** be arbitrary values **returns** `#unspecified` or throws `&unsupported-operation-exception` if `collection-set!` is not supported.

modifies `object` so that value at **key** is now **value** A generic function that sets the value found at **key** to the given value. If the key is not valid for the collection, `&invalid-index-exception` is thrown.

`collection-slice` *object keys* [generic]

requires `object` support the `indexable` protocol and **keys** be an object implementing the `enumerable` protocol

returns an `enumerator` providing access to the elements in the collection `object` represented by the provided enumerable of **keys**.

2.2.3 Examples

The standard Bigloo lists, vectors, strings, and hashtables are indexable.

```
(collection-indexable? (list 1 2 3))
⇒ #t

(collection-indexable? (vector 1 2 3))
⇒ #t

(collection-indexable? "test string")
⇒ #t

(collection-indexable? (create-hashtable))
⇒ #t
```

For collections that are position addressable such as lists, vectors, and strings as well as other, you can reference each individual element with `collection-ref` given its position as a key.

```
(collection-ref (list 1 2 3) 1)
⇒ 2

(collection-ref (vector 1 2 3) 2)
⇒ 3

(collection-ref "test string" 0)
⇒ t

(collection-ref (vector 1 2 3) 3 -1)
⇒ -1
```

```
(collection-ref (vector 1 2 3) 3)
  error    &invalid-index-exception
```

For dictionary-like collections, such as a hashtables, `collection-ref` obtains the value in the collection associated with the provided `key`.

```
(let ((table (create-hashtable)))
  (hashtable-put! 'a 1)
  (hashtable-put! 'b 2)
  (hashtable-put! 'c 3)
  (collection-ref table 'b))
⇒ 2
```

```
(let ((table (create-hashtable)))
  (hashtable-put! 'a 1)
  (hashtable-put! 'b 2)
  (hashtable-put! 'c 3)
  (collection-ref table 'd -1))
⇒ -1
```

```
(let ((table (create-hashtable)))
  (hashtable-put! 'a 1)
  (hashtable-put! 'b 2)
  (hashtable-put! 'c 3)
  (collection-ref table 'd))
  error    &invalid-index-exception
```

It is sometimes useful to obtain a subset of elements provided by an indexable collection. `collection-slice` provides this functionality.

```
(let ((slice-enumer (collection-slice (iota 50) (range :start 15 :end 30))))
  (enumerable-collect slice-enumer +list-collector+))
⇒ (15 16 17 18 19 20 21 22 23 24 25 26 27 28 29)

(enumerable-collect (collection-slice (vector 3 4 5 6) '(2 3))
  +list-collector+)
⇒ (5 6)
```

2.3 extendable

2.3.1 Overview

The extendable protocol specifies the operations expected of a collection that can be dynamically extended beyond its initially allocated size.

2.3.2 API Reference

`collection-extendable?` *object* [generic]
returns a boolean indicating whether or not `object` is extendable.

`collection-extend!` *object value* [generic]
requires `object` support the `extendable` protocol and `value` be an arbitrary value. **returns** `#unspecified` or throws `&unsupported-operation-exception` if `collection-extend!` is not supported.

modifies *object* by adding *value*.

note for dictionary-like collections *value* should be an **association** representing the key and value.

2.3.3 Examples

Bigloo lists and hashtables (as well as a number of other collection types) implement the **extendable** protocol:

```
(collection-extendable? (list 1 2 3))
⇒ #t

(collection-extendable? (create-hashtable))
⇒ #t
```

Both can be extended:

```
(collection-extend! (list 1 2 3 4) 5)
⇒ (5 1 2 3 4)

(let ((table (hashtable :comparator +string-comparator+ (=> "a" 1) (=> "b" 2))))
  (collection-extend! table (=> "c" 3))
  (enumerable-collect table +list-collector+))
⇒ (1 2 3)
```

2.4 mutable

2.4.1 Overview

The mutable protocol specifies the operations expected of an mutable collection. A mutable collection is one in which the collection can be modified in place.

2.4.2 API Reference

collection-mutable? *object* [generic]
returns a boolean indicating whether or not *object* is mutable

2.4.3 Examples

Not surprisingly, the standard Bigloo lists, vectors, and hashtables are mutable.

```
(collection-mutable? (list))
⇒ #t

(collection-mutable? (vector 1 2 3))
⇒ #t

(collection-mutable? "test string")
⇒ #t
```

2.5 enumerator

2.5.1 Overview

The `enumerator` protocol is an abstraction for enumerating or iterating through the items contained by an object. These items may be pre-existing or generated on demand. Collections are the most common object to provide `enumerators` but other objects, such as interval ranges, can provide enumerators as well.

2.5.2 API Reference

`enumerator? object` [generic]
returns a boolean indicating whether or not `object` supports the `enumerator` protocol

`enumerator-move-next! object` [generic]
requires `object` support the `enumerator` protocol

returns a boolean indicating whether or not `object` additional items available

modifies `object` such that upon returning `#t` the next item under enumeration is current. Otherwise, `object` remains unmodified.

note `enumerator-move-next!` must be called before `enumerator-current`. If it is not, `&invalid-state-exception` is thrown.

`enumerator-current object` [generic]
requires `object` support the `enumerator` protocol

returns the item found at the `enumerators` current position or if `enumerator-move-next!` has not been called before, `&invalid-state-exception` is thrown.

`enumerator-copy object` [generic]
requires `object` support the `enumerator` protocol

returns a copy of the `enumerator`.

2.5.3 Examples

You seldom use `enumerator` directly but, instead, use the procedures and macros provided by `enumerable`. However, if needed you can use the `enumerator` protocol directly.

```
(let ((enumer (enumerable-enumerator (list 1 2 3 4 5))))
  (let loop ((cont (enumerator-move-next! enumer)))
    (when cont
      (print (enumerator-current enumer))
      (loop (enumerator-move-next! enumer)))))
⇒ 1
⇒ 2
⇒ 3
⇒ 4
⇒ 5
⇒ #unspecified
```

2.6 enumerable

2.6.1 Overview

`enumerable` is a protocol implemented by those objects that support a notion of enumeration or iteration. By providing an `enumerator`, they gain support for mapping, folding, filtering, and more.

2.6.2 API Reference

`enumerable? object` [generic]
returns a boolean indicating whether or not `object` supports the `enumerable` protocol

`enumerable-enumerator obj` [generic]
requires `object` support the `enumerable` protocol
returns an `enumerator`

`enumerable-for-each proc enum1 enum2 ...` [syntax]
requires `enums` to either support the `enumerable` or `enumerator` protocol and `proc` be a procedure with an arity compatible with applying it element-wise to the elements provided by the `enums`.
returns `#unspecified`
note `enumerable-for-each` is applied for the side-effects resulting from applying `proc`.

`enumerable-map proc enum1 enum2 ...` [syntax]
requires `enums` to either support the `enumerable` or `enumerator` protocol and `proc` be a procedure with an arity compatible with applying it element-wise to the elements provided by the `enums`.
returns an `enumerator` providing the results of applying `proc`

`enumerable-filter predicate enum` [syntax]
requires `enum` to either support the `enumerable` or `enumerator` protocol and `predicate` be a procedure returning a boolean indicating whether or not an element should be retained.
returns an `enumerator` providing the retained elements

`enumerable-take-while predicate enum` [syntax]
requires `enum` to either support the `enumerable` or `enumerator` protocol and `predicate` be a procedure returning a boolean indicating whether or not an element should continue to be consumed.
returns an `enumerator` providing the consumed elements

enumerable-take *n enum* [syntax]
requires *enum* to either support the **enumerable** or **enumerator** protocol and *n* be an integer representing the max number of items to take

returns an **enumerator** providing upto *n* elements

enumerable-fold *proc seed enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol, *proc* to be a procedure compatible with applying it to a seed and the element-wise elements provided by the *enums* (it should produce a new seed value), and *seed* should be an appropriate initial seed value for *proc*.

returns the result of folding *proc* over the provided *enums*

note *proc* is applied left to right with the seed resulting from the previous application being used in the next. When no more elements are available, the final seed is returned.

enumerable-any? *predicate enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol and *predicate* to be a procedure compatible with applying it element-wise to the elements provided by the *enums*, returning a boolean.

returns a boolean indicating whether or not any of the elements are **#t** for *predicate*.

enumerable-every? *predicate enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol and *predicate* to be a procedure compatible with applying it element-wise to the elements provided by the *enums*, returning a boolean.

returns a boolean indicating whether or not all of the elements are **#t** for *predicate*.

enumerable-skip-while *predicate enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol and *predicate* to be a procedure compatible with applying it element-wise to the elements provided by the *enums*, returning a boolean indicating whether those elements should be skipped.

returns an **enumerator** providing access to the elements in the original *enums* after those that were skipped according to *predicate*.

enumerable-skip *n enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol and *n* to be an integer representing the number of elements to skip from *enums*.

returns an **enumerator** providing access to the elements in the original *enums* after those that were skipped.

enumerable-append *enum1 enum2 ...* [syntax]
requires *enums* to either support the **enumerable** or **enumerator** protocol.

returns an **enumerator** providing access to the elements in the original *enums* appended left to right.

enumerable-collect *enum collector* [syntax]
requires *enum* to either support the **enumerable** or **enumerator** protocol and *collector* to support the **collector** protocol.

returns a value collected from the given *enum* according to provided *collector*.

note **enumerable-collect** is commonly used to transform the values provided by **enumerators** into concrete collections, although their uses are more flexible than that. For example, to collect all of the values from an **enumerator** into a list you could do the following:

```
(enumerable-collect enumerator +list-collector+)
```

See Section 2.7 [collector], page 12, for more information.

2.6.3 Examples

All of the built in Bigloo collection types are **enumerables**.

```
(enumerable? (list 1 2 3))
⇒ #t

(enumerable? (vector 1 2 3))
⇒ #t

(enumerable? "test string")
⇒ #t

(enumerable? (create-hashtable))
⇒ #t
```

With **enumerable-for-each**, it is possible to iterate over any **enumerable**. A few examples follow:

```
(let ((count 0))
  (enumerable-for-each (lambda (x) (set! count (+ x count)))
    (vector 1 2 3))
  count)
⇒ 6

(enumerable-for-each (lambda (x) (print x)) (range :start 1 :end 5))

+ 1
+ 2
+ 3
+ 4
⇒ #unspecified
```

It is also possible to map a function over **enumerables**.

```
(enumerable-collect (enumerable-map (lambda (x) (+ x 1))
  (list 1 2 3 4))
```

```
+list-collector+)

⇒ (2 3 4 5)
```

For dictionary type collections, the values are mapped over.

```
(let ((table (hashtable (=> 'a 1) (=> 'b 2) (=> 'c 3))))
  (print (enumerable-collect (enumerable-map (lambda (x) (+ x 1)) table)
    +vector-collector+)))
```

Given an appropriate seed and procedure, `enumerable-fold` can be used to reduce an enumerable to a single value.

```
(enumerable-fold (lambda (s v) (+ s v)) 0 (range :start 1 :end 6))

⇒ 15
```

Filtering of values is also supported.

```
(enumerable-collect (enumerable-filter odd? (range :start 1 :end 10))
  +list-collector+)

⇒ (1 3 5 7 9)
```

It is also possible to consume values while a predicate remains true.

```
(enumerable-collect
  (enumerable-take-while (lambda (x) (< x 5)) (range :start 0 :end 10))
  +list-collector+)

⇒ (0 1 2 3 4)
```

Or to test whether any or all values match a given predicate.

```
(enumerable-any? odd? (list 4 6 8 7))

⇒ #t

(enumerable-any? odd? (list 4 6 8 10))

⇒ #f

(enumerable-every? even? (list 2 4 6 8))

⇒ #t

(enumerable-every? even? (list 2 4 6 7))

⇒ #f
```

As shown in the above examples, `enumerable-collect` can be used to gather the values of an enumerable into a new collection, but it is more general than that. In fact, it is a general reduction facility. For example, the sum of an enumerable can be obtained as follows:

```
(enumerable-collect (range :start 1 :end 6) +sum-collector+)

⇒ 15
```

For full details, See Section 2.7 [collector], page 12.

2.7 collector

2.7.1 Overview

The `collector` protocol defines the methods required for a general reduction facility for `enumerables`. Examples include `collection` conversion and various accumulations. It is modeled after the `Collector` interface of Java.

2.7.2 API Reference

`collector? object` [generic]
returns a boolean indicating whether or not `object` supports the `collector` protocol

`collector-supplier object` [generic]
requires `object` support the `collector` protocol
returns a thunk that when called returns an object for collecting results

`collector-accumulate coll supp val` [generic]
requires `coll` support the `collector` protocol, `supp` be an object originally created via the thunk returned by `collector-supplier`, and `val` be an arbitrary item to be accumulated.
returns `supp` updated with `val`

`collector-combine coll suppa suppb` [generic]
requires `coll` support the `collector` protocol and `suppa` and `suppb` be objects originally created via the thunk returned by `collector-supplier`,
returns a single entity combining both `suppa` and `suppb`

`collector-finish coll supp` [generic]
requires `coll` support the `collector` protocol and `supp` be an object originally created via the thunk returned by `collector-supplier`,
returns a single entity from the accumulated `supp` possibly with a final transformation.

`make-collector :supplier :accumulate :combine :finish` [procedure]
requires `:supplier` be a thunk returning an object used for accumulation by the collector, `:accumulate` be a procedure taking the current accumulation object and a `val` and returning an updated accumulation object, `:combine` be a procedure taking 2 accumulation objects and returning an accumulation object combining the 2, and `:finish` be a procedure taking the final accumulation object and returning an possibly transformed result.
returns a final accumulation object.

`variable +list-collector+` [Variable]
`+list-collector+` is a collector that accumulates the items provided by an `enumerator` into a list.

variable *+stretchy-vector-collector+* [Variable]
+stretchy-vector-collector+ is a collector that accumulates the items provided by an **enumerator** into a stretchy-vector.

variable *+vector-collector+* [Variable]
+vector-collector+ is a collector that accumulates the items provided by an **enumerator** into a vector.

variable *+sum-collector+* [Variable]
+sum-collector+ is a collector that sums the items provided by an **enumerator**.

2.7.3 Examples

To create your own version of a list collector is as simple as the following:

```
(define +my-list-collector+
  (make-collector :supplier (lambda ()
                              '()))
  :accumulate (lambda (supp val)
                (cons val supp))
  :combine (lambda (a b)
             (append a b))
  :finish (lambda (x) (reverse x))))
```

To obtain the product of all numbers in an **enumerable**

```
(define +product-collector+
  (make-collector :supplier (lambda () 1)
  :accumulate (lambda (supp val)
                (* supp val))
  :combine (lambda (a b) (* a b))
  :finish (lambda (x)
            x))))
```

2.8 comparator

2.8.1 Overview

The **comparator** protocol defines those methods required to support comparison and, optionally, total ordering of a specific type. Although not identical, it is very similar to the functionality found in SRFI-128.

2.8.2 API Reference

comparator? *object* [generic]
returns a boolean indicating whether or not *object* supports the **comparator** protocol

comparator-ordered? *comp* [generic]
requires *comp* implement the **comparator** protocol.

returns a boolean indicating whether or not *comp* supports ordering.

comparator-hashable? *comp* [generic]
requires *comp* implement the **comparator** protocol.

returns a boolean indicating whether or not *comp* supports hashing.

`comparator-type? comp val` [generic]
requires `comp` implement the `comparator` protocol and `val` be an arbitrary object.

returns a boolean indicating whether or not `val` is of an appropriate type for `comp`

`comparator=? comp a b` [generic]
requires `comp` implement the `comparator` protocol and `a` and `b` be of the type supported by `comp`.

returns a boolean indicating whether or not `a` is equal to `b`

note `comparator=?` is supported by all `comparator` instances.

`comparator<? comp a b` [generic]
requires `comp` implement the `comparator` protocol and `a` and `b` be of the type supported by `comp`.

returns a boolean indicating whether or not `a` is less than `b`

note `comparator<?` is only supported by `comparator` instances that are ordered.

`comparator>? comp a b` [generic]
requires `comp` implement the `comparator` protocol and `a` and `b` be of the type supported by `comp`.

returns a boolean indicating whether or not `a` is greater than `b`

note `comparator>?` is only supported by `comparator` instances that are ordered.

`comparator<=? comp a b` [generic]
requires `comp` implement the `comparator` protocol and `a` and `b` be of the type supported by `comp`.

returns a boolean indicating whether or not `a` is less than or equal to `b`

note `comparator<=?` is only supported by `comparator` instances that are ordered.

`comparator>=? comp a b` [generic]
requires `comp` implement the `comparator` protocol and `a` and `b` be of the type supported by `comp`.

returns a boolean indicating whether or not `a` is greater than or equal to `b`

note `comparator>=?` is only supported by `comparator` instances that are ordered.

`comparator-hash comp val` [generic]
requires `comp` implement the `comparator` protocol and `val` of the type supported by `comp`.

returns an integer hash value

note `comparator-hash` is only supported by `comparator` instances that are hashable.

make-comparator *:type?* *:equal?* [*:less-than?*] [*:hash*] [procedure]
requires *:type?* be a single argument procedure returning a boolean indicating whether or not the argument is of the type supported by the `comparator`, *:equal?* be a 2 argument procedure returning whether or not the arguments are equal, *:less-than?* be a 2 argument procedure returning whether or not the first argument is less than or equal to the second, and *:hash* be a single argument procedure returning an appropriate integer value.

returns a comparator

note *:less-than?* and *:hash* are optional but at least one needs to be provided. Obviously, both can also be provided. If *:less-than?* is not provided, the comparator will not be ordered. Similarly, if the *:hash* is not provided, the comparator will not be hashable.

variable *+number-comparator+* [Variable]
+number-comparator+ is a comparator instance for numbers. It is ordered and hashable.

variable *+char-comparator+* [Variable]
+char-comparator+ is a comparator instance for characters. It is ordered and hashable. The ordering is case-sensitive.

variable *+char-ci-comparator+* [Variable]
+char-ci-comparator+ is a comparator instance for characters. It is ordered and hashable. The ordering is case-insensitive.

variable *+ucs2-comparator+* [Variable]
+ucs2-comparator+ is a comparator instance for unicode characters. It is ordered and hashable. The ordering is case-sensitive.

variable *+ucs2-ci-comparator+* [Variable]
+ucs2-ci-comparator+ is a comparator instance for unicode characters. It is ordered and hashable. The ordering is case-insensitive.

variable *+string-comparator+* [Variable]
+string-comparator+ is a comparator instance for strings. It is ordered and hashable. The ordering is case-sensitive.

variable *+string-ci-comparator+* [Variable]
+string-ci-comparator+ is a comparator instance for strings. It is ordered and hashable. The ordering is case-insensitive.

variable *+symbol-comparator+* [Variable]
+symbol-comparator+ is a comparator instance for symbols. It is ordered and hashable. The ordering is case-sensitive.

variable *+symbol-ci-comparator+* [Variable]
+symbol-ci-comparator+ is a comparator instance for symbols. It is ordered and hashable. The ordering is case-insensitive.

variable *+ucs2-string-comparator+* [Variable]
+ucs2-string-comparator+ is a comparator instance for unicode strings. It is ordered and hashable. The ordering is case-sensitive.

variable *+ucs2-string-ci-comparator+* [Variable]
+ucs2-string-ci-comparator+ is a comparator instance for unicode strings. It is ordered and hashable. The ordering is case-insensitive.

variable *+keyword-comparator+* [Variable]
+keyword-comparator+ is a comparator instance for keywords. It is ordered and hashable. The ordering is case-sensitive.

variable *+keyword-ci-comparator+* [Variable]
+keyword-ci-comparator+ is a comparator instance for keywords. It is ordered and hashable. The ordering is case-insensitive.

2.8.3 Examples

To demonstrate the use of the comparator protocol, we will use the *+number-comparator+* instance.

+number-comparator+ is both ordered and hashable:

```
(comparator-ordered? +number-comparator+)
⇒ #t
```

```
(comparator-hashable? +number-comparator+)
⇒ #t
```

All comparators must support type checking and equality:

```
(comparator-type? +number-comparator+ 4)
⇒ #t
```

```
(comparator-type? +number-comparator+ "dog")
⇒ #f
```

```
(comparator=? +number-comparator+ 4 4)
⇒ #t
```

```
(comparator=? +number-comparator+ 3 4)
⇒ #f
```

Being ordered, we can use the ordered comparison methods with *+number-comparator+*:

```
(comparator<? +number-comparator+ 4 5)
⇒ #t
```

```
(comparator>? +number-comparator+ 4.0 5)
⇒ #f
```

```
(comparator<=? +number-comparator+ 5 5)
⇒ #t
```

```
(comparator>=? +number-comparator+ 5 6.0)
```

```
⇒ #f
```

And being hashable, we can use the hash method:

```
(comparator-hash comp 4)
⇒ 4
```

```
(comparator-hash comp 5.0)
⇒ 5
```

2.9 bag

2.9.1 Overview

The **bag** protocol defines those methods required by a bag implementation. A bag is set-like data structure that can contain multiple copies of an item.

2.9.2 API Reference

bag? *object* [generic]
returns a boolean indicating whether or not *object* supports the **bag** protocol

bag-copy *bag* [generic]
requires *bag* implement the bag protocol.
returns a shallow copy of *bag*.

bag-empty? *bag* [generic]
requires *bag* implement the bag protocol.
returns a boolean indicating whether or not *bag* contains any items.

bag-insert! *bag item* [generic]
requires *bag* implement the bag protocol, and *item* be an arbitrary object.
modifies *bag* so that it contains a copy or an additional copy, if one already exists, of *item*.
returns unspecified

bag-delete! *bag item* [generic]
requires *bag* implement the bag protocol, and *item* be an arbitrary object.
modifies *bag* so that it contains one less copy of *item*. If 0 copies of *item* exist it is removed from *bag*.
returns unspecified

bag-contains? *bag item* [generic]
requires *bag* implement the bag protocol, and *item* be an arbitrary object.
returns a boolean indicating whether or not the *bag* contains *item*.

bag-count *bag item* [generic]
requires *bag* implement the bag protocol, and *item* be an arbitrary object.

returns the number of *items* found in *bag*.

bag-count-set! *bag item count* [generic]
requires *bag* implement the bag protocol, *item* be an arbitrary object, and *count* be an integer representing the number of *items* to include in *bag*

modifies *bag* to contain *count* number of *items* unless *count* is less than or equal to 0 which results in the all *items* begin removed from *bag*.

returns #unspecified

bag-length *bag* [generic]
requires *bag* implement the bag protocol

returns the number of items contained in *bag*

2.9.3 Examples

2 different implementations of the bag protocol are currently provided by *hoard*. One is tree-based, and the other is hash-based. To create a tree-based bag use:

```
(let ((bag (make-sorted-bag :comparator +number-comparator+)))
  (bag? bag))
⇒ #t
```

The **:comparator** argument must be an object implementing the comparator protocol for the type of item to be stored in the bag. The comparator must be ordered.

To create a hash-based bag use:

```
(let ((bag (make-hash-bag :comparator +number-comparator+)))
  (bag? bag))
⇒ #t
```

The **:comparator** argument, like in the tree-based example, must be an object implementing the comparator protocol for the type of item to be stored in the bag. However, the comparator must be hashable not ordered.

Assuming a bag has been created as above, to insert an item into a bag use:

```
(bag-insert! bag 1)
⇒ #unspecified
```

The count of an item can be obtained with:

```
(bag-count bag 1)
⇒ 1
```

```
(bag-count bag 2)
⇒ 0
```

And the count can be explicitly set using:

```
(bag-count-set! bag 1 4)
⇒ #unspecified
```

```
(bag-count bag 1)
⇒ 4
```

Or a single copy deleted with:

```
(bag-delete! bag 1)
⇒ #unspecified
```

```
(bag-count bag 1)
⇒ 3
```

To check to see if a bag is empty:

```
(bag-empty? bag)
⇒ #f
```

To check whether an item is a member of a bag:

```
(bag-contains? bag 1)
⇒ #t
```

```
(bag-contains? bag 3)
⇒ #f
```

And finally, to make a copy:

```
(let ((bag2 (bag-copy? bag)))
  (eq? bag bag2))
⇒ #f
```

In addition, `sorted-bag` implements the `enumerable` protocol. See Section 2.6.3 [enumerable Examples], page 11.

2.10 set

2.10.1 Overview

The `set` protocol defines those methods required by a set implementation. A set is a collection of objects where each object is unique.

2.10.2 API Reference

`set? object` [generic]

returns a boolean indicating whether or not `object` supports the `set` protocol

`set-copy set` [generic]

requires `set` implement the set protocol.

returns a shallow copy of `set`.

`set-empty? set` [generic]

requires `set` implement the set protocol.

returns a boolean indicating whether or not `set` contains any items.

`set-insert! set item` [generic]

requires `set` implement the set protocol, and `item` be an arbitrary object.

modifies `set` so that it contains a copy or an additional copy, if one already exists, of `item`.

returns unspecified

set-delete! *set item* [generic]
requires *set* implement the set protocol, and *item* be an arbitrary object.

modifies *set* so that it contains one less copy of *item*. If 0 copies of *item* exist it is removed from *set*.

returns unspecified

set-contains? *set item* [generic]
requires *set* implement the set protocol, and *item* be an arbitrary object.

returns a boolean indicating whether or not the *set* contains *item*.

set-length *set* [generic]
requires *set* implement the set protocol

returns the number of items contained in *set*

set-union! *set . sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

modifies *set* to be the union of all sets provided. **returns** #unspecified

set-union *set . sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

returns a new set of the same type as *set* containing the union of all sets provided.

set-intersect! *set . sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

modifies *set* to be the intersection of all sets provided. **returns** #unspecified

set-intersect *set . sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

returns a new set of the same type as *set* containing the intersection of all sets provided.

set-difference! *set . sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

modifies *set* to be the difference of all sets provided. **returns** #unspecified

set-difference *set* . *sets* [generic]
requires *set* implement the set protocol and *sets* be an arbitrary number of additional objects implementing the set protocol.

returns a new set of the same type as *set* containing the difference of all sets provided.

2.10.3 Examples

2 different implementations of the set protocol are currently provided by hoard. One is tree-based, and the other is hash-based. To create a tree-based set use:

```
(let ((set (make-sorted-set :comparator +number-comparator+)))
  (set? set))
⇒ #t
```

The `:comparator` argument must be an object implementing the comparator protocol for the type of item to be stored in the set. The comparator must be ordered.

To create a hash-based set use:

```
(let ((set (make-hash-set :comparator +number-comparator+)))
  (set? set))
⇒ #t
```

The `:comparator` argument, like in the tree-based example, must be an object implementing the comparator protocol for the type of item to be stored in the set. However, the comparator must be hashable not ordered.

Assuming a set has been created, to insert an item into a set use:

```
(set-insert! set 1)
⇒ #unspecified
```

Or deleted with:

```
(set-delete! set 1)
⇒ #unspecified
```

```
(set-contains? set 1)
⇒ #f
```

To check to see if a set is empty:

```
(set-empty? set)
⇒ #f
```

To check whether an item is a member of a set:

```
(set-contains? set 1)
⇒ #t
```

```
(set-contains? set 3)
⇒ #f
```

To make a copy:

```
(let ((set2 (set-copy? set)))
  (eq? set set2))
⇒ #f
```

To non-destructively perform the union, intersection, and difference:

```
(let* ((set1 (sorted-set :comparator +number-comparator+ 1 2))
      (set2 (hash-set :comparator +number-comparator+ 2 3))
      (uset (set-union set1 set2))
      (iset (set-intersect set1 set2)))
```



```
(dset (set-difference set1 set2)))

(list (enumerable-collect uset +list-collector+))
(enumerable-collect iset +list-collector+)
(enumerable-collect dset +list-collector+))
```

2.11 queue

2.11.1 Overview

The `queue` protocol defines the methods required by a queue implementation. A queue is a first-in-first-out sequential data structure.

2.11.2 API Reference

`queue?` *object* [generic]

returns a boolean indicating whether or not *object* supports the `queue` protocol

`queue-copy` *queue* [generic]

requires *queue* implement the `queue` protocol.

returns a shallow copy of *queue*.

`queue-empty?` *queue* [generic]

requires *queue* implement the `queue` protocol.

returns a boolean indicating whether or not *queue* contains any items.

`queue-first` *queue* [generic]

requires *queue* implement the `queue` protocol.

returns returns the first item in *queue*. If *queue* is empty, a `&invalid-state-exception` is thrown.

`queue-enqueue!` *queue item* [generic]

requires *queue* implement the `queue` protocol and *item* be an arbitrary item

returns returns `unspecified`. If *queue* has a fixed capacity and is full, a `&invalid-state-exception` is thrown.

modifies *queue* by placing *item* on the end.

`queue-dequeue!` *queue* [generic]

requires *queue* implement the `queue` protocol.

returns returns the first item in *queue*. If *queue* is empty, a `&invalid-state-exception` is thrown.

modifies *queue* by removing the first item.

queue-length *queue* [generic]
requires *queue* implement the queue protocol.

returns returns the the number of items in *queue*

queue-fixed-capacity? *queue* [generic]
requires *queue* implement the queue protocol.

returns returns a boolean indicating whether or not *queue* has a fixed capacity.

queue-capacity *queue* [generic]
requires *queue* implement the queue protocol.

returns returns the capacity (i.e., the number of items that it can hold) of *queue* or unspecified if it has no fixed capacity.

2.11.3 Examples

hoard provides linked and contiguous implementations of the *queue* protocol.

```
(queue? (contiguous-queue :capacity 5))
⇒ #t
(queue? (linked-queue))
⇒ #t
```

You can add items to a queue:

```
(let ((q (linked-queue)))
  (queue-enqueue! q 1)
  (queue-enqueue! q 2)
  (enumerable-collect q +list-collector+))
⇒ (1 2)
```

look at the first item:

```
(let ((q (linked-queue)))
  (queue-enqueue! q 1)
  (queue-enqueue! q 2)
  (queue-first q))
⇒ 1
```

or remove the first item:

```
(let ((q (linked-queue)))
  (queue-enqueue! q 1)
  (queue-enqueue! q 2)
  (queue-dequeue! q)
  (queue-front q))
⇒ 2
```

It is also possible to test to see if a queue is empty:

```
(queue-empty? (linked-queue))
⇒ #t

(queue-empty? (linked-queue 1 2 3))
⇒ #f
```

A copy of a queue can be useful:

```
(let* ((q1 (linked-queue 1 2 3))
      (q2 (queue-copy q1)))
  (eq? q1 q2))
```

```
⇒ #f
```

Some queue implementations have a fixed-capacity:

```
(queue-fixed-capacity? (contiguous-queue :capacity 5))
⇒ #t
```

```
(queue-fixed-capacity? (linked-queue))
⇒ #f
```

```
(queue-capacity (contiguous-queue :capacity 5))
⇒ 5
```

```
(queue-capacity (linked-queue))
⇒ #unspecified
```

2.12 stack

2.12.1 Overview

The `stack` protocol defines the methods required by a stack implementation. A stack is a last-in-first-out sequential data structure.

2.12.2 API Reference

`stack? object` [generic]

returns a boolean indicating whether or not `object` supports the `stack` protocol

`stack-copy stack` [generic]

requires `stack` implement the stack protocol.

returns a shallow copy of `stack`.

`stack-empty? stack` [generic]

requires `stack` implement the stack protocol.

returns a boolean indicating whether or not `stack` contains any items.

`stack-top stack` [generic]

requires `stack` implement the stack protocol.

returns returns the top item on `stack`. If `stack` is empty, a `&invalid-state-exception` is thrown.

`stack-push! stack item` [generic]

requires `stack` implement the stack protocol and `item` be an arbitrary item

returns returns `unspecified`. If `stack` has a fixed capacity and is full, a `&invalid-state-exception` is thrown.

modifies `stack` by placing `item` on the top.

stack-pop! *stack* [generic]
requires *stack* implement the stack protocol.

returns returns the top item on *stack*. If *stack* is empty, a `&invalid-state-exception` is thrown.

modifies *stack* by removing the top item.

stack-length *stack* [generic]
requires *stack* implement the stack protocol.

returns returns the the number of items on *stack*

stack-fixed-capacity? *stack* [generic]
requires *stack* implement the stack protocol.

returns returns a boolean indicating whether or not *stack* has a fixed capacity.

stack-capacity *stack* [generic]
requires *stack* implement the stack protocol.

returns returns the capacity (i.e., the number of items that it can hold) of *stack* or unspecified if it has no fixed capacity.

2.12.3 Examples

hoard provides linked and contiguous implementations of the **stack** protocol.

```
(stack? (contiguous-stack :capacity 5))
⇒ #t
(stack? (linked-stack))
⇒ #t
```

You can push items on a stack:

```
(let ((s (linked-stack)))
  (stack-push! s 1)
  (stack-push! s 2)
  (enumerable-collect s +list-collector+))
⇒ (2 1)
```

look at the top item:

```
(let ((s (linked-stack)))
  (stack-push! s 1)
  (stack-push! s 2)
  (stack-top s))
⇒ 2
```

or remove the top item:

```
(let ((s (linked-stack)))
  (stack-push! q 1)
  (stack-push! q 2)
  (stack-pop! q)
  (stack-top q))
⇒ 1
```

It is also possible to test to see if a stack is empty:

```
(stack-empty? (linked-stack))
⇒ #t

(stack-empty? (linked-stack 1 2 3))
⇒ #f
```

A copy of a stack can be useful:

```
(let* ((q1 (linked-stack 1 2 3))
      (q2 (stack-copy q1)))
  (eq? q1 q2))
⇒ #f
```

Some stack implementations have a fixed-capacity:

```
(stack-fixed-capacity? (contiguous-stack :capacity 5))
⇒ #t

(stack-fixed-capacity? (linked-stack))
⇒ #f

(stack-capacity (contiguous-stack :capacity 5))
⇒ 5

(stack-capacity (linked-stack))
⇒ #unspecified
```

2.13 priority-queue

2.13.1 Overview

The `priority-queue` protocol defines the methods required by a priority-queue implementation. A priority-queue is a sequential data structure where items are ordered by priority.

2.13.2 API Reference

`priority-queue? object` [generic]
returns a boolean indicating whether or not *object* supports the `priority-queue` protocol

`priority-queue-copy priority-queue` [generic]
requires *priority-queue* implement the `priority-queue` protocol.
returns a shallow copy of *priority-queue*.

`priority-queue-empty? priority-queue` [generic]
requires *priority-queue* implement the `priority-queue` protocol.
returns a boolean indicating whether or not *priority-queue* contains any items.

`priority-queue-first priority-queue` [generic]
requires *priority-queue* implement the `priority-queue` protocol.
returns returns the first item in *priority-queue*. If *priority-queue* is empty, a `&invalid-state-exception` is thrown.

priority-queue-enqueue! *priority-queue item* [generic]
requires *priority-queue* implement the priority-queue protocol and *item* be an arbitrary item

returns returns unspecified. If *priority-queue* has a fixed capacity and is full, a `&invalid-state-exception` is thrown.

modifies *priority-queue* by placing *item* in the queue according to its priority.

priority-queue-dequeue! *priority-queue* [generic]
requires *priority-queue* implement the priority-queue protocol.

returns returns the first item in *priority-queue*. If *priority-queue* is empty, a `&invalid-state-exception` is thrown.

modifies *priority-queue* by removing the first item.

priority-queue-length *priority-queue* [generic]
requires *priority-queue* implement the priority-queue protocol.

returns returns the the number of items in *priority-queue*

priority-queue-fixed-capacity? *priority-queue* [generic]
requires *priority-queue* implement the priority-queue protocol.

returns returns a boolean indicating whether or not *priority-queue* has a fixed capacity.

priority-queue-capacity *priority-queue* [generic]
requires *priority-queue* implement the priority-queue protocol.

returns returns the capacity (i.e., the number of items that it can hold) of *priority-queue* or unspecified if it has no fixed capacity.

2.13.3 Examples

hoard provides linked and contiguous implementations of the **priority-queue** protocol.

```
(priority-queue? (binary-heap :capacity 5 :comparator +number-comparator+))
⇒ #t
(priority-queue? (pairing-heap :comparator +number-comparator+))
⇒ #t
```

You can add items to a priority-queue:

```
(let ((q (pairing-heap :comparator +number-comparator+)))
  (priority-queue-enqueue! q 1)
  (priority-queue-enqueue! q 2)
  (enumerable-collect q +list-collector+))
⇒ (1 2)
```

look at the first item:

```
(let ((q (pairing-heap :comparator +number-comparator+)))
  (priority-queue-enqueue! q 2)
```

```
(priority-queue-enqueue! q 1)
(priority-queue-first q))
⇒ 1
```

or remove the first item:

```
(let ((q (pairing-heap :comparator +number-comparator+)))
  (priority-queue-enqueue! q 1)
  (priority-queue-enqueue! q 2)
  (priority-queue-dequeue! q)
  (priority-queue-front q))
⇒ 2
```

It is also possible to test to see if a priority-queue is empty:

```
(priority-queue-empty? (pairing-heap :comparator +number-comparator+))
⇒ #t
```

```
(priority-queue-empty? (pairing-heap :comparator +number-comparator+))
⇒ #f
```

A copy of a priority-queue can be useful:

```
(let* ((q1 (pairing-heap :comparator +number-comparator+ 1 2 3))
      (q2 (priority-queue-copy q1)))
  (eq? q1 q2))
⇒ #f
```

Some priority-queue implementations have a fixed-capacity:

```
(priority-queue-fixed-capacity? (binary-heap :capacity 5 :comparator +number-comparator+))
⇒ #t
```

```
(priority-queue-fixed-capacity? (pairing-heap :comparator +number-comparator+))
⇒ #f
```

```
(priority-queue-capacity (binary-heap :capacity 5 :comparator +number-comparator+))
⇒ 5
```

```
(priority-queue-capacity (pairing-heap :comparator +number-comparator+))
⇒ #unspecified
```

2.14 dictionary

2.14.1 Overview

The `dictionary` protocol defines the methods required by a dictionary implementation. A dictionary is a data structure maintaining associations between keys and values.

2.14.2 API Reference

`dictionary? object` [generic]
returns a boolean indicating whether or not `object` supports the `dictionary` protocol

`dictionary-copy dict` [generic]
requires `dict` implement the `dictionary` protocol.

returns a shallow copy of `dict`

dictionary-empty? *dict* [generic]
requires *dict* implement the dictionary protocol.

returns a boolean indicating whether or not the dictionary contains any associations.

dictionary-get *dict key* [generic]
requires *dict* implement the dictionary protocol and *key* be an arbitrary object

returns the value associated with *key* or **#f** if no such association exists.

dictionary-put! *dict key value* [generic]
requires *dict* implement the dictionary protocol and *key* and *value* be arbitrary objects

modifies *dict* so that it contains the association of *key* to *value*. If an association with *key* already exists it is replaced, and if not, a new association is created.

returns **#unspecified**

dictionary-length *dict* [generic]
requires *dict* implement the dictionary protocol.

returns the number of items in *dict*.

dictionary-remove! *dict key* [generic]
requires *dict* implement the dictionary protocol and *key* be an arbitrary object.

modifies *dict* by removing the association with the key *key*.

returns **#unspecified**

dictionary-contains? *dict key* [generic]
requires *dict* implement the dictionary protocol and *key* be an arbitrary object.

returns a boolean indicating whether or not *dict* contains an association with the key *key*.

dictionary-update! *dict key value exist-fun* [generic]
requires *dict* implement the dictionary protocol, *key* and *value* be arbitrary objects, and *exist-fun* which is a procedure excepting a single value and returning an updated value when an association with a key *key* already exists.

modifies *dict* such that if the dictionary doesn't currently contain an association with a key *key*, it contains an association with key *key* and value *value*, or if an existing association exists updates it so that has the value obtained by applying *exist-fun* to its value.

returns **unspecified**

`dictionary-enumerator` *dict* [generic]
 requires `dict` implement the dictionary protocol.

returns an object implementing the `dictionary-enumerator` protocol allowing the enumeration of the associations contained in `dict`.

2.14.3 Examples

Bigloo's native hashtable and the hoard provided sorted-dictionary implement the dictionary protocol.

```
(dictionary? (create-hashtable))
⇒ #t
```

```
(dictionary? (sorted-dictionary :comparator +number-comparator+))
```

Checking whether a dictionary is empty:

```
(dictionary-empty? (create-hashtable))
⇒ #t
```

```
(dictionary-empty? (hashtable (=> "A" 1)))
⇒ #f
```

Associations can be added to a dictionary:

```
(let ((dict (create-hashtable)))
  (dictionary-put! dict "a" 1)
  (dictionary-put! dict "b" 2)
  (map (lambda (kv) (cons (=>key kv) (=>value kv)))
       (dictionary-enumerable-collect dict +list-collector+)))
⇒ (("a" . 1) ("b" . 2))
```

And removed (assuming the insertions above):

```
(dictionary-remove! dict "a")
(map (lambda (kv) (cons (=>key kv) (=>value kv)))
     (dictionary-enumerable-collect dict +list-collector+))
⇒ (("b" . 2))
```

The value associated with a given key is easily obtained:

```
(let ((dict (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (dictionary-get dict "b")
⇒ 2
```

The `dictionary-update!` method can be used to update an existing value or insert a new value if an existing association does not exist:

```
(let ((dict (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (dictionary-update! dict "b" 0 (lambda (x) (+ x 1)))
  (dictionary-update! dict "d" 0 (lambda (x) (+ x 1)))
  (dictionary-get dict "b")
⇒ 3
  (dictionary-get dict "d")
⇒ 0
```

To obtain the number of associations in a dictionary, call `dictionary-length`:

```
(let ((dict (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (dictionary-length dict)
⇒ 3
```

Querying whether an association with a given key is accomplished with `dictionary-contains?`:

```
(let ((dict (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (dictionary-contains? dict "a")
  => #t

  (dictionary-contains? dict "d")
  => #f
```

Copying a dictionary is accomplished with `dictionary-copy`:

```
(let* ((dict1 (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3)))
      (dict2 (dictionary-copy dict1)))
  (eq? dict1 dict2)
  => #f
  (and (dictionary-contains? dict1 "a")
        (dictionary-contains? dict2 "a"))
  => #t
```

And last, but not least, you can obtain a `dictionary-enumerator` to enumerate the elements of the dictionary:

```
(let ((dict (hashtable (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (dictionary-enumerator? (dictionary-enumerator dict)))
  => #t
```

2.15 dictionary-enumerator

2.15.1 Overview

The `dictionary-enumerator` protocol is an abstraction for enumerating or iterating through the items contained by an object supporting the `dictionary` protocol. These items may be pre-existing or generated on demand. It is very similar to the `enumerator` protocol but provides access to both the keys and values of the dictionary.

2.15.2 API Reference

`dictionary-enumerator? object` [generic]
returns a boolean indicating whether or not `object` supports the `dictionary-enumerator` protocol

`dictionary-enumerator-move-next! object` [generic]
requires `object` support the `dictionary-enumerator` protocol

returns a boolean indicating whether or not `object` has additional items available

modifies `object` such that upon returning `#t` the next item under enumeration is current. Otherwise, `object` remains unmodified.

note `dictionary-enumerator-move-next!` must be called before `dictionary-enumerator-current`. If it is not, `&invalid-state-exception` is thrown.

`dictionary-enumerator-current` *object* [generic]

requires object support the dictionary-enumerator protocol

returns the association found at the `dictionary-enumers` current position or if `dictionary-enumerator-move-next!` has not been called before, `&invalid-state-exception` is thrown.

`dictionary-enumerator-key` *object* [generic]

requires object support the dictionary-enumerator protocol

returns the key found at the `dictionary-enumers` current position or if `dictionary-enumerator-move-next!` has not been called before, `&invalid-state-exception` is thrown.

`dictionary-enumerator-value` *object* [generic]

requires object support the dictionary-enumerator protocol

returns the value found at the `dictionary-enumers` current position or if `dictionary-enumerator-move-next!` has not been called before, `&invalid-state-exception` is thrown.

`dictionary-enumerator-copy` *object* [generic]

requires object support the dictionary-enumerator protocol

returns a copy of the dictionary-enumerator.

2.15.3 Examples

You seldom use `dictionary-enumerator` directly but, instead, use the procedures and macros provided by `dictionary-enumerable`. However, if needed you can use the `dictionary-enumerator` protocol directly.

```
(let ((enumer (enumerable-dictionary-enumerator (hashtable :comparator +number-comparator+
                                                    (=> 'a 1) (=> 'b 2) (=> 'c 3))))
  (let loop ((cont (dictionary-enumerator-move-next! enumer)))
    (when cont
      (print (dictionary-enumerator-value enumer))
      (loop (dictionary-enumerator-move-next! enumer)))))
+ 1
+ 2
+ 3
=> #unspecified
```

2.16 dictionary-enumerable

2.16.1 Overview

`dictionary-enumerable` is a protocol implemented by those dictionary objects that support a notion of enumeration or iteration. By providing an `enumerator`, they gain support for mapping, folding, filtering, and more.

2.16.2 API Reference

dictionary-enumerable? *object* [generic]
returns a boolean indicating whether or not *object* supports the dictionary-enumerable protocol

dictionary-enumerable-enumerator *obj* [generic]
requires *object* support the dictionary-enumerable protocol
returns an dictionary-enumerator

dictionary-enumerable-for-each *proc enum* [syntax]
requires *enum* to either support the dictionary-enumerable or dictionary-enumerator protocol and *proc* be a procedure that accepts two arguments, a key and value.
returns #unspecified

note **dictionary-enumerable-for-each** is applied for the side-effects resulting from applying *proc*.

dictionary-enumerable-map *proc enum* [syntax]
requires *enum* to either support the dictionary-enumerable or dictionary-enumerator protocol and *proc* be a procedure taking the key and value of an association and returning a new association.
returns an enumerator providing the results of applying *proc*

dictionary-enumerable-filter *predicate enum* [syntax]
requires *enum* to either support the dictionary-enumerable or enumerator protocol and *predicate* be a procedure accepting a key and a value and returning a boolean indicating whether or not the association should be retained.
returns an dictionary-enumerator providing the retained elements

dictionary-enumerable-fold *proc seed enum* [syntax]
requires *enum* to either support the dictionary-enumerable or dictionary-enumerator protocols, *proc* to be a procedure compatible with applying it to a seed and a key and value provided by *enum* (it should produce a new seed value), and *seed* should be an appropriate initial seed value for *proc*.
returns the result of folding *proc* over the provided *enum*

note *proc* is applied left to right with the seed resulting from the previous application being used in the next. When no more elements are available, the final seed is returned.

dictionary-enumerable-any? *predicate enum* [syntax]
requires *enum* to either support the dictionary-enumerable or dictionary-enumerator protocols and *predicate* to be a procedure ac-

cepting a key and a value and returning a boolean.

returns a boolean indicating whether or not any of the associations are **#t** for predicate.

dictionary-enumerable-every? *predicate enum* [syntax]
requires *enum* to either support the **dictionary-enumerable** or **dictionary-enumerator** protocols and **predicate** to be a procedure accepting a key and a value and returning a boolean.

returns a boolean indicating whether or not all of the associations are **#t** for predicate.

dictionary-enumerable-append *enum1 enum2 ...* [syntax]
requires *enums* to either support the **dictionary-enumerable** or **dictionary-enumerator** protocols.

returns an **dictionary-enumerator** providing access to the elements in the original *enums* appended left to right.

dictionary-enumerable-collect *enum collector* [syntax]
requires *enum* to either support the **dictionary-enumerable** or **dictionary-enumerator** protocol and *collector* to support the **collector** protocol.

returns a value collected from the given *enum* according to the provided *collector*.

note **dictionary-enumerable-collect** is commonly used to transform the keys and values provided by **dictionary-enumerators** into concrete collections, although their uses are more flexible than that. For example, to collect all of the values from an **dictionary-enumerator** into a list you could do the following:

```
(dictionary-enumerable-collect enumerator +list-collector+)
```

See Section 2.7 [collector], page 12, for more information.

2.16.3 Examples

Bigloo's hashtables and hoard's sorted-dictionary are **dictionary-enumerables**.

```
(dictionary-enumerable? (create-hashtable))
⇒ #t
```

```
(dictionary-enumerable? (sorted-dictionary :comparator +number-comparator+))
```

With **numerable-for-each**, it is possible to iterate over any **dictionary-enumerable**. A few examples follow:

```
(let ((count 0))
  (dictionary-enumerable-for-each (lambda (k v) (set! count (+ v count)))
    (hashtable (=> 'a 1) (=> 'b 2) (=> 'c 3)))
  count)
⇒ 6
```

It is also possible to map a function over `dictionary-enumerables`.

```
(map =>value (dictionary-enumerable-collect (dictionary-enumerable-map (lambda (k v) (=> k (+ v 1))) (hashtable (=> 'a 1) (=> 'b 2) (=> 'c 3) (=> 'd 4) (=> 'e 5))))
=> (2 3 4)
```

Given an appropriate seed and procedure, `dictionary-enumerable-fold` can be used to reduce an `dictionary-enumerable` to a single value.

```
(dictionary-enumerable-fold (lambda (s k v) (+ s v)) 0
  (hashtable (=> 'a 1) (=> 'b 2)
    (=> 'c 3) (=> 'd 4) (=> 'e 5)))
=> 15
```

Filtering of values is also supported.

```
(map =>value (dictionary-enumerable-collect (dictionary-enumerable-filter (lambda (k v) (odd? v))
  (hashtable (=> 'a 1) (=> 'b 2)
    (=> 'c 3) (=> 'd 4) (=> 'e 5))))
  +list-collector+)
=> (2 3 4 5)
```

Or to test whether any or all associations match a give predicate.

```
(dictionary-enumerable-any? (lambda (k v) (odd? v)) (hashtable (=> 'a 1) (=> 'b 2)
  (=> 'c 3) (=> 'd 4) (=> 'e 5)))
=> #t
```

```
(dictionary-enumerable-any? (lambda (k v) (odd? v)) (hashtable (=> 'a 2) (=> 'b 4)
  (=> 'c 6) (=> 'd 8) (=> 'e 10)))
=> #f
```

```
(dictionary-enumerable-every? (lambda (k v) (even? v)) (hashtable (=> 'a 2) (=> 'b 4)
  (=> 'c 6) (=> 'd 8) (=> 'e 10)))
=> #t
```

```
(dictionary-enumerable-every? (lambda (k v) (even? v)) (hashtable (=> 'a 2) (=> 'b 3)
  (=> 'c 6) (=> 'd 8) (=> 'e 10)))
=> #f
```

As shown in the above examples, `dictionary-enumerable-collect` can be used to gather the values of an `dictionary-enumerable` into a new collection, but it is more general than that. In fact, it is a general reduction facility. For full details, See Section 2.7 [collector], page 12.

3 Implementations and Supporting Data Types

Each of the collection implementations and supporting data types are documented here.

3.1 association

3.1.1 Overview

`association` is a simple data structure containing a key and a value. It is used by the dictionary protocol.

3.1.2 API Reference

`association? object` [procedure]
returns a boolean indicating whether or not `object` is an association.

`=> key value` [procedure]
requires `key` and `value` be arbitrary objects.

returns a new association with key `key` and value `value`.

`=>key assoc` [procedure]
requires `assoc` be an association

returns the key of the association.

`=>value assoc` [procedure]
requires `assoc` be an association

returns the value of the association.

`pair->association kv-pair` [procedure]
requires `kv-pair` be a pair with the car the key and the cdr the value

returns an association with key the car of `kv-pair` and the value the cdr of `kv-pair`.

3.1.3 Examples

`association?` tests whether an object is an `association` or not:

```
(association? '(key . value))
⇒ #f
```

```
(association? (=> 'key 'value))
⇒ #t
```

A new association is constructed with `=>`:

```
(let ((assoc (=> 'key 'value)))
  (=>key assoc))
⇒ 'key
```

A pair consisting of a key and value can also be converted to an `association`:

```
(let ((assoc (pair->association '(key . value))))
  (=>key assoc))
```

```
⇒ 'key
```

The key of an association is obtained with `=>key`:

```
(=>key (=> "key" 1))
⇒ "key"
```

The value of an association is obtained with `=>value`:

```
(=>value (=> "key" 1))
⇒ 1
```

3.2 range

3.2.1 Overview

`range` is a data structure representing an integer interval having a start and an end (exclusive) possessing values between the two at a given step. It supports methods for iterating and mapping over the specified interval.

3.2.2 API Reference

`range` implements the `enumerable` protocol. See Section 2.6 [enumerable], page 9.

`range? object` [procedure]

returns a boolean indicating whether or not `object` is a range.

`range [:start 0] :end [:step 1]` [procedure]

requires `:start`, `:end`, and `:step` be integers with `:start <= :end` when `:step` is positive or `:start >= :end` when `:step` is negative. `:step` can not be 0. `:start` and `:step` are optional and default to 0 and 1, respectively.

returns a range with the specified `start`, `end`, and `step`.

`range-for-each proc range` [procedure]

requires `proc` be a procedure compatible with applying it element-wise to the values represented by `range` and `range` be a valid instance of the range data type.

returns `#unspecified`.

note `range-for-each` is applied for the side-effects resulting from applying `proc`.

`range-map proc range` [procedure]

requires `proc` be a procedure compatible with applying it element-wise to the values represented by `range` and `range` be a valid instance of the range data type.

returns a list providing the results of applying `proc` to each integer in `range`

3.2.3 Examples

Creating a `range` is straight forward:

```
(range :end 5) ; [0...4]
(range :start 2 :end 5) ; [2,3,4]
(range :start 2 :end 10 :step 2) ; [2,4,6,8]
```


Once you have a **range**, you can iterate and map over it:

```
(range-for-each print (range :end 5))
+ 0
+ 1
+ 2
+ 3
+ 4
⇒ #unspecified

(range-map (lambda (x) (+ x 1)) (range :end 5))
⇒ (1 2 3 4 5)
```

In addition, **range** implements the **enumerable** protocol. See Section 2.6.3 [enumerable Examples], page 11.

3.3 sorted-bag

3.3.1 Overview

sorted-bag is an implementation of **bag**. It is based on a balanced-binary tree and keeps the elements of the bag sorted.

3.3.2 API Reference

sorted-bag implements the **bag**, **collection**, **extendable**, **mutable**, and **enumerable** protocols. See Section 2.9 [bag], page 18. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

sorted-bag? *object* [procedure]

returns a boolean indicating whether or not *object* is a sorted-bag.

make-sorted-bag *:comparator* [procedure]

requires *:comparator* be an object implementing the **comparator** protocol. *comparator* must be ordered.

returns an instance of **sorted-bag**

sorted-bag *:comparator . items* [procedure]

requires *:comparator* be an object implementing the **comparator** protocol and *items* be a list of objects for which *comparator* is applicable. *comparator* must be ordered.

returns an instance of **sorted-bag**

modifies the returned **sorted-bag** so that it contains *items*

sorted-bag-copy *bag* [procedure]

requires *bag* be a sorted-bag

returns a shallow copy of *bag*.

sorted-bag-empty? *bag* [procedure]

requires *bag* be a sorted-bag

returns a boolean indicating whether or not *bag* contains any items.

sorted-bag-insert! *bag item* [procedure]
requires *bag* be a sorted-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*.

modifies *bag* so that it contains a copy or an additional copy, if one already exists, of *item*.

returns unspecified

sorted-bag-delete! *bag item* [procedure]
requires *bag* be a sorted-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*.

modifies *bag* so that it contains one less copy of *item*. If 0 copies of *item* exist it is removed from *bag*.

returns unspecified

sorted-bag-contains? *bag item* [procedure]
requires *bag* be a sorted-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*

returns a boolean indicating whether or not the *bag* contains *item*.

sorted-bag-count *bag item* [procedure]
requires *bag* be a sorted-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*

returns the number of *items* found in *bag*.

sorted-bag-count-set! *bag item count* [procedure]
requires *bag* be a sorted-bag, *item* be *item* be an arbitrary object supported by the comparator used to create *bag*, and *count* be an integer representing the number of *items* to include in *bag*

modifies *bag* to contain *count* number of *items* unless *count* is less than or equal to 0 which results in the all *items* begin removed from *bag*.

returns #unspecified

bag-length *bag* [procedure]
requires *bag* be a sorted-bag

returns the number of *items* contained in *bag*

3.3.3 Examples

2 procedures are provided for creating a **sorted-bag**. The first creates an empty bag and the other populates the bag with the items passed to it:

```
(enumerable-collect (make-sorted-bag :comparator +number-comparator+)
```

```
+list-collector+)
⇒ ()
```

```
(enumerable-collect (sorted-bag :comparator +number-comparator+ 1 1 1 3)
  +list-collector+)
```

```
⇒ (1 1 1 3)
```

Assuming a sorted-bag has been created as above, to insert an item into a sorted-bag use:

```
(sorted-bag-insert! bag 1)
⇒ #unspecified
```

The count of an item can be obtained with:

```
(sorted-bag-count bag 1)
⇒ 1
```

```
(sorted-bag-count bag 2)
⇒ 0
```

And the count can be explicitly set using:

```
(sorted-bag-count-set! bag 1 4)
⇒ #unspecified
```

```
(sorted-bag-count bag 1)
⇒ 4
```

Or a single copy deleted with:

```
(sorted-bag-delete! bag 1)
⇒ #unspecified
```

```
(sorted-bag-count bag 1)
⇒ 3
```

To check to see if a sorted-bag is empty:

```
(sorted-bag-empty? bag)
⇒ #f
```

To check whether an item is a member of a sorted-bag:

```
(sorted-bag-contains? bag 1)
⇒ #t
```

```
(sorted-bag-contains? bag 3)
⇒ #f
```

And finally, to make a copy:

```
(let ((bag2 (sorted-bag-copy? bag)))
  (eq? bag bag2))
⇒ #f
```

`sorted-bag` also implements the `bag`, `collection`, `mutable`, and `enumerable` protocols. See Section 2.9.3 [bag Examples], page 19. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.4 hash-bag

3.4.1 Overview

hash-bag is an implementation of **bag**. As its name would imply, it is a hashtable-based implementation.

3.4.2 API Reference

hash-bag implements the **bag**, **collection**, **extendable**, **mutable**, and **enumerable** protocols. See Section 2.9 [bag], page 18. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

hash-bag? *object* [procedure]
returns a boolean indicating whether or not **object** is a hash-bag.

make-hash-bag *[:comparator]* [procedure]
requires **:comparator** be an object implementing the **comparator** protocol. **comparator** must be hashable. If it is not provided the default hashtable equality and hash functions are used.

returns an instance of **hash-bag**

hash-bag *[:comparator] . items* [procedure]
requires **:comparator** be an object implementing the **comparator** protocol and **items** be a list of objects for which **comparator** is applicable. **comparator** must be hashable. If it is not provided the default hashtable equality and hash functions are used.

returns an instance of **hash-bag**

modifies the returned **hash-bag** so that it contains **items**

hash-bag-copy *bag* [procedure]
requires **bag** be a hash-bag

returns a shallow copy of **bag**.

hash-bag-empty? *bag* [procedure]
requires **bag** be a hash-bag

returns a boolean indicating whether or not **bag** contains any items.

hash-bag-insert! *bag item* [procedure]
requires **bag** be a hash-bag, and **item** be an arbitrary object supported by the **comparator** used to create **bag**.

modifies **bag** so that it contains a copy or an additional copy, if one already exists, of **item**.

returns unspecified

hash-bag-delete! *bag item* [procedure]
requires *bag* be a hash-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*.

modifies *bag* so that it contains one less copy of *item*. If 0 copies of *item* exist it is removed from *bag*.

returns unspecified

hash-bag-contains? *bag item* [procedure]
requires *bag* be a hash-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*

returns a boolean indicating whether or not the *bag* contains *item*.

hash-bag-count *bag item* [procedure]
requires *bag* be a hash-bag, and *item* be an arbitrary object supported by the comparator used to create *bag*

returns the number of *items* found in *bag*.

hash-bag-count-set! *bag item count* [procedure]
requires *bag* be a hash-bag, *item* be an arbitrary object supported by the comparator used to create *bag*, and *count* be an integer representing the number of *items* to include in *bag*

modifies *bag* to contain *count* number of *items* unless *count* is less than or equal to 0 which results in the all *items* begin removed from *bag*.

returns #unspecified

bag-length *bag* [procedure]
requires *bag* be a hash-bag

returns the number of items contained in *bag*

3.4.3 Examples

2 procedures are provided for creating a **hash-bag**. The first creates an empty bag and the other populates the bag with the items passed to it:

```
(enumerable-collect (make-hash-bag :comparator +number-comparator+
  +list-collector+))
⇒ ()

(enumerable-collect (hash-bag :comparator +number-comparator+ 1 1 1 3)
  +list-collector+)
⇒ (1 1 1 3)
```

Assuming a hash-bag has been created as above, to insert an item into a hash-bag use:

```
(hash-bag-insert! bag 1)
```

```
⇒ #unspecified
```

The count of an item can be obtained with:

```
(hash-bag-count bag 1)
⇒ 1
```

```
(hash-bag-count bag 2)
⇒ 0
```

And the count can be explicitly set using:

```
(hash-bag-count-set! bag 1 4)
⇒ #unspecified
```

```
(hash-bag-count bag 1)
⇒ 4
```

Or a single copy deleted with:

```
(hash-bag-delete! bag 1)
⇒ #unspecified
```

```
(hash-bag-count bag 1)
⇒ 3
```

To check to see if a hash-bag is empty:

```
(hash-bag-empty? bag)
⇒ #f
```

To check whether an item is a member of a hash-bag:

```
(hash-bag-contains? bag 1)
⇒ #t
```

```
(hash-bag-contains? bag 3)
⇒ #f
```

And finally, to make a copy:

```
(let ((bag2 (hash-bag-copy? bag)))
  (eq? bag bag2))
⇒ #f
```

`hash-bag` also implements the `bag`, `collection`, `mutable`, and `enumerable` protocols. See Section 2.9.3 [bag Examples], page 19. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.5 sorted-set

3.5.1 Overview

`sorted-set` is an implementation of `set`. It is based on a balanced-binary tree and keeps the elements of the set sorted.

3.5.2 API Reference

`sorted-set` implements the `set`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.10 [set], page 20. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

sorted-set? *object* [procedure]
 returns a boolean indicating whether or not *object* is a sorted-set.

make-sorted-set *:comparator* [procedure]
 requires *:comparator* be an object implementing the *comparator* protocol.
 comparator must be ordered.

 returns an instance of *sorted-set*

sorted-set *:comparator . items* [procedure]
 requires *:comparator* be an object implementing the *comparator* protocol and *items*
 be a list of objects for which *comparator* is applicable. *comparator* must be ordered.

 returns an instance of *sorted-set*

 modifies the returned *sorted-set* so that it contains *items*

sorted-set-copy *set* [procedure]
 requires *set* be a sorted-set

 returns a shallow copy of *set*.

sorted-set-empty? *set* [procedure]
 requires *set* be a sorted-set

 returns a boolean indicating whether or not *set* contains any items.

sorted-set-insert! *set item* [procedure]
 requires *set* be a sorted-set, and *item* be an arbitrary object supported by the *comparator* used to create *set*.

 modifies *set* so that it contains a copy or an additional copy, if one already exists, of *item*.

 returns unspecified

sorted-set-delete! *set item* [procedure]
 requires *set* be a sorted-set, and *item* be an arbitrary object supported by the *comparator* used to create *set*.

 modifies *set* so that it contains one less copy of *item*. If 0 copies of *item* exist it is removed from *set*.

 returns unspecified

sorted-set-contains? *set item* [procedure]
 requires *set* be a sorted-set, and *item* be an arbitrary object supported by the *comparator* used to create *set*

 returns a boolean indicating whether or not the *set* contains *item*.

set-length *set* [procedure]
requires *set* be a sorted-set

returns the number of items contained in *set*

3.5.3 Examples

2 procedures are provided for creating a **sorted-set**. The first creates an empty set and the other populates the set with the items passed to it:

```
(enumerable-collect (make-sorted-set :comparator +number-comparator+)
  +list-collector+)
⇒ ()

(enumerable-collect (sorted-set :comparator +number-comparator+ 1 1 1 3)
  +list-collector+)

⇒ (1 3)
```

Assuming a sorted-set has been created as above, to insert an item into a sorted-set use:

```
(sorted-set-insert! set 1)
⇒ #unspecified
```

Or deleted with:

```
(sorted-set-delete! set 1)
⇒ #unspecified
```

To check to see if a sorted-set is empty:

```
(sorted-set-empty? set)
⇒ #f
```

To check whether an item is a member of a sorted-set:

```
(sorted-set-contains? set 1)
⇒ #t

(sorted-set-contains? set 3)
⇒ #f
```

And finally, to make a copy:

```
(let ((set2 (sorted-set-copy? set)))
  (eq? set set2))
⇒ #f
```

sorted-set also implements the **set**, **collection**, **mutable**, and **enumerable** protocols. See Section 2.10.3 [set Examples], page 22. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.6 hash-set

3.6.1 Overview

hash-set is an implementation of **set**. As its name would imply, it is a hashtable-based implementation.

3.6.2 API Reference

`hash-set` implements the `set`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.10 [`set`], page 20. See Section 2.1 [`collection`], page 3. See Section 2.3 [`extendable`], page 6. See Section 2.4 [`mutable`], page 7. See Section 2.6 [`enumerable`], page 9.

`hash-set? object` [procedure]

returns a boolean indicating whether or not `object` is a hash-set.

`make-hash-set [:comparator]` [procedure]

requires `comparator` be an object implementing the `comparator` protocol. `comparator` must be hashable. If it is not provided the default hashtable equality and hash functions are used.

returns an instance of `hash-set`

`hash-set [:comparator] . items` [procedure]

requires `comparator` be an object implementing the `comparator` protocol and `items` be a list of objects for which `comparator` is applicable. `comparator` must be hashable. If it is not provided the default hashtable equality and hash functions are used.

returns an instance of `hash-set`

modifies the returned `hash-set` so that it contains `items`

`hash-set-copy set` [procedure]

requires `set` be a hash-set

returns a shallow copy of `set`.

`hash-set-empty? set` [procedure]

requires `set` be a hash-set

returns a boolean indicating whether or not `set` contains any items.

`hash-set-insert! set item` [procedure]

requires `set` be a hash-set, and `item` be an arbitrary object supported by the comparator used to create `set`.

modifies `set` so that it contains a copy or an additional copy, if one already exists, of `item`.

returns unspecified

`hash-set-delete! set item` [procedure]

requires `set` be a hash-set, and `item` be an arbitrary object supported by the comparator used to create `set`.

modifies `set` so that it contains one less copy of `item`. If 0 copies of `item` exist it is removed from `set`.

returns unspecified

hash-set-contains? *set item* [procedure]

requires *set* be a hash-set, and *item* be an arbitrary object supported by the comparator used to create *set*

returns a boolean indicating whether or not the *set* contains *item*.

set-length *set* [procedure]

requires *set* be a hash-set

returns the number of items contained in *set*

3.6.3 Examples

2 procedures are provided for creating a **hash-set**. The first creates an empty set and the other populates the set with the items passed to it:

```
(enumerable-collect (make-hash-set :comparator +number-comparator+)
  +list-collector+)
⇒ ()
```

```
(enumerable-collect (hash-set :comparator +number-comparator+ 1 1 1 3)
  +list-collector+)
⇒ (1 3)
```

Assuming a hash-set has been created as above, to insert an item into a hash-set use:

```
(hash-set-insert! set 1)
⇒ #unspecified
```

Or deleted with:

```
(hash-set-delete! set 1)
⇒ #unspecified
```

To check to see if a hash-set is empty:

```
(hash-set-empty? set)
⇒ #f
```

To check whether an item is a member of a hash-set:

```
(hash-set-contains? set 1)
⇒ #t
```

```
(hash-set-contains? set 3)
⇒ #f
```

And finally, to make a copy:

```
(let ((set2 (hash-set-copy? set)))
  (eq? set set2))
⇒ #f
```

hash-set also implements the **set**, **collection**, **mutable**, and **enumerable** protocols. See Section 2.10.3 [set Examples], page 22. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7, See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.7 stretchy-vector

3.7.1 Overview

stretchy-vector is an auto-resizing vector; it grows and shrinks as items are added and deleted. It provides amortized constant time access.

3.7.2 API Reference

stretchy-vector implements the `collection`, `extendable`, `indexable`, `mutable`, and `enumerable` protocols. See Section 2.10 [set], page 20. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.2 [indexable], page 4. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

stretchy-vector? *object* [procedure]
returns a boolean indicating whether or not *object* is a stretchy-vector.

make-stretchy-vector *len* [:*capacity* *len*] [*fill*] [procedure]
requires *len* be an integer specifying the requested initial vector length, *:capacity* the initial capacity, and *fill* be an arbitrary value to initialize each element. If not provided, *fill* defaults to `#unspecified` and *:capacity* is equal to *len*, unless *len* is less than the minimal stretchy-vector capacity then it is the minimal stretchy-vector capacity (i.e., 16).
returns a stretchy-vector with an initial capacity of at least *len*.

stretchy-vector . *elems* [procedure]
requires *elems* be a list of arbitrary objects.
returns a stretchy-vector with initial elements *elems*.

stretchy-vector-length *vec* [procedure]
requires *vec* be a stretchy-vector.
returns the length of the stretchy-vector *vec*.

stretchy-vector-expand! *vec len* [procedure]
requires *vec* be a stretchy-vector and *len* be a positive integer.
returns a *vec* expanded to at least *len*.

stretchy-vector-resize! *vec new-len* [procedure]
requires *vec* be a stretchy-vector and *new-len* be a positive integer.
modifies *vec* such that if *new-len* is larger than the the current length then all of the new elements are set to `#unspecified`, and if *new-len* is smaller than the current length, the elements greater than or equal to *new-len* are dropped.
returns a *vec* resized to *new-len*.

stretchy-vector-capacity *vec* [procedure]
requires *vec* be a stretchy-vector.

returns the capacity of the stretchy-vector *vec*.

stretchy-vector-set! *vec index val* [procedure]
requires *vec* be a stretchy-vector, *index* be a positive integer, and *val* be an arbitrary object.

modifies *vec* so that the value at *index* is *value*. This may require expanding the vect, if it currently does not contain *index*.

returns #unspecified.

stretchy-vector-ref *vec index* [procedure]
requires *vec* be a stretchy-vector and *index* be a positive integer.

returns the value found at *index* or throws &invalid-index-exception if *index* is not in *vec*.

list->stretchy-vector *lst* [procedure]
requires *lst* be a list of arbitrary objects.

returns a stretchy-vector containing the elements of *lst*.

stretchy-vector->list *vec* [procedure]
requires *vec* be a stretchy-vector of arbitrary objects.

returns a list containing the elements of *vec*.

vector->stretchy-vector *vec* [procedure]
requires *vec* be a vector of arbitrary objects.

returns a stretchy-vector containing the elements of *vec*.

stretchy-vector->vector *vec* [procedure]
requires *vec* be a stretchy-vector of arbitrary objects.

returns a vector containing the elements of *vec*.

stretchy-vector-map *proc vec* [procedure]
requires *proc* be a single argument procedure compatible with being called element-wise to *vec* and *vec* be a stretchy-vector of arbitrary objects.

returns a new stretchy-vector containing the results of applying *proc* to the elements of *vec*.

stretchy-vector-map *proc vec* [procedure]
requires *proc* be a single argument procedure compatible with being called element-wise to *vec* and *vec* be a stretchy-vector of arbitrary objects.

modifies the elements of `vec` so that they are the value obtained by applying `proc` to each element.

returns `vec`.

`stretchy-vector-copy vec` [procedure]

requires `vec` be a stretchy-vector of arbitrary objects.

returns a shallow copy of `vec`.

`stretchy-vector-extend! vec val` [procedure]

requires `vec` be a stretchy-vector of arbitrary objects and `val` be an arbitrary object.

modifies `vec` by adding `val` to the end.

returns `#unspecified`.

`stretchy-vector-remove! vec` [procedure]

requires `vec` be a stretchy-vector of arbitrary objects

modifies `vec` by removing the last element.

returns the element removed from `vec`.

`stretchy-vector-append vec1 vec2` [procedure]

requires `vec1` and `vec2` be stretchy-vectors of arbitrary objects

returns a new stretchy-vector containing the elements of `vec1` followed by those in `vec2`.

`stretchy-vector-append! vec1 vec2` [procedure]

requires `vec1` and `vec2` be stretchy-vectors of arbitrary objects

modifies `vec1` so that its current elements are followed by the elements of `vec2`.

returns `#unspecified`.

3.7.3 Examples

To test whether an object is a `stretchy-vector` use the predicate `stretchy-vector?`:

```
(stretchy-vector? (stretchy-vector))
⇒ #t
```

```
(stretchy-vector? (vector))
⇒ #f
```

Two procedures are used to create `stretchy-vectors`. The first creates an empty vector of a specified size with an optional fill value, and the second allows for the creation of a stretchy vector containing the passed values.

```
(let ((vec (make-stretchy-vector 3 9)))
  (enumerable-collect vec +list-collector+))
```

```

⇒ (9 9 9)

(let ((vec (stretchy-vector 1 2 3)))
  (enumerable-collect vec +list-collector+))
⇒ (1 2 3)

```

As with regular vectors, you can reference and set the values of individual `stretchy-vector` elements:

```

(let ((vec (stretchy-vector 1 2 3)))
  (stretchy-vector-ref vec 1))
⇒ 2

(let ((vec (stretchy-vector 4 5 6)))
  (stretchy-vector-set! vec 2 7)
  (stretchy-vector-ref vec 2))
⇒ 7

```

The length of a `stretchy-vector` is determined with `stretchy-vector-length`:

```

(stretchy-vector-length (stretchy-vector 1 2 3 4 5))
⇒ 5

```

A shallow copy of a `stretchy-vector` is obtained with `stretchy-vector-copy`:

```

(let* ((vec1 (stretchy-vector 1 2 3))
      (vec2 (stretchy-vector-copy vec1)))
  (eq? vec1 vec2))
⇒ #f
(equal? vec2 vec2)
⇒ #t

```

`stretchy-vector` also implements the `collection`, `mutable`, `indexable`, `extendable`, `enumerable`, and `dictionary-enumerable` protocols. See Section 2.1.3 [collection Examples], page 4. See Section 2.4.3 [mutable Examples], page 7. See Section 2.2.3 [indexable Examples], page 5. See Section 2.3.3 [extendable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11. See Section 2.16.3 [dictionary-enumerable Examples], page 35.

3.8 contiguous-stack

3.8.1 Overview

`contiguous-stack` is a contiguous implementation of a stack, a last-in-first-out data structure, with a finite capacity.

3.8.2 API Reference

`contiguous-stack` implements the `stack`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.12 [stack], page 25. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

contiguous-stack? *object* [procedure]
returns a boolean indicating whether or not *object* is a contiguous-stack.

make-contiguous-stack *:capacity* [procedure]
requires *:capacity* be a positive integer specifying the maximum capacity of the stack.

returns a new `contiguous-stack` with a capacity of `:capacity`

`contiguous-stack :capacity . items` [procedure]

requires `:capacity` be a positive integer specifying the maximum capacity of the stack and `items` be a list of items to initialize the stack with.

returns a new `contiguous-stack` with a capacity of `:capacity` containing `items` pushed from right-to-left onto the stack. If the number of `items` is greater than `:capacity`, `&invalid-argument-exception` is thrown.

`contiguous-stack-copy stack` [procedure]

requires `stack` be a `contiguous-stack`.

returns a shallow copy of `stack`.

`contiguous-stack-empty? stack` [procedure]

requires `stack` be a `contiguous-stack`.

returns a boolean indicating whether or not the stack is empty.

`contiguous-stack-length stack` [procedure]

requires `stack` be a `contiguous-stack`.

returns the number of items on the stack (i.e., `length`) .

`contiguous-stack-capacity stack` [procedure]

requires `stack` be a `contiguous-stack`.

returns the maximum size (i.e., `length`) of `stack`.

`contiguous-stack-push! stack item` [procedure]

requires `stack` be a `contiguous-stack` and `item` be an arbitrary object.

modifies `stack` by pushing `item` on the top of the stack.

returns `#unspecified` or if there is no free capacity, throws `&invalid-state-exception`.

`contiguous-stack-pop! stack` [procedure]

requires `stack` be a `contiguous-stack`.

modifies `stack` by removing the item on the top of the stack.

returns the item removed from `stack` or if `stack` is empty, throws `&invalid-state-exception`.

`contiguous-stack-top stack` [procedure]

requires `stack` be a `contiguous-stack`.

returns the top item from `stack` or if `stack` is empty, throws `&invalid-state-exception`.

3.8.3 Examples

2 procedures are provided for creating a `contiguous-stack`: The first creates an empty stack and the other populates the stack with the items passed to it:

```
(enumerable-collect (make-contiguous-stack :capacity 4)
  +list-collector+)
⇒ ()

(enumerable-collect (contiguous-stack :capacity 4 1 2 3)
  +list-collector+)
⇒ (1 2 3)
```

An item can be pushed onto the stack with `contiguous-stack-push!`:

```
(let ((stack (contiguous-stack :capacity 4)))
  (contiguous-stack-push! stack 1)
  (contiguous-stack-top stack))
⇒ 1
```

The top item of the stack can be non-destructively obtained with `contiguous-stack-top`:

```
(let ((stack (contiguous-stack :capacity 4 1 2 3)))
  (contiguous-stack-top stack))
⇒ 1
```

The top item can be removed from the stack with `contiguous-stack-pop!`:

```
(let ((stack (contiguous-stack :capacity 4 1 2 3)))
  (contiguous-stack-pop! stack)
  (contiguous-stack-top stack))
⇒ 2
```

To test if a stack is empty, use `contiguous-stack-empty?`:

```
(contiguous-stack-empty? (contiguous-stack :capacity 4))
⇒ #t

(contiguous-stack-empty? (contiguous-stack :capacity 4 1 2))
⇒ #f
```

The size or length of a stack is obtained with `contiguous-stack-length`:

```
(contiguous-stack-length (contiguous-stack :capacity 4 1 2))
⇒ 2
```

The capacity or maximum length of a stack is obtained with `contiguous-stack-capacity`:

```
(contiguous-stack-capacity (contiguous-stack :capacity 4 1 2))
⇒ 4
```

To make a shallow copy a stack, use `contiguous-stack-copy`:

```
(let* ((stack1 (contiguous-stack :capacity 4 1 2))
      (stack2 (contiguous-stack-copy stack1)))
  (eq? stack1 stack2))
⇒ #f
```

`contiguous-stack` also implements the `stack`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.12.3 [stack Examples], page 26. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.9 linked-stack

3.9.1 Overview

`linked-stack` is a linked-list based implementation of a stack, a last-in-first-out data structure.

3.9.2 API Reference

`linked-stack` implements the `stack`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.12 [stack], page 25. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

`linked-stack?` *object* [procedure]

returns a boolean indicating whether or not *object* is a linked-stack.

`make-linked-stack` [procedure]

returns a new empty linked-stack.

`linked-stack . items` [procedure]

requires *items* be a list of items to initialize the stack with.

returns a new linked-stack containing *items* pushed from right-to-left onto the stack.

`linked-stack-copy stack` [procedure]

requires *stack* be a linked-stack.

returns a shallow copy of *stack*.

`linked-stack-empty? stack` [procedure]

requires *stack* be a linked-stack.

returns a boolean indicating whether or not the stack is empty.

`linked-stack-length stack` [procedure]

requires *stack* be a linked-stack.

returns the number of items on the stack (i.e., length) .

`linked-stack-push! stack item` [procedure]

requires *stack* be a linked-stack and *item* be an arbitrary object.

modifies *stack* by pushing *item* on the top of the stack.

returns #unspecified.

`linked-stack-pop! stack` [procedure]

requires *stack* be a linked-stack.

modifies `stack` by removing the item on the top of the stack.

returns the item removed from `stack` or if `stack` is empty, throws `&invalid-state-exception`.

`linked-stack-top stack` [procedure]
requires `stack` be a `linked-stack`.

returns the top item from `stack` or if `stack` is empty, throws `&invalid-state-exception`.

3.9.3 Examples

2 procedures are provided for creating a `linked-stack`: The first creates an empty stack and the other populates the stack with the items passed to it:

```
(enumerable-collect (make-linked-stack)
  +list-collector+)
⇒ ()

(enumerable-collect (linked-stack 1 2 3)
  +list-collector+)
⇒ (1 2 3)
```

An item can be pushed onto the stack with `linked-stack-push!`:

```
(let ((stack (linked-stack)))
  (linked-stack-push! stack 1)
  (linked-stack-top stack))
⇒ 1
```

The top item of the stack can be non-destructively obtained with `linked-stack-top`:

```
(let ((stack (linked-stack 1 2 3)))
  (linked-stack-top stack))
⇒ 1
```

The top item can be removed from the stack with `linked-stack-pop!`:

```
(let ((stack (linked-stack 1 2 3)))
  (linked-stack-pop! stack)
  (linked-stack-top stack))
⇒ 2
```

To test if a stack is empty, use `linked-stack-empty?`:

```
(linked-stack-empty? (linked-stack))
⇒ #t

(linked-stack-empty? (linked-stack 1 2))
⇒ #f
```

The size or length of a stack is obtained with `linked-stack-length`:

```
(linked-stack-length (linked-stack 1 2))
⇒ 2
```

To make a shallow copy a stack, use `linked-stack-copy`:

```
(let* ((stack1 (linked-stack 1 2))
      (stack2 (linked-stack-copy stack1)))
  (eq? stack1 stack2))
⇒ #f
```

`linked-stack` also implements the `stack`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.12.3 [stack Examples], page 26. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.10 contiguous-queue

3.10.1 Overview

`contiguous-queue` is a contiguous implementation of a queue, a last-in-first-out data structure, with a finite capacity.

3.10.2 API Reference

`contiguous-queue` implements the `queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.11 [queue], page 23. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

`contiguous-queue? object` [procedure]
returns a boolean indicating whether or not `object` is a contiguous-queue.

`make-contiguous-queue :capacity` [procedure]
requires `:capacity` be a positive integer specifying the maximum capacity of the queue.
returns a new `contiguous-queue` with a capacity of `:capacity`

`contiguous-queue :capacity . items` [procedure]
requires `:capacity` be a positive integer specifying the maximum capacity of the queue and `items` be a list of items to initialize the queue with.
returns a new `contiguous-queue` with a capacity of `:capacity` containing `items` enqueued from left-to-right onto the queue. If the number of `items` is greater than `:capacity`, `&invalid-argument-exception` is thrown.

`contiguous-queue-copy queue` [procedure]
requires `queue` be a `contiguous-queue`.
returns a shallow copy of `queue`.

`contiguous-queue-empty? queue` [procedure]
requires `queue` be a `contiguous-queue`.
returns a boolean indicating whether or not the queue is empty.

`contiguous-queue-length queue` [procedure]
requires `queue` be a `contiguous-queue`.
returns the length the queue.

contiguous-queue-capacity *queue* [procedure]
requires *queue* be a contiguous-queue.

returns the maximum size length of *queue*.

contiguous-queue-enqueue! *queue item* [procedure]
requires *queue* be a contiguous-queue and *item* be an arbitrary object.

modifies *queue* by placing *item* on the end of the queue.

returns #unspecified or if there is no free capacity, throws &invalid-state-exception.

contiguous-queue-dequeue! *queue* [procedure]
requires *queue* be a contiguous-queue.

modifies *queue* by removing the first item from the queue.

returns the item removed from *queue* or if *queue* is empty, throws &invalid-state-exception.

contiguous-queue-first *queue* [procedure]
requires *queue* be a contiguous-queue.

returns the first item from *queue* or if *queue* is empty, throws &invalid-state-exception.

3.10.3 Examples

2 procedures are provided for creating a contiguous-queue: The first creates an empty queue and the other populates the queue with the items passed to it:

```
(enumerable-collect (make-contiguous-queue :capacity 4)
  +list-collector+)
⇒ ()
```

```
(enumerable-collect (contiguous-queue :capacity 4 1 2 3)
  +list-collector+)
⇒ (1 2 3)
```

An item can be placed onto the queue with **contiguous-queue-enqueue!**:

```
(let ((queue (contiguous-queue :capacity 4 1 2 3)))
  (contiguous-queue-enqueue! queue 4)
  (contiguous-queue-first queue))
⇒ 1
```

The first item of the queue can be non-destructively obtained with **contiguous-queue-first**:

```
(let ((queue (contiguous-queue :capacity 4 1 2 3)))
  (contiguous-queue-first queue))
⇒ 1
```

The first item can be removed from the queue with **contiguous-queue-dequeue!**:

```
(let ((queue (contiguous-queue :capacity 4 1 2 3)))
```

```
(contiguous-queue-dequeue! queue)
(contiguous-queue-first queue))
⇒ 2
```

To test if a queue is empty, use `contiguous-queue-empty?`:

```
(contiguous-queue-empty? (contiguous-queue :capacity 4))
⇒ #t
```

```
(contiguous-queue-empty? (contiguous-queue :capacity 4 1 2))
⇒ #f
```

The size or length of a queue is obtained with `contiguous-queue-length`:

```
(contiguous-queue-length (contiguous-queue :capacity 4 1 2))
⇒ 2
```

The capacity or maximum length of a queue is obtained with `contiguous-queue-capacity`:

```
(contiguous-queue-capacity (contiguous-queue-capacity :capacity 4 1 2))
⇒ 4
```

To make a shallow copy a queue, use `contiguous-queue-copy`:

```
(let* ((queue1 (contiguous-queue :capacity 4 1 2))
      (queue2 (contiguous-queue-copy queue1)))
  (eq? queue1 queue2))
⇒ #f
```

`contiguous-queue` also implements the `queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.11.3 [queue Examples], page 24. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.11 linked-queue

3.11.1 Overview

`linked-queue` is a linked-list based implementation of a queue, a last-in-first-out data structure.

3.11.2 API Reference

`linked-queue` implements the `queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.11 [queue], page 23. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

linked-queue? *object* [procedure]
returns a boolean indicating whether or not *object* is a linked-queue.

make-linked-queue [procedure]
returns a new linked-queue.

linked-queue . *items* [procedure]
requires *items* be a list of items to initialize the queue with.

returns a new linked-queue containing *items* enqueued from left-to-right onto the queue.

linked-queue-copy *queue* [procedure]
requires *queue* be a linked-queue.

returns returns a shallow copy of *queue*.

linked-queue-empty? *queue* [procedure]
requires *queue* be a linked-queue.

returns returns a boolean indicating whether or not the *queue* is empty.

linked-queue-length *queue* [procedure]
requires *queue* be a linked-queue.

returns returns the length the *queue*.

linked-queue-enqueue! *queue item* [procedure]
requires *queue* be a linked-queue and *item* be an arbitrary object.

modifies *queue* by placing *item* on the end of the *queue*.

returns #unspecified.

linked-queue-dequeue! *queue* [procedure]
requires *queue* be a linked-queue.

modifies *queue* by removing the first item from the *queue*.

returns the item removed from *queue* or if *queue* is empty, throws `&invalid-state-exception`.

linked-queue-first *queue* [procedure]
requires *queue* be a linked-queue.

returns the first item from *queue* or if *queue* is empty, throws `&invalid-state-exception`.

3.11.3 Examples

2 procedures are provided for creating a **linked-queue**: The first creates an empty *queue* and the other populates the *queue* with the items passed to it:

```
(enumerable-collect (make-linked-queue)
  +list-collector+)
⇒ ()

(enumerable-collect (linked-queue 1 2 3)
  +list-collector+)
⇒ (1 2 3)
```

An item can be placed onto the *queue* with **linked-queue-enqueue!**:

```
(let ((queue (linked-queue 1 2 3)))
  (linked-queue-enqueue! queue 4)
  (linked-queue-first queue))
```

```
⇒ 1
```

The first item of the queue can be non-destructively obtained with `linked-queue-first`:

```
(let ((queue (linked-queue 1 2 3)))
  (linked-queue-first queue))
⇒ 1
```

The first item can be removed from the queue with `linked-queue-dequeue!`:

```
(let ((queue (linked-queue 1 2 3)))
  (linked-queue-dequeue! queue)
  (linked-queue-first queue))
⇒ 2
```

To test if a queue is empty, use `linked-queue-empty?`:

```
(linked-queue-empty? (linked-queue))
⇒ #t

(linked-queue-empty? (linked-queue 1 2))
⇒ #f
```

The size or length of a queue is obtained with `linked-queue-length`:

```
(linked-queue-length (linked-queue 1 2))
⇒ 2
```

To make a shallow copy a queue, use `linked-queue-copy`:

```
(let* ((queue1 (linked-queue 1 2))
      (queue2 (linked-queue-copy queue1)))
  (eq? queue1 queue2))
⇒ #f
```

`linked-queue` also implements the `queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.11.3 [queue Examples], page 24. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.12 binary-heap

3.12.1 Overview

A `binary-heap` is an implementation of a priority queue featuring contiguous storage and a specified maximum size or capacity.

3.12.2 API Reference

`binary-heap` implements the `priority-queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.13 [priority-queue], page 27. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

`binary-heap?` *object* [procedure]
returns a boolean indicating whether or not *object* is a `binary-heap`.

`make-binary-heap` *:capacity* *:comparator* [procedure]
requires *:capacity* be a positive integer specifying the maximum capacity of the priority queue and *:comparator* be an object implementing the `comparator` protocol.
:comparator must be ordered.

returns a new `binary-heap` with a capacity of `:capacity`

`binary-heap :capacity :comparator . items` [procedure]

requires `:capacity` be a positive integer specifying the maximum capacity of the priority queue, `:comparator` be an object implementing the `comparator` protocol, and `items` be a list of items to initialize the queue with. `:comparator` must be ordered.

returns a new `binary-heap` with a capacity of `:capacity` containing `items` enqueued on the priority queue. If the number of `items` is greater than `:capacity`, `&invalid-argument-exception` is thrown.

`binary-heap-copy pqueue` [procedure]

requires `pqueue` be a `binary-heap`.

returns a shallow copy of `pqueue`.

`binary-heap-empty? pqueue` [procedure]

requires `pqueue` be a `binary-heap`.

returns a boolean indicating whether or not the priority queue is empty.

`binary-heap-length pqueue` [procedure]

requires `pqueue` be a `binary-heap`.

returns the length of the priority queue.

`binary-heap-capacity pqueue` [procedure]

requires `pqueue` be a `binary-heap`.

returns the maximum size or length of `queue`.

`binary-heap-enqueue! pqueue item` [procedure]

requires `pqueue` be a `binary-heap` and `item` be an arbitrary object.

modifies `pqueue` by placing `item` on the priority queue.

returns `#unspecified` or if there is no free capacity, throws `&invalid-state-exception`.

`binary-heap-dequeue! pqueue` [procedure]

requires `pqueue` be a `binary-heap`.

modifies `pqueue` by removing the highest (or lowest, depending on the comparator) priority item from the priority queue.

returns the item removed from `pqueue` or if `pqueue` is empty, throws `&invalid-state-exception`.

binary-heap-first *pqueue* [procedure]
requires *pqueue* be a **binary-heap**.

returns the the highest (or lowest, depending on the comparator) priority item from *pqueue* or if *pqueue* is empty, throws **&invalid-state-exception**.

3.12.3 Examples

2 procedures are provided for creating a **binary-heap**: The first creates an empty queue and the other populates the queue with the items passed to it:

```
(enumerable-collect (make-binary-heap :capacity 4 :comparator +number-comparator+)
  +list-collector+)
⇒ ()

(enumerable-collect (binary-heap :capacity 4 :comparator +number-comparator+ 1 2 3)
  +list-collector+)
⇒ (1 2 3)
```

An item can be placed onto the priority queue with **binary-heap-enqueue!**:

```
(let ((pqueue (binary-heap :capacity 4 :comparator +number-comparator+ 1 2 3)))
  (binary-heap-enqueue! pqueue 4)
  (binary-heap-first pqueue))
⇒ 1
```

The highest (or lowest, depending on the comparator) priority item of the priority queue can be non-destructively obtained with **binary-heap-first**:

```
(let ((pqueue (binary-heap :capacity 4 :comparator +number-comparator+ 1 2 3)))
  (binary-heap-first pqueue))
⇒ 1
```

The highest (or lowest, depending on the comparator) priority item can be removed from the priority queue with **binary-heap-dequeue!**:

```
(let ((pqueue (binary-heap :capacity 4 :comparator +number-comparator+ 1 2 3)))
  (binary-heap-dequeue! pqueue)
  (binary-heap-first pqueue))
⇒ 2
```

To test if a priority queue is empty, use **binary-heap-empty?**:

```
(binary-heap-empty? (binary-heap :capacity 4 :comparator +number-comparator+))
⇒ #t

(binary-heap-empty? (binary-heap :capacity 4 :comparator +number-comparator+ 1 2))
⇒ #f
```

The size or length of a priority queue is obtained with **binary-heap-length**:

```
(binary-heap-length (binary-heap :capacity 4 :comparator +number-comparator+ 1 2))
⇒ 2
```

The capacity or maximum length of a priority queue is obtained with **binary-heap-capacity**:

```
(binary-heap-capacity (binary-heap :capacity 4 :comparator +number-comparator+ 1 2))
⇒ 4
```

To make a shallow copy of a priority queue, use **binary-heap-copy**:

```
(let* ((pqueue1 (binary-heap :capacity 4 :comparator +number-comparator+ 1 2))
      (pqueue2 (binary-heap-copy pqueue1)))
  (eq? pqueue1 pqueue2))
⇒ #f
```

`binary-heap` also implements the `priority-queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.13.3 [priority-queue Examples], page 28. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.13 pairing-heap

3.13.1 Overview

3.13.2 API Reference

`pairing-heap` implements the `priority-queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.13 [priority-queue], page 27. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

`pairing-heap?` *object* [procedure]

returns a boolean indicating whether or not *object* is a `pairing-heap`.

`make-pairing-heap` *:comparator* [procedure]

requires *:comparator* be an object implementing the `comparator` protocol.
:comparator must be ordered.

returns a new `pairing-heap`.

`pairing-heap` *:comparator . items* [procedure]

requires *:comparator* be an object implementing the `comparator` protocol and *items* be a list of items to initialize the priority queue with. *:comparator* must be ordered.

returns a new `pairing-heap` containing *items* enqueued from left-to-right onto the priority queue.

`pairing-heap-copy` *queue* [procedure]

requires *queue* be a `pairing-heap`.

returns returns a shallow copy of *queue*.

`pairing-heap-empty?` *pqueue* [procedure]

requires *pqueue* be a `pairing-heap`.

returns returns a boolean indicating whether or not the priority queue is empty.

`pairing-heap-length` *pqueue* [procedure]

requires *pqueue* be a `pairing-heap`.

returns returns the length the priority queue.

`pairing-heap-enqueue!` *pqueue item* [procedure]

requires *pqueue* be a `pairing-heap` and *item* be an arbitrary object.

modifies *pqueue* by placing item on the priority queue.

returns #unspecified.

pairing-heap-dequeue! *pqueue* [procedure]
requires *pqueue* be a **pairing-heap**.

modifies *pqueue* by removing the highest(or lowest, depending on the comparator) priority item from the priority queue.

returns the item removed from *pqueue* or if *pqueue* is empty, throws &invalid-state-exception.

pairing-heap-first *pqueue* [procedure]
requires *pqueue* be a **pairing-heap**.

returns the highest(or lowest, depending on the comparator) item from *pqueue* or if *pqueue* is empty, throws &invalid-state-exception.

3.13.3 Examples

2 procedures are provided for creating a **pairing-heap**: The first creates an empty queue and the other populates the queue with the items passed to it:

```
(enumerable-collect (make-pairing-heap :comparator +number-comparator+)
  +list-collector+)
⇒ ()

(enumerable-collect (pairing-heap :comparator +number-comparator+ 1 2 3)
  +list-collector+)
⇒ (1 3 2)
```

An item can be placed onto the priority queue with **pairing-heap-enqueue!**:

```
(let ((pqueue (pairing-heap :comparator +number-comparator+ 1 2 3)))
  (pairing-heap-enqueue! pqueue 4)
  (pairing-heap-first pqueue))
⇒ 1
```

The highest(or lowest, depending on the comparator) priority item of the queue can be non-destructively obtained with **pairing-heap-first**:

```
(let ((pqueue (pairing-heap :comparator +number-comparator+ 1 2 3)))
  (pairing-heap-first pqueue))
⇒ 1
```

The highest(or lowest, depending on the comparator) priority item can be removed from the priority queue with **pairing-heap-dequeue!**:

```
(let ((pqueue (pairing-heap :comparator +number-comparator+ 1 2 3)))
  (pairing-heap-dequeue! pqueue)
  (pairing-heap-first pqueue))
⇒ 2
```

To test if a priority queue is empty, use **pairing-heap-empty?**:

```
(pairing-heap-empty? (pairing-heap :comparator +number-comparator+))
⇒ #t

(pairing-heap-empty? (pairing-heap :comparator +number-comparator+ 1 2))
```

```
⇒ #f
```

The size or length of a priority queue is obtained with `pairing-heap-length`:

```
(pairing-heap-length (pairing-heap :comparator +number-comparator+ 1 2))
⇒ 2
```

To make a shallow copy of a priority queue, use `pairing-heap-copy`:

```
(let* ((pqueue1 (pairing-heap :comparator +number-comparator+ 1 2))
      (pqueue2 (pairing-heap-copy queue1)))
  (eq? pqueue1 pqueue2))
⇒ #f
```

`pairing-heap` also implements the `priority-queue`, `collection`, `extendable`, `mutable`, and `enumerable` protocols. See Section 2.13.3 [priority-queue Examples], page 28. See Section 2.1.3 [collection Examples], page 4. See Section 2.3.3 [extendable Examples], page 7. See Section 2.4.3 [mutable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11.

3.14 sorted-dictionary

3.14.1 Overview

`sorted-dictionary` is a balanced-tree based implementation of the `dictionary` protocol.

3.14.2 API Reference

`sorted-dictionary` implements the `dictionary`, `collection`, `extendable`, `indexable`, `mutable`, and `enumerable` protocols. See Section 2.14 [dictionary], page 29. See Section 2.1 [collection], page 3. See Section 2.3 [extendable], page 6. See Section 2.2 [indexable], page 4. See Section 2.4 [mutable], page 7. See Section 2.6 [enumerable], page 9.

`sorted-dictionary? object` [procedure]
returns a boolean indicating whether or not *object* is a sorted-dictionary.

`make-sorted-dictionary :comparator` [procedure]
requires `:comparator` be an object supporting the `comparator` protocol.
`:comparator` must be ordered.

returns a sorted-dictionary.

`sorted-dictionary :comparator . list-of-associations` [procedure]
requires `:comparator` be an object supporting the `comparator` protocol and
`list-of-associations` be a list of `associations`. `:comparator` must be ordered.

returns a sorted-dictionary.

`sorted-dictionary-get dict key` [procedure]
requires `dict` be a `sorted-dictionary` and `key` be an arbitrary object. `key` must be
supported by the `comparator` used when creating `dict`

returns the value associated with `key` or `#f` if no such association exists.

sorted-dictionary-put! *dict key value* [procedure]
requires *dict* be a **sorted-dictionary** *key* and *value* be arbitrary objects. *key* must be supported by the **comparator** used when creating *dict*.

modifies *dict* so that it contains the association of *key* to *value*. If an association with *key* already exists it is replaced, and if not, a new association is created.

returns **#unspecified**

sorted-dictionary-update! *dict key value exist-fun* [procedure]
requires *dict* be a **sorted-dictionary**, *key* and *value* be arbitrary objects, and *exist-fun* which is a procedure excepting a single value and returning an updated value when an association with a key *key* already exists. *key* must be supported by the **comparator** used when creating *dict*.

modifies *dict* such that if the **sorted-dictionary** doesn't currently contain an association with a key *key*, it contains an association with key *key* and value *value*, or if an existing association exists updates it so that has the value obtained by applying *exist-fun* to its value.

returns **#unspecified**

sorted-dictionary-contains? *dict key* [procedure]
requires *dict* be a **sorted-dictionary** and *key* be an arbitrary object.

returns a boolean indicating whether or not *dict* contains an association with the key *key*.

sorted-dictionary-remove! *dict key* [procedure]
requires *dict* be a **sorted-dictionary** and *key* be an arbitrary object. *key* must be supported by the **comparator** used when creating *dict*

modifies *dict* by removing the association with the key *key*.

returns **#unspecified**

sorted-dictionary-empty? *dict* [procedure]
requires *dict* be **sorted-dictionary**.

returns a boolean indicating whether or not the **sorted-dictionary** contains any associations.

sorted-dictionary-copy *dict* [procedure]
requires *dict* be a **sorted-dictionary**.

returns a shallow copy of *dict*

`sorted-dictionary-length` *dict* [procedure]
 requires *dict* be a sorted-dictionary.

returns the number of items in *dict*.

3.14.3 Examples

To test whether an object is a sorted-dictionary use the predicate `sorted-dictionary?`:

```
(sorted-dictionary? (sorted-dictionary :comparator +string-comparator+))
⇒ #t
```

```
(sorted-dictionary? (vector))
⇒ #f
```

Two procedures are used to create sorted-dictionaries. The first creates an empty dictionary, and the second allows for the creation of a dictionary with the provided values. Both require a `:comparator` argument supporting the type of the key. The `:comparator` must be ordered.

```
(let ((dict (make-sorted-dictionary :comparator +string-comparator+)))
  (sorted-dictionary? dict))
⇒ #t
```

```
(let ((dict (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2))))
  (sorted-dictionary-length dict))
⇒ 2
```

Checking whether a dictionary is empty is accomplished with `sorted-dictionary-empty?`:

```
(sorted-dictionary-empty? (sorted-dictionary :comparator +string-comparator+))
⇒ #t
```

```
(sorted-dictionary-empty? (sorted-dictionary :comparator +string-comparator+ (=> "A" 1)))
⇒ #f
```

Associations can be added to a dictionary with `sorted-dictionary-put!`:

```
(let ((dict (sorted-dictionary :comparator +string-comparator+)))
  (sorted-dictionary-put! dict "a" 1)
  (sorted-dictionary-put! dict "b" 2)
  (map (lambda (kv) (cons (=>key kv) (=>value kv)))
       (dictionary-enumerable-collect dict +list-collector+)))
⇒ (("a" . 1) ("b" . 2))
```

And removed (assuming the insertions above) with `sorted-dictionary-remove!`:

```
(sorted-dictionary-remove! dict "a")
(map (lambda (kv) (cons (=>key kv) (=>value kv)))
     (dictionary-enumerable-collect dict +list-collector+))
⇒ (("b" . 2))
```

The value associated with a given key is easily obtained:

```
(let ((dict (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (sorted-dictionary-get dict "b"))
⇒ 2
```

The `dictionary-update!` method can be used to update an existing value or insert a new value if an existing association does not exist:

```
(let ((dict (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2) (=> "c" 3))))
```

```

(sorted-dictionary-update! dict "b" 0 (lambda (x) (+ x 1)))
(sorted-dictionary-update! dict "d" 0 (lambda (x) (+ x 1)))
(sorted-dictionary-get dict "b")
⇒ 3
(sorted-dictionary-get dict "d")
⇒ 0

```

To obtain the number of associations in a dictionary, call `sorted-dictionary-length`:

```

(let ((dict (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (sorted-dictionary-length dict))
⇒ 3

```

Querying whether an association with a given key is accomplished with `sorted-dictionary-contains?`:

```

(let ((dict (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2) (=> "c" 3))))
  (sorted-dictionary-contains? dict "a"))
⇒ #t

(sorted-dictionary-contains? dict "d")
⇒ #f

```

Copying a dictionary is accomplished with `dictionary-copy`:

```

(let* ((dict1 (sorted-dictionary :comparator +string-comparator+ (=> "a" 1) (=> "b" 2) (=> "c" 3)))
      (dict2 (sorted-dictionary-copy dict1)))
  (eq? dict1 dict2))
⇒ #f

(and (sorted-dictionary-contains? dict1 "a")
     (sorted-dictionary-contains? dict2 "a"))
⇒ #t

```

`sorted-dictionary` also implements the `dictionary`, `collection`, `mutable`, `indexable`, `extendable`, `enumerable`, and `dictionary-enumerable` protocols. See Section 2.14 [dictionary], page 29. See Section 2.1.3 [collection Examples], page 4. See Section 2.4.3 [mutable Examples], page 7. See Section 2.2.3 [indexable Examples], page 5. See Section 2.3.3 [extendable Examples], page 7. See Section 2.6.3 [enumerable Examples], page 11. See Section 2.16.3 [dictionary-enumerable Examples], page 35.

4 Global Index

=

=>	37
=>key	37
=>value	37

A

association?	37
--------------------	----

B

bag-contains?	18
bag-copy	18
bag-count	19
bag-count-set!	19
bag-delete!	18
bag-empty?	18
bag-insert!	18
bag-length	19, 40, 43
bag?	18
binary-heap	62
binary-heap-capacity	62
binary-heap-copy	62
binary-heap-dequeue!	62
binary-heap-empty?	62
binary-heap-enqueue!	62
binary-heap-first	63
binary-heap-length	62
binary-heap?	61

C

collection-contains?	3
collection-copy	3
collection-empty?	3
collection-enumerator	3
collection-extend!	6
collection-extendable?	6
collection-indexable?	4
collection-length	3
collection-mutable?	7
collection-ref	4
collection-set!	5
collection-slice	5
collection?	3
collector-accumulate	13
collector-combine	13
collector-finish	13
collector-supplier	13
collector?	13
comparator-hash	15
comparator-hashable?	14
comparator-ordered?	14
comparator-type?	15

comparator<=?	15
comparator<?	15
comparator=?	15
comparator>=?	15
comparator>?	15
comparator?	14
contiguous-queue	57
contiguous-queue-capacity	58
contiguous-queue-copy	57
contiguous-queue-dequeue!	58
contiguous-queue-empty?	57
contiguous-queue-enqueue!	58
contiguous-queue-first	58
contiguous-queue-length	57
contiguous-queue?	57
contiguous-stack	53
contiguous-stack-capacity	53
contiguous-stack-copy	53
contiguous-stack-empty?	53
contiguous-stack-length	53
contiguous-stack-pop!	53
contiguous-stack-push!	53
contiguous-stack-top	53
contiguous-stack?	52

D

dictionary-contains?	30
dictionary-copy	29
dictionary-empty?	30
dictionary-enumerable-any?	34
dictionary-enumerable-append	35
dictionary-enumerable-collect	35
dictionary-enumerable-enumerator	34
dictionary-enumerable-every?	35
dictionary-enumerable-filter	34
dictionary-enumerable-fold	34
dictionary-enumerable-for-each	34
dictionary-enumerable-map	34
dictionary-enumerable?	34
dictionary-enumerator	31
dictionary-enumerator-copy	33
dictionary-enumerator-current	33
dictionary-enumerator-key	33
dictionary-enumerator-move-next!	32
dictionary-enumerator-value	33
dictionary-enumerator?	32
dictionary-get	30
dictionary-length	30
dictionary-put!	30
dictionary-remove!	30
dictionary-update!	30
dictionary?	29

E

enumerable-any?	10
enumerable-append	11
enumerable-collect	11
enumerable-enumerator	9
enumerable-every?	10
enumerable-filter	9
enumerable-fold	10
enumerable-for-each	9
enumerable-map	9
enumerable-skip	10
enumerable-skip-while	10
enumerable-take	10
enumerable-take-while	9
enumerable?	9
enumerator-copy	8
enumerator-current	8
enumerator-move-next!	8
enumerator?	8

H

hash-bag	42
hash-bag-contains?	43
hash-bag-copy	42
hash-bag-count	43
hash-bag-count-set!	43
hash-bag-delete!	43
hash-bag-empty?	42
hash-bag-insert!	42
hash-bag?	42
hash-set	47
hash-set-contains?	48
hash-set-copy	47
hash-set-delete!	47
hash-set-empty?	47
hash-set-insert!	47
hash-set?	47
hoard	1

I

Implementations	37
-----------------	----

L

linked-queue	59
linked-queue-copy	60
linked-queue-dequeue!	60
linked-queue-empty?	60
linked-queue-enqueue!	60
linked-queue-first	60
linked-queue-length	60
linked-queue?	59
linked-stack	55
linked-stack-copy	55
linked-stack-empty?	55
linked-stack-length	55

linked-stack-pop!	55
linked-stack-push!	55
linked-stack-top	56
linked-stack?	55
list->stretchy-vector	50

M

make-binary-heap	61
make-collector	13
make-comparator	16
make-contiguous-queue	57
make-contiguous-stack	52
make-hash-bag	42
make-hash-set	47
make-linked-queue	59
make-linked-stack	55
make-pairing-heap	64
make-sorted-bag	39
make-sorted-dictionary	66
make-sorted-set	45
make-stretchy-vector	49

O

Overview of hoard	1
-------------------	---

P

pair->association	37
pairing-heap	64
pairing-heap-copy	64
pairing-heap-dequeue!	65
pairing-heap-empty?	64
pairing-heap-enqueue!	64
pairing-heap-first	65
pairing-heap-length	64
pairing-heap?	64
priority-queue-capacity	28
priority-queue-copy	27
priority-queue-dequeue!	28
priority-queue-empty?	27
priority-queue-enqueue!	28
priority-queue-first	27
priority-queue-fixed-capacity?	28
priority-queue-length	28
priority-queue?	27
Protocols	3

Q

queue-capacity	24
queue-copy	23
queue-dequeue!	23
queue-empty?	23
queue-enqueue!	23
queue-first	23
queue-fixed-capacity?	24
queue-length	24
queue?	23

R

range	38
range-for-each	38
range-map	38
range?	38

S

set-contains?	21
set-copy	20
set-delete!	21
set-difference	22
set-difference!	21
set-empty?	20
set-insert!	20
set-intersect	21
set-intersect!	21
set-length	21, 46, 48
set-union	21
set-union!	21
set?	20
sorted-bag	39
sorted-bag-contains?	40
sorted-bag-copy	39
sorted-bag-count	40
sorted-bag-count-set!	40
sorted-bag-delete!	40
sorted-bag-empty?	39
sorted-bag-insert!	40
sorted-bag?	39
sorted-dictionary	66
sorted-dictionary-contains?	67

sorted-dictionary-copy	67
sorted-dictionary-empty?	67
sorted-dictionary-get	66
sorted-dictionary-length	68
sorted-dictionary-put!	67
sorted-dictionary-remove!	67
sorted-dictionary-update!	67
sorted-dictionary?	66
sorted-set	45
sorted-set-contains?	45
sorted-set-copy	45
sorted-set-delete!	45
sorted-set-empty?	45
sorted-set-insert!	45
sorted-set?	45
stack-capacity	26
stack-copy	25
stack-empty?	25
stack-fixed-capacity?	26
stack-length	26
stack-pop!	26
stack-push!	25
stack-top	25
stack?	25
stretchy-vector	49
stretchy-vector->list	50
stretchy-vector->vector	50
stretchy-vector-append	51
stretchy-vector-append!	51
stretchy-vector-capacity	50
stretchy-vector-copy	51
stretchy-vector-expand!	49
stretchy-vector-extend!	51
stretchy-vector-length	49
stretchy-vector-map	50
stretchy-vector-ref	50
stretchy-vector-remove!	51
stretchy-vector-resize!	49
stretchy-vector-set!	50
stretchy-vector?	49

V

variable	13, 14, 16, 17
vector->stretchy-vector	50

5 Table of contents

Table of Contents

1	Overview of hoard	1
2	Protocols	3
2.1	collection	3
2.1.1	Overview	3
2.1.2	API Reference	3
2.1.3	Examples	4
2.2	indexable	4
2.2.1	Overview	4
2.2.2	API Reference	4
2.2.3	Examples	5
2.3	extendable	6
2.3.1	Overview	6
2.3.2	API Reference	6
2.3.3	Examples	7
2.4	mutable	7
2.4.1	Overview	7
2.4.2	API Reference	7
2.4.3	Examples	7
2.5	enumerator	7
2.5.1	Overview	8
2.5.2	API Reference	8
2.5.3	Examples	8
2.6	enumerable	9
2.6.1	Overview	9
2.6.2	API Reference	9
2.6.3	Examples	11
2.7	collector	12
2.7.1	Overview	13
2.7.2	API Reference	13
2.7.3	Examples	14
2.8	comparator	14
2.8.1	Overview	14
2.8.2	API Reference	14
2.8.3	Examples	17
2.9	bag	18
2.9.1	Overview	18
2.9.2	API Reference	18
2.9.3	Examples	19
2.10	set	20
2.10.1	Overview	20
2.10.2	API Reference	20
2.10.3	Examples	22

2.11	queue	23
2.11.1	Overview	23
2.11.2	API Reference	23
2.11.3	Examples	24
2.12	stack	25
2.12.1	Overview	25
2.12.2	API Reference	25
2.12.3	Examples	26
2.13	priority-queue	27
2.13.1	Overview	27
2.13.2	API Reference	27
2.13.3	Examples	28
2.14	dictionary	29
2.14.1	Overview	29
2.14.2	API Reference	29
2.14.3	Examples	31
2.15	dictionary-enumerator	32
2.15.1	Overview	32
2.15.2	API Reference	32
2.15.3	Examples	33
2.16	dictionary-enumerable	33
2.16.1	Overview	33
2.16.2	API Reference	34
2.16.3	Examples	35

3 Implementations and Supporting Data Types .. 37

3.1	association	37
3.1.1	Overview	37
3.1.2	API Reference	37
3.1.3	Examples	37
3.2	range	38
3.2.1	Overview	38
3.2.2	API Reference	38
3.2.3	Examples	38
3.3	sorted-bag	39
3.3.1	Overview	39
3.3.2	API Reference	39
3.3.3	Examples	40
3.4	hash-bag	42
3.4.1	Overview	42
3.4.2	API Reference	42
3.4.3	Examples	43
3.5	sorted-set	44
3.5.1	Overview	44
3.5.2	API Reference	44
3.5.3	Examples	46
3.6	hash-set	46
3.6.1	Overview	46

3.6.2	API Reference	47
3.6.3	Examples	48
3.7	stretchy-vector	49
3.7.1	Overview	49
3.7.2	API Reference	49
3.7.3	Examples	51
3.8	contiguous-stack	52
3.8.1	Overview	52
3.8.2	API Reference	52
3.8.3	Examples	54
3.9	linked-stack	55
3.9.1	Overview	55
3.9.2	API Reference	55
3.9.3	Examples	56
3.10	contiguous-queue	57
3.10.1	Overview	57
3.10.2	API Reference	57
3.10.3	Examples	58
3.11	linked-queue	59
3.11.1	Overview	59
3.11.2	API Reference	59
3.11.3	Examples	60
3.12	binary-heap	61
3.12.1	Overview	61
3.12.2	API Reference	61
3.12.3	Examples	63
3.13	pairing-heap	64
3.13.1	Overview	64
3.13.2	API Reference	64
3.13.3	Examples	65
3.14	sorted-dictionary	66
3.14.1	Overview	66
3.14.2	API Reference	66
3.14.3	Examples	68
4	Global Index	71
5	Table of contents	75

Short Contents

1	Overview of hoard	1
2	Protocols	3
3	Implementations and Supporting Data Types	37
4	Global Index	71
5	Table of contents	75

