

# Model selection in R

In this lesson, we will implement various model selection methods on real data in R.

Let's use the `fabric` data to illustrate the implementation of model selection techniques. This dataset contains the acoustic absorption coefficients of 24 woven fabrics with different air gap distances ( $d = 0, 1, 2, 3\text{cm}$ ). There are four different possible response variables based on these air gap distances:

1. `acoustic0` : air gap distance  $d = 0\text{cm}$
2. **`acoustic1`** : air gap distance  $d = 1\text{cm}$
3. `acoustic2` : air gap distance  $d = 2\text{cm}$
4. `acoustic3` : air gap distance  $d = 3\text{cm}$

For simplicity, we'll focus on `acoustic1`. The following predictors are given:

1. `thickness` : the thickness of the woven fabric, in mm
2. `diameter` : the diameter of the woven fabric, in mm
3. `perforation` : perforation was measured as a percentage, and is relate to the pore width and yarn width of the woven fabric
4. `weight` : the weight of the woven fabric, measured in  $\text{g/m}^2$
5. `stiffness` : the weight of the woven fabric, measured in  $\text{mN} \times \text{cm}$
6. `airPerm` : the air permeability of the woven fabric, measured in  $\text{mm/s}$

According to Tang, Kong, and Yan, "It has been found that the acoustic absorption properties" of a woven fabric are "mainly determined by the perforation ratio and air permeability." The goal of this analysis is to see if other fabric properties can useful in predicting the absorption coefficient with  $d = 1$ , i.e., `acoustic1`. We'll use several different model selection techniques to show how they are implemented and how they might differ from one another.

Source: X. Tang, D. Kong, X. Yan (2018). "Multiple Regression Analysis of a Woven Fabric Sound Absorber," Textile Research Journal, <https://doi.org/10.1177/0040517518758001>.

In [35]:

```
fabric = read.table("http://users.stat.ufl.edu/~winner/data/fabricsoundabsorb.csv")
library(RCurl) #a package that includes the function getURL(), which allows for
library(ggplot2)
url = getURL(paste0("https://raw.githubusercontent.com/bzaharatos/",
                    "-Statistical-Modeling-for-Data-Science-Applications/",
                    "master/Modern%20Regression%20Analysis%20/",
                    "Datasets/fabricsoundabsorb.csv"))
fabric = read.csv(text = url, sep = ",")
```

```
#names(hprice) = c("price", "area", "bath", "bed", "fireplace", "lot", "age", "fire")

head(fabric)
summary(fabric)
```

Loading required package: bitops

Registered S3 methods overwritten by 'ggplot2':


```
method      from
[.quosures  rlang
c.quosures  rlang
print.quosures rlang
```

sampleID	thickness	diameter	perforation	weight	stiffness	airPerm	acoustic0	acoustic1	aco
1	0.547	0.269	6.14	247	181.90	805.4	0.076	0.330	
2	0.541	0.378	6.08	253	74.40	887.8	0.092	0.339	
3	0.875	0.584	4.97	366	71.41	598.4	0.129	0.455	
4	0.640	0.527	4.87	319	161.50	799.2	0.115	0.433	
5	0.750	0.534	4.51	292	156.20	753.2	0.095	0.362	
6	0.539	0.368	4.39	232	171.50	704.0	0.073	0.371	

sampleID	thickness	diameter	perforation
Min. : 1.00	Min. : 0.5260	Min. : 0.2200	Min. : 1.210
1st Qu.: 6.75	1st Qu.: 0.6438	1st Qu.: 0.3395	1st Qu.: 2.460
Median : 12.50	Median : 0.7685	Median : 0.4705	Median : 3.110
Mean : 12.50	Mean : 0.7302	Mean : 0.4320	Mean : 3.378
3rd Qu.: 18.25	3rd Qu.: 0.8097	3rd Qu.: 0.5340	3rd Qu.: 4.195
Max. : 24.00	Max. : 0.9310	Max. : 0.5840	Max. : 6.140
weight	stiffness	airPerm	acoustic0
Min. : 228.0	Min. : 49.60	Min. : 401.5	Min. : 0.0730
1st Qu.: 251.8	1st Qu.: 81.91	1st Qu.: 510.4	1st Qu.: 0.0905
Median : 303.5	Median : 139.41	Median : 600.6	Median : 0.1120
Mean : 302.0	Mean : 134.81	Mean : 601.4	Mean : 0.1163
3rd Qu.: 347.8	3rd Qu.: 171.40	3rd Qu.: 685.7	3rd Qu.: 0.1355
Max. : 373.0	Max. : 275.56	Max. : 887.8	Max. : 0.1890
acoustic1	acoustic2	acoustic3	
Min. : 0.3300	Min. : 0.3470	Min. : 0.2610	
1st Qu.: 0.4412	1st Qu.: 0.4203	1st Qu.: 0.3175	
Median : 0.4775	Median : 0.4800	Median : 0.3625	
Mean : 0.4793	Mean : 0.4834	Mean : 0.3699	
3rd Qu.: 0.5420	3rd Qu.: 0.5355	3rd Qu.: 0.4148	
Max. : 0.6170	Max. : 0.6260	Max. : 0.4830	

In [36]:

```
library(corrplot)
col4 = colorRampPalette(c("black", "darkgrey", "grey", "#CFB87C"))
corrplot(cor(fabric[c(2:7,9)]), method = "ellipse", col = col4(100), addCoef.co
```



Let's start with the full model, which uses `acoustic1` as the response and `thickness`, `diameter`, `perforation`, `weight`, `stiffness`, and `airPerm` as predictors.

In [37]:

```
lm_fabric = lm(acoustic1 ~ thickness + diameter + perforation + weight + stiffne
summary(lm_fabric)
```

Call:

```
lm(formula = acoustic1 ~ thickness + diameter + perforation +
    weight + stiffness + airPerm, data = fabric)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.062713	-0.021894	-0.002938	0.020573	0.065304

Coefficients:

	Estimate	Std. Error	t value	Pr(> t )
(Intercept)	0.5858162	0.0896400	6.535	5.09e-06 ***
thickness	-0.0288504	0.1606300	-0.180	0.8596
diameter	-0.1340331	0.1192525	-1.124	0.2767

```

perforation -0.0215229  0.0128301  -1.678   0.1117
weight      0.0008418  0.0004612   1.825   0.0856 .
stiffness   -0.0002042  0.0001622  -1.258   0.2253
airPerm     -0.0003019  0.0001228  -2.458   0.0250 *
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Residual standard error: 0.03871 on 17 degrees of freedom
Multiple R-squared:  0.8393,    Adjusted R-squared:  0.7826
F-statistic: 14.8 on 6 and 17 DF,  p-value: 6.511e-06

```

Here, we see that several of the predictors have t-tests with high p-values (higher than the standard  $\alpha = 0.05$ ). Instead of just removing all of those, let's perform backward selection, removing the predictor with the largest p-value greater than  $\alpha_0 = 0.15$ , thickness in this case, and then refit the model. We can do this with the `update()` function. Remember that  $\alpha_0$ , sometimes called the "p-to-remove", is used as a cutoff in backward selection, and if the goal is prediction, then 0.15 or 0.2 is thought to work well.

In [38]:

```

lm_fabric = update(lm_fabric, . - . -thickness)
summary(lm_fabric)

```

Call:

```

lm(formula = acoustic1 ~ diameter + perforation + weight + stiffness +
    airPerm, data = fabric)

```

Residuals:

```

      Min       1Q   Median       3Q      Max
-0.061055 -0.024693 -0.003761  0.020839  0.064457

```

Coefficients:

```

              Estimate Std. Error t value Pr(>|t|)
(Intercept)  0.5766761   0.0717833   8.034 2.31e-07 ***
diameter     -0.1299283   0.1138523  -1.141  0.2687
perforation  -0.0211186   0.0122868  -1.719  0.1028
weight        0.0007765   0.0002758   2.815  0.0115 *
stiffness    -0.0001961   0.0001516  -1.293  0.2122
airPerm      -0.0002959   0.0001150  -2.573  0.0192 *
---

```

```

Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

```

Residual standard error: 0.03765 on 18 degrees of freedom
Multiple R-squared:  0.839,    Adjusted R-squared:  0.7943
F-statistic: 18.76 on 5 and 18 DF,  p-value: 1.416e-06

```

Notice that our p-values have changed! For example, before, `weight` was not significant at the  $\alpha = 0.05$  level and now it is. And, importantly, we still have p-values above  $\alpha_0 = 0.15$ . So, let's remove the predictor with the largest p-value, namely, `diameter`.

In [39]:

```

lm_fabric = update(lm_fabric, . - . -diameter)
summary(lm_fabric)

```

Call:

```

lm(formula = acoustic1 ~ perforation + weight + stiffness + airPerm,
    data = fabric)

```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.056134	-0.032975	-0.000806	0.025339	0.071500

Coefficients:

	Estimate	Std. Error	t value	Pr(> t )
(Intercept)	0.6009065	0.0691148	8.694	4.76e-08 ***
perforation	-0.0241498	0.0120914	-1.997	0.06032 .
weight	0.0005408	0.0001842	2.935	0.00849 **
stiffness	-0.0001887	0.0001526	-1.236	0.23144
airPerm	-0.0002958	0.0001159	-2.551	0.01950 *

---

Signif. codes: 0 '\*\*\*' 0.001 '\*\*' 0.01 '\*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.03795 on 19 degrees of freedom

Multiple R-squared: 0.8274, Adjusted R-squared: 0.791

F-statistic: 22.77 on 4 and 19 DF, p-value: 5.01e-07

It looks like we have at least one more iteration, since `stiffness` has a p-value greater than  $\alpha_0$ .

In [40]:

```
lm_fabric = update(lm_fabric, . ~ . -stiffness)
summary(lm_fabric)
```

Call:

```
lm(formula = acoustic1 ~ perforation + weight + airPerm, data = fabric)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.074211	-0.025324	0.003821	0.020601	0.076329

Coefficients:

	Estimate	Std. Error	t value	Pr(> t )
(Intercept)	0.6159414	0.0689289	8.936	2.03e-08 ***
perforation	-0.0244787	0.0122470	-1.999	0.0594 .
weight	0.0004294	0.0001628	2.638	0.0158 *
airPerm	-0.0003053	0.0001172	-2.605	0.0169 *

---

Signif. codes: 0 '\*\*\*' 0.001 '\*\*' 0.01 '\*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.03845 on 20 degrees of freedom

Multiple R-squared: 0.8135, Adjusted R-squared: 0.7855

F-statistic: 29.08 on 3 and 20 DF, p-value: 1.717e-07

Notice that each of our remaining predictors have a p-value less than  $\alpha_0 = 0.15$ . This is the "best" model, according to backward selection. Of course, there's nothing about backward selection that is consistent with statistical inference, so we should use this procedure with caution! The same is true for forward selection and other stepwise selection methods.

In [ ]:

## AIC, BIC, and adjusted $R^2$

Recall that AIC is defined as

$$AIC(g(\mathbf{x}; \hat{\beta})) = 2(p+1) + n \log(RSS/n).$$

We can use AIC (or BIC, or adjusted  $R^2$ ) to help us choose a "best" model. One way to do this would be:

1. Fit *all* simple linear regression models, and report the one with the lowest RSS. This is allowed because when the number of predictors is the same, RSS (and equivalently,  $R^2$ ) can be used to compare models.
1. Fit all two-predictor models, and report the one with the lowest RSS.
1. Continue this process: fit all  $k$ -predictor models, and report the one with the lowest RSS.
1. At this point, we should have the "best" models (in terms of RSS) for all models of size  $k$ , where  $k$  ranges from 1 to  $p$ . We can no longer use RSS to compare across *these* models, since each is of a different size. So, we use a criterion that takes into account the tradeoff between fit (RSS) and model size/complexity ( $p$ ).

The `regsubsets()` function in the `leaps` library can help us streamline this process.


```
In [41]: library(leaps)
library(MASS)

n = dim(fabric)[1];
reg1 = regsubsets(acoustic1 ~ thickness + diameter + perforation + weight + stif
  data = fabric)
rs = summary(reg1)
rs$which
```

(Intercept)	thickness	diameter	perforation	weight	stiffness	airPerm
TRUE	FALSE	FALSE	FALSE	FALSE	FALSE	TRUE
TRUE	TRUE	FALSE	FALSE	FALSE	FALSE	TRUE
TRUE	FALSE	FALSE	TRUE	TRUE	FALSE	TRUE
TRUE	FALSE	FALSE	TRUE	TRUE	TRUE	TRUE
TRUE	FALSE	TRUE	TRUE	TRUE	TRUE	TRUE
TRUE	TRUE	TRUE	TRUE	TRUE	TRUE	TRUE

The table above provides the best model (in terms of RSS) of size  $k$ , for  $k = 1, 2, \dots, 6$ . For example, the best simple linear regression model is the model  $\text{acoustic1} = \hat{\beta}_0 + \hat{\beta}_1 \times \text{airPerm}$ . Now, to compare these models with each other, we calculate AIC, and plot the AIC values as a function of model size.

```
In [42]: AIC = 2*(2:7) + n*log(rs$rss/n)
plot(AIC ~ 1:6, xlab = "number of predictors", ylab = "AIC")
```



In this plot, we see that the model of size  $k = 3$  has the lowest AIC. That means that our model selection procedure has chosen:

$$\text{acoustic1} = \hat{\beta}_0 + \hat{\beta}_1 \times \text{perforation} + \hat{\beta}_2 \times \text{weight} + \hat{\beta}_3 \times \text{airPerm}.$$


Interestingly, using

$$R_a^2 = 1 - \frac{RSS / (n - (p + 1))}{TSS / (n - 1)},$$

we get a different model, namely the model with five predictors ( diameter , perforation , weight , stiffness , airPerm ):

In [43]: 

```
plot(1:6, rs$adjr2, xlab = "number of predictors", ylab = "adjusted R-squared")
```




And BIC, which is given as

$$BIC\left(g\left(\mathbf{x};\hat{\boldsymbol{\beta}}\right)\right)=\left(p+1\right)\log\left(n\right)-2\log L\left(\hat{\boldsymbol{\beta}}\right),$$

chooses the same model as AIC.

```
In [44]: BIC = log(n)*(2:7) + n*log(rs$rss/n)
plot(BIC ~ I(1:6), xlab = "number of predictors", ylab = "BIC")
```





In [ ]:

In [ ]: