DELOITTE CYBER GURUKUL MCQ BLUEPRINT

Focus Analysis: Mostly Asked vs. Rarely Asked Cybersecurity-Only Concepts

SECTION 1: MOSTLY ASKED CYBERSECURITY CORE TOPICS

MOSTLY ASKED

1. OWASP Top 10 Web Vulnerabilities & Attack Signatures

Operational Impact: Platform tests prioritize application flaw scenarios where you must analyze an attack signature or code log snippet.

- **SQL Injection (SQLi):** Manipulating application database input fields using structural SQL punctuation characters to alter backend queries.

  > *Signature Prompt: admin' OR '1'='1*

- **Cross-Site Scripting (XSS):** Feeding unauthorized client-side JavaScript tags into user input forms. You must distinguish between Stored XSS (saved directly in the database server) and Reflected XSS (passed via single-use URL payloads).

  > *Signature Prompt: <script>alert(document.cookie)</script>*

- **Broken Object Level Authorization (BOLA / IDOR):** Modifying structural parameter variables inside a resource identifier string to unauthorized access accounts.

  > *Signature Prompt: Changing /api/v1/profile?id=1001 to id=1002*

- **Server-Side Request Forgery (SSRF):** Forcing vulnerable enterprise servers into generating malicious lookup requests directed toward backend isolated networks.

MOSTLY ASKED

2. Active Architectural Defensive Appliances

Operational Impact: Positioning perimeter defense devices effectively based on traffic topology demands.

- **IDS vs. IPS Deployments:** Intrusion Detection Systems run completely out-of-band passively tracking copies of network flows via SPAN or TAP configurations. Intrusion Prevention Systems reside inline directly across data lanes to actively drop malicious packet flows.
- **Firewall Operational Classes:** Traditional Packet Filters review simple Layer 3/4 headers. Stateful Packet Inspection (SPI) tracks active session connection maps. Web Application Firewalls (WAF) parse deep Layer 7 application payloads for web attack variations.
- **Demilitarized Zone (DMZ) Layout:** Segregating public-facing boundary services (such as Web, Mail, or external DNS servers) from isolated internal enterprise segments.

MOSTLY ASKED

3. Security Principles & Identity Management Frameworks

- **Principle of Least Privilege (PoLP):** Restricting users and runtime processes strictly to the minimal administrative rights essential to fulfill their tasks.
- **Defense-in-Depth Architecture:** Enforcing layered, independent security measures (e.g., matching application validation controls with firewalls and endpoint protection arrays) so no singular failure compromises the system.
- **The AAA Security Matrix:** Differentiating the operational phases of Authentication (verifying identity claims), Authorization (validating explicit access permissions), and Accounting (maintaining non-repudiation audit trails).

MOSTLY ASKED

4. Malware Taxonomy & Engineering Tactics

- **Viruses vs. Autonomous Worms:** Viruses strictly demand explicit human execution steps or host carrier files to distribute malware, whereas Worms independently replicate and spread across open network ports without modifying external host files.
- **Social Engineering Target Variations:** Dissecting Phishing vectors including broad standard Phishing, localized Spear Phishing targeting specific organizations, and high-value Whaling targets aimed at executive leadership levels.

SECTION 2: RARELY ASKED CYBERSECURITY TOPICS

RARELY ASKED

5. Threat Frameworks & Structural Incident Frameworks

Operational Impact: Broad procedural concepts that infrequently manifest in quick timed technical assessments.

- **MITRE ATT&CK Mapping:** Cataloging real-world threat actors' distinct tactical methodologies, techniques, and procedures (TTPs).
- **Linear Cyber Kill Chain Paths:** Memorizing the rigid sequential phases of defensive attack progressions (Reconnaissance, Weaponization, Delivery, Exploitation, Installation, Command & Control, Actions on Objectives).

RARELY ASKED

6. Forensic Investigations & Endpoint Operations

- **Order of Volatility Metrics:** Prioritizing evidence collections based on systemic degradation rates. Data captures must strip temporary components (CPU Cache, Registers, RAM) prior to long-term physical storage systems (Hard Drives, Logs).
- **EDR Behavioral Heuristics:** Modern Endpoint Detection and Response nodes tracking real-time execution anomalies vs. legacy signature-matching antivirus suites.

RARELY ASKED

7. Risk Models & Cloud Responsibility Frameworks

- **CVSS Vector Computations:** Evaluating raw severity grades via the Common Vulnerability Scoring System based on Base, Temporal, and Environmental metrics.
- **Cloud Provider Boundary Splits (IaaS vs. PaaS vs. SaaS):** Determining shared asset boundaries (e.g., Infrastructure as a Service providers isolate hardware and hypervisors, leaving guest OS patching and system security rules completely to the client).

This is for informational purposes only. For medical advice or diagnosis, consult a professional. AI responses may include mistakes.