

Governing Equations of the **fuzzy-couscous** Solver

Clean-room compressible LES solver for blast-induced turbulence

Generated 2026-05-23

Abstract

This document collects every governing equation the **fuzzy-couscous** solver discretizes: the compressible Navier–Stokes system, the inviscid and viscous fluxes, the equations of state (ideal gas, two- γ mixture, Jones–Wilkins–Lee, and stiffened gas), the multifluid models (the transported- γ marker and the five-equation diffuse-interface model), the LES closure (hyperdissipation, localized artificial diffusivity, Ducros sensor), the Besnard–Harlow–Rauenzahn (BHR) variable-density turbulence model, the SSP-RK3 time integrator, and the diagnostic identities. Each section cites the file that implements it, so the equations stay traceable to the code.

Contents

1	Compressible Navier–Stokes system	1
2	Inviscid flux	1
3	Viscous fluxes	2
4	Equation of state	2
4.1	Ideal gas	2
4.2	Two- γ mixture (variable-density contact)	2
4.3	Jones–Wilkins–Lee (JWL) for real high explosives	2
4.4	Stiffened gas	3
4.5	Five-equation mixture (volume-fraction / Wood rule)	3
5	Multifluid models	4
5.1	Model taxonomy	4
5.2	Transported- γ marker transport	4
5.3	Five-equation diffuse-interface model	4
6	LES closure and shock capturing	5
6.1	Spectral hyperdissipation (LES sink)	5
6.2	Ducros shock sensor	5
6.3	Localized artificial diffusivity (LAD)	5
7	BHR variable-density turbulence model	5
8	Time integration	6

9	Diagnostic identities	6
9.1	Helmholtz decomposition	6
9.2	Dissipation budget	6
9.3	Conservation monitors	6

1 Compressible Navier–Stokes system

The solver advances the conservative compressible Navier–Stokes equations for a single fluid (or a mixture; see §4) on a periodic / slip-wall Cartesian box. With conserved state $\mathbf{U} = (\rho, \rho\mathbf{u}, \rho E)^\top$,

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) = 0, \quad (1)$$

$$\frac{\partial(\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \otimes \mathbf{u} + p \mathbf{I}) = \nabla \cdot \boldsymbol{\tau}, \quad (2)$$

$$\frac{\partial(\rho E)}{\partial t} + \nabla \cdot [(\rho E + p) \mathbf{u}] = \nabla \cdot (\boldsymbol{\tau} \cdot \mathbf{u}) - \nabla \cdot \mathbf{q}, \quad (3)$$

where ρ is density, $\mathbf{u} = (u, v, w)$ velocity, p pressure, and the total specific energy is $E = e + \frac{1}{2} |\mathbf{u}|^2$ with e the specific internal energy. The right-hand side is assembled as a telescoping difference of face fluxes, $R_i = (F_{i+1/2} - F_{i-1/2})/\Delta x$, so the discrete scheme is conservative by construction (`numerics/RHS.cpp`).

2 Inviscid flux

The hyperbolic (Euler) flux in direction $d \in \{x, y, z\}$ with unit normal $\mathbf{n}_d$ and normal velocity $u_d = \mathbf{u} \cdot \mathbf{n}_d$ is

$$\mathbf{F}_d^{\text{euler}}(\mathbf{U}, p) = \begin{pmatrix} \rho u_d \\ \rho u u_d + p n_{d,x} \\ \rho v u_d + p n_{d,y} \\ \rho w u_d + p n_{d,z} \\ (\rho E + p) u_d \end{pmatrix}. \quad (4)$$

It is evaluated by a hybrid 6th-order central / 5th-order WENO reconstruction [4, 10] in flux-difference form with Lax–Friedrichs splitting; the WENO weight is gated by the shock sensor of §6 (`physics/EulerFlux.hpp`, `numerics/WENO5.hpp`). The flux is EOS-agnostic: p is supplied by §4.

3 Viscous fluxes

The viscous stress is the compressible Stokes tensor with an optional bulk viscosity μ_b ,

$$\tau_{ij} = \mu \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} - \frac{2}{3} \delta_{ij} \nabla \cdot \mathbf{u} \right) + \mu_b \delta_{ij} \nabla \cdot \mathbf{u}, \quad (5)$$

and the heat flux is Fourier’s law

$$\mathbf{q} = -\kappa \nabla T, \quad \kappa = \frac{\mu c_p}{\text{Pr}}, \quad (6)$$

with T the temperature and Pr the Prandtl number. First derivatives use composed 6th-order central stencils (`NGHOST = 6`), so the viscous Laplacian is 6th-order accurate (`physics/ViscousFlux.hpp`, `numerics/Gradients.cpp`).

4 Equation of state

The pressure closure maps $(\text{marker}, \rho, e) \mapsto (p, c)$ through a single mixture dispatcher (`physics/MixtureEOS.hpp`), where c is the sound speed used at the flux and CFL sites.

4.1 Ideal gas

$$p = (\gamma - 1) \rho e, \quad c^2 = \frac{\gamma p}{\rho}. \quad (7)$$

4.2 Two- γ mixture (variable-density contact)

A per-cell advected marker $G = 1/(\gamma - 1)$ selects between ambient air and a second ideal gas (products with γ_p). The effective ratio of specific heats is recovered as $\gamma = 1 + 1/G$, giving

$$p = \frac{\rho e}{G}, \quad c^2 = \frac{(1 + 1/G) p}{\rho}. \quad (8)$$

This is the original variable-density contact model (`physics/Multifluid.hpp`).

4.3 Jones–Wilkins–Lee (JWL) for real high explosives

Detonation products (e.g. TNT) obey the JWL EOS, which an ideal gas cannot represent. With relative volume $V = \rho_0/\rho$ (ρ_0 the reference/solid density) and Grüneisen coefficient ω ,

$$p(\rho, e) = A \left(1 - \frac{\omega}{R_1 V}\right) e^{-R_1 V} + B \left(1 - \frac{\omega}{R_2 V}\right) e^{-R_2 V} + \omega \rho e. \quad (9)$$

Writing $f(V)$ for the reference-curve (first two) terms, $p = f(V) + \omega \rho e$, which inverts in closed form for the internal energy at fixed density, $e = (p - f(V))/(\omega \rho)$, and yields the isentropic sound speed $c^2 = (\partial p / \partial \rho)_s$. With $A = B = 0$ the EOS reduces to an ideal gas with $\gamma = 1 + \omega$, the hook that lets the mixture dispatcher treat air and products uniformly (`physics/JWL.hpp`).

The shipped TNT parameter set (LLNL / Dobratz & Crawford [16]) is:

Parameter	Symbol	Value
Reference coefficient	A	371.2 GPa
Reference coefficient	B	3.231 GPa
Reference exponent	R_1	4.15
Reference exponent	R_2	0.95
Grüneisen coefficient	ω	0.30
Reference density	ρ_0	1630 kg/m ³
Detonation energy	E_0	7.0 GPa
CJ pressure	p_{CJ}	21 GPa
Detonation speed	D	6930 m/s

Runs are nondimensionalized with $\rho_{\text{ref}} = \rho_0$ and $p_{\text{ref}} = p_{\text{CJ}}$ so the $\sim 1000:1$ density and $\sim 10^5:1$ pressure contrasts (Atwood ≈ 0.999) stay well conditioned. The CJ density $\rho_{\text{CJ}} = \rho_0 / (1 - p_{\text{CJ}} / (\rho_0 D^2))$ is the Rankine–Hugoniot value, self-consistent with the JWL sound speed at CJ ($c_{\text{CJ}} = D - u_{\text{CJ}}$).

4.4 Stiffened gas

The stiffened-gas (Noble–Abel/Tammann) EOS adds a constant stiffness pressure p_∞ to the ideal-gas law so that nearly incompressible phases (water, condensed explosives) share the same Grüneisen-type closure as a gas:

$$p = (\gamma - 1) \rho e - \gamma p_\infty, \quad c^2 = \frac{\gamma (p + p_\infty)}{\rho}. \quad (10)$$

With $p_\infty = 0$ this reduces to the ideal gas (the analogue of JWL’s $A = B = 0$ reduction), so a stiffened-gas phase doubles as an ideal-gas phase (`physics/StiffenedGas.hpp`).

4.5 Five-equation mixture (volume-fraction / Wood rule)

For the five-equation model (§5.3) [11, 12] two phases coexist in each cell with volume fraction α_1 ($\alpha_2 = 1 - \alpha_1$) and partial densities $Z_k = \alpha_k \rho_k$. Each phase obeys a Grüneisen split of its internal-energy density, $\rho_k e_k = (p + \Phi_k)/(\Gamma_k - 1)$, where

$$\Gamma_k - 1 = \begin{cases} \gamma_k - 1 & \text{stiffened gas} \\ \omega_k & \text{JWL} \end{cases}, \quad \Phi_k = \begin{cases} \gamma_k p_{\infty,k} & \text{stiffened gas} \\ -f_k(V_k) & \text{JWL (ref. curve, §4.3)} \end{cases}. \quad (11)$$

Summing $\rho e = \sum_k \alpha_k \rho_k e_k$ over the phases gives the volume-fraction-averaged (Wood) pressure

$$p = \frac{\rho e - \Pi}{S}, \quad S = \sum_k \frac{\alpha_k}{\Gamma_k - 1}, \quad \Pi = \sum_k \frac{\alpha_k \Phi_k}{\Gamma_k - 1}, \quad (12)$$

with ρe the mixture internal-energy density and $\rho = Z_1 + Z_2$. The frozen mixture sound speed is the mass-weighted phase average

$$c^2 = \sum_k Y_k c_k^2, \quad Y_k = Z_k / \rho, \quad (13)$$

where c_k^2 is the per-phase stiffened-gas/JWL sound speed at the common pressure p . For stiffened-gas phases S and Π are linear in α_1 — the property that lets an isolated interface stay pressure-oscillation-free (`physics/MixtureEOS.hpp`, `p_c5eq`).

5 Multifluid models

5.1 Model taxonomy

The solver carries two multifluid models, both single-velocity and single-pressure, related by the diffuse-interface hierarchy (Baer–Nunziato’s seven-equation non-equilibrium system [1] being the full parent):

- **Transported- γ four-equation model** [5, 9, 2, 3]: the three conservative hydrodynamic equations of §1 plus *one* advected EOS marker (below). The equation of state is selected per cell by the marker; there are no per-phase masses. This is distinct from the *mass-fraction* four-equation model (two partial masses closed by temperature equilibrium [12]), which this code does not implement.
- **Five-equation diffuse-interface model** [11, 8]: velocity- and pressure-equilibrium two-phase flow with two partial-mass equations, mixture momentum and energy, and a volume-fraction transport (§5.3).

The $4 \rightarrow 5$ transition splits the single mixture mass into the two partial masses $\alpha_1 \rho_1, \alpha_2 \rho_2$ and replaces the transported γ marker by the volume fraction α_1 .

5.2 Transported- γ marker transport

The marker (the two- γ field G , or the products mass fraction $\phi \in [0, 1]$ for JWL) is advected with the flow,

$$\frac{\partial(\rho\chi)}{\partial t} + \nabla \cdot (\rho\chi \mathbf{u}) = 0, \quad \chi \in \{G, \phi\}, \quad (14)$$

equivalently $\partial\chi/\partial t + \mathbf{u} \cdot \nabla\chi = 0$ by continuity. The contact is handled either by a gated double-flux (non-oscillatory) or an opt-in fully conservative flux (`conservative = true`); the latter conserves total energy at the cost of small contact oscillations (`physics/Multifluid.cpp`). The double-flux method — freezing the per-cell EOS across the flux stencil so a single-material conservative scheme handles the contact without spurious pressure oscillation — is that of Abgrall & Karni [9] (building on Karni [2] and Abgrall [3]); “gated” here denotes that it is applied only within a few cells of a contact (bulk cells take the cheap shared flux), an implementation optimization rather than a separately named scheme.

5.3 Five-equation diffuse-interface model

The true five-equation system [11, 8] advances the two partial masses, the mixture momentum and energy, and the volume fraction:

$$\frac{\partial(\alpha_1\rho_1)}{\partial t} + \nabla \cdot (\alpha_1\rho_1 \mathbf{u}) = 0, \quad (15)$$

$$\frac{\partial(\alpha_2\rho_2)}{\partial t} + \nabla \cdot (\alpha_2\rho_2 \mathbf{u}) = 0, \quad (16)$$

$$\frac{\partial(\rho\mathbf{u})}{\partial t} + \nabla \cdot (\rho\mathbf{u} \otimes \mathbf{u} + p\mathbf{I}) = \nabla \cdot \boldsymbol{\tau}, \quad (17)$$

$$\frac{\partial(\rho E)}{\partial t} + \nabla \cdot [(\rho E + p)\mathbf{u}] = \nabla \cdot (\boldsymbol{\tau} \cdot \mathbf{u}) - \nabla \cdot \mathbf{q}, \quad (18)$$

$$\frac{\partial\alpha_1}{\partial t} + \mathbf{u} \cdot \nabla\alpha_1 = 0, \quad (19)$$

with mixture density $\rho = \alpha_1\rho_1 + \alpha_2\rho_2$ and pressure p from the Wood-rule law (§4.5). The non-conservative volume-fraction equation is discretized in quasi-conservative form, $\partial\alpha_1/\partial t + \nabla \cdot (\alpha_1\mathbf{u}) = \alpha_1 \nabla \cdot \mathbf{u}$, using the same face velocities as the conservative fluxes. The two partial-mass fluxes reuse the same reconstruction as the mixture-mass flux, so $Z_1 + Z_2 \equiv \rho$ to round-off, and the interface stays pressure/velocity-equilibrium (no spurious oscillation at a contact). The state is advanced in lockstep with the conserved fields through every SSP-RK3 stage (`numerics/RHS.cpp`, `add_inviscid_divergence_5eq`; `numerics/RK3.cpp`, `step_5eq/step_mpi_5eq`).

6 LES closure and shock capturing

6.1 Spectral hyperdissipation (LES sink)

The sub-grid sink is a hyper-viscous term applied to every conserved variable,

$$\left. \frac{\partial \mathbf{U}}{\partial t} \right|_{\text{LES}} = -\nu_h \nabla^4 \mathbf{U}, \quad (20)$$

whose discrete operator matches the analytic k^4 damping; under SSP-RK3 it preserves the $e^{-\nu_h k^4 t}$ eigenvalue decay (`numerics/HyperdissipationSpectral.cpp`). The empirical stability invariant is fixed $\nu_{\text{eff}} = \nu_h k_{\text{max}}^2$; between resolutions ν_h scales as Δx^2 (see the README TGV note).

6.2 Ducros shock sensor

The hybrid central/WENO blend [10] and the artificial diffusivity are gated by the Ducros sensor [7]

$$\theta = \frac{(\nabla \cdot \mathbf{u})^2}{(\nabla \cdot \mathbf{u})^2 + |\boldsymbol{\omega}|^2 + \varepsilon}, \quad (21)$$

with vorticity $\boldsymbol{\omega} = \nabla \times \mathbf{u}$ and a small ε ; $\theta \rightarrow 1$ in compression (shocks), $\theta \rightarrow 0$ in smooth/vortical regions. A pressure-jump tanh ramp and a half-width-2 dilation along the face direction sharpen the gate (`numerics/Ducros.cpp`).

6.3 Localized artificial diffusivity (LAD)

For strong blasts the Cook/Kawai–Lele localized artificial diffusivity [13, 14] adds grid-dependent, sensor-localized dissipation to shocks and contacts,

$$\mu^* = C_\mu \rho |\nabla^r (\nabla \cdot \mathbf{u})| \Delta^{r+2}, \quad \beta^* = C_\beta \rho |\nabla^r (\nabla \cdot \mathbf{u})| \Delta^{r+2}, \quad (22)$$

with an analogous artificial mass/contact diffusivity D^* for the density-contact piece; the canonical order is $r = 4$ (`numerics/ArtificialDiffusivity.cpp`).

7 BHR variable-density turbulence model

The Besnard–Harlow–Rauenzahn [15] k - ε - a - b model runs as an operator-split sub-step alongside the LES hydro. The six primitives are the turbulent kinetic energy k , its dissipation ε , the turbulent mass flux a_i , and the density-specific-volume covariance $b = -\overline{\rho' (1/\rho)'}$. The dominant TKE source is the variable-density (baroclinic) production

$$P_{VD} = -a_i \frac{\partial p}{\partial x_i}, \quad (23)$$

validated as dominant in the LES a/b budget. The turbulent viscosity is $\nu_t = C_\mu k^2/\varepsilon$, and the modeled transport equations carry gradient-diffusion terms with Schmidt numbers ($\sigma_k, \sigma_\varepsilon, \sigma_a, \sigma_b$) (`turbulence/BHR.hpp`, `turbulence/BHR.cpp`).

When two-way feedback is enabled, the model returns a Reynolds-stress divergence and dissipative heating to $\mathbf{U}$, blended by the resolution-adequacy sensor

$$f_k = \frac{k_{\text{sgs}}}{k_{\text{res}} + k_{\text{sgs}}}, \quad k_{\text{res}} = \frac{1}{2} |\mathbf{u} - \tilde{\mathbf{u}}|^2, \quad (24)$$

where $\tilde{\mathbf{u}}$ is a test-filtered velocity (resolved energy in the $[\Delta x, 2\Delta x]$ octave); $f_k \rightarrow 1$ under-resolved (RANS), $f_k \rightarrow 0$ when the LES resolves the energy.

8 Time integration

Time advance uses the three-stage strong-stability-preserving Runge–Kutta (SSP-RK3, Gottlieb–Shu [6]) scheme on $\mathbf{U}^n \rightarrow \mathbf{U}^{n+1}$ with right-hand side $\mathcal{L}(\mathbf{U})$:

$$\mathbf{U}^{(1)} = \mathbf{U}^n + \Delta t \mathcal{L}(\mathbf{U}^n), \quad (25)$$

$$\mathbf{U}^{(2)} = \frac{3}{4} \mathbf{U}^n + \frac{1}{4} \mathbf{U}^{(1)} + \frac{1}{4} \Delta t \mathcal{L}(\mathbf{U}^{(1)}), \quad (26)$$

$$\mathbf{U}^{n+1} = \frac{1}{3} \mathbf{U}^n + \frac{2}{3} \mathbf{U}^{(2)} + \frac{2}{3} \Delta t \mathcal{L}(\mathbf{U}^{(2)}). \quad (27)$$

The time step obeys the minimum of a hyperbolic CFL ($\propto \Delta x/(|\mathbf{u}| + c)$) and a viscous limit; in MPI runs both are reduced with `MPI_Allreduce(MIN)` (`numerics/RK3.cpp`, `numerics/RHS.cpp`).

9 Diagnostic identities

9.1 Helmholtz decomposition

The velocity is split into solenoidal and dilatational parts, $\mathbf{u} = \mathbf{u}_s + \mathbf{u}_d$ with $\nabla \cdot \mathbf{u}_s = 0$ and $\nabla \times \mathbf{u}_d = \mathbf{0}$, giving the kinetic-energy split $K = K_{\text{sol}} + K_{\text{dil}}$ and the per-shell spectra $E(k) = E_{\text{sol}}(k) + E_{\text{dil}}(k)$ (`diagnostics/Spectra.cpp`).

9.2 Dissipation budget

The resolved dissipation is split into solenoidal and dilatational contributions,

$$\varepsilon_{\text{total}} = \frac{\mu}{\rho} \langle \tau_{ij} \partial_j u_i \rangle, \quad \varepsilon_{\text{sol}} = \nu \langle |\boldsymbol{\omega}|^2 \rangle, \quad \varepsilon_{\text{dil}} = \frac{4}{3} \nu \langle (\nabla \cdot \mathbf{u})^2 \rangle, \quad (28)$$

together with the turbulent Mach number $M_t = u_{\text{rms}}/\langle c \rangle$ (`diagnostics/Statistics.cpp`).

9.3 Conservation monitors

For a closed chamber the totals E/E_0 and M/M_0 are conserved to round-off by the discrete divergence theorem (telescoping face fluxes plus $\mathbf{u} \cdot \mathbf{n} = 0$ at slip walls); the internal energy $e_{\text{int}} = \sum (\rho E - \frac{1}{2} \rho |\mathbf{u}|^2)$ is accumulated directly so $KE + e_{\text{int}} = e_{\text{total}}$ is a genuine consistency check rather than an identity (`diagnostics/Statistics.cpp`; see the README for the conservation-vs-truncation discussion).

References

- [1] M. R. Baer and J. W. Nunziato, “A two-phase mixture theory for the deflagration-to-detonation transition (DDT) in reactive granular materials,” *Int. J. Multiphase Flow* **12**(6):861–889, 1986.
- [2] S. Karni, “Multicomponent flow calculations by a consistent primitive algorithm,” *J. Comput. Phys.* **112**(1):31–43, 1994.
- [3] R. Abgrall, “How to prevent pressure oscillations in multicomponent flow calculations: a quasi conservative approach,” *J. Comput. Phys.* **125**(1):150–160, 1996.
- [4] G.-S. Jiang and C.-W. Shu, “Efficient implementation of weighted ENO schemes,” *J. Comput. Phys.* **126**(1):202–228, 1996.
- [5] K.-M. Shyue, “An efficient shock-capturing algorithm for compressible multicomponent problems,” *J. Comput. Phys.* **142**(1):208–242, 1998.
- [6] S. Gottlieb and C.-W. Shu, “Total variation diminishing Runge–Kutta schemes,” *Math. Comp.* **67**(221):73–85, 1998.
- [7] F. Ducros, V. Ferrand, F. Nicoud, C. Weber, D. Darracq, C. Gacherieu, and T. Poinsot, “Large-eddy simulation of the shock/turbulence interaction,” *J. Comput. Phys.* **152**(2):517–549, 1999.
- [8] A. K. Kapila, R. Menikoff, J. B. Bdzil, S. F. Son, and D. S. Stewart, “Two-phase modeling of deflagration-to-detonation transition in granular materials: reduced equations,” *Phys. Fluids* **13**(10):3002–3024, 2001.

- [9] R. Abgrall and S. Karni, “Computations of compressible multifluids,” *J. Comput. Phys.* **169**(2):594–623, 2001.
- [10] S. Pirozzoli, “Conservative hybrid compact-WENO schemes for shock-turbulence interaction,” *J. Comput. Phys.* **178**(1):81–117, 2002.
- [11] G. Allaire, S. Clerc, and S. Kokh, “A five-equation model for the simulation of interfaces between compressible fluids,” *J. Comput. Phys.* **181**(2):577–616, 2002.
- [12] A. Murrone and H. Guillard, “A five equation reduced model for compressible two phase flow problems,” *J. Comput. Phys.* **202**(2):664–698, 2005.
- [13] A. W. Cook, “Artificial fluid properties for large-eddy simulation of compressible turbulent mixing,” *Phys. Fluids* **19**(5):055103, 2007.
- [14] S. Kawai and S. K. Lele, “Localized artificial diffusivity scheme for discontinuity capturing on curvilinear meshes,” *J. Comput. Phys.* **227**(22):9498–9526, 2008.
- [15] D. Besnard, F. H. Harlow, R. M. Rauenzahn, and C. Spangler, “Turbulence transport equations for variable-density turbulence and their relationship to two-field models,” Tech. Rep. LA-12303-MS, Los Alamos National Laboratory, 1992.
- [16] B. M. Dobratz and P. C. Crawford, “LLNL Explosives Handbook: Properties of Chemical Explosives and Explosive Simulants,” Tech. Rep. UCRL-52997, Lawrence Livermore National Laboratory, 1985.