

CoaXPress 线缆规格说明

说明

Hello-FPGA 的 CoaXPress 接口电缆用于连接 DIN 1.0/2.3、 BNC 公头、BNC 母头或 HD-BNC 接头，用于 CoaXPress 接口相机与其它 CoaXPress 设备互联。使用高质量连接器与线缆，可以满足 CoaXPress 规范要求的高速信号传输。

型号

接头描述	6.25G 系列型号	12.5G 系列型号
DIN (1.0/2.3) to DIN (1.0/2.3)	HF-C6-000-xxx.x	HF-C12-100-xxx.x
BNC male to DIN (1.0/2.3)	HF-C6-010-xxx.x	HF- C12-110-xxx.x
BNC male to BNC male	HF- C6-011-xxx.x	HF- C12-111-xxx.x
DIN (1.0/2.3) to BNC Female	HF- C6-002-xxx.x	HF- C12-102-xxx.x
BNC male to BNC Female	HF- C6-012-xxx.x	HF- C12-112-xxx.x
BNC Female to BNC Female	HF- C6-022-xxx.x	HF- C12-122-xxx.x
Micro-BNC to Micro-BNC	HF- C6-033-xxx.x	HF- C12-133-xxx.x
Micro-BNC to DIN (1.0/2.3)	HF- C6-030-xxx.x	HF- C12-130-xxx.x
Micro-BNC to BNC male	HF- C6-031-xxx.x	HF- C12-131-xxx.x
Micro-BNC to BNC Female	HF- C6-032-xxx.x	HF- C12-132-xxx.x

线缆长度: xxx.x 是对应的线缆长度 1m = 1.00
选购示例: HF- C12-133-10.0 = Micro-BNC 转 Micro-BNC 12G 10 米

