

Assignment #2

An Exercise of SQL Using SQL*Plus

KAIST

Myoung Ho Kim

Table of Contents



- ◆ **SQL*Plus**
 - Oracle SQL*Plus
 - Access to database
- ◆ **SQL*Plus Commands**
- ◆ **Assignment #2**
 - SQL Queries

SQL*Plus



Oracle SQL*Plus

- ◆ An Oracle command-line utility program that can run SQL commands interactively or from a script.



Access to DB using SQL*Plus

◆ Install Oracle Client

- 1) <http://www.oracle.com/technetwork/database/enterprise-edition/downloads/index.html>
- 2) Scroll down to *Oracle Database 11g Release 2*
- 3) Click *See All*



ORACLE

Oracle Database 11g Release 2

Standard Edition, Standard Edition One, and Enterprise Edition

7/13: Patch Set 11.2.0.4 for Linux and Solaris is now available on support.oracle.com. Note: it is a full installation (you do not need to download 11.2.0.1 first). See the [README](#) for more info (login to My Oracle Support required).


(11.2.0.1.0)

Microsoft Windows (32-bit)	File 1, File 2 (2GB) See All
Microsoft Windows (x64)	File 1, File 2 (2GB) See All
Linux x86	File 1, File 2 (2GB) See All
Linux x86-64	File 1, File 2 (2GB) See All

Access to DB using SQL*Plus (Cont'd)

◆ Install Oracle Client

4) Download *Oracle Database 11g Release 2 Client*




5) Run *setup.exe*

6) Install 'Manager' type

Access to DB using SQL*Plus (cont'd)

◆ Run SQL Plus


- 1) Download *tnsnames.ora* from course homepage and copy it to (directory that *Oracle Client* is installed: ex. C:\app\MyDirect\product\11.2.0\client_2\network\admin
- 2) Run *SQL Plus*



Access to DB using SQL*Plus (cont'd)

◆ Access to database

- User-name: `s[studentID]@cs360`
 - » ex) If your studentID is 20151234, then your user-name is `s20151234@cs360`
- Password: `s[studentID]`
 - » ex) If your studentID is 20151234, then your password is `s20151234`
 - It is recommended to change your password for security



```
SQL Plus

SQL*Plus: Release 11.2.0.1.0 Production on 2015. 3월 14 01:31:07

Copyright (c) 1982, 2010, Oracle. All rights reserved.

Enter user-name: s20151234@cs360
Enter password:

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 - 64bit Production
With the Partitioning, OLAP, Data Mining and Real Application Testing options

SQL> password
Changing password for S20151234
Old password:
```


SQL*Plus Commands



SQL*Plus Commands

◆ SQL*Plus buffer commands

- **LIST** List one or more lines of the SQL buffer
- **CHANGE** Change text on the current line in the buffer
- **DEL** Delete one or more lines of the buffer
- **APPEND** Add specified text to the end of the current line in the buffer
- **RUN** Execute the SQL command currently stored in the SQL buffer
- **CLEAN BUFFER** Erase the SQL command currently stored in the SQL buffer

◆ SQL*Plus file commands

- **SAVE** Save the contents of the SQL buffer in a host operating system file
- **GET** Load a host operating system file into the SQL buffer
- **START** Execute the contents of the specified script
- **SPOOL** Store query results in an operating system file (.sql)
- **HOST** Execute a host operating system command without leaving SQL*Plus
- **EDIT** Open a text editor like the notepad to edit an text file (.sql, .lst, etc)

SQL*Plus Commands (cont'd)

- ◆ **SQL*Plus buffer commands**

- » Besides sending SQL statements to the server, SQL*Plus also saves them into a local buffer and allow users to view and change the statements
- *LIST*
 - » Display one or more lines of the SQL buffer
- *CHANGE*
 - » Change text on the current line in the buffer
- *RUN*(or */*)
 - » Execute the SQL command currently stored in the SQL buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus buffer commands

- *DEL*

- » Delete one or more lines of the buffer

- *APPEND/ INPUT*

- » Add specified text / line(s) to the end of the current line in the buffer

- *CLEAR BUFFER*

- » Erase the SQL command currently stored in the SQL buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus buffer commands
 - *LIST, CHANGE*

```
SQL> select customer_numberr
2 , email
3 from customer
4 where state='TX';
select customer_numberr
*
```

ERROR at line 1:
ORA-00904: "customer_numberr": invalid
identifier

```
SQL> list;
1 select customer_numberr
2 , email
3 from customer
4* where state='TX'
```

Show the contents
in the sql buffer



```
SQL> list 1;
1* select customer_numberr
```

List the first line

```
SQL> change /numberr/number;
1* select customer_number
```

Change text
on the current line

```
SQL> list;
1 select customer_number
2 , email
3 from customer
4* where state='TX'
```

Show the contents
in the sql buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus buffer commands
 - *RUN*(or */*), *DEL*

```
SQL> list;
1 select customer_number
2 , email
3 from customer
4* where state='TX'
```

Show the contents
in the sql buffer

```
SQL> /
```

CUSTOMER_NUMBER	EMAIL
321654987	bfarmer@email.com

Execute the command
currently stored
in the sql buffer



```
SQL> list;
1 select customer_numbererr
2 , email
3 from customer
4* where state='TX'
```

Show the contents
in the sql buffer

```
SQL> del 4;
```

Delete the 4th line

```
SQL> list;
1 select customer_number
2 , email
3* from customer
```

Show the contents
in the sql buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus buffer commands
 - *APPEND*

```
SQL> list;  
1 select customer_numberr  
2 , email  
3 from customer  
4* where state='TX'
```

Show the contents
in the sql buffer

```
SQL> list 2;  
2* , email
```

Show the second line

```
SQL> append ,city  
2* , email,city
```

Add text to the end
of the current line
in the buffer



```
SQL> list;  
1 select customer_number  
2 , email,city  
3 from customer  
4* where state='TX'
```

Show the contents
in the sql buffer

```
SQL> /  
CUSTOMER_NUMBER      EMAIL      CITY  
-----  
321654987             bfarmer@email.com  DALLAS
```

Execute the command
currently stored
in the sql buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus buffer commands
 - *INPUT, CLEAR BUFFER*

SQL> **list;**

```
1 select customer_number
2 , email,city
3 from customer
4* where state='TX'
```

Show the contents
in the sql buffer

SQL> **del 4;**

Delete the 4th line

SQL> **list;**

```
1 select customer_number
2 , email,city
3* from customer
```

Show the contents
in the sql buffer



SQL> **input where state='FL'**

Add a line to the end
of the current line
in the buffer

SQL> **list;**

```
1 select customer_number
2 , email,city
3 from customer
4* where state='FL'
```

Show the contents
in the sql buffer

SQL> **clear buffer;**

Buffer cleared

Erase the commands
currently stored
in the buffer

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus file commands

- *SAVE, GET, START(or @)*

- » Save the contents of the SQL buffer into a script file
 - » Load a contents of script file into the SQL buffer
 - » Execute the contents of the specified script

- *SPOOL*

- » Store query results in an operating system file
 - » SPOOL result.lst : start to write in result.lst
 - » SPOOL OFF : stop to write

- *HOST*

- » Execute a host operating system command without leaving SQL*Plus
 - ex) HOST *dir* : execute a MS-DOS command *dir*

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus file commands
 - *SAVE, GET, START*(or *@*)

cf. If you cannot execute these commands, please run SQL*Plus in administrator mode

```
SQL> select customer_number,  
2 email, city from customer  
3 where state='TX';
```

CUSTOMER_NUMBER	EMAIL	CITY
321654987	bfarmer@email.com	DALLAS



```
SQL> save query.sql;
```

Save buffer contents
into a file

```
SQL> get query.sql;
```

```
1 select customer_number,  
2 email, city from customer  
3 where state='TX'
```

Retrieve a file
and place it
into the buffer

```
SQL> @query.sql
```

CUSTOMER_NUMBER	EMAIL	CITY
321654987	bfarmer@email.com	DALLAS

SQL*Plus Commands (cont'd)

- ◆ SQL*Plus file commands
 - *SPOOL, HOST*

SQL> **spool result.lst**

Start to write
in result.lst

SQL> **create table Spooled(name char(10));**
Table created.

SQL> **spool off**

Stop to write

SQL> **create table NotSpooled(name integer);**
Table created.

SQL> **spool result.lst append**

Restart to write
in result.lst

SQL> **create table
anotherSpooled(name char(10));**
Table created.

SQL> **spool off**

Stop to write

SQL> **host dir**
result.lst schema.sql insert.sql

Execute
a command /s

SQL> **edit result.lst**

Open *result.lst*
to see or edit



Assignment #2



Submission

- ◆ **Due**

- Sep. 23, 2:00 a.m.
- Delay is not accepted

- ◆ **Submission standard**

- *[student ID].lst* contains the executions of SQL commands and their results. You may use **SPOOL** command.
- Upload the .lst file to course homepage


- ◆ **Evaluation**

- You will get points if your **SQL queries** find the right answers.
- Do not cheat others. Both of them will get no point.

Example Database

- ◆ Create tables for homework.

- 1) Download *HW2db.sql* from the course homepage and Copy it to (directory that *Oracle Client* is installed)\BIN
- 2) *@HW2db.sql* or *start HW2db.sql*

A screenshot of a Windows-style window titled "SQL Plus". The window has a black background with white text. The prompt "SQL>" is followed by the command "@HW2db.sql", which is highlighted by a yellow rectangular box. Below the command, the output shows "Table dropped." three times and "Table created." once. The window includes standard Windows window controls (minimize, maximize, close) in the top right corner and a scrollbar on the right side.

```
SQL Plus
SQL> @HW2db.sql
Table dropped.
Table dropped.
Table dropped.
Table created.
```

Example Database (cont'd)

◆ Database Design

- You can see all the tables stored in your database using a command '**select * from tab**'

PRODUCT	maker	<u>model</u>	type
	A	2001	pc
	A	1002	pc
	...		

PC	<u>model</u>	speed	ram	hd	price
	1001	2.66	1024	250	2114
	1002	2.10	512	250	995
	...				

LAPTOP	<u>model</u>	speed	ram	hd	screen	price
	2001	2.00	2048	240	20.1	3673
	2002	1.73	1024	80	17.0	949
	...					

PRINTER	<u>model</u>	color	type	price
	3001	true	Ink-jet	99
	3002	false	laser	239
	...			

Queries

- ◆ **Q1. Find all the tuples in the Printer relation for color printers. Remember that color is a boolean-valued attribute.**
 - If a value of color attribute is 1 then the printer is a color printer.
 - If a value of color attribute is 0 then the printer is not a color printer
- ◆ **Q2. Find the model number, speed, and hard-disk size for all PC's whose price is under \$800.**
- ◆ **Q3. Find the manufacturers of laptops**

Queries

- ◆ **Q4. Find those manufactures that sell PC's but not Laptops**
 - In oracle, the operator for difference of sets is 'MINUS' (instead of 'EXCEPT')
- ◆ **Q5. Find the model number and price of all products (of any type) made by manufacturer C**
- ◆ **Q6. Find those processor speeds that occur in two or more PC's**

References

- ◆ Lecture notes
- ◆ Text book
 - Chapter 6.1, 6.2, 6.3
- ◆ Oracle SQL Plus Tutorial
 - <http://www.holowczak.com/oracle/sqlplus/>