

## Team Dynamic

### Hai Tong Yang

Weeder, invalid programs, milestone2 documentation, design decision, debugging the type checker

### Shaokun Deng

Type checker, design decision, debugging the type checker

### Dong Kyu Kim

PrettyPrinter, design decision, debugging the type checker

## Design Decision for the Symbol Table and the Type Checker

### Symbol Table

- We used a linked list of HashMap instead of a stack of HashMap
- The first element of the linked list is always the current scope
- HashMap is structured as HashMap<String, Type> where String is the name of a variable and Type is the type of that variable

### Type

- We created a Type class which encapsulates all the types, such as int, float64, function, slice, etc.
- We have implemented "is(Type t)" method in the Type class to check if the two Types are the same Type.
- We also have implemented "assign(Type t)" method in each of basic type classes to check if t can be assigned to each of the basic type.
- AliasType
  - It has a Type attribute, which is the real type of the alias
- ArrayType
  - It has a Type attribute, which is the Type of element
  - It has an int attribute, which is the size of the array
- FunctionType
  - It has an ArrayList<Type> attribute, which contain the Types of parameters
  - It has a Type attribute, which is the Type of return value
- SliceType
  - It has a Type attribute, which is the Type of element
- StructType
  - It has a HashMap<String, Type> attribute, which contain the name and the Type of the fields
  - For the fields of the struct, instead of putting "x.a" into the symbol table,

we put the Struct type with the linked list of attributes into the symbol table.

Stuff for code generation

- We have decided not to change alias type casting from function call node to type casting node.

We do return the correct type for the type cast. The decision was made because we find changing,

adding and deleting nodes quite messy and decided to do the same checks during the code generation phase.

## Enumeration of the type checks

=====

Declaration

=====

Variable declaration

checks variables with same name cannot be repeatedly declared in same scope

basic types: var\_decl\_exp.go, var\_decl\_type\_exp.go,  
var\_decl\_type.go

struct: type\_decl\_struct.go

array: type\_decl\_struct.go

Function declaration

check function with same name cannot be repeatedly declared in same scope

function: func\_decl.go, func\_param.go

Type declaration

checks alias types are well defined

type\_decl\_badAlias.go

=====

Statement

=====

Return

\*for a function of non-void return type, check the return type on every execution path is assignable to the function signature.

test file: return\_nonvoid.go

\*for a function of void return type, check the return type on every execution path is void(i.e. just "return").

test file: return\_void.go

Assignment capability:

| <u>lhs\rhs</u> | <u>int</u> | <u>float64</u> | <u>string</u> | <u>bool</u> | <u>rune</u> |
|----------------|------------|----------------|---------------|-------------|-------------|
| <u>int</u>     | YES        | NO             | NO            | NO          | YES         |
| <u>float64</u> | YES        | YES            | NO            | NO          | YES         |
| <u>string</u>  | NO         | NO             | YES           | NO          | NO          |
| <u>bool</u>    | NO         | NO             | NO            | YES         | NO          |
| <u>rune</u>    | YES        | NO             | NO            | NO          | YES         |

test files: assign\_floatToInt.go, assign\_stringToFloat.go,  
assign\_stringToInt.go

For loop

check condition is type bool  
test file: for\_condition.go

If statement

check condition is type bool  
test file: if\_condition.go, elseif\_condition.go

Switch statement

check expression in cases has same type as in the beginning of  
the switch statement  
test file: switch\_type\_match.go

=====

Expression

=====

Casting capability:

| <u>to\from</u> | <u>int</u> | <u>float64</u> | <u>string</u> | <u>bool</u> | <u>rune</u> |
|----------------|------------|----------------|---------------|-------------|-------------|
| <u>int</u>     | YES        | YES            | NO            | NO          | YES         |
| <u>float64</u> | YES        | YES            | NO            | NO          | YES         |
| <u>string</u>  | NO         | NO             | YES           | NO          | NO          |
| <u>bool</u>    | NO         | NO             | NO            | YES         | NO          |
| <u>rune</u>    | YES        | YES            | NO            | NO          | YES         |

test files: cast\_boolToRune.go, cast\_intToBool.go,  
cast\_stringToInt.go

Binary operators:

`+=, +`

| <u>lhs\rhs</u> | <u>int</u> | <u>float64</u> | <u>string</u> | <u>bool</u> | <u>rune</u> |
|----------------|------------|----------------|---------------|-------------|-------------|
| <u>int</u>     | YES        | NO             | NO            | NO          | YES         |
| <u>float64</u> | YES        | YES            | NO            | NO          | YES         |
| <u>string</u>  | NO         | NO             | YES           | NO          | NO          |
| <u>bool</u>    | NO         | NO             | NO            | NO          | NO          |
| <u>rune</u>    | YES        | NO             | NO            | NO          | YES         |

test files: `op_assign_plus.go`, `binary_intAddString.go`

`-=, *=, /=, %=, -, *, /, %`

| <u>lhs\rhs</u> | <u>int</u> | <u>float64</u> | <u>string</u> | <u>bool</u> | <u>rune</u> |
|----------------|------------|----------------|---------------|-------------|-------------|
| <u>int</u>     | YES        | NO             | NO            | NO          | YES         |
| <u>float64</u> | YES        | YES            | NO            | NO          | YES         |
| <u>string</u>  | NO         | NO             | NO            | NO          | NO          |
| <u>bool</u>    | NO         | NO             | NO            | NO          | NO          |
| <u>rune</u>    | YES        | NO             | NO            | NO          | YES         |

test files: `op_assign_sub_stringToString.go`

`|=, ^=, &=, ||, &&`

both lhs and rhs must be bool

test files:

`<<=, >>=, &^=`

both lhs and rhs must be int

Unary operator

`+`: expr must be numeric (int, float64, rune)

test file: `unary_plus_string.go`

-:expr must be numeric (int, float64, rune)  
test file: unary\_neg\_string.go  
!:expr must be a bool  
test file: unary\_not\_int.go, unary\_not\_string.go

#### Indexing

check index is well-typed and has type int.  
test file:index\_float.go  
check the result of the indexing expression is the type of the array/  
slice  
test file:index\_expressionMatch.go

#### Field selection (expr.id)

check expr is of type struct and has field named id  
test file:fieldSelect\_notStruct.go, fieldSelect\_hasField.go

#### Append append(id, expr)

check id is found in the symbol table and maps to a Slice<T>  
test file:append\_notSlice.go  
check type of expr is compatible with type of the slice  
test file:append\_incompatibleType.go