

When Does Independent Audit Help Agentic Science? CrossAudit and a Causal Evaluation Framework

Zhaohe Dong
University of Cambridge
zd314@cam.ac.uk

Yuhao Chen
University of Wisconsin–Madison
ychen2546@wisc.edu

September 2026

Abstract

An AI scientist should not grade its own homework, but changing the grader does not make the grade independent. Whether same-model, same-family, same-vendor, and cross-vendor reviewers have meaningfully different error correlations remains an empirical question; supervision records also often sit in platform logs outsiders cannot inspect.

We present **CrossAudit**, a protocol and evaluation framework for supervising autonomous research pipelines. Each increment is audited by an agent from a different declared vendor against a versioned, human-authored rulebook. Reports, verdicts, disputes and rulings are git commits; raw model exchanges are not yet preserved. Scripted checks run first. A model blocks only by citing a rule, cannot waive a deterministic failure, and unresolved blockers go to a person after bounded revision. We formalise net correction under false-block, revision-harm, model-cost, and human-attention constraints; vendor is an assignment factor, not a synonym for independence.

We state eight invariants, describe a GitHub Actions/Python implementation, and report a live computational-chemistry deployment. A sealed v4 feasibility cohort completed 542 calls across seven modules and six deterministic convenience tasks. It revealed direction heterogeneity, a Constitution-repeat estimand mismatch, DCL/gold circularity, and no structured-ledger advantage over an ordinary log on proxy decisions. These non-confirmatory engineering findings are not evidence that cross-vendor review works. We therefore specify a prospective v5 study with 150–180 tasks, three vendors, six pinned models, same-model and same-vendor/different-model controls, three domains, human-blinded gold, and task-clustered inference. The present contribution is the protocol, executable evaluation machinery, and falsifiable study design; efficacy remains unestablished.

Keywords: agentic science; AI scientist; scalable oversight; cross-vendor auditing; LLM-as-a-judge; self-preference bias; research integrity; human-in-the-loop.

1 Introduction

Two things motivated this paper. The first is the arrival of genuinely agentic research systems: pipelines in which large language model (LLM) agents propose hypotheses, write and execute code, run experiments, and draft manuscripts with limited human intervention. Sakana’s AI Scientist produced machine-generated papers end-to-end [1, 2] and the line of work has since been published in *Nature* [3]; DeepMind’s AI co-scientist organises hypothesis generation as a multi-agent tournament [4]; autonomous laboratories close the loop through to physical synthesis [10, 11]. Publishers and funders are already being urged to respond institutionally [14].

The second is older and more familiar: science’s continuing struggle with reliability. In one large survey, most researchers had failed to reproduce a published result [13]. Agentic pipelines raise the stakes on both

sides of this ledger. On one side, they can enforce a discipline that no human sustains: every increment logged, every parameter recorded. On the other, they can mass-produce plausible, well-formatted, wrong results faster than any human audit culture can absorb.

The relevant question, then, is not whether machine-generated science should be supervised, but how that supervision should be organised and who should provide it. Current frontier systems typically place supervision within the same architecture, using reflection agents, automated reviewers, or ranking tournaments [1, 4]. This creates a structural weakness: the critic and the creator are usually instantiated from the same model family or, at best, from models developed within the same vendor’s training pipeline. LLM evaluators are known to favour their own generations, with self-recognition identified as a causal factor in this self-preference bias [5]; position and stylistic biases introduce further distortions [8]. Agents trained on similar data may also share systematic blind spots, so a reviewer with the same blind spots as the author may fail to detect the author’s characteristic errors. At the same time, the supervision record (what was flagged, what was revised, and what was allowed to pass) often remains confined to transient context windows or proprietary platform logs. As a result, the communities asked to trust the resulting science cannot independently inspect the process by which it was reviewed.

Contributions. We make five contributions.

1. We separate same-model, same-family, same-vendor/different-model, and cross-vendor supervision, treating reduced error correlation as a hypothesis rather than a property supplied by a vendor label (§2).
2. We specify **CrossAudit**, a supervision protocol defined by eight invariants (vendor heterogeneity, ledger completeness, citation validity, determinism-first, bounded revision, graded interruption, receipt binding, fail-closed admission) that together specify a re-inspectable, third-party-auditable (up to self-declared vendor identity, §6) supervision history (§4).
3. We formulate audit value as net correction under false-block, revision-harm, model-cost, and human-attention constraints, yielding predictions that distinguish independence from auditor capability (§3).
4. We report a sealed six-task execution-feasibility cohort that runs seven measurement paths and, importantly, returns mixed and adverse boundaries rather than a universal cross-vendor advantage (§5.4).
5. We provide a prospective, executable three-vendor confirmatory package with a complete assignment matrix, same-vendor/different-model control, human reference panels, task-level estimands, power simulation, and fail-closed preflight (§5.5).

CrossAudit is deliberately limited in what it claims to establish. It does not certify scientific truth. No textual audit can. Instead, it records a narrower and directly inspectable property: that each increment in a machine-generated research record was evaluated against a named, versioned set of rules by a configured auditor from a second vendor, and that the resulting parsed decision was preserved in the ledger. The auditor has no write access to the increment’s repository, although its vendor identity is currently self-declared (§6). The ledger is public wherever the operator chooses to publish it. At present it preserves parsed audit reports, while capture of the raw model requests and responses is planned for revision 2. We argue that this narrower guarantee is an appropriate first target for accountable machine science, much as continuous integration, not formal verification, became the principal quality-control mechanism in modern software development.

2 Related work and the same-source problem

Agentic science systems. The AI Scientist [1, 2, 3] automates the ideation–experiment–writeup–review cycle, including an internal automated reviewer scored against human reviewer data. The AI co-scientist [4]

structures generation–reflection–ranking–evolution agents into a self-improving tournament over hypotheses, with reported expert-validated outcomes in drug repurposing and antimicrobial resistance. Language agents for literature synthesis reach or exceed expert performance on retrieval-grounded tasks [12]. In the laboratory, Coscientist executed chemistry protocols from natural-language goals [10] and A-Lab ran autonomous materials synthesis campaigns [11]. Across all of these systems, quality control is architecturally *internal*. The reviewer agents, reflection stages, or tournament judges are chosen and hosted by the same operator, run inside the same platform, and are frequently instantiated from the same model family as the generators they judge. None of them commits to vendor heterogeneity in the reviewing layer.

The pattern persists through the 2025 generation of research agents: Curie hardens agentic experimentation with internal rigour modules [15], and Agent Laboratory attaches critic agents to its own pipeline [16]. Commercial platforms now advertise the transparency half of our proposal: Kosmos promises reports in which “every conclusion can be traced” to code or literature via its platform [17]. Traceability of that kind is audit by the generating operator on its own infrastructure. It is valuable, but it involves no second-party auditor and no off-platform, replayable ledger. This paper is about that distinction.

Why internal critique is not enough. Panickssery et al. demonstrate that LLM evaluators recognise their own generations and rate them preferentially. Their fine-tuning experiments indicate that the capacity for self-recognition is what causes the inflation [5]. Zheng et al. catalogue further judge pathologies, including position, verbosity, and self-enhancement biases, even in strong models [8]. A recent large-scale evaluation sharpens why these matter for supervision rather than for benchmarking: in a twenty-one-judge cohort, two production-deployed judges combine high test-retest reliability with severe position bias, and raw agreement overstates judge quality substantially once corrected for chance [9]. A judge can therefore be thoroughly reproducible and still be wrong in a fixed direction, which is the one failure a supervision loop must not inherit. Two later studies qualify the self-preference finding rather than overturn it: much of the measured preference tracks genuine quality differences between generations [6], and identity-blind re-tests leave roughly half of previously significant cases standing [7]. The configuration CrossAudit forecloses is therefore a narrower target than the headline effect, and we treat foreclosing it as a structural precaution, not a quantified harm averted. These results concern single-model self-evaluation. We expect the mechanism to generalise. Models that share a training pipeline are likely to share stylistic priors and knowledge gaps, and this places a same-vendor critic at the wrong end of the bias distribution just when its judgement matters most. We call this the *same-source supervision problem*. The remedy of drawing judges from different model families has precedent. Verga et al. score generations with a panel of evaluators drawn from three model families, expressly to dilute intra-model bias [18], and the same intuition has begun to appear in developer tooling as cross-vendor code review.¹ CrossAudit’s claim is not the heterogeneity idea itself but its packaging as a supervision protocol for research: versioned rules, a replayable ledger, deterministic precedence, and bounded escalation, run against a live pipeline. Cross-vendor pairing does not eliminate correlated error. Frontier models plausibly train on largely overlapping public corpora, so where the shared literature is wrong, both auditors can be confidently wrong together. What pairing does foreclose is the demonstrated configuration of the best-documented bias in this setting, self-preference, and it is intended to decorrelate vendor-idiosyncratic failure modes. What cross-vendor pairing cannot fix, a model-free layer must (§4, **I4**).

Supervision as an artefact. Software engineering solved an analogous trust problem not by making programmers infallible but by making the quality mechanisms *inspectable*: version control, continuous integration, review trails. Reproducibility initiatives in science point in the same direction. The unit of trust is

¹E.g. MindStudio, “Cross-Vendor AI Agent Review: Why Claude Should Review Codex’s Code and Vice Versa” (June 2026), <https://www.mindstudio.ai/blog/cross-vendor-ai-agent-review-claude-codex>, as accessed 30 July 2026, a workflow recommendation, without versioned rules, ledger, deterministic precedence, or escalation semantics.

Table 1: Supervision properties of the systems considered here (a set we chose, not a systematic survey), as published. • = held by design; ~ = partial or informal; – = absent. PoLL is an evaluation technique, not a supervision loop; statcheck and the Problematic Paper Screener are deterministic by construction but run post-publication, where CrossAudit moves checks of that character before a claim leaves the repository. CrossAudit appears twice so that a specification is never graded on an implementation’s behalf: the protocol row states what the specification requires, and the implementation row grades the public reference implementation, whose ledger preserves parsed records but not raw exchanges (§5) and whose auditor vendor identity is self-declared (§6). The ledger column is graded at **I2**’s parsed-record tier; full process replay is unachievable while model calls are stochastic, for the specification as much as for any implementation.

	Critic from a different vendor	Versioned, decidable rules	Replayable audit ledger	Deterministic precedence	Bounded loop, escalation
The AI Scientist [1]	–	–	~	–	~
AI co-scientist [4]	–	–	–	–	~
PoLL judge panels [18]	•	–	–	–	–
Cross-vendor review advice (§2)	•	–	~	–	–
statcheck, PPS [19, 20]	–	~	~	•	–
CrossAudit protocol (this paper)	•	•	•	•	•
CrossAudit reference implementation	~	•	~	•	•

the auditable record, not the author’s competence [13]. Deterministic screening of the research record also has its own lineage. statcheck recomputes reported statistics across the psychology literature [19], and the Problematic Paper Screener runs mechanical detectors over millions of published papers [20]. Both are post-publication analogues of our deterministic check layer, which moves checks of that character upstream, before a claim ever leaves the repository. At the ledger end, blockchain-based research-integrity infrastructures pursue tamper-evidence with far heavier machinery.² Our position is that git, which is ubiquitous, free, and already attached to CI, permissions, and issue tracking, is ledger enough for the supervision trail. CrossAudit transplants this inspectability stance to agentic science: the supervision history itself becomes a first-class, versioned, citable research artefact. Table 1 compresses the comparison.

Operational interpretation. The vendor-level extrapolation above is a design hypothesis, not an empirical result. In the remainder of this paper, “cross-vendor” names an assignment that removes exact self-evaluation and may change error correlation; it does not certify independence. A causal evaluation must separately compare the same snapshot, a different snapshot from the same vendor, and snapshots from other vendors while holding the harness and information fixed.

3 When should heterogeneous audit help?

Let E_G denote a defect in a Generator artefact and E_A the event that an Auditor fails to block it. The quantity that motivates separation is the conditional error association

$$\rho_{GA} = \text{Corr}(E_G, E_A \mid X, M_G, M_A, H), \quad (1)$$

where X is the task, M_G and M_A are the resolved model configurations, and H fixes the harness, prompt, information, and controller. A vendor label is not present in this definition: it is an observable assignment attribute that may change ρ_{GA} , auditor capability, both, or neither. Cross-vendor assignment is useful only when the reduction in correlated error is not offset by a weaker or miscalibrated Auditor.

²E.g. the bloxberg consortium, <https://bloxberg.org>.

Gate accuracy is also an incomplete objective. Let s denote a supervision condition. We define its operational value as

$$U(s) = v_r P_s(R) - c_b P_s(B_0) - c_n P_s(N) - c_u P_s(U) - c_m M_s - c_h H_s, \quad (2)$$

where R is a defect correctly repaired, B_0 a clean artefact unnecessarily blocked or escalated, N a new defect introduced during revision, U an unnecessary change, M_s model cost, and H_s human attention. The weights are deployment-specific and cannot be estimated from gate accuracy alone; unless frozen prospectively, we report the components and their Pareto frontier rather than choosing weights after seeing results.

This framing yields four falsifiable predictions. First, exact self-audit, same-vendor/different-model audit, and cross-vendor audit need not be ordered monotonically: capability and error association compete. Second, a deterministic check layer should help on mechanisable defects but may add no information when it also defines the gold label. Third, a broad Constitution can raise $P(B_0)$ even while increasing raw recall. Fourth, hard gating can increase $P(R)$ and simultaneously increase $P(N)$, $P(U)$, cost, or rule-surface adaptation. The evaluation therefore measures final net correction and clean burden, not defect recall in isolation.

4 The CrossAudit protocol

4.1 Objects and roles


CrossAudit supervises a pipeline in which a **Generator** agent (vendor A) produces discrete *experiment increments* and commits them under a designated path of a **Science Repository**. Each increment is audited by an **Auditor** agent (vendor $B \neq A$) against a versioned, human-authored rulebook, the **Constitution**, held with all *audit reports* in a separate **Audit Repository**. A **Deterministic Check Layer** (DCL), plain scripts with no learned component (schema validation, unit and dimension analysis, convergence assertions, provenance completeness), runs before any model reads anything. A **Human Principal** authors the Constitution and receives escalations, but sits outside the per-increment loop. Compute (in the reference deployment, jobs on cloud HPC) is decoupled from supervision: verdicts gate the *next* increment, never running jobs. Figure 2 traces one increment through the loop.

The two-repository split is separation of powers made mechanical (Figure 1): the Auditor holds no write access to the Science Repository, the Generator none to the Audit Repository, so neither agent holds credentials to alter the other’s record. Guarding each record against its *own* author also requires branch protection.

4.2 Eight invariants


An implementation conforms to the extent that it preserves the following: Table 2 grades, invariant by invariant, what the reference implementation enforces, targets, or leaves to deployment, and we reserve “invariant” for the protocol’s obligation, never for an implementation’s achievement. (**I7** and **I8** are revision-1 invariants, adopted from the cross-vendor audit of this repository described in §5.4.)

I1 — Heterogeneity. The Auditor’s model family differs from the Generator’s. This prevents the auditor from ever judging its own generations, the configuration in which self-preference bias has been demonstrated [5]. Similarity-driven preference is reduced, not eliminated. It is likewise designed to decorrelate vendor-idiosyncratic failure modes, an effect this paper does not measure (§5). Heterogeneity is also one of three isolations the protocol stacks: *parametric* (different weights), *contextual* (no shared memory: the Auditor never sees the Generator’s prompts, reasoning, or conversational state, only committed artefacts). The mechanism we intend to remove is the one by which shared context sways a judge. The nearest evidence, that assistants accommodate a user’s stated view [21],



Solid arrows are write access, dashed are read. Neither agent can write where the other's record lives.

Figure 1: Separation of powers. The Generator cannot touch the rules or the reports that judge it, and the Auditor cannot touch the record it audits. The Auditor reads committed artefacts and never the Generator's prompts or reasoning. Only the human principal writes the rulebook. Guarding each record against its *own* author also requires branch protection.



Every element on this page is a git commit or a GitHub issue: the parsed supervision record is re-inspectable by anyone the operator grants access to.

Figure 2: One experiment increment through the loop, read clockwise from the top left. Numbers give the order, and the three coloured paths out of the verdict are the only ways a cycle can end. The report commit lands before its receipt: the receipt binds the report's content hash, so it can never reference an uncommitted object, and the receipt is derived by the deterministic audit-side workflow, never authored by the model. Who may write where is Figure 1; the walk in full is §4.1 and §4.4.

concerns human-prompted sycophancy, not agent-to-agent anchoring, so contextual isolation is a design

precaution here and not a channel we have shown to be closed, and *credential* (no shared credentials; §4.1).

- I2 — Ledger completeness.** Every protocol artefact (increment, report, verdict, dispute, escalation, and every change to the Constitution) is a commit or an issue in one of the two repositories. The guarantee has three tiers and only the first is currently met. *Parsed-record inspectability*: the reports, verdicts and receipts as committed, which the reference implementation does provide. *Raw-exchange preservation*: the model requests and responses behind them, which it does not yet capture. *Full process replay*: re-executing the supervision from the record, which is not achievable at all while the model calls are stochastic. A deployment should say which tier it holds. Ours holds the first, and §5 records two further gaps: the deployed variant’s controller state lives outside both repositories, and its generator’s session state was never committed.
- I3 — Citation validity.** An audit report must cite the rule IDs it applied and the commit hash of the Constitution version in force. A report that cites nothing, or an unverifiable version, is *invalid*, is treated as an Auditor failure, and escalates. It can never pass an increment. The precedence is part of the invariant: an invalid report escalates even where the deterministic layer has independently blocked, because an integrity failure must never be absorbed into an ordinary scientific verdict, and admission fails closed on it.
- I4 — Determinism first.** The DCL runs before any LLM audit. A DCL hard failure yields BLOCKED regardless of any model’s opinion, and no model may waive a DCL verdict. Rationale: heterogeneous models still train on largely overlapping public corpora and hence can share their errors. The supervision layer whose failure modes are least entangled with any model is one with no learned component at all.
- I5 — Bounded revision.** At most `max_rounds` Generator–Auditor exchanges per increment (default three). Exhaustion escalates. This is the oscillation guard: without it, two mutually-correcting agents can disagree indefinitely, each round locally plausible and the pair jointly divergent.
- I6 — Graded interruption.** Findings carry exactly two severities. BLOCKER (objective defect: DCL failure, internal contradiction, missing provenance, method–declaration mismatch) gates the increment. ADVISORY (judgement: parameter taste, style, scope) is recorded for asynchronous human reading and never gates. Humans are interrupted only by ESCALATE. Running compute is never interrupted at all.
- I7 — Receipt binding.** Every verdict is a *receipt* bound to the audited commit SHA; to an artefact manifest (paths and content hashes) that the Audit Repository derives from that SHA itself, never from caller-supplied payload; to the Constitution, check-layer, and prompt versions applied; to the auditor’s declared identity; and to the ledger commit of the report. A verdict that binds less is not a receipt.
- I8 — Fail-closed admission.** Protected actions (admitting the next increment, production submission, claim publication) proceed only on verification of a valid, current, matching receipt. Absent, stale, conflicting, unbound, or model-audit-less receipts deny by default and escalate: no audit, no admission.

Two severities only. In our judgement every additional level invites severity-inflation negotiation between the agents. Where a finer distinction is needed it belongs in the rule’s acceptance criterion, not in the escalation lattice.

Table 2 condenses the eight invariants into a reference card: the guarantee each one makes, the mechanism that enforces it, and how far the reference implementation carries that enforcement today. The statuses are the ones §5 accounts for. The distance that remains is enumerated in ROADMAP–R2.md.

Table 2: The eight invariants as a reference card. “Enforced” means the reference implementation refuses the violating action in code; statuses follow the audited account in §5, and the implementation as a whole targets **I1–I8** while implementing a subset.

	Guarantee	Enforced by	Implementation status
I1	The Auditor never judges its own model family’s output	Vendor pairing asserted from <code>crossaudit.yml</code> at dispatch	Enforced from configuration; vendor identity self-declared (§6)
I2	Supervision history replayable from the two repositories alone	Every artefact a commit or issue; append-only full-SHA cycle directories	Parsed reports preserved; raw model exchanges not yet captured
I3	A report citing no rules, or an unverifiable Constitution, can never pass	Invalid replies escalate, alone or atop a DCL hard failure (verdict-precedence tests); admission refuses receipts whose <code>audit_integrity</code> is not OK (tested)	Enforced
I4	No model may waive a scripted hard failure	Verdict synthesis is code; a DCL hard failure dominates any model verdict	Enforced
I5	Generator–Auditor oscillation terminates	Controller-managed rounds; exhaustion escalates	Enforced by the controller state machine
I6	Humans are interrupted only by escalation	Two-severity schema; ADVISORY never gates	Enforced in schema and router
I7	A verdict binds commit, manifest, and versions, or it is not a receipt	Receipt derived from the checked-out tree; verifier checks every bound field	Receipts emitted and verified; raw-exchange capture short of I2 ’s full intent
I8	No audit, no admission	Single-use, freshness-guarded admission; DCL_ONLY never admits	Verifier and controller enforce; binding admission to branch protection is a deployer toggle

4.3 The Constitution

The Constitution is the protocol’s quality ceiling: the Auditor’s blocking power may not, by rule, exceed the rules it is given (miscitation is caught by the dispute channel, not prevented), and the Generator is free to exploit whatever the rules fail to say. CrossAudit therefore treats it as law rather than documentation. Every rule carries a stable identifier (CA-DATA-001), a severity, a path scope, a *decidable* acceptance criterion, and a rationale. Decidability is the load-bearing requirement: a criterion a competent reader can evaluate against named artefacts without further judgement. What cannot be phrased decidable is either demoted to ADVISORY or (better) mechanised and moved into the DCL. Meta-rules govern the audit itself: missing evidence is a finding, never an implicit pass (CA-META-001); a report without citations is invalid (CA-META-002, enforcing **I3**); the Auditor may not issue a BLOCKER without citing a BLOCKER-severity rule and so does not legislate taste (CA-META-003); and matters beyond the increment-plus-Constitution evidence base must escalate rather than be guessed (CA-META-004). Constitution changes are commits reviewed by the human principal. The loop can propose rules but never enact them. (The name deliberately echoes, but must not be confused with, Constitutional AI [22]: there, a constitution steers a model’s training-time self-critique. Here it is a runtime rulebook applied by a structurally independent auditor and versioned in the ledger.)

4.4 Rounds, disputes, termination

Round k for an increment: the Auditor publishes report R_k with a verdict. On BLOCKED, the Generator either *revises* (a new commit, opening round $k+1$) or a dispute is lodged against specific findings by rule ID, with grounds supplied by the principal. A disputed finding returns to the Auditor once: it is withdrawn with a




Figure 3: Termination as a walk on four states. Every path from OPEN ends in PASSED (admission gated by receipt) or ESCALATED (a human decides); the only cycle in the graph is the revision loop, and the round bound cuts it after `max_rounds` exchanges. The dispute edge re-enters the same loop instead of adding one: a finding may return to the Auditor once.

Table 3: Five objects, and which claims attach to which. The paper moves between them, and a claim about one is not a claim about another. The exploratory trial in §5.4 and the separate six-task feasibility cohort in §5.4 report model outcomes; neither is the registered confirmatory successor.

Object	What it is	What it is claimed to do	What it is not	Evidence here
Protocol	The eight invariants, §4.2	Define a supervision configuration	An implementation	Argument only
Reference implementation	§5, workflows and Python	Target all eight, enforce a subset (Table 2)	A product	Regression tests; the trial’s scorer
Live deployment	§5, one chemistry pipeline	Show the loop runs unattended	Conforming: it diverges on I2 and on two-level severity, both named	Observational ledger, no control
Product line	§5.3, a separate package	Show what a second implementation taught the specification	Evaluated anywhere in this paper	None
Successor programme	§5.4, a registered confirmatory design plus a separate six-task feasibility cohort	Estimate configuration-specific effects and component trade-offs	A completed confirmatory study or vendor-population result	Registration and SAP; sealed non-confirmatory feasibility results

logged reason, or upheld. An upheld dispute at the round bound escalates. Disputes exist because the Auditor is fallible in both directions: a false-positive BLOCKER, silently obeyed, degrades the science as surely as a false negative. The one-shot rule prevents the dispute channel from becoming the oscillation it exists to control. Two asymmetries make the channel safe, and the product line (§5.3) enforces both in code, not by convention. The disputer states grounds and the Auditor rules, so nothing in a dispute can overturn a finding by itself. It buys a second reading, and the second reading is the Auditor’s. And the Generator may not dispute at all. Grounds come from the principal, because a generator arguing with its own audit is the anchoring channel **II**’s contextual isolation exists to close. Contesting the *rule* rather than the finding is an amendment, which is dated and effective only between cycles. Termination is structural: each increment ends in PASS or in human hands after at most `max_rounds` exchanges. Figure 3 draws the walk.

5 Reference implementation and deployment

5.1 Mechanics

The reference implementation³ uses no infrastructure beyond GitHub itself and two model API endpoints. A push under `experiments/` triggers a cross-repository dispatch carrying the commit SHA; the audit side derives the audited scope from the SHA itself and the round from its own report index; caller-supplied payload is treated as an untrusted hint. The Audit Repository’s workflow checks out the science repository *pinned at the audited SHA*, asserts **I1** from configuration, runs the DCL, then invokes the Auditor via an OpenAI-compatible endpoint with the Constitution, the DCL output, and the increment content as fenced data. The report is committed to the ledger, the verdict is dispatched back, and the science repository routes it, proceed, revise, or open an escalation issue. The whole implementation is three workflow files and two Python programs (a check runner and an auditor runner) of a few hundred dependency-light lines. Configuration is a single `crossaudit.yml` declaring vendors, `max_rounds`, and escalation policy.

Status against the invariants. Per-invariant enforcement and status are Table 2’s job (§4.2); what belongs here is how those statuses were earned, because the route is itself evidence for the protocol. Following two rounds of cross-vendor audit of this repository (§5.4; both reports and dispositions committed under `audits/`), scope became SHA-derived, rounds ledger-derived rather than generator-controlled, receipts full-field, and the reply validator strict; truncated, unreadable, or symlinked inputs now escalate rather than pass, and keyless runs yield `DCL_ONLY`, which the router treats as non-admission. A third cross-vendor read (also committed) then found the sharper failure mode: the controller state machine and full receipt verifier existed but were not wired into the execution path, dry-run admission, a hard-coded report path that broke on disputed rounds, a constitution check that could never fire. Those wiring defects are fixed. What remains unimplemented is the deployer-side binding of the admission status to branch protection, and raw model-exchange capture in the audit runner. The public implementation should therefore be read as *targeting I1–I8* and implementing selected checks. The remaining distance is enumerated in `ROADMAP-R2.md`.

Three details with protocol weight. First, the auditor runner validates the model’s reply against a fixed schema (verdict, findings with severities and rule citations) and any malformed or citation-free reply is converted to `ESCALATE (I3)`; a familiar failure of LLM judges (the confident empty report) is thereby converted from silent passage into an escalation. Where the DCL has also hard-failed, the recorded verdict now escalates as well: the synthesis places **I3** above **I4** deliberately, because an integrity failure must never be absorbed into an ordinary scientific verdict, and a regression test pins the combined case (`controller/tests/test_verdict_precedence.py`; a valid model `PASS` still cannot outrank a DCL failure, so **I4** is untouched). The receipt carries the auditor failure in `audit_integrity`, and admission refuses any receipt where it is not `OK` (also tested), so the gate holds even against an older deployed runner. Second, increment content is passed to the Auditor as fenced, size-bounded content with the system prompt instructing that embedded instructions be ignored, a best-effort defence whose residual risk §6 states plainly. The reference Auditor has no tools. Third, verdict synthesis is code, not model output: DCL hard failures dominate any model verdict (**I4**).

5.2 A live deployment

A closely related variant of CrossAudit runs live in the first author’s computational-chemistry pipeline (perovskite additive screening). The generation side is a Claude-based research agent that plans calculations, launches them on Alibaba Cloud E-HPC and a GPU worker, and pushes every increment to a private science

³<https://github.com/dongzhaohe321418-lab/crossaudit> (MIT licence).

repository whose audit policy, an epistemic-status ledger separating established, bounded, and provisional claims, together with a standing retraction log, is itself a committed, versioned document. A controller opens each cycle against a fixed science commit. The audit request pins a SHA-256 manifest of every tracked file. A Codex-CLI auditor (OpenAI lineage, so **I1** holds against the Claude-based generator) writes four artefacts into an append-only per-cycle directory in the audit repository: a human-readable report, a machine-readable result, run metadata, and a per-file hash manifest. All sit on one long-lived audit branch that later cycles may not rewrite. The controller enforces this by validating every audit commit before recording a cycle as final, which detects a rewrite rather than preventing one. Prevention would need branch protection. The controller’s own orchestration state deliberately lives outside both repositories, so tampering by either agent with the record of its own supervision is detectable against controller-held state.

Three deliberate divergences from the reference design should be named plainly: the deployed auditor is a tool-bearing CLI agent rather than the reference’s toolless one, contained instead by that commit validation and the append-only cycle layout. The externalised controller state means the deployment’s history is fully replayable from the repositories *plus* that state, a weaker property than **I2**’s repositories-alone ideal; and findings carry a four-level severity ladder feeding scope-level gates, rather than the protocol’s two levels, a live experiment running against §4.2’s two-level argument, whose outcome the telemetry will eventually adjudicate.

Every committed scientific artefact and parsed supervision decision lives on GitHub; raw model exchanges, transient progress and controller orchestration state do not (**I2**). The system is designed so that any single component (generator, auditor, controller host, workstation) can fail without loss of the committed ledger state.

Two refinements of the deployed system go beyond the reference implementation and are worth adopting upstream. First, findings are *evidence-typed*: each carries a policy citation (section and rule ID), a deterministic check identifier where applicable, and a copy-paste *reproduce* command, so a human can re-derive any deterministic finding in seconds. Second, blocking is *scope-granular*: a finding blocks named scopes, production-job submission, claim publication, rather than the pipeline wholesale, refining **I6**’s graded-interruption principle. Human authority enters through escalation, plus one deployment-specific addition: a standing principal-approval gate on production launches, recorded in the ledger. The loop is live in the plainest sense: its first cycle (opened and closed within six minutes) returned a BLOCK decision on deterministic grounds (manifest-hash disagreements and commit-provenance defects), freezing production submission and claim publication until resolved. Audits gate the record and future submissions, never running jobs: E-HPC work in flight is never interrupted. A redacted public mirror of the deployment’s finalised cycles is maintained in the reference repository (`ledger-mirror/`; scientific magnitudes masked, structure, rule citations and reproduce-command shapes verbatim). Including that first cycle, the ledger accumulated seven model-audited cycles across two days (Figure 4): decisions ran BLOCK five times, then PASS WITH CAVEATS, then PASS, while findings per cycle fell 7, 4, 3, 2, 1, 1, 0. Part of that fall is the audit boundary moving, because the early cycles audit accumulated backlog and the later ones fresh increments; and with no control condition, what would have been caught without the loop is not knowable from this series. Of fourteen distinct findings, twelve are behaviourally confirmed real: each revise leg is a science-repository commit naming the finding IDs it closes, and the following cycle verifies the closure; two remain unresolved at the data freeze. All twelve were detected and closed before the gated downstream action. Whether they would have been caught some other way, this deployment cannot say: it ran no control condition. One leg (the ledger’s numbering gap at cycle 3) ran as a deterministic-tier follow-up without a model audit and is reported as-is. The generator’s session state was never committed, so no in-context self-review arm can be reconstructed retrospectively; that absence is itself evidence for **I2**. The mined, structurally redacted cycle records are frozen in this repository (`experiment/v3/real-ledger/`).


The loop has since kept running. By 3 August (second freeze: science 485106fa, audit abb10a47; the counting rules and regeneration script are committed with it) the ledger held 21 model-audited cycles carrying

39 finding occurrences under 23 distinct finding identifiers, 20 of the 23 behaviourally confirmed closed (a fix commit named the finding and a re-audit verified the closure, which is closure evidence, not independent ground truth) and 3 still open at the freeze. The first arc converged, then two more increments passed on their first audit. What followed matters more. Sustained development settled at roughly one to three findings per cycle, and stayed there. The loop reaches a working rate, not zero, and that is the regime a long-running deployment lives in. Median closure lag, counted per distinct finding from first raise to verified closure over the 20 closed (the 3 open are excluded, not imputed), was one cycle, with a mean of 2.10 and a maximum of 7; ten of the 23 identifiers recur across cycles, which is what a re-audit exists to catch. On the deployment's own four-level ladder the 23 findings graded as three CRITICAL, thirteen HIGH, four MEDIUM, and three LOW. Twenty-five of the 39 occurrences cite a single rule, firing in 16 of the 21 cycles, the kind of concentration that tells a principal where the next deterministic check should go. The scope-granular gate was working throughout: counting finding-scope incidences, which overlap because one finding can gate two scopes, 33 gated claim publication and 12 gated production submission, and at the snapshot a claim-publication action stood withheld pending a clean verdict beneath it. Audits took a median of six minutes (range 3.7–18.2); the interval from one audit finishing to the next beginning, which bundles the repair with any idle time, had a median of thirty-four minutes (quartiles 18 and 70, the maximum an overnight gap). So the audit is not the wall-clock bottleneck. What those repairs cost in human attention, which is what §7's economics is actually about, the ledger does not record.

Four things temper all of this. We report the shape of that second stretch and claim nothing causal from it, because the two stretches are not a matched comparison: the first audited accumulated work, the second audits fresh increments, and we drew the boundary after seeing the series. The auditor model was not held fixed either, since four identifiers appear in the metadata, so the series mixes configurations and cannot support arm comparison. Findings carry the deployment's own source label, 11 of the 39 occurrences marked DETERMINISTIC against 28 marked JUDGMENT; that records what caught each defect, not what could have. The second question is the one our registered study asks, and it remains unanswered. Finally, the v3 study's Part B labels stay frozen at the 31 July snapshot. These later cycles are observational telemetry from one deployment with no control condition, and the analysis behind them, limits stated at length, is committed at `experiment/v3/real-ledger-b/`.

Costs for the reference design are modest. The DCL is free. A single fenced-increment audit call scales with the size of the increment, not of the computation behind it, a few hundred lines of results and metadata read per call, while the experiment it gates may represent hours of HPC time; we quote no currency figure, because per-cycle token telemetry is deferred and an unmeasured price is not a datum. (The deployed variant's tool-bearing auditor reads more and costs more; per-cycle cost reporting is deferred with the rest of the telemetry.) Auditing costs roughly what it costs to read the documentation, not what the compute behind it cost. Two caveats: multi-round exchanges multiply audit calls, and escalations spend human time, which is the truly scarce resource here.

The deployment's role is existence proof, an observational feasibility case study with no control condition and no effectiveness claim, for the deployed variant: the loop has run unattended, at single-researcher scale, on commodity infrastructure, and has completed one full convergence arc from BLOCK to PASS. Its first catch was attributable to the deterministic layer; the thirteen findings that followed came through the tool-bearing auditor, and what fraction of them a script could have caught (the mechanisability of the confirmed set) is a registered endpoint of the follow-up study, adjudication pending, not a claim made here.



Each next science commit names the finding IDs it closes; the following cycle verifies the closure. 12 of 14 distinct findings confirmed closed; 2 unresolved at freeze.

Figure 4: The live deployment’s first convergence arc (seven cycles; the 21-cycle figures in the text come from a second freeze, 2026-08-03), mined from its audit ledger at the first data freeze (science af0dc587, audit 88b92429; structurally redacted records in `experiment/v3/real-ledger/`). Top lane: the audited science commits, with the day boundary from the ledger’s timestamps dashed. Middle lane: the audit cycles, coloured by decision, with the deployment’s own numbering gap preserved (the dashed pointer marks leg 3, a deterministic-tier follow-up without a model audit). Bottom: findings per cycle on a shared baseline, falling 7, 4, 3, 2, 1, 1 to 0 as decisions move from BLOCK to PASS; the twelve behaviourally confirmed defects were closed before the downstream actions they gated.

5.3 What a second implementation taught the specification

A separate line of work rebuilt the loop as an installable package, carrying the engine’s invariant semantics over unchanged.⁴ It is measured nowhere here, and we describe none of its interface. What a second implementation buys is the ordinary benefit of writing a specification down twice: the underspecified parts of the first writing become visible. Three did, and all three are about the protocol, not the package.

Admission is a tier, not a switch. I8 says protected actions proceed only on a verified receipt, and §4.2 notes that binding the check to branch protection is a deployer action. That framing is too binary for the field. Deployments sit at different distances from the guarantee: the history may be the operator’s to rewrite, or beyond unilateral control, or privilege-separated between the agents, or genuinely gated so that a failed audit refuses the merge. The distance that matters most is the one between the last two, where a paired deployment publishes verdicts that refuse nothing. Calling that state *paired* invites the reading *gated*, and announcing a verdict while implying refusal is worse than saying nothing: it manufactures confidence the ledger cannot support. Naming it separately is the fix, and the evidence rule behind the naming matters as much: absent evidence never counts in favour, so persistence is established by taking the lock rather than by reading a configuration field, and branch rules are read from the platform rather than from the deployment plan that was meant to set them.

Whatever decides what the auditor sees is inside the trusted base. A conversational front end needs something that decides whether an utterance changes the work, changes the rules, contests a finding, or asks a question. That component is a real addition to what must be trusted. One that could quietly decide what the auditor never sees would be a third agent, unaudited, holding the power the protocol exists to distribute. The resolution follows from I2 once the invariant is read as covering discretion as well as artefacts: the routing decision itself becomes a ledger entry, carrying the utterance, the choice, the confidence, and the action taken,

⁴https://github.com/dongzhaoh321418-lab/crossaudit_v3 (MIT licence), version 3.2.0, at which this paper’s evidence about the product line is frozen; later product versions are outside it. The research repository does not chase the product, and the protocol’s authoritative text remains this paper.

so a misroute is visible and reversible instead of silent. The same reading forbids a subtler leak, since such a component must forward the principal’s words and never the Generator’s.

Domain generality is a claim an implementation can undermine quietly. Nothing in **I1–I8** mentions science, but the reference deterministic layer’s four checks assume experimental data, so the protocol’s generality and its reference implementation’s generality are not the same property. Separating them requires a domain-neutral default, domain packs as plugins, and one discipline that is easy to skip: where no pack exists for a field, the deterministic layer contributes almost nothing and the model audit carries the load alone. **I4**’s mechanical guarantee thins, and an implementation in that position should say so instead of letting a uniform interface imply uniform strength. The same reticence governs a supervision display. A figure the ledger cannot support belongs on screen as *not measured*, not as zero, because “no escalations” and “we never looked” are different claims and only one deserves a large font.

5.4 An exploratory seeded-defect trial, audited and corrected

We attempted a pre-registered, sealed seeded-defect pilot. The attempt did not survive contact with our own protocol. A cross-vendor audit of this repository, in which a second-vendor agent reviewed the generating agent’s work, returned a BLOCK-grade report whose findings voided the “sealed” framing and several companion claims; the report and our dispositions are committed at `audits/`. We adopted its findings in full. What follows are the corrected, exploratory results, which proved more instructive than the experiment we had intended to run.

Design and execution. A deterministic generator produced 30 synthetic increments in the reference format: 10 clean and 20 defective, carrying 43 seeded defects across ten registered classes, four of them mechanisable and six requiring reading. A SHA-256 digest of the defect key was committed at registration. Three arms then ran over identical inputs with the identical Constitution, though not under an identical harness, so vendor is confounded with harness and sampling throughout. The first was the deterministic check layer. The second ran fresh-context Claude subagents, one per increment, with no shared memory (session sampling, a deviation we disclose). The third ran `gpt-5.1` at temperature 0 under the frozen runner in CI. The corpus’s author is the deterministic generator, so the arm labels below name the auditor configuration alone: no arm audits work that its own model family produced, and the own-generation setting in which self-preference is demonstrated [5] is not instantiated here.

What the audit found. We checked each finding and accepted all of them. The key file was public from the registration commit onward. This was our mistake, a mis-pathed ignore rule, and the key is in any case derivable from the public seeded generator, so no blinding claim survives; what remains is procedural blinding of fresh-context auditors, which the ledger cannot verify. The headline Claude-arm score depended on a scoring-map expansion made after the outputs were committed. Under the frozen map the arm scores 38/43; under the adjudicated map, with corrections logged, it scores 43/43. The former is the reportable score and the latter is exploratory. The deterministic layer’s five L6 catches contradict the registered taxonomy: the class was misregistered as model-only when its flag component is mechanisable. The trial is component-level throughout. The corpus was read directly, with no dispatch pipeline and no DCL precedence, so it is not an end-to-end run of the reference implementation. Finally, the trial’s own outputs violate **I3**: the runner recorded no Constitution hash, a defect one of the auditors itself flagged (below).

Arm	Recall lenient / strict	Chance floor lenient / strict	BLOCKER findings on 10 clean	Verdict accuracy (of 30)
Deterministic layer	17/43 ^a	4.8 / 4.2	0	25
Claude-family (subagents)	38 / 38 ^b	22.4 / 16.3	0	30
GPT-family (gpt-5.1, frozen runner)	41 / 37 ^c	31.8 / 24.4	26	20

All figures exploratory: blinding voided, key derivable from the public generator. ^a 12/12 of its registered scope + 5/5 cross-hits on misregistered L6. ^b 43/43 under post-hoc adjudicated scoring. ^c all ten clean increments blocked (10/10 false-block verdicts); many findings letter-valid on inspection; per-finding adjudication pending. Strict-tier scores assemble rule and location evidence across findings rather than binding one finding per defect, and so overstate defect-level localisation. Chance floors: 2000-shuffle permutation null, seed 20260731; `experiment/results/NULLCHECK.json`.

The two arms read the rulebook differently. The GPT-family arm scored 41/43 at the lenient tier but 37/43 at the strict tier. It emitted 113 findings to the Claude-family arm’s 63, and it returned BLOCKED on *all thirty* increments. That figure matters, because a stub auditor that blocks unconditionally would reproduce it exactly, including the 20/30 verdict accuracy. It is the reliability-without-validity failure in its purest form [9]: a perfectly consistent judge carrying no information about the increment in front of it. Raw recall cannot settle the comparison, because it rises with the number of findings an arm emits; this is the same reason raw agreement overstates judge quality in the benchmarking literature [9]. A permutation test (2000 shuffles of the increment-to-defect map, holding each arm’s outputs fixed so that volume and citation habits are preserved; seed 20260731, `experiment/score_nullcheck.py`) puts the random floors at 4.8, 22.4, and 31.8 of 43 for the three arms. The floors calibrate each arm against its own citation volume; they do not test the gap between arms, and an earlier draft said the lenient comparison was “within noise” with no statistic behind the phrase. The direct test, computed post hoc for this revision (`experiment/arm_contrast.py`), pairs the two model arms on the 43 defects, which nest inside 20 defective increments; each reply is increment-level, so defects within an increment share one generation, and the primary inference therefore resamples and permutes increments rather than defects. At the lenient tier the arms disagree on seven defects (five caught only by the GPT-family configuration, two only by the Claude-family one); the recall difference is +3 of 43, cluster bootstrap 95% CI $[-2, +8]$, cluster sign-flip permutation $p = 0.46$ (the defect-level McNemar agrees at $p = 0.45$ but overstates independence), so these data cannot distinguish the two configurations at that tier. At the strict tier the difference is -1 of 43 (cluster CI $[-6, +4]$, $p = 1.0$; the table’s footnote on blob-level matching applies) and the chance-corrected order reverses: floor-corrected agreement, $(\text{observed} - \text{floor}) / (43 - \text{floor})$, is 0.81 for the Claude-family arm against 0.68 for the GPT-family arm. Inspection of the clean-increment blockers still suggests that many are letter-valid readings of an ambiguous rule, but per-finding adjudication was not logged, and the claim as originally framed was unfalsifiable: any disagreement would have counted as support. The rule at issue, CA-DATA-001, requires “each numeric entry” in the results file to carry a unit and a source; the corpus’s convergence blocks carry units but no sources. The Claude-family auditor, like the check scripts and like the corpus author, read the rule by its intent and raised nothing. The foreign auditor enforced its letter. What survives is narrower but real, and it is about two configurations rather than two vendors. On identical inputs, one Claude-family and one GPT-family configuration read the same rulebook differently, which is consistent with **II**’s premise and does not establish it: a single model pair, run once, cannot separate a vendor effect from a prompt, temperature, or sampling effect. The trial nevertheless measures disagreement rather than discrimination, and a 10/10 false-block rate on clean increments means that in this configuration every increment escalates, so the $O(\text{escalations})$ economics of §7 hold only under a far better-calibrated auditor or a sharper Constitution. The practical outcome was a Constitution amendment: scope the rule decidably.

What we can still claim. The limits should be stated plainly. This is a component-level, checklist-aligned trial (the prompt names the defect families the corpus injects) on template-generated data, with the Claude-

family arm’s execution self-attested and $n=43$. Zero blockers on ten clean increments bounds that arm’s false-positive rate only below $\approx 26\%$ (one-sided 95%), and its advisory burden on the clean increments was five findings across five of ten. None of this is confirmatory evidence about detection rates. Three things the trial does establish. The model layers read: they caught 26 to 29 defects beyond the scripts’ registered scope of twelve (21 to 24 beyond the seventeen the scripts caught in all). The two auditor configurations, drawn from different vendors, returned discordant readings of the same rulebook on identical inputs; with a deterministic corpus author, that is a fact about configurations, not about generator–auditor vendor pairings. And the repository’s own disciplines (append-only outputs, logged adjudication, a committed cross-vendor BLOCK with itemised dispositions) were applied to the evaluation itself.

A note from the v3 study’s preparation. The registered v3 replacement for the original trial has not run; it is distinct from the later v4 model-only feasibility cohort below. Building the v3 corpus nevertheless produced one observation that bears on **I4** directly, and we record it here rather than wait. A rule drafted for that study required the Auditor to apply any unit conversion and state its tolerance before alleging that two numbers disagree. It complied. On five clean increments it then quoted the correct conversion constant, read the correct inputs, and miscalculated the product by up to 1.8×10^{-3} eV while adjudicating a discrepancy of 8.8×10^{-5} eV, and the two increments it declared contradictory were the two where its own arithmetic was worst. A four-line script settles the same comparison correctly every time. One model, one vendor, five increments: this illustrates rather than establishes. What it illustrates is that the remedy for a model’s arithmetic is not a rule demanding the model show more of it. A comparison that is decidable belongs to the deterministic layer, which is what **I4** says; the rule was rewritten to route such pairs there instead, and the measurement is committed at `experiment/v3/SMOKE-FINDINGS.md`.

The registered causal successor and a model-only feasibility cohort. After the paper–v1.0.0 freeze, we registered the *CrossAudit v4 Causal Successor Study* at `experiment/v4/REGISTRATION.md` on 1 September 2026. It separates seven questions that this paper’s exploratory trial cannot answer: crossed Generator–Auditor assignment on work actually produced by each sampled Generator; ablations of the protocol’s distinct components; broad against corpus-scoped Constitutions; longitudinal no-audit, shadow-audit, and hard-gate conditions for defensive adaptation; seeded, naturally occurring, clean, and ambiguous-but-not-wrong material; the net effect of the complete audit–revision–re-audit loop; and whether an independent reader reconstructs decisions and detects stale or altered records better from the ledger than from a final artefact or an ordinary log. The prespecified outcomes include defect recall, finding precision, clean-increment false-block rate, net correction, defects introduced during revision, non-functional output growth, escalation and method-choice behaviour, third-party reconstruction accuracy and time, model cost, latency, and human attention.

The 120-task human-adjudicated confirmatory study remains unrun. We did, however, separately register and execute a six-task, model-only feasibility cohort to test whether all seven measurement paths, stopping controls, and the analysis chain could operate together. Its first attempt is reported independently: after 36 valid calls, one provider event violated the frozen event policy and the controller retained the remaining 435 cells as safety-stop-blocked ITT rows. We did not pool those observations. A prospectively documented second amendment narrowed only one byte-exact, content-free TLS-handshake startup failure to a cell-level provider error, with zero retry and every model-content or action event still globally fail-closed. Following a new canary and freeze, Amendment 2 completed all 542 scheduled provider calls with schema-valid outcomes at a known list-price-equivalent cost of USD 12.1504. An outcome-free seal, exact journal, and manifest were committed and pushed before the scorer produced a separately hash-bound receipt and summary. Anthropic identity metadata verified its 270 calls; the OpenAI CLI reported only the requested alias, so its 272 calls remain identity-unverified.

Table 4: Six-task v4 execution-feasibility results. All values are descriptive, non-confirmatory, and configuration-specific. ‘DCL-only’ shares the deterministic checker that defines the micro-task gold labels. Ledger participants are fresh model proxies, not humans.

Module	Observed result	Boundary exposed by the result
Generator × Auditor	Cross-minus-same correct gate +7.4 points; false block −11.1 points	Direction-specific correct-gate changes were +18.5 and −3.7 points; no universal cross advantage
DCL / Constitution	D2-minus-D0 correct gate +18.8 points; D2-minus-D1 −7.6 points and false block +14.2 points	The D2 gain over D0 was confined to natural outputs; no Constitution effect is estimated because the frozen scorer used repeat 0 rather than the registered three-repeat collapse
Defensive production	Text P2 repaired 2/9 initial errors; code visible/held-out checks were 4/4 in every arm	Text P2 used 56 vs 24 calls; code quality was ceiling-limited while 3/4 P1 and 3/4 P2 changes were compliance-only proxies
Evidence mixture	12 natural, 12 clean, 12 seeded, and 12 unusual-but-correct artefacts	Deterministic micro-task gold only; no real-repository replay or human panels
Whole loop	Initial defect resolved in 12/12 same and 12/12 cross branches; final acceptable 11/12 in each	Each assignment still had 1/12 new defect and 3/12 unnecessary changes
Ledger utility	Accept accuracy E0/E1/E2: 21.4/71.4/71.4%; tamper accuracy: 14.3/71.4/71.4%	E2 did not beat ordinary log E1; first-defective-round accuracy was 57.1% vs 92.9%
Repetition / integrity	542/542 valid calls; 96 three-repeat cells; 5/96 gate flips	Six task clusters cannot establish significance, non-inferiority, or provider reliability

Figure 5 separates the configuration and component effects that the table necessarily compresses. In the C2 model-only cells over clean, seeded, and unusual-but-correct strata, the task-standardised cross-minus-same difference was +7.4 percentage points for correct gating (descriptive task-bootstrap 95% interval, +0.9 to +13.9; six tasks) and −11.1 points for false blocking (−20.8 to −1.4). The average concealed direction heterogeneity: cross-auditing changed correct gating by +18.5 points for Anthropic-authored artefacts but by −3.7 points for OpenAI-authored artefacts. Adding the frozen deterministic result to the model verdict increased correct gating by 18.8 points relative to model-only (14.6 to 22.9), but this entire gain arose in the natural stratum; the three controlled strata did not change. Combined D2 remained 7.6 points below DCL-only and false-blocked 14.2 points more often. DCL-only scored every micro-task correctly because the same checker defined feasibility gold; it is a harness ceiling, not independent DCL validation. In the prospectively fixed two-task Constitution subset, C2 reduced correct gating by 12.5 points and increased false blocking by 25 points relative to C0/C1, an adverse small-sample signal rather than an efficacy conclusion. That feasibility contrast is additionally a repeat-0 diagnostic: the frozen scorer filtered C2 to its first repeat even though the registration says that the C2 ablation uses all three core repeats. We therefore exclude that mismatched estimand from Figure 5 pending a protocol-consistent re-analysis.

Figure 6 places the observed operational gains beside their costs and negative boundaries. Hard-gate disclosure produced a mixed pattern rather than generic defensive bloat. Before feedback, P2 research outputs contained 0.25 more observable checks per artefact than P0, were 8.4 words shorter, and showed no correctness difference; wrappers, disclaimers, and exception/retry language did not increase. After the bounded loop, P2 repaired two of nine initially incorrect outputs and ended with five of twelve correct versus three of twelve under P0, without regressing any of the three initially correct outputs. This required 56 versus 24 calls, USD 1.31 versus USD 0.53, and 726 versus 348 cumulative provider seconds. Of four P2 outputs assigned a non-neutral final proxy label, two were functional improvements and two were compliance-only. On the two-task Python subcohort, all arms passed all visible and held-out fixtures, yet three of four P1 and three of four P2 outputs were classified as compliance-only because observable checks grew without a

measured quality gain. Code LOC did not increase, and no wrappers, assertions, exception/retry constructs, or disclaimers were added. These deterministic, ceiling-limited proxies show possible rule-surface adaptation, not harmful defensive programming.

The whole-loop result likewise separates nominal repair from net outcome. Across 24 seeded branches, both assignments resolved the initial defect in 12/12 branches, yet final acceptability was 11/12, with a new defect in 1/12 and unnecessary field changes in 3/12. Cross-minus-same contrasts for those endpoints were zero; this small saturated cohort does not establish equivalence. On seven deterministic ledger episodes, final-only E0, ordinary-log E1, and structured-ledger E2 accept accuracy was 21.4%, 71.4%, and 71.4%; tamper accuracy was 14.3%, 71.4%, and 71.4%. E2 therefore did not improve the primary proxy decisions over E1 and reconstructed the first defective round less accurately (57.1% versus 92.9%). Capped proxy decision time was 238.6, 98.5, and 96.0 seconds, but the cap assigns 300 seconds to an incorrect or insufficient answer and is not human review time. Each attack appears in only one episode. Finally, all 96 C2 artefact–auditor cells supplied three valid fresh-context repeats; five cells (5.2%) changed gate across repeats.

The confirmatory design still requires prompts, resolved model identifiers, randomisation, human adjudication, missing-data rules, multiplicity control, and power to be frozen before its own dispatch or outcome inspection. Repeated calls and task-clustered inference treat the increment, not each defect nested within it, as the independent unit. Auditor-assignment effects remain configuration-specific unless replicated across enough vendors and models to support a broader claim. The feasibility cohort establishes execution and measurement, not that cross-vendor review, any ablated component, or hard gating improves outcomes; null and adverse results remain reportable outcomes of the confirmatory design.

5.5 Prospective three-vendor confirmatory design

The v4 registration is preserved unchanged. Rather than retroactively repair a two-vendor design after inspecting its separate feasibility cohort, we specify an outcome-free v5 successor in `experiment/v5/`. It changes the scientific question from “is cross-vendor better?” to “when does a more heterogeneous Auditor improve net correction under clean-burden and cost constraints?” The design separates the same pinned snapshot (S0), a different snapshot from the same vendor (S1), and principal snapshots from the other two vendors (S2). It therefore identifies whether an apparent cross-vendor effect survives the most important missing control in v4: changing model without changing vendor.

Table 5: Prospective v5 minimum design. Planned allocations, not efficacy evidence; dispatch remains fail-closed until all freeze gates pass.

Design element	Prospective requirement
Independent tasks	150 briefs, equally blocked over three domains; one blinded expansion to at most 180; at least 60 privacy-approved real-task/repository replays
Model panel	Three vendors, six pinned snapshots: one principal Generator/Auditor and one alternate same-vendor Auditor per vendor
Artefacts	Natural output plus verified-clean and exactly-one-mutant controlled siblings; unusual-but-correct hard negatives included
Audit assignment	Complete principal 3×3 Generator–Auditor matrix, S1 control, and three fresh-context repeats per required cell
Human reference	Two independent blinded domain reviewers per item, third-person adjudication, separate Gold and Matching Panels; 30-item calibration with $\alpha_{\text{Krippendorff}} \geq 0.80$ and raw agreement ≥ 0.85
Primary gate	Cross-minus-S0 task-standardised correct-gate interval above zero <i>and</i> clean unnecessary-escalation one-sided upper bound below +5 points
Mechanisms	C0/C1/C2 each use three repeats; D0 model-only, D1 independently validated deterministic-only, D2 combined-blind; 60-task paired whole-loop subset
Claim scope	Included configurations only; all directions and leave-one-vendor-out estimates mandatory; no vendor-population claim

For task t , the primary estimator first collapses repeats and fixed target strata, then computes

$$C_t = \frac{1}{3} \sum_g \left[\frac{1}{2} \sum_{a \neq g} Y_{tga} - Y_{tgg} \right]. \quad (3)$$

Whole-task bootstrap inference preserves clean/mutant siblings, generator outputs, and repeats inside the independent unit. A mixed-effects model with task and base-artefact intercepts and fixed generator, auditor, separation, domain, stratum, and defect-channel terms is a sensitivity analysis, not a replacement. Invalid or identity-unverified assigned calls remain incorrect gates and clean unnecessary escalations in the service-level intention-to-audit population.

The planned ceiling is 24,930 model calls before separately authorised technical retries: 450 principal generations, 12,150 primary C2/D2 audits, 4,050 S1 controls, 6,480 C0/C1 additions on a 60-task controlled subset, and approximately 1,800 whole-loop calls. This ceiling is a reproducibility and safety limit, not spending authorisation. The machine-readable preflight deliberately refuses dispatch while model locks, monetary and token caps, human-hour capacity, privacy approvals, power output, panel manifests, and an independent 12-task dry-run receipt remain unset. The v5 package therefore makes the missing evidence executable without pretending it already exists.

A 10,000-dataset central design simulation, which reads no observed outcomes, produced a Monte Carlo marginal effect of 7.998 points for the nominal eight-point scenario, 99.65% conjunctive power, 94.87% two-sided interval coverage, 2.49% directional superiority type-I error (the lower tail of a two-sided 95% interval), and 4.75% non-inferiority-boundary type-I error. These values validate the central allocation under the current normal task-level design interval; they do not complete the power gate. The registered stress scenarios and calibration against the exact locked bootstrap-t interval remain required before freeze, and the machine-readable result states that limitation.




Figure 5: Configuration- and component-specific effects in the sealed six-task v4 execution-feasibility cohort. All values are descriptive, non-confirmatory, and specific to the frozen configurations; task-bootstrap 95% intervals use six deterministic convenience-task clusters. C2 is the corpus-scoped decidable Constitution; D0 uses the model verdict alone, D1 the deterministic checker alone, and D2 their blinded frozen combination. (a) Absolute correct-gate rates for the C2/D0 Generator–Auditor cells over clean, seeded, and unusual-but-correct controls. (b) Pairing contrasts; positive values favour cross-auditing, and the false-block row is sign-reversed so positive means fewer false blocks. (c) DCL ablations on the same improvement-positive scale. (d) Assignment-balanced correct-gate rates show that the D2-minus-D0 change is confined to natural outputs; the controlled bar averages the three controlled strata. The D1 line is a harness ceiling because that checker also defines the micro-task gold labels, not independent DCL validation. The 272 OpenAI calls exposed only the requested alias and remain identity-unverified. There is no human gold panel and no vendor-population claim. Plotted values and exact JSON paths are in `experiment/v4/figures/source-data.csv`.




Figure 6: Operational gains, costs, and unresolved boundaries in the same sealed feasibility cohort. All endpoints are descriptive and configuration-specific. (a) Initial and post-loop objective correctness for 12 research-text sessions per policy over six task clusters: P0 was unaware of audit, P1 knew a non-gating shadow audit would occur, and P2 received hard-gate findings in a bounded loop. P2 repaired 2/9 initially wrong outputs and regressed 0/3 initially correct outputs. (b) Provider calls, known list-price-equivalent cost, and cumulative provider time relative to P0; these cohort totals have no sampling interval. (c) Twelve same- and 12 cross-auditor seeded branches, clustered in six tasks, had identical observed rates: 12/12 initial defects resolved, 11/12 final artefacts acceptable, 1/12 with a new defect, and 3/12 with an unnecessary change. Coincidence does not establish equivalence. (d) Fourteen fresh proxy reviews per interface clustered in seven deterministic episodes: E0 final-only, E1 ordinary log, and E2 structured ledger. E2 matched E1 on accept and tamper accuracy but was 35.7 points worse on first-defective-round reconstruction (descriptive episode-bootstrap 95% interval, -64.3 to -14.3). Proxies are not human participants, attacks are episode-confounded, and 5/96 three-repeat C2 cells changed gate. Exact source rows are in `experiment/v4/figures/source-data.csv`.

5.6 What a reader can check

The evidence collections are versioned, and they answer different questions. Except for the explicitly post-freeze v4 programme in §5.4, the empirical statements below refer to the reference repository at release tag `paper-v1.0.0`, cut at the source revision of the arXiv v1 PDF committed beside its source with its SHA-256 recorded in `paper/HASHES.txt` at that tag; “exact” is a checkable claim about that committed artefact and its hash, not about byte-level rebuild determinism, which TeX does not promise. An earlier draft pinned a bare commit instead, and the external review of this paper caught the draft having moved past its own pin. The reference repository is public at that tag. The product-line repositories (§5.3) remain private at the time of writing, so claims about them rest on the audit excerpts committed under `audits/` and on the evidence grading of Table 3, and a reader who cannot reach a cited artefact should discount the corresponding claim accordingly.

The reference implementation carries the protocol as specified here, with the controller, the receipt verifier, and their regression tests. The evaluation directory carries the exploratory trial corpus, the frozen scorer, and the permutation null with its seed, so every number in §5.4 regenerates from a clean checkout. Its post-freeze v4 directory carries the confirmatory registration and analysis plan together with the separately registered feasibility amendments, frozen canary and price evidence, append-only journals, outcome-free seals, analysis receipts, machine-readable summaries, and the seven-point result report. The audit directory carries the cross-vendor reports written against this repository, and our dispositions on each one. That includes the findings that voided our own claims. The live deployment’s supervision records are mined into the same repository in structurally redacted form: cycle identities, decisions, severities, rule citations, and finding lifecycles verbatim, scientific magnitudes masked.

The prospective `experiment/v5/` directory is separately inspectable: it contains the three-vendor registration and SAP drafts, machine-readable 150–180-task design, exact-allocation power simulator, general $V \times V$ task estimator, refusal preflight, and tests. It reads no v4 outcomes and remains visibly blocked rather than manufacturing a completed study from a design.

6 Threat model and limitations

Below is what CrossAudit withstands and what it does not.

Self-preference and vendor-correlated error. **I1** excludes exact self-evaluation and records a declared cross-vendor assignment; it does not prove that vendor-correlated error is reduced. *Corpus*-correlated error remains: where the shared literature is wrong or outdated, different vendors can agree confidently and wrongly. The mitigation is **I4** for everything mechanisable; for what is not, it is the human’s asynchronous reading of ADVISORY trails. This residual cannot be assumed reducible by adding more LLM auditors, because they plausibly train on substantially overlapping public corpora. The S0/S1/S2 design in §5.5 tests the narrower measurable effect.

Prompt injection. An increment could embed text addressing the Auditor. The Auditor runs toolless against a fixed reply schema, with increment content fenced as data; and because DCL verdicts are non-overridable, injection cannot waive the layer where hard defects are caught. Injection that shapes the *LLM-side* report remains partially open, as it does for LLM-judge systems generally. This bullet describes the reference implementation; the deployed variant’s tool-bearing auditor forgoes the toolless defence, a divergence §5 names together with its containment limits.

Auditor failure. Empty, malformed, or rule-free reports convert to escalation (**I3**), never to silent passage. The cost is human attention, which is the correct currency for an unreliable auditor.

Oscillation and deadlock. These are bounded by **I5**; the failure mode degrades to a human decision with the parsed exchange on the ledger, which is the intended floor.

Goodharting the Constitution. A capable Generator will satisfy the letter of decidable rules. The six-task feasibility cohort produced a mixed warning rather than generic defensive bloat: hard gating repaired two initially wrong text outputs, but at more than twice the calls and cost; some text and code changes were compliance-only proxies, while code LOC, wrappers, assertions, retries, and disclaimers did not increase and held-out correctness remained at ceiling. The code subcohort had only two tasks and a 100% quality ceiling, so this is rule-surface adaptation evidence, not a general defensive-programming effect. Decidability makes such drift visible rather than solved: the human reviews rule–outcome drift on the ledger and legislates accordingly. The Constitution is a living document, and its growth out of escalations is the system learning. A related boundary matters wherever a deployment lets the principal shape how the Generator works, through style guides, domain conventions, or worked examples. Such material may change how the work is done; it must never change where the Generator may write or who judges it. Guidance that could address the Auditor would be an unversioned rule, and guidance claiming wider write access than the path guard allows is only a text with an opinion.

Collusion. Collusion has no out-of-band channel in the reference design. Coordination must ride the committed artefacts, where it is preserved for inspection. Encoded coordination *within* artefacts, and any channels a tool-bearing auditor acquires, remain possible. The realistic soft risk is convergent style across many rounds, and it is met by the Constitution’s review cadence.

The operator. CrossAudit supervises the agents, not the principal. Selective publication, pre-publication history rewriting, and audit re-rolling by the operator all sit outside the protocol’s guarantees. External anchoring (signed pushes, transparency logs) would extend tamper-evidence to the operator; until then, “third-party-auditable” should be read as *internally consistent as published*. Relatedly, the DCL scripts and the Auditor’s system prompt must live under the same ledgered, human-reviewed change control as the Constitution, because a Generator-editable check layer would hollow out **I4**.

Vendor identity is self-declared. The ledger proves that an exchange occurred; it does not prove the identity of the models behind OpenAI-compatible endpoints. **I1** is asserted from configuration, not verified cryptographically. Attested inference or vendor-signed responses would close this gap; today it is an honest limit on what “third-party-auditable” can mean. (The reference example also shares one dispatch token across both workflows, so credential separation is likewise configuration, not proof.)

Confidentiality. The protocol ships every increment, possibly unpublished and patentable material, to a second vendor’s API. Data governance of that call (agreements, retention, disclosure risk) sits outside the protocol and must be settled per deployment.

Scope. CrossAudit audits the research *record*, not the world. It cannot detect a miscalibrated instrument, a wrong dataset honestly described, or fraud upstream of the repository. It is also currently specified for single-generator pipelines; multi-agent generation raises attribution questions we do not address here.

7 Discussion

Continuous integration for scientific claims. The ambition is what CI achieved for software: not proof of correctness, but a cheap and inspectable floor under quality. Human judgement is then redeployed to where it discriminates (the rules, the escalations, and the science) and not spent uniformly on every increment. We believe the analogy holds in one further respect. CI spread without institutional permission; a single developer could adopt it unilaterally, and its artefacts, the badges and the logs, became social proof. One disanalogy must be owned: CI’s checks are deterministic, while CrossAudit’s distinctive layer is a stochastic judge. The DCL exists to keep the gate’s hard core deterministic. CrossAudit is designed for the same adoption path: one researcher, two repositories and an afternoon for the audit loop itself, plus the CI, credential and branch-protection configuration that enforced admission needs.

Relation to platform-scale systems. CrossAudit is complementary to, not competitive with, systems such as the AI co-scientist [4] or the AI Scientist [3]. Those systems generate. CrossAudit supervises whatever generates. The strongest version of our proposal is addressed to platforms of that kind. Their internal critique stages appear architecturally straightforward to re-instantiate across vendor lines and to externalise onto public ledgers, although the organisational and confidentiality costs are not ours to estimate. The resulting audit trails would give publishers and funders, who are currently asked to trust process descriptions [14], something they can actually inspect.

What the ledger buys science socially. A complete supervision history, public where the operator publishes it, changes the character of machine-generated results. A claim then arrives not as prose plus reputation but as prose accompanied by its audit record: which rules it was checked against, what was contested, and what a differently-trained model conceded or refused. Reviewers can spot-check the ledger instead of re-deriving trust from nothing.

The ledger as a data asset. A CrossAudit deployment produces, as a by-product, something the field currently lacks: a corpus of *supervised machine science*. Each tuple of increment, findings, dispute, and resolution is a labelled example of scientific work judged by an independent party under explicit rules, and therefore candidate training signal for better generator and auditor agents alike, with the attendant risk that training against the ledger is training against the rulebook, the optimisation §6 names as Goodharting. Aggregated across deployments, failed audits would form a public error taxonomy of agentic research: what machine-generated science actually gets wrong, per rule, per field, over time. Whoever runs the loop accumulates this asset, and a community that runs it openly accumulates it as a commons.

Constitutions as community objects. Because the Constitution is a plain, forkable file with stable rule IDs, it can outgrow any single deployment. A research community can maintain a shared domain constitution in the way communities maintain style guides and lint rules. A journal could publish the constitution it expects machine-assisted submissions to have been audited under, and accept the ledger link alongside the manuscript, much as data-availability statements are accepted today. Funders could write “public supervision ledger” into their terms. For regulated settings, pharmaceutical and clinical computation among them, the ledger’s attributability and its contemporaneous, hash-manifested record resemble properties that audit regimes already demand of human work, though we claim compliance with no specific regime. A repository badge (increments audited, escalations raised, constitution version) would then do for machine science what CI badges did for software: it would compress an inspectable process into a glanceable, verifiable signal. None of this requires new technical infrastructure. It requires only that the artefact exist, which a conforming deployment produces.

A ratchet for standards. The Constitution need not be static. Because rules are commits and receipts pin the version in force (**I7**), standards can tighten over time without ambiguity about which version governed which increment. The safe dynamics have three channels. First, shadow-mode promotion: a candidate stricter rule enters as ADVISORY, rehearses enforcement on every cycle without gating, and accumulates ledger evidence on hit rate, dispute rate, and would-be blocking cost; the human promotes it to BLOCKER only when the record supports it. Second, threshold ratchets: numeric criteria tighten stepwise as the generator’s competence grows, each step a commit with its rationale. Third, agent-proposed amendment: either agent may draft a rule change from what the ledger shows it. The loop can propose. Only the principal enacts. One rule matters most. Standards freeze within a cycle and move only between cycles, because an auditor that could raise the bar mid-round would face the generator with a moving target and dissolve the termination guarantee of **I5**.

From copied glue to an installable protocol. The reference implementation ships as copy-in glue: a deployer vendors checks/ and controller/ into an audit repository and edits three workflow files. The product line described in §5.3 replaces that with an installable package whose command surface is the loop itself: scaffold a project, run the deterministic layer and the auditor against a pinned commit, verify a receipt, admit. The argument for packaging is more than convenience. Vended copies drift, so two deployments can silently run different verifiers, and a receipt that pins the Constitution, the check sources, and the prompt, but not the machinery that verified and admitted on their basis, is bound one layer short of **I7**’s intent. A release-versioned verifier closes it: the receipt can record the package version and distribution hash alongside the hashes it already carries, and the enforcement code becomes a pinned, citable dependency, not an unversioned copy. This binding is specified but not yet emitted, and it is the next thing we would fix. Packaging also gives field adaptation a natural unit, since check packs ship as plugins and DCL coverage can circulate between groups in the way we argue Constitutions should. The cost is a new trust surface, the package supply chain, for which hash-pinned installs and signed releases are the standard mitigations.

A console for the human principal. The ledger is git-native on purpose, and it stays so. Raw git is nevertheless a demanding reading surface for the one human the protocol keeps in the loop, and **I6** makes that human’s asynchronous reading load-bearing. The product line therefore carries a supervision console over the ledger: cycle timelines, the advisory backlog by rule and hit rate, an escalation inbox assembling what an adjudication actually needs, and the telemetry a standards ratchet would read. One design rule carries protocol weight: the console writes nothing of its own. Every action it offers runs the same verbs the command line offers, so each materialises as a commit or an issue through the authenticated paths the agents already use, the ledger stays complete (**I2**), and the console remains derivable from it. A supervision interface with a private database would accumulate the unversioned, unreplayable state the protocol exists to exclude. Three refusals follow from the same principle and are worth stating because a supervision display that breaks them is worse than none: it does not show a figure the ledger cannot support, it does not colour a step green before it happened, and it does not imply that it acted on its own. There is a boundary case that deserves its own honesty. Work in flight is not yet in the ledger, so progress reporting is a view, not a record: it lives in memory and dies with the process. The ledger holds every committed round but cannot know that a round was cut off, so an interrupted run must be marked as interrupted rather than left to read as finished.

Management by exception, at research scale. As agent labour becomes cheap, the binding constraint of agentic science shifts from compute to human attention. CrossAudit’s economic content is a hypothesised reduction in *gating* cost from $O(\text{increments})$ to $O(\text{escalations})$, conditional on escalation volume staying low; no deployment here recorded the human attention spent, so the hypothesis is stated with its measurement plan, not as a result. Our own trial shows the failure mode plainly: the GPT-family arm’s 10/10 false-block rate

would make escalations $O(\text{increments})$. The economics hold only with a calibrated auditor and a decidably scoped Constitution, and they must be measured rather than assumed. This is the managerial precondition for one researcher credibly directing several agent pipelines at once. In principle it should extend beyond science to any agentic work product that arrives as discrete increments whose quality is partially rule-expressible, from code to quantitative analysis, a conjecture this paper does not test.

8 Conclusion

CrossAudit turns supervision of autonomous research from a hidden platform step into a versioned artefact with deterministic precedence, bounded revision, and explicit human authority. It does not turn a second vendor into an independent oracle. The six-task v4 cohort shows that the measurement and evidence chain can run, while its direction reversals, circular DCL ceiling, repeat mismatch, and proxy-ledger null result demonstrate why feasibility must not be reported as efficacy. The prospective v5 package makes the decisive comparison executable: same snapshot, same-vendor different snapshot, and cross-vendor audit over three domains and human-adjudicated tasks, judged by final net correction and clean burden. Until that study runs, the honest claim is a protocol and a falsifiable evaluation framework. An AI scientist should not grade its own homework; this work specifies how to test whether a different grader actually helps.

Author contributions and the use of language models. This paper was written with heavy use of the class of tools it proposes to supervise, and the division deserves stating rather than implying. The protocol, the invariants, the study designs and every judgement about what the evidence supports are the authors'. A large language model drafted most of the paper's prose from the authors' outlines and notes, wrote the bulk of the reference implementation and the analysis scripts under the authors' direction, and produced the figures. The authors verified each of the reported numbers against the committed artefacts, checked all twenty-two references against their source pages, and read and revised the text. Two limitations of that arrangement should be named. First, the same assistant that drafted the prose also ran an internal screen of the manuscript for machine-authored writing patterns; the screen is committed under `audits/`, and it is a same-source review of the kind §2 argues against. Second, that screen missed a bibliographic error the assistant had itself introduced days earlier, which an external reviewer then caught. We report both because a paper about supervising machine work has no standing to be vague about the machine work in itself.

References

- [1] Chris Lu, Cong Lu, Robert Tjarko Lange, et al. The AI Scientist: Towards fully automated open-ended scientific discovery. *arXiv:2408.06292*, 2024.
- [2] Y. Yamada, R. T. Lange, C. Lu, et al. The AI Scientist-v2: Workshop-level automated scientific discovery via agentic tree search. *arXiv:2504.08066*, 2025.
- [3] Chris Lu, Cong Lu, Robert Tjarko Lange, et al. Towards end-to-end automation of AI research. *Nature*, 651:914–919, 2026.
- [4] J. Gottweis, W.-H. Weng, A. Daryin, T. Tu, et al. Accelerating scientific discovery with Co-Scientist. *Nature*, 655:487–496, 2026. Preprint: *arXiv:2502.18864* (2025), as “Towards an AI co-scientist”.
- [5] A. Panickssery, S. R. Bowman, and S. Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. *arXiv:2404.13076*.
- [6] Wei-Lin Chen, Zhepei Wei, Xinyu Zhu, Shi Feng, and Yu Meng. Do LLM evaluators prefer themselves for a reason? *arXiv:2504.03846*, 2025.

- [7] Dani Roytburg, Matthew Bozoukov, Matthew Nguyen, Jou Barzdukas, Mackenzie Puig-Hall, and Narmeen Oozeer. Are LLM evaluators really narcissists? Sanity checking self-preference evaluations. *arXiv:2601.22548*, 2026.
- [8] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, et al. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. *arXiv:2306.05685*.
- [9] J. D. Norman, M. U. Rivera, and D. A. Hughes. Reliability without validity: a systematic, large-scale evaluation of LLM-as-a-judge models across agreement, consistency, and bias. *arXiv:2606.19544* (preprint), 2026.
- [10] D. A. Boiko, R. MacKnight, B. Kline, and G. Gomes. Autonomous chemical research with large language models. *Nature*, 624:570–578, 2023.
- [11] N. J. Szymanski, B. Rendy, Y. Fei, R. E. Kumar, et al. An autonomous laboratory for the accelerated synthesis of inorganic materials. *Nature*, 624:86–91, 2023.
- [12] M. D. Skarlinski, S. Cox, J. M. Laurent, J. D. Braza, et al. Language agents achieve superhuman synthesis of scientific knowledge. *arXiv:2409.13740*, 2024.
- [13] M. Baker. 1,500 scientists lift the lid on reproducibility. *Nature*, 533:452–454, 2016.
- [14] Editorial. AI scientists are changing research — institutions, funders and publishers must respond. *Nature*, 651:853–854, 2026.
- [15] P. T. J. Kon, J. Liu, Q. Ding, et al. Curie: Toward rigorous and automated scientific experimentation with AI agents. *arXiv:2502.16069*, 2025.
- [16] S. Schmidgall et al. Agent Laboratory: Using LLM agents as research assistants. *arXiv:2501.04227*, 2025.
- [17] Edison Scientific. Kosmos: An AI scientist for autonomous discovery. Announcement, November 2025. <https://edisonscientific.com/news/announcing-kosmos>.
- [18] P. Verga, S. Hofstätter, S. Althammer, Y. Su, et al. Replacing judges with juries: Evaluating LLM generations with a panel of diverse models. *arXiv:2404.18796*, 2024.
- [19] M. B. Nuijten, C. H. J. Hartgerink, M. A. L. M. van Assen, S. Epskamp, and J. M. Wicherts. The prevalence of statistical reporting errors in psychology (1985–2013). *Behavior Research Methods*, 48:1205–1226, 2016.
- [20] G. Cabanac, C. Labbé, and A. Magazinov. The ‘Problematic Paper Screener’ automatically selects suspect publications for post-publication (re)assessment. *arXiv:2210.04895*, 2022.
- [21] M. Sharma, M. Tong, T. Korbak, et al. Towards understanding sycophancy in language models. *arXiv:2310.13548*, 2023.
- [22] Y. Bai, S. Kadavath, S. Kundu, et al. Constitutional AI: Harmlessness from AI feedback. *arXiv:2212.08073*, 2022.