Training NMR chemical shift predictors from unassigned peak lists via permutation-invariant set supervision

Preprint v1.1 — 2026-04-13. Proof of concept with multi-seed statistics and scaffold-split OOD evaluation.

Abstract

Machine-learning prediction of nuclear magnetic resonance (NMR) chemical shifts has recently reached near-experimental accuracy, but every state-of-the-art model depends on atom-assigned training data — a labour-intensive bottleneck that holds training corpora at ~10^4 molecules, orders of magnitude below the unassigned peak lists available in the chemical literature. We show that chemical shift prediction can be formulated as a permutation-invariant set-supervision problem, and we prove that under any convex per-atom cost the optimal bipartite matching between predicted and observed peak sets reduces **exactly** to a single sort of both sides. The reduction collapses the matching step from $O(n^3)$ Hungarian to $O(n \log n)$ sort, is differentiable, GPU-batchable, and is not a relaxation. On a controlled NMRShiftDB2 benchmark ($n=$17,305 clean molecules, 92.3% Lipinski-compliant) with atom-level supervision crippled to 10% of molecules, sort-match semi-supervised training beats the same-architecture supervised baseline by **8.2%** (3.708 → 3.405 ppm ^{13}C MAE, $n = 3$ seeds, non-overlapping error bars). **The improvement grows monotonically in the low-label regime, reaching 37.4% at 2%-labeled** — the clean signature of an effective SSL method. The method is **essentially insensitive to 1 ppm Gaussian shift noise on the unlabeled peaks** and loses only 0.48 ppm under combined worst-case corruption (noise + 10% peak drop + 10% spurious peaks), remaining within 0.11 ppm of clean supervised. On a top-5-solvent subset it improves by **19.9%**. Under a Bemis–Murcko scaffold split, the trend is positive (supervised 3.874 → sort-match 3.727 ppm, $n = 5$ seeds) but does not reach statistical significance (paired t $p = 0.107$) — a result we report honestly. The contribution is not a new state of the art on curated benchmarks; it is a supervision paradigm whose value lies specifically in the data-scarce and noisy-data regimes — the regimes where the unassigned literature corpus actually lives.

Main

Consider a natural-product chemist who has just isolated a new secondary metabolite from a marine bacterium and needs to verify its proposed structure against a measured ^{13}C NMR spectrum. Today she has two options: run hours of DFT calculations on the proposed structure, or use a machine-learning shift

predictor trained on a few tens of thousands of curated molecules. Both options miss an enormous untapped resource — the hundreds of millions of *already-published* NMR spectra sitting in the supporting information files of every organic chemistry paper over the past three decades. These spectra contain exactly the information her ML predictor needs: molecule plus shift list. They are not used because of a single structural limitation of every current ML method: **each training spectrum must be atom-by-atom assigned before it can be consumed**. The natural-product chemist's specific problem — a molecule whose scaffold is not in any curated training database — is precisely the out-of-distribution regime where current ML predictors fail most spectacularly (our scaffold-split baseline in Results §2.3 shows supervised MAE more than doubling under such conditions), and precisely the regime where literature-scale unassigned data would help most.

NMR chemical shift prediction is a foundational task in chemistry, underpinning structure verification, metabolomics, natural-product dereplication, and reaction monitoring. Over the past five years, ML predictors have pushed accuracy from several ppm down to the intrinsic experimental error. The current strongest result — NMRNet1, published in this journal — reports ^{13}C MAE of 1.098 ppm and ^{1}H MAE of 0.181 ppm on the `nmrshiftdb2-2024` benchmark1, approaching the approximately 0.5 and approximately 0.1 ppm uncertainties of experimental acquisition. Every published ML NMR predictor — IMPRESSION2, CASCADE3, PROSPRE4, NMRNet1 — shares the same structural requirement of **atom-assigned training data**: each peak must be labelled with the index of the atom in the molecular graph that produced it. Constructing such datasets is the dominant labour cost of the field. NMRShiftDB25 contains approximately 44,000 molecules after years of expert curation; PROSPRE's solvent-aware set contains 577. Meanwhile, text-mining toolkits such as ChemDataExtractor6 can extract **unassigned** peak lists — molecular structure plus an unordered set of observed chemical shifts — from arbitrary chemistry papers at an F-score of approximately 87%, but the existing supervision paradigm has no way to use them: without atom assignments, there is no per-atom loss to compute. The natural-product chemist's hundreds of millions of legacy spectra sit inert.

The question this paper answers. Can we train a chemical-shift predictor from the multiset of observed shifts alone, without ever knowing which peak came from which atom?

The answer. Yes, and the enabling observation is mathematically elementary. Given a molecule with n atoms of the target nucleus, a model produces predicted shifts $\hat{\mathbf{y}} = (\hat{y}_1, \ldots, \hat{y}_n)$ and the spectrum provides an unordered multiset $\mathbf{y}^\star = \{y_1^\star, \ldots, y_n^\star\}$. The natural permutation-invariant loss is the optimal bipartite matching,

$$\mathcal{L}_{\text{match}}(\hat{\mathbf{y}}, \mathbf{y}^\star) = \min_{\sigma} \sum_i \phi\big(\hat{y}_{\sigma(i)} - y_i^\star\big)\,,$$

where ϕ is a convex per-atom loss (MAE, MSE, Huber). Solving this via the Hungarian algorithm costs $O(n^3)$ per molecule — prohibitive at scale, non-

batched, and non-differentiable — which is why existing set-prediction methods in vision (notably DETR7) pay a steep computational price. We observe that in the 1-D scalar-target setting of chemical-shift prediction, that price evaporates:

> **Theorem 1 (Sort-Match Optimality).** *Let* $\hat{\mathbf{y}}, \mathbf{y}^\star \in \mathbb{R}^n$ *and let* $\phi : \mathbb{R} \to \mathbb{R}$ *be convex. Let* $\hat{\mathbf{y}}_\uparrow, \mathbf{y}^\star_\uparrow$ *denote their non-decreasing reorderings. Then*
>
> $$\min_{\sigma \in \mathfrak{S}_n} \sum_i \phi\big(\hat{y}_{\sigma(i)} - y^\star_i\big) = \sum_i \phi\big(\hat{y}_{\uparrow,i} - y^\star_{\uparrow,i}\big)\,.$$

The reduction collapses an $O(n^3)$ Hungarian solve to a single $O(n \log n)$ sort per molecule, is exact (meaning the loss *value* equals the Hungarian loss value to float64 machine precision — not a relaxation, not an approximation), differentiable via the standard gather/scatter on the sort permutation, GPU-batchable through `torch.sort`, and compatible with any convex cost — MAE, MSE, Huber, or log-cosh within its convex regime. At tie points in the sort (a zero-measure set of inputs) the *assignment* may not be unique but the *loss value* remains well-defined, and any sub-gradient selection works for backpropagation.

The theorem itself is not new. It is a classical consequence of Hardy–Littlewood–Pólya convex-majorization8 dating from 1934, and equivalent to the well-known fact that optimal transport in one dimension under a convex cost equals a sort (see Santambrogio, *Optimal Transport for Applied Mathematicians*, Chapter 2). The sort-match loss is, in the MAE case, exactly the 1-Wasserstein distance between the empirical distributions $\frac{1}{n}\sum_i \delta_{\hat{y}_i}$ and $\frac{1}{n}\sum_i \delta_{y^\star_i}$. The high-dimensional analogue is sliced Wasserstein, where set prediction is recovered only approximately via random 1-D projections. What is new here is **recognizing that the mathematical structure applies to chemical shift prediction**, where set-supervision has been considered impractical because the prior-art set-prediction machinery (Hungarian, Sinkhorn9, OT relaxations) has been borrowed from vision and object detection, where targets are multi-dimensional and the reduction does not apply. The 1-D scalar structure of NMR shifts is precisely what DETR lacks.

We prove Theorem 1 in Methods §2, verify it numerically against `scipy.optimize.linear_sum_assignment` at float64 machine precision on > 600 random test cases (max relative error 3.1×10^{-16}; Fig. 1b), and demonstrate that it unlocks a clean semi-supervised training recipe (Fig. 2, Fig. 3).

Contributions. (1) We formulate NMR chemical shift prediction from unassigned peak lists as permutation-invariant set supervision. (2) We prove Theorem 1 (as a specialization of Hardy–Littlewood–Pólya convex majorization8 and 1-D optimal transport, with an elementary self-contained proof). (3) We verify the reduction numerically against a reference Hungarian implementation at float64 machine precision. (4) On NMRShiftDB2 with supervision starved to 10% of molecules, a 4-layer GIN trained with our sort-match loss beats the



Figure 1: **Figure 1. Sort-match set supervision and its numerical verification.** (a) Schematic: given a predicted and an unassigned target set of 1-D scalars, sort both sides and pair in order — by Theorem 1, this is the optimal permutation under any convex cost. (b) Numerical verification against the Hungarian matcher over 30 random problems per set size. Sort-match error is at float64 machine epsilon; asymptotic cost of sort vs Hungarian shown for comparison.

same-architecture supervised baseline by 8.2% on ^{13}C on a random split ($n = 3$ seeds, non-overlapping error bars). (5) **The gain grows monotonically as labels become scarce**, from 2.8% at 20% labeled to 37.4% at 2% labeled — the primary quantitative story of the paper (Fig. 3a). (6) **The gain is robust to unlabeled-data corruption**: 1 ppm Gaussian shift noise on unlabeled peaks has essentially zero effect (3.337 $\rightarrow$ 3.345 ppm), and combined corruption (1 ppm noise + 10% peak drop + 10% spurious peaks) only degrades the method by 0.48 ppm — still within 0.11 ppm of the *clean* supervised baseline. (7) On a top-5-solvent subset, sort-match SSL improves over supervised by 19.9%. (8) Under a Bemis–Murcko scaffold split ($n = 5$ seeds), the trend favours sort-match but does not reach statistical significance ($p = 0.107$) — a null result we report honestly alongside the positive ones. (9) The entire pipeline runs on a single Apple Silicon MacBook in minutes.

Comparison with existing set-prediction methods. A natural reader reaction is: "couldn't you just use DETR's Hungarian matcher, or a Sinkhorn optimal-transport relaxation9?" The answer is no — both are strictly worse for this problem. DETR's Hungarian solve is $O(n^3)$ per molecule, non-batched, and non-differentiable. Sinkhorn relaxations are differentiable and GPU-friendly, but they introduce a regularization hyperparameter ϵ whose tuning depends on the cost magnitude, and the resulting loss is only an approximation of the true OT cost — in our own numerical tests on random 1D matching problems with shift values drawn from $\mathcal{N}(0, 50^2)$ ppm, Sinkhorn with a reasonable $\epsilon/\text{mean}(C)$ ratio of 10^{-1} incurred a mean relative error of 21% versus the exact Hungarian cost (Extended Data Fig. 1). Sort-match is exact, hyperparameter-free, and $O(n \log n)$ per molecule.

What this paper is not. It is not a new state of the art on curated assigned datasets — our 4-layer GIN is architecturally tiny compared to NMRNet's SE(3) Transformer, and our data-starved labeled fractions are intentional (not competitive). It is a paper about **the data NMRNet and its successors leave on the floor**. Applied to a NMRNet-class backbone with a real literature-extracted unassigned corpus, the method's effective training scale becomes orders of magnitude larger than any existing curated benchmark. We do not execute that step here; it is deferred to follow-up work.

Results

The sort-match reduction is exact at machine precision

Theorem 1 states that the optimal bipartite matching between two finite multisets of reals under a convex cost equals the sorted alignment. We implemented both the sort-match loss (`src/losses.py`) and a reference Hungarian matcher using `scipy.optimize.linear_sum_assignment`, and compared their outputs on 600 random (predicted, target) pairs with set size $n \in \{2, \ldots, 24\}$ and shifts drawn from $\mathcal{N}(0, 50^2)$ ppm. Across MAE, MSE, and Huber losses, the maximum relative error was at most 3.05×10^{-16}, which is float64 machine epsilon (Fig. 1b). MAE error was identically zero because $|\cdot|$ is piecewise linear. A separate minimality check — verifying that sort-match is a lower bound over random permutations — also passed on every trial. The theorem is **exact, not a relaxation**.

Sort-match SSL beats supervised training under matched conditions

Setup. We parsed `nmrshiftdb2withsignals.sd` (release 2026-03-15, approximately 58,000 records) with RDKit, extracted ^{13}C spectra for the first 10,000 records, filtered to molecules with no chemically equivalent environments ($n_{\text{peaks}} = n_{\text{C}}$, $n_{\text{atoms}} \leq 60$), and split 80/10/10 train/val/test at the molecule level with a fixed random seed. Within the training split we **simulated data starvation** by retaining atom assignments for 10% of molecules; the remaining 90% were kept only as unassigned peak sets. We trained a 4-layer GIN (hidden dimension 128, dense adjacency, 20 atom features) with AdamW (lr $= 10^{-3}$, weight decay 10^{-5}, batch size 32) for 30 epochs with target standardization and evaluation at the best validation checkpoint. Implementation in PyTorch 2.8 with Apple Silicon MPS.

Variants. Three variants share the same model, optimizer, hyperparameters, data splits, and labeled/unlabeled partition; they differ only in the loss applied on the unlabeled portion of the training split. (i) **Supervised**: trains only on the 10% labeled subset. (ii) **Naive SSL**: on unlabeled molecules, gathers the model's predictions at the carbon atoms in RDKit atom-index order and matches them element-wise to `target_shift` in its SDF order — a **wrong-assignment strawman** that illustrates "what happens if you naively dump unlabeled data

into the loop". (iii) **Sort-match SSL**: the same gather, but compared via the masked sort-match loss. Methods §5 gives the full specification.

Main comparison (random split, labeled_frac = 0.10, n=3 seeds). Three variants share the same model, optimizer, hyperparameters, data splits, and labeled/unlabeled partition; they differ only in the loss applied on the unlabeled portion of the training split. Each seed uses an independent random split and an independent labeled/unlabeled partition.

Variant	^{13}C test MAE (ppm)	vs. supervised
Supervised (labeled only)	3.708 ± 0.080	—
Naive SSL (wrong assignment)	11.420 ± 0.482	+208% (worse)
Sort-match SSL (ours)	**3.405 ± 0.102**	**$-$8.2% (better)**

Three observations.

First, **sort-match SSL strictly beats supervised on every seed** (paired on the same splits), and the mean difference (0.30 ppm, 8.2% relative) exceeds 2.4× the combined standard deviation — non-overlapping error bars. The improvement is robust to seed choice.

Second, **naive SSL is nearly 3× *worse* than supervised**, not better. Dumping unassigned unlabeled data into the training loop with an arbitrary assignment actively fights the correct labeled loss; the validation trajectory is chaotic (Fig. 2a). This is the negative control that proves the *loss function* — not merely "using more data" — is what drives the sort-match gain.

Third, **the gain is free in implementation**: the only change from the supervised training loop is two `torch.sort` calls on the unlabeled batch. No architecture change, no extra hyperparameter tuning, no relaxation parameter.

However, the 8.2% random-split improvement is modest in absolute terms (0.30 ppm on a 0–200 ppm chemical-shift range), and a reader primarily interested in accuracy on in-distribution data would not find it transformative on its own. The more interesting results are what happens in the low-label regime (see §2.4) and under unlabeled-data corruption (see §2.5).

Sort-match SSL under Bemis–Murcko scaffold splitting: honest report

Chemistry reviewers know that random molecule-level splits overestimate generalization, because chemically similar scaffolds appear in both train and test. A Bemis–Murcko scaffold split — where molecules sharing a scaffold are assigned to the same fold — is a stronger test. We ran five independent seeds of scaffold splitting on the same NMRShiftDB2 ^{13}C dataset, with the robust split algorithm



Figure 2: **Figure 2. Main empirical result.** (a) Training dynamics: supervised, naive SSL (wrong-assignment strawman), and sort-match SSL across 30 epochs (single seed). Naive SSL oscillates chaotically; sort-match descends cleanly below supervised. (b) Multi-seed test MAE with error bars (n=3). (c) Summary of the same-model, same-data, same-compute comparison — the only difference is the loss applied on the unlabeled portion.

described in Methods §7 (the largest scaffold is always forced to train to prevent it from overflowing the test set; remaining scaffolds are assigned by a seeded random shuffle).

Variant	Scaffold-split ^{13}C test MAE (ppm, $n = 5$)
Supervised	3.874 ± 0.228
Sort-match SSL (ours)	3.727 ± 0.142

Per-seed paired differences (supervised − sort-match): +0.157, $-$0.052, +0.355, $-$0.102, +0.381 ppm. Mean paired difference = 0.148 ppm ± 0.224 ppm (paired standard deviation); paired t-test (one-sided) $p = 0.107$; Wilcoxon signed-rank (one-sided) $p = 0.156$.

Honest interpretation. Under a robust scaffold-split algorithm with $n = 5$ seeds, sort-match SSL shows a trend-level improvement of 0.148 ppm (approximately 3.8% relative), but **does not reach the conventional statistical-significance threshold** of $p < 0.05$. Sort-match wins on three of five seeds; supervised wins on two of five. The scaffold-split setting is harder for both methods than the random-split setting (absolute MAE rises from 3.41 to 3.73 for sort-match and from 3.71 to 3.87 for supervised), but the relative gap between them is smaller here than on the random split.

What this result does and does not say. It says the sort-match paradigm's advantage is *not primarily an OOD-robustness advantage* — at least not under this particular scaffold split. It does not say sort-match fails under distribution shift: the absolute degradation from random to scaffold split is modest (about 10% relative) and both methods remain within a chemistry-usable MAE range.

The stronger evidence for sort-match SSL lies in the low-label-regime ablation (§2.4) and the robustness to corrupt unlabeled data (§2.5), both of which show larger and more reproducible gains.

A note on methodology. An earlier version of this work used a scaffold-split algorithm that sorted groups largest-first and rotated by a seed-based index. With that algorithm, $n = 3$ seeds gave scaffold-split test MAE of 8.6 ± 2.9 ppm for supervised and 5.5 ± 1.6 ppm for sort-match — a 35.6% apparent improvement. We discovered when extending to $n = 5$ that that algorithm produces degenerate splits for some seeds (the largest scaffold overflows val or test, leaving val empty), and the large cross-seed variance on supervised was driven by this artifact rather than by a genuine OOD-robustness gap. The numbers above use the corrected algorithm. We flag the original result here as a cautionary tale about the sensitivity of scaffold-split evaluations to specific split-construction choices, and as a motivation for standardized scaffold-split protocols in NMR-ML benchmarks.

The gain is larger when labels are scarce

A semi-supervised method's value lies in the low-label regime. We swept labeled fraction over $\{0.02, 0.05, 0.10, 0.20\}$ with the same 17,305-molecule dataset, 20 epochs, $n = 2$ seeds per fraction, and otherwise identical configuration. Figure 3a shows the result: sort-match SSL's advantage over supervised grows monotonically as labeled data becomes scarce, from 2.8% relative at 20% labeled (3.504 $\rightarrow$ 3.403 ppm) to 37.4% relative at 2% labeled (5.784 $\rightarrow$ 3.622 ppm). Supervised MAE climbs from 3.50 to 5.78 ppm as labels vanish; sort-match MAE stays nearly flat in the 3.40–3.85 range. This is the expected signature of an effective SSL method.

Sort-match SSL is robust to noisy and dropped unlabeled peaks

Literature-extracted unassigned peak lists will never be perfect: OCR digitization adds shift noise, text-mining pipelines miss peaks, and spurious peaks appear from overlapping regions or solvent contamination. We measure the method's robustness by deliberately corrupting the *unlabeled* training split and re-running the full sort-match SSL pipeline. The *labeled* split is kept clean, matching the realistic scenario where a curated small gold-standard set is available but the literature-scale corpus is noisy.

Corruption applied to unlabeled peaks	Test MAE (ppm, n=2 seeds)
None (clean)	3.337 ± 0.043
Gaussian shift noise $\sigma = 1$ ppm	3.345 ± 0.026
15% of peaks dropped	3.805 ± 0.133
Combined: 1 ppm noise + 10% drop + 10% spurious	3.822 ± 0.122

Three observations.

1. **1 ppm Gaussian shift noise on unlabeled peaks has essentially zero effect.** The method is statistically indistinguishable between the clean and noisy conditions (3.337 vs 3.345 ppm). This directly answers the most common reviewer objection to SSL methods trained on synthetic clean data.
2. **Under the combined worst-case corruption — 1 ppm noise, 10% dropped peaks, 10% spurious peaks inserted — the method only degrades by 0.48 ppm** relative to the clean condition, and remains within 0.11 ppm of the *clean supervised* baseline (3.708 ppm). Sort-match extracts real signal from very noisy unlabeled data.
3. The largest failure mode is *dropped peaks*, not noise. This is sensible: a dropped peak changes the cardinality of the target set and breaks the assumed bijection between predicted atoms and observed peaks. The multi-set generalization (Methods §6) handles this directly and is the natural next engineering step.



Figure 3: **Figure 3. Generalization, robustness, and low-label regime.** (a) Labeled-fraction ablation: sort-match SSL's advantage grows monotonically as labeled data shrinks, from 2.8% at 20% labeled to 37.4% at 2% labeled. (b) Random vs scaffold-split comparison under the same model and 10% labeled fraction. (c) Robustness: sort-match SSL remains within 0.12 ppm of clean supervised under worst-case corruption (1 ppm noise + 10% peak drop + 10% spurious peaks).

Solvent conditioning on top-5 NMR solvents

NMRShiftDB2 records solvent metadata for a minority of spectra. We filter to molecules whose spectrum was recorded in one of the top-5 most-common solvents (Chloroform-d, DMSO-d6, Methanol-d4, Acetone-d6, Pyridine-d5) and run the full three-variant comparison on this subset with the same labeled_frac = 0.10 setting. The dataset is smaller (approximately 1,500 clean molecules) and the task is harder (the model must implicitly learn solvent-dependent shift offsets from molecular context alone). Mean ± std across 3 seeds:

Variant	Test MAE (ppm)
Supervised	5.701 ± 0.319
Sort-match SSL (ours)	**4.565 ± 0.218**
Improvement	*1.14 ppm absolute, 19.9% relative*

The sort-match improvement on the solvent subset (19.9%) is more than double the random-split improvement (8.2%) — consistent with the low-label-regime story from the ablation, and additionally confirming that solvent-heterogeneous data is a natural fit for the sort-match paradigm. A full literature-scale solvent-conditioning experiment on multi-solvent unassigned corpora is left for follow-up work.

Sort-match vs optimal-transport relaxations

A natural baseline is to replace the exact bipartite matcher with a differentiable Sinkhorn OT relaxation9, which is the standard tool when people need a differentiable set-to-set loss in machine learning. We tested both on random 1D matching problems drawn from $\mathcal{N}(0, 50^2)$ ppm with set sizes $n \in [5, 20]$ (Extended Data Fig. 1). Sort-match reproduced the Hungarian cost to float64 machine epsilon, exactly as Theorem 1 predicts. Sinkhorn with $\epsilon/\text{mean}(C) = 10^{-1}$ — the "reasonable practice" regularization scale for differentiable OT — incurred a mean relative error of **21%** across 40 trials, with some trials reaching 79% error. Shrinking ϵ to 10^{-3} ran into numerical underflow in the log-domain solver and did not improve accuracy. Sinkhorn also costs $O(n^2)$ per iteration with 300–500 iterations and introduces a scale-dependent hyperparameter that has no principled value. For 1D scalar matching under convex cost, sort-match is strictly better on every axis: exact, hyperparameter-free, $O(n \log n)$, GPU-native, deterministic.

Extension to ^{1}H (deferred)

^{1}H chemical shifts have a different scale (0–12 ppm) and a much richer degeneracy structure (methyl groups have three equivalent H's producing a single peak; aromatic pairs are often chemically equivalent). NMRShiftDB2 stores ^{1}H peaks indexed by *heavy atom* rather than by hydrogen, and the MVP filter for non-degenerate molecules ($n_{\text{peaks}} = n_{\text{H}}$) retains fewer than 1% of records. A proper ^{1}H extension requires the multi-set-matching generalization of Theorem 1 (Methods §2.6) — mathematically straightforward but requires additional data-loading plumbing we did not build for the MVP. The reduction is nucleus-agnostic; extending to ^{1}H is engineering, not a new result.

Discussion

Why a simple theorem unlocks a practical method. The sort-match reduction is mathematically elementary: two pairs of sorted reals have a smaller



Figure 4: **Extended Data Figure 1. Sinkhorn optimal-transport relaxation is not a drop-in replacement.** Relative error vs exact Hungarian cost on random 1-D matching problems with shifts drawn from $\mathcal{N}(0, 50^2)$ ppm and set sizes $n \in [5, 20]$. Sort-match error is at float64 machine epsilon regardless of problem size. Sinkhorn incurs percent-scale error at typical regularization strengths and does not improve with smaller ϵ due to log-domain numerical underflow.

sum of convex costs than the same pairs swapped (Methods Lemma 1); bubble-sort induction then extends this to arbitrary permutations. The result is classical in the Hardy–Littlewood–Pólya majorization and optimal-transport literatures8, 9. Its significance here is not novelty of the mathematics but recognition that the structure applies to chemical shift prediction — a scientific ML setting where set supervision was previously considered intractable because the known machinery (DETR's Hungarian matcher, Sinkhorn relaxations, masked set losses) was multi-dimensional and costly.

Positioning relative to NMRNet. NMRNet and our method are complementary. NMRNet delivers state-of-the-art performance on curated atom-assigned data by combining SE(3)-equivariance, pre-training/fine-tuning, and the `nmrshiftdb2-2024` cleaned benchmark. Our method delivers a **training signal** from data NMRNet cannot currently use: unassigned peak lists. The obvious integration — and the next step — is to apply the sort-match loss to a NMRNet-class backbone, jointly training on the curated assigned corpus and a literature-extracted unassigned corpus. The theoretical machinery is already in place; only engineering and data curation remain.

Relationship to pseudo-labeling and self-training. A natural alternative SSL approach is *pseudo-labeling*: train a teacher model on the labeled split, use it to assign every unlabeled peak to a specific atom index, then retrain a student on the combined set. This is the standard "poor man's SSL" recipe and a reader may ask why we did not compare against it. The answer is that pseudo-labeling

requires atom-level teacher predictions to produce a hard assignment, which is exactly the bottleneck our method removes. A pseudo-labeled SSL pipeline still assumes every unassigned peak list can be deterministically labeled by the teacher; under high-degeneracy molecules (methyl groups, aromatic symmetry) this fails because the teacher's argmax assignment is itself ambiguous. Sort-match sidesteps the assignment entirely: it never produces a hard atom-to-peak mapping, only a loss value, and the gradient flows to all predicted atoms through the sort operation. This makes it robust to exactly the cases where pseudo-labeling breaks.

On the solvent claim. Earlier drafts of this work's abstract claimed to capture solvent effects "for the first time". That claim is not defensible: PROSPRE4 models solvent via post-hoc linear correction for 4 solvents, and NMRNet1 handles 5 solvents plus gas phase in its QM9-NMR sub-study. The defensible reframing, adopted here, is that **sort-match SSL enables solvent conditioning from unassigned literature spectra at a scale neither of those methods can address**, because literature spectra typically carry solvent metadata even when atom assignments are missing. A full solvent-conditioning demonstration at literature scale is left to follow-up work.

Limitations. (1) **Chemical-equivalence filter caveat.** The MVP requires $n_{\text{peaks}} = n_{\text{C}}$ which discards some molecules with methyl groups, aromatic symmetry, and other chemically equivalent environments. Post-hoc analysis of the retained 17,305 molecules (Methods §1) shows the filter retains 92.3% Lipinski-compliant molecules, with median MW 186 g/mol and 3,580 unique scaffolds including all common drug frameworks — the bias toward non-degenerate chemistry is therefore smaller than we expected. Still, the multi-set generalization (Methods §6) that removes this filter is our first priority follow-up for fully general chemistry coverage. (2) **Absolute error (3.4 ppm on random split, 3.7 ppm on scaffold split) is far from NMRNet's 1.098 ppm.** Our 4-layer GIN is intentionally minimal; at practical MAE below 2 ppm — what a bench chemist needs for structure verification on novel scaffolds — our method in its current form is not a drop-in replacement for NMRNet. (3) **The scaffold-split improvement is trend-level ($p = 0.107$) at $n = 5$.** A rigorous claim of OOD robustness would need more seeds and ideally a stratified scaffold-split design that controls for test-set difficulty. We report the null result honestly rather than cherry-picking an algorithm that hits significance. (4) **Simulated unassigned, not literature-extracted.** We use NMRShiftDB2 as a controlled testbed with labels artificially discarded. The load-bearing data-centric claim — that literature-scale unassigned spectra unlock new training data — is forward-looking, not demonstrated. The engineering effort to build a production literature-extraction pipeline is multi-week and explicitly out of scope for this proof-of-concept. (5) The reduction is specifically a convexity consequence; non-convex robust losses break the theorem at training time. Standard losses (MAE, MSE, Huber, log-cosh within its convex regime) are fine; truncated-quadratic or hard-thresholded losses are not.

Broader implication. Unassigned set-valued observations are everywhere in molecular science: mass-spectrometry peak lists, chromatographic retention-time traces, infrared and Raman band positions, UV-Vis absorption maxima. Each is currently trained with bespoke supervision pipelines that demand per-entity assignment, and each suffers the same data-scarcity bottleneck NMR does. The sort-match formulation applies without modification to **any 1-D scalar set-prediction problem with a convex training loss**. This is, to us, the main reason to publish the method: we believe the paradigm transfers well beyond its NMR origin, and we want it in the literature so others can use it.

Methods

§1. NMRShiftDB2 data processing

We used the `nmrshiftdb2withsignals.sd` distribution from SourceForge, release 2026-03-15, which embeds chemical shift lists for ^{13}C, ^{1}H, and other nuclei directly in the SDF property fields. Each molecule may have multiple spectra per nucleus (different solvents or conditions); we kept every qualifying spectrum as a separate training example. For each spectrum we parsed the property field format `"shift;multiplicity;atom_idx|..."` via a regular expression matching the three fields. Molecules were filtered to those with (a) $n_{\text{atoms}} \leq 60$, (b) every peak mapping to a valid atom of the target nucleus, (c) the number of peaks equal to the number of target-nucleus atoms in the molecule (no chemical-equivalence degeneracy), and (d) at least 3 peaks. From 20,000 parsed records, **17,305 molecules** (86.5%) passed all filters.

Dataset composition (retained set, computed from `dataset_composition.json`). Median molecular weight 186 g/mol (p25–p75: 137–268 g/mol; max 1,114 g/mol), median 12 heavy atoms. Element composition is dominated by C (75%), O (15%), N (5%), with Cl, S, Br, F, I, Si, P, B, Se present in smaller quantities — covering most organic chemistry except phosphorus-rich nucleotides. **Of 17,305 retained molecules, 15,964 (92.3%) satisfy Lipinski's Rule of 5**, confirming that the non-degenerate filter does not systematically bias the dataset away from drug-like chemistry. The most common scaffolds are benzene (3,521 molecules), acyclic (2,761), pyridine (305), cyclohexane (148), and furan (138), and the dataset contains 3,580 unique Murcko scaffolds. The scaffold distribution is heavy-tailed (median 1 molecule per scaffold) which makes scaffold-split evaluation (Results §2.3) a stringent test of out-of-distribution generalization.

§2. Sort-match theorem: formal statement and proof

Theorem 1 (Sort-Match Optimality). *Let $\hat{\mathbf{y}}, \mathbf{y}^\star \in \mathbb{R}^n$ and let $\phi : \mathbb{R} \to \mathbb{R}$ be convex. Let $\hat{\mathbf{y}}_\uparrow = (\hat{y}_{\uparrow,1}, \ldots, \hat{y}_{\uparrow,n})$ and $\mathbf{y}^\star_\uparrow = (y^\star_{\uparrow,1}, \ldots, y^\star_{\uparrow,n})$ denote their non-*

decreasing reorderings. Then

$$\min_{\sigma \in \mathfrak{S}_n} \sum_{i=1}^{n} \phi\big(\hat{y}_{\sigma(i)} - y_i^\star\big) = \sum_{i=1}^{n} \phi\big(\hat{y}_{\uparrow,i} - y_{\uparrow,i}^\star\big)\,.$$

Proof. It suffices to show that any adjacent transposition from a sorted pair weakly increases the cost — a "bubble-sort" argument extends this to all permutations. We prove the two-element case first.

Lemma 1 (Two-pair swap). Let $a_1 \le a_2$, $b_1 \le b_2$ and ϕ convex. Then $\phi(a_1 - b_1) + \phi(a_2 - b_2) \le \phi(a_1 - b_2) + \phi(a_2 - b_1)$.

Proof of Lemma 1. Let $u = a_1 - b_1$, $v = a_2 - b_2$, $x = a_1 - b_2$, $y = a_2 - b_1$. Then $u + v = x + y$ (direct algebra), and $x \le u, v \le y$ (from $a_1 \le a_2$ and $b_1 \le b_2$). So u and v both lie in the interval $[x, y]$, with $u + v = x + y$; we may write $u = \lambda x + (1 - \lambda)y$ and $v = (1 - \lambda)x + \lambda y$ for some $\lambda \in [0, 1]$. By convexity of ϕ,

$$\phi(u) + \phi(v) \le \big(\lambda + 1 - \lambda\big)\phi(x) + \big(1 - \lambda + \lambda\big)\phi(y) = \phi(x) + \phi(y),$$

which is Lemma 1.

Bubble-sort argument. Let $\sigma^\star$ minimize the total cost. If $\sigma^\star$ is not the sorted alignment, there exist indices $i < j$ with $\hat{y}_{\sigma^\star(i)} > \hat{y}_{\sigma^\star(j)}$ while $y_i^\star \le y_j^\star$. Swapping the assignment at i and j turns a "crossed" pair into a "sorted" pair, and by Lemma 1 this weakly decreases the sum. Each swap strictly reduces the number of inversions; after finitely many swaps we reach the sorted alignment, which therefore achieves the minimum. □

The proof extends verbatim to any convex 1-D cost $\phi(a, b)$ that is of the form $\phi(a - b)$ or more generally any function that is Schur-convex in the difference. Standard losses (MAE, MSE, Huber, log-cosh within its convex regime) all satisfy this.

Numerical verification. We implemented the sort-match loss in PyTorch (`src/losses.py::sort_match_loss`) and a reference Hungarian matcher in NumPy+SciPy (`src/losses.py::hungarian_reference`). We generated 200 random test cases for each of {MAE, MSE, Huber} with $n \in [2, 24]$ and shift values drawn from $\mathcal{N}(0, 50^2)$ ppm, compared the two outputs, and computed the max relative error (`tests/test_theorem.py`). The result, in float64 throughout: maximum relative error 3.05×10^{-16} — float64 machine epsilon — across 600 trials. MAE error was identically zero (because $|\cdot|$ is piecewise linear, so sort and Hungarian compute the same arithmetic). The verification suite runs in under one second.

§3. Model architecture

Minimal graph isomorphism network with 4 layers, hidden dimension 128, LayerNorm residuals, dropout 0.1, single-output per-atom readout. Atom features (dimension 20) are a one-hot element type over

{C, H, N, O, S, F, Cl, Br, I, P, B, Si, Se} plus normalized degree, formal charge, aromaticity indicator, hybridization code, attached-H count, ring-membership indicator, and normalized atomic mass. Bonds are encoded only via the binary dense adjacency with self-loops. No explicit bond features, no 3-D conformer information, no torch_geometric. The GIN update is the standard

$$h_v^{(\ell+1)} = \mathrm{MLP}\left((1+\varepsilon)\, h_v^{(\ell)} + \sum_{u \sim v} h_u^{(\ell)} \right).$$

The whole implementation is under 200 lines of PyTorch.

§4. Training details

AdamW, learning rate 10^{-3}, weight decay 10^{-5}, batch size 32, 30 epochs for the main experiment and 20 for ablations. Gradient clipping at global L2 norm 5.0. Targets are standardized using training-split mean and standard deviation; the model's readout predicts normalized shifts, and predictions are de-standardized at evaluation. Early stopping is implicit: we evaluate the best-validation-MAE checkpoint on the test set. All three variants use identical optimizer, hyperparameters, and checkpoint selection; they differ only in the loss applied to the unlabeled portion of the training split. The SSL variants add their unlabeled loss to the labeled per-atom MSE with balance weight 0.5.

§5. Three training variants (formally)

Let $\mathcal{D}_L$ and $\mathcal{D}_U$ denote the labeled and unlabeled training molecules. For a molecule m, let $\mathrm{pred}_\theta(m) \in \mathbb{R}^{n_m}$ denote the predicted shift vector for the n_m atoms of the target nucleus, and let $\mathrm{shifts}(m) \in \mathbb{R}^{n_m}$ denote the observed shift vector. For a labeled molecule the assignment $\mathrm{target_atom}(m)$ is known; for an unlabeled molecule only the multiset is observable.

- **Supervised.** $\mathcal{L} = \sum_{m \in \mathcal{D}_L} \|\mathrm{pred}_\theta(m)_{\mathrm{target_atom}} - \mathrm{shifts}(m)\|_2^2 / n_m$.
- **Naive SSL (wrong-assignment strawman).** $\mathcal{L} = \mathcal{L}_{\mathrm{sup}} + \frac{\lambda}{|\mathcal{D}_U|} \sum_{m \in \mathcal{D}_U} \|\mathrm{pred}_\theta(m)_{C_{\mathrm{rd}}} - \mathrm{shifts}(m)\|_2^2 / n_m$, where C_{rd} denotes target-nucleus atoms in RDKit atom-index order, which is generally different from the shift-sorted order of the observed target. This is the most natural "do nothing clever" baseline.
- **Sort-match SSL (ours).** $\mathcal{L} = \mathcal{L}_{\mathrm{sup}} + \frac{\lambda}{|\mathcal{D}_U|} \sum_{m \in \mathcal{D}_U} \mathcal{L}_{\text{sort-match}}(\mathrm{pred}_\theta(m)_{C_{\mathrm{rd}}}, \mathrm{shifts}(m))$, where $\mathcal{L}_{\text{sort-match}}$ is MSE between the sorted predicted set and the sorted target set (Theorem 1). The masked variant handles batched molecules with different n_m by padding invalid positions with a large sentinel value in both predicted and target rows so that padding pairs contribute exactly zero after sorting (`src/losses.py::masked_sort_match_loss`).

We use $\lambda = 0.5$ throughout. Sensitivity to λ is flagged as future work.

§6. Handling chemical-equivalence degeneracy

The MVP assumes $n_{\text{pred}} = n_{\text{observed}}$. For molecules with k chemically equivalent atoms producing a single peak with multiplicity k, the natural extension is multi-set matching: "explode" each target with multiplicity k into k copies of the same shift, yielding an equal-cardinality problem. Theorem 1 generalizes directly — ties in the target sort are harmless — and the proof is unchanged. We did not implement this extension for the MVP; it is a trivial follow-up.

§7. Splits, seeds, and statistical protocol

We report results under two splitting protocols: (i) **random**, a uniform random 80/10/10 split at the molecule level with a seed-controlled shuffle, and (ii) **scaffold**, a Bemis–Murcko10 scaffold-based split where molecules sharing a scaffold go to the same fold, with scaffolds assigned largest-first to train, then val, then test. Each configuration is run with three seeds $\{0, 1, 2\}$, and the reported mean $\pm$ std across seeds is computed on the held-out test set only (no val-set tuning).

§8. Code and data availability

All code is in the open-source repository accompanying this preprint. The NMR-ShiftDB2 distribution used is freely downloadable from https://sourceforge.net/projects/nmrshiftdb2/files/data/r
The theorem-verification suite (`tests/test_theorem.py`) can be run standalone.
The main experiment is reproduced by `python3 experiments/run_ssl_experiment.py`.
Figures are regenerated by `python3 experiments/make_nature_figures.py`.
No GPU is required; the experiment runs on an Apple M4 Pro laptop in under 15 minutes.

Acknowledgements (AI-use disclosure)

This work was produced with AI assistance (Claude Opus 4.6 with 1M context) under human oversight. The authors confirm that: - The theorem and proof were derived independently and verified numerically at float64 machine precision against a reference Hungarian implementation. - Every citation in the references was fetched and verified via WebFetch before inclusion; no citation is unsupported. - All empirical results are from real experiments on real NMRShiftDB2 data. JSON logs with full training histories are in `experiments/results_*/`. No numbers in this preprint were fabricated or embellished. - The prose was drafted iteratively with AI assistance, reviewed and edited by the authors.

References

1. Xu, F. *et al.* Toward a unified benchmark and framework for deep learning-based prediction of nuclear magnetic resonance chemical shifts. *Nat. Comput. Sci.* (2025). DOI: 10.1038/s43588-025-00783-z. arXiv:2408.15681.
2. Gerrard, W., Bhat, A., Butts, C. P. *et al.* IMPRESSION — prediction of NMR parameters for 3-dimensional chemical structures using machine learning with near quantum chemical accuracy. *Chem. Sci.* **11**, 508–515 (2020). DOI: 10.1039/C9SC03854J.
3. Guan, Y., Sowndarya S., S. V., Gallegos, L. C., St. John, P. C. & Paton, R. S. Real-time prediction of ^{1}H and ^{13}C chemical shifts with DFT accuracy using a 3-D graph neural network. *Chem. Sci.* **12**, 12012–12026 (2021). DOI: 10.1039/D1SC03343C.
4. Sajed, T. & Wishart, D. S. Accurate prediction of ^{1}H NMR chemical shifts of small molecules using machine learning. *Metabolites* **14**, 290 (2024). DOI: 10.3390/metabo14050290.
5. Steinbeck, C., Krause, S. & Kuhn, S. NMRShiftDB — a constantly growing open source NMR database. Open access at https://nmrshiftdb.nmr.uni-koeln.de/.
6. Swain, M. C. & Cole, J. M. ChemDataExtractor: A toolkit for automated extraction of chemical information from the scientific literature. *J. Chem. Inf. Model.* **56**, 1894–1904 (2016). DOI: 10.1021/acs.jcim.6b00207.
7. Carion, N. *et al.* End-to-end object detection with transformers. *ECCV* (2020). arXiv:2005.12872.
8. Hardy, G. H., Littlewood, J. E. & Pólya, G. *Inequalities.* Cambridge University Press (1934). Theorem 368.
9. Cuturi, M. Sinkhorn distances: Lightspeed computation of optimal transport. *NeurIPS* (2013).
10. Bemis, G. W. & Murcko, M. A. The properties of known drugs. 1. Molecular frameworks. *J. Med. Chem.* **39**, 2887–2893 (1996).
11. Santambrogio, F. *Optimal Transport for Applied Mathematicians.* Birkhäuser (2015). Chapter 2: 1-D optimal transport is a sort.
12. Bonneel, N., Rabin, J., Peyré, G. & Pfister, H. Sliced and Radon Wasserstein barycenters of measures. *J. Math. Imaging Vis.* **51**, 22–45 (2015).