



Random forests

Jeffrey Leek, Assistant Professor of Biostatistics
Johns Hopkins Bloomberg School of Public Health

Random forests

1. Bootstrap samples
2. At each split, bootstrap variables
3. Grow multiple trees and vote


Pros:

1. Accuracy

Cons:


1. Speed
2. Interpretability
3. Overfitting

Random forests



The ensemble model

Forest output probability $p(c|\mathbf{v}) = \frac{1}{T} \sum_t p_t(c|\mathbf{v})$



<http://www.robots.ox.ac.uk/~az/lectures/ml/lect5.pdf>

Iris data

```
data(iris); library(ggplot2)
inTrain <- createDataPartition(y=iris$Species,
                               p=0.7, list=FALSE)
training <- iris[inTrain,]
testing <- iris[-inTrain,]
```

Random forests

```
library(caret)
modFit <- train(Species~ .,data=training,method="rf",prox=TRUE)
modFit
```

```
105 samples
  4 predictors
  3 classes: 'setosa', 'versicolor', 'virginica'
```

No pre-processing

Resampling: Bootstrap (25 reps)

Summary of sample sizes: 105, 105, 105, 105, 105, 105, ...

Resampling results across tuning parameters:

| mtry | Accuracy | Kappa | Accuracy SD | Kappa SD |
|------|----------|-------|-------------|----------|
| 2 | 0.9 | 0.9 | 0.03 | 0.04 |
| 3 | 0.9 | 0.9 | 0.03 | 0.05 |
| 4 | 0.9 | 0.9 | 0.03 | 0.05 |

Accuracy was used to select the optimal model using the largest value.

The final value used for the model was mtry = 3.


Getting a single tree

```
getTree(modFit$finalModel,k=2)
```

| | left daughter | right daughter | split var | split point | status | prediction |
|----|---------------|----------------|-----------|-------------|--------|------------|
| 1 | 2 | 3 | 4 | 0.70 | 1 | 0 |
| 2 | 0 | 0 | 0 | 0.00 | -1 | 1 |
| 3 | 4 | 5 | 4 | 1.70 | 1 | 0 |
| 4 | 6 | 7 | 3 | 4.95 | 1 | 0 |
| 5 | 8 | 9 | 3 | 4.85 | 1 | 0 |
| 6 | 0 | 0 | 0 | 0.00 | -1 | 2 |
| 7 | 10 | 11 | 4 | 1.55 | 1 | 0 |
| 8 | 12 | 13 | 1 | 5.95 | 1 | 0 |
| 9 | 0 | 0 | 0 | 0.00 | -1 | 3 |
| 10 | 0 | 0 | 0 | 0.00 | -1 | 3 |
| 11 | 0 | 0 | 0 | 0.00 | -1 | 2 |
| 12 | 0 | 0 | 0 | 0.00 | -1 | 2 |
| 13 | 0 | 0 | 0 | 0.00 | -1 | 3 |

Class "centers"

```
irisP <- classCenter(training[,c(3,4)], training$Species, modFit$finalModel$prox)
irisP <- as.data.frame(irisP); irisP$Species <- rownames(irisP)
p <- qplot(Petal.Width, Petal.Length, col=Species, data=training)
p + geom_point(aes(x=Petal.Width, y=Petal.Length, col=Species), size=5, shape=4, data=irisP)
```




Predicting new values

```
pred <- predict(modFit,testing); testing$predRight <- pred==testing$Species  
table(pred,testing$Species)
```

| pred | setosa | versicolor | virginica |
|------------|--------|------------|-----------|
| setosa | 15 | 0 | 0 |
| versicolor | 0 | 14 | 1 |
| virginica | 0 | 1 | 14 |

Predicting new values

```
qplot(Petal.Width, Petal.Length, colour=predRight, data=testing, main="newdata Predictions")
```



Notes and further resources

Notes:

- Random forests are usually one of the two top performing algorithms along with boosting in prediction contests.
- Random forests are difficult to interpret but often very accurate.
- Care should be taken to avoid overfitting (see [rfcv](#) function)

Further resources:

- [Random forests](#)
- [Random forest Wikipedia](#)
- [Elements of Statistical Learning](#)