



Forecasting

Jeffrey Leek, Assistant Professor of Biostatistics
Johns Hopkins Bloomberg School of Public Health

Time series data

Finance

Google Inc (NASDAQ:GOOG)

Add to portfolio

More results

Company

Summary

News

Option chain

Related companies

Historical prices

Financials

Markets

News

Portfolios

Stock screener

Google Domestic Trends

Recent Quotes ([Turn on](#))

You have no recent quotes

1,120.71

+11.25 (1.01%)

Dec 31 - Close

NASDAQ real-time data - Disclaimer

Currency in USD

Range 1,106.26 - 1,121.00
52 week 695.52 - 1,121.00
Open 1,112.24
Vol / Avg. 1.36M/1.54M
Mkt cap 374.42B
P/E 32.19
Div/yield -
EPS 34.81
Shares 334.09M
Beta 0.87
Inst. own 72%

 +1 9.4k

Dow Jones	16,576.66	0.44%	
Nasdaq	4,176.59	0.00%	
Technology		0.70%	
GOOG	1,120.71	1.01%	

Compare:

Add

☐ Dow Jones ☐ Nasdaq ☐ BIDU ☐ YNDX ☐ MSFT ☐ YHOO ☐ BCOR ☐ IACI ☐ AAPL

Zoom: [1d](#) [5d](#) [1m](#) [3m](#) [6m](#) [YTD](#) [1y](#) [5y](#) [10y](#) [All](#)

Dec 27, 2013 - Dec 31, 2013 +2.83 (0.25%)



[Settings](#) [Technical](#) [Log](#) [Link to this view](#)

Values delayed by 45 min


<https://www.google.com/finance>

What is different?

- Data are dependent over time
- Specific pattern types
 - Trends - long term increase or decrease
 - Seasonal patterns - patterns related to time of week, month, year, etc.
 - Cycles - patterns that rise and fall periodically
- Subsampling into training/test is more complicated
- Similar issues arise in spatial data
 - Dependency between nearby observations
 - Location specific effects
- Typically goal is to predict one or more observations into the future.
- All standard predictions can be used (with caution!)

Beware spurious correlations!


User uploaded activity for Google stock price and US Web Search activity for **solitaire network** ($r=0.8312$)



<http://www.google.com/trends/correlate>


<http://www.newscientist.com/blogs/onepercent/2011/05/google-correlate-passes-our-we.html>

Also common in geographic analyses



<http://xkcd.com/1138/>

Beware extrapolation!



<http://www.nature.com/nature/journal/v431/n7008/full/431525a.html>

Google data

```
library(quantmod)
from.dat <- as.Date("01/01/08", format="%m/%d/%y")
to.dat <- as.Date("12/31/13", format="%m/%d/%y")
getSymbols("GOOG", src="google", from = from.dat, to = to.dat)
```


```
[1] "GOOG"
```

```
head(GOOG)
```

	GOOG.Open	GOOG.High	GOOG.Low	GOOG.Close	GOOG.Volume
2008-01-02	692.9	697.4	677.7	685.2	4306848
2008-01-03	685.3	686.9	676.5	685.3	3252846
2008-01-04	679.7	681.0	655.0	657.0	5359834
2008-01-07	653.9	662.3	637.4	649.2	6404945
2008-01-08	653.0	660.0	631.0	631.7	5341949
2008-01-09	630.0	653.3	622.5	653.2	6744242

Summarize monthly and store as time series

```
mGoog <- to.monthly(GOOG)  
googOpen <- Op(mGoog)  
ts1 <- ts(googOpen, frequency=12)  
plot(ts1, xlab="Years+1", ylab="GOOG")
```




Example time series decomposition

- **Trend** - Consistently increasing pattern over time
- **Seasonal** - When there is a pattern over a fixed period of time that recurs.
- **Cyclic** - When data rises and falls over non fixed periods

<https://www.otexts.org/fpp/6/1>

Decompose a time series into parts

```
plot(decompose(ts1),xlab="Years+1")
```



Training and test sets


```
ts1Train <- window(ts1,start=1,end=5)
ts1Test  <- window(ts1,start=5,end=(7-0.01))
ts1Train
```

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	692.9	528.7	471.5	447.7	578.3	582.5	519.6	472.5	476.8	412.1	357.6	286.7
2	308.6	334.3	333.3	343.8	395.0	418.7	424.2	448.7	459.7	493.0	537.1	588.1
3	627.0	534.6	529.2	571.4	526.5	480.4	445.3	489.0	455.0	530.0	615.7	563.0
4	596.5	604.5	617.8	588.8	545.7	528.0	506.7	611.2	540.8	509.9	580.1	600.0
5	652.9											

Simple moving average

$$Y_t = \frac{1}{2 * k + 1} \sum_{j=-k}^k y_{t+j}$$

```
plot(ts1Train)  
lines(ma(ts1Train,order=3),col="red")
```



Exponential smoothing

Example - simple exponential smoothing


$$\hat{y}_{t+1} = \alpha y_t + (1 - \alpha) \hat{y}_{t-1}$$

Trend Component	Seasonal Component		
	N	A	M
(None)	(None)	(Additive)	(Multiplicative)
N (None)	(N,N)	(N,A)	(N,M)
A (Additive)	(A,N)	(A,A)	(A,M)
A _d (Additive damped)	(A _d ,N)	(A _d ,A)	(A _d ,M)
M (Multiplicative)	(M,N)	(M,A)	(M,M)
M _d (Multiplicative damped)	(M _d ,N)	(M _d ,A)	(M _d ,M)

<https://www.otexts.org/fpp/7/6>

Exponential smoothing

```
ets1 <- ets(ts1Train,model="MMM")  
fcast <- forecast(ets1)  
plot(fcast); lines(ts1Test,col="red")
```



Get the accuracy

```
accuracy(fcast,ts1Test)
```

	ME	RMSE	MAE	MPE	MAPE	MASE	ACF1	Theil's U
Training set	0.9464	48.78	39.35	-0.3297	7.932	0.3733	0.07298	NA
Test set	156.1890	205.76	160.78	18.1819	18.971	1.5254	0.77025	3.745

Notes and further resources

- [Forecasting and timeseries prediction](#) is an entire field
- Rob Hyndman's [Forecasting: principles and practice](#) is a good place to start
- Cautions
 - Be wary of spurious correlations
 - Be careful how far you predict (extrapolation)
 - Be wary of dependencies over time
- See [quantmod](#) or [quandl](#) packages for finance-related problems.