

1. Given: `a = np.array([[2, 4, 6], [3, 6, 9], [5, 10, 15]])`

Divide every element by the sum of its own row.

2. Given: `a = np.array([[12, 45, 23], [56, 21, 34], [18, 39, 27]])`

Replace the maximum element of each column with 0.

3. Given: `a = np.array([[10, 20, 30], [5, 15, 25], [40, 50, 60]])`

For each row, replace elements greater than that row's mean with -1.

4. Given: `a = np.arange(1, 26).reshape(5, 5)`

Extract all boundary elements in clockwise order, starting from the top-left.

5. Given: `a = np.array([[12, 45, 23], [56, 21, 34], [18, 39, 27]])`

Find the second-largest unique value using NumPy.

6. Given: `a = np.array([[10, 20, 30], [5, 15, 25], [40, 50, 60], [7, 8, 9]])`

Find the row indices whose row sum is greater than 50.

7. Given: `a = np.array([[10, 20, 30], [20, 40, 60], [30, 60, 90]])`

Divide every element by the sum of its column.

8. Given: `a = np.array([[1, 2, 3], [2, 5, 6], [3, 6, 9]])`

Check whether `a` is symmetric using NumPy. No loops.

9. Given: `a = np.array([[2, 7, 8, 11], [4, 6, 9, 13], [5, 10, 12, 14]])`

Find the index of the row containing the largest number of even elements.

10. Given: `a =`

`np.array([[10, 20, 30, 40], [50, 60, 70, 80], [90, 100, 110, 120], [130, 140, 150, 160]])`

Produce `[10 40 70 100 130 160]` using NumPy indexing/slicing. Then produce `[40 70 100 130]` using indexing/slicing, without manually constructing the array.