Low ESR / High-Q Capacitor Selection Chart

EIA Size		Miniature Size - Portable Electronics				RF Power Applications							
		01005	0201 (R05)		0402	0603	0805	1111		2525**	3838**		
Cap. Value			(R03S)	NPO (R05L)	X7R* (R05W)	(R07S)	(R14S)	(R15S)	(S42E)		(S48E)	(S58E)	
Capac pF	itance Code	Toler- ance	Voltage										
36	360			25 V			250 V	250 V	500V	1000V			
39	390			25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
43	430			25 V			250 V	250 V	500V	1000V			
47	470			25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
51	510			25 V			250 V	250 V	500V	1000V			
56	560			25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
62	620			25 V			250 V	250 V	500V	1000V			
68	680			25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
75	750			25 V			250 V	250 V	500V	1000V			
82	820	F		25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
91	910			25 V			250 V	250 V	500V	1000V			
100	101	G		25 V			250 V	250 V	500V	1000V	2500V	3600V	7200V
110	111	_			16 V			250 V	500V				
120	121	J						250 V	500V		2500V	3600V	5000V
130	131	U						250 V	500V		05001/	0.0001/	500011
150	151	1/						250 V	500V		2500V	3600V	5000V
160	161	K						250 V	500V		05001	00001	E0001/
180	181	-						250 V	500V		2500V	3600V	5000V
200 220	201 221	-			16 V			250 V 250 V	500V 500V		2500V	3600V	
240	241	-			16 V			250 V	500V		2500V	30007	
270	271	-							500V		2500V	3600V	
300	301	-							500V		2000 V	3000 V	
330	331								500V		1500V	3600V	
360	361	-							500V		10001	00001	
390	391								500V		1500V	3600V	
430	431								500V				
470	471				16 V				500V		1500V	2500V	
510	511								500V				
560	561								500V		1000V	2500V	
620	621								500V				
680	681				16 V				50V		1000V	2500V	
750	751								50V				
820	821	G			16 V				50V		1000V	1000V	
910	911								50V				
1000	102	J			10 V				50V		1000V	1000V	
1200	122	J									1000V	1000V	
1500	152	IZ.									500V	1000V	
1800	182	K			1611						500V	1000V	
2200	222				10 V						300V	1000V	
2700	272				-						300V	500V	
3300	332				-							500V	
3900	392				101/							500V	
4700	472				10 V							500V	
5100	512				601/							500V	
10000	103				6.3 V								

^{*} The R05W parts, which are X7R, can only be provided with "K" tolerance. Consult factory for Non-Standard values.

