

Chapter 3: Introduction to SQL

Database System Concepts, 7th Ed.

©Silberschatz, Korth and Sudarshan
See www.db-book.com for conditions on re-use



Outline

- Overview of The SQL Query Language
- SQL Data Definition
- Basic Query Structure of SQL Queries
- Additional Basic Operations
- Set Operations
- Null Values
- Aggregate Functions 统计函数
- Nested Subqueries 嵌套子查询
- Modification of the Database

“增删改查”

©Silberschatz, Korth and Sudarshan



History

- IBM Sequel language developed as part of System R project at the IBM San Jose Research Laboratory
- Renamed Structured Query Language (SQL)
- ANSI and ISO standard SQL: 结构化查询语言
  - SQL-86
  - SQL-89
  - SQL-92
  - SQL:1999 (language name became Y2K compliant!)
  - SQL:2003
- Commercial systems offer most, if not all, SQL-92 features, plus varying feature sets from later standards and special proprietary features.
  - Not all examples here may work on your particular system.



SQL Parts

- DML -- provides the ability to query information from the database and to insert tuples into, delete tuples from, and modify tuples in the database.
- integrity – the DDL includes commands for specifying integrity constraints.
- View definition -- The DDL includes commands for defining views.
- Transaction control –includes commands for specifying the beginning and ending of transactions. 事务
- Embedded SQL and dynamic SQL -- define how SQL statements can be embedded within general-purpose programming languages.
- Authorization – includes commands for specifying access rights to relations and views.



Data Definition Language

The SQL data-definition language (DDL) allows the specification of information about relations, including:

- The schema for each relation.
- The type of values associated with each attribute.
- The Integrity constraints
- The set of indices (索引) to be maintained for each relation.
- Security and authorization information for each relation.
- The physical storage structure of each relation on disk.



Domain Types in SQL

- **char(n).** Fixed length character string, with user-specified length *n.*
- **varchar(n).** Variable length character strings, with user-specified maximum length *n.*
- **int.** Integer (a finite subset of the integers that is machine-dependent).
- **smallint.** Small integer (a machine-dependent subset of the integer domain type).
- **numeric(p,d).** Fixed point number, with user-specified precision of *p* digits, with *d* digits to the right of decimal point. (ex., **numeric**(3,1), allows 44.5 to be stores exactly, but not 444.5 or 0.32)
- **real, double precision.** Floating point and double-precision floating point numbers, with machine-dependent precision.
- **float(n).** Floating point number, with user-specified precision of at least *n* digits.
- More are covered in Chapter 4.



Create Table Construct

- An SQL relation is defined using the **create table** command:

  create table *r*

  (A_1 D_1, A_2 D_2, ..., A_n D_n,
  (integrity-constraint$_1$),
  ...,
  (integrity-constraint$_k$))

  - *r* is the name of the relation
  - each A_i is an attribute name in the schema of relation *r*
  - D_i is the data type of values in the domain of attribute A_i
- Example:

```
create table instructor (
        ID              char(5),
        name            varchar(20),
        dept_name       varchar(20),
        salary          numeric(8,2))
```

未指定时，系统内部会维护主键



Integrity Constraints in Create Table

完整性约束

- Types of integrity constraints
  - **primary key** (A_1, ..., A_n) 主键默认not null
  - **foreign key** (A_m, ..., A_n) **references** *r*
  - **not null**
- SQL prevents any update to the database that violates an integrity constraint.
- Example:

```
create table instructor (
        ID              char(5),
        name            varchar(20) not null,
        dept_name       varchar(20),
        salary          numeric(8,2),
        primary key (ID),
        foreign key (dept_name) references department);
```

关联/来源于



And a Few More Relation Definitions

- **create table** *student* (
  ID **varchar**(5),
  name **varchar**(20) not null,
  dept_name **varchar**(20),
  tot_cred **numeric**(3,0),
  primary key *(ID),*
  foreign key *(dept_name*) **references** *department*);

- **create table** *takes* (
  ID **varchar**(5),
  course_id **varchar**(8),
  sec_id **varchar**(8),
  semester **varchar**(6),
  year **numeric**(4,0),
  grade **varchar**(2),
  primary key *(ID, course_id, sec_id, semester, year)* ,
  foreign key (*ID*) **references** *student,*
  foreign key (*course_id, sec_id, semester, year*) **references** *section*);

©Silberschatz, Korth and Sudarshan



And more still

- **create table** *course* (
  course_id **varchar**(8),
  title **varchar(**50),
  dept_name **varchar**(20),
  credits **numeric**(2,0),
  primary key *(course_id),*
  foreign key *(dept_name*) **references** *department*);



Updates to tables

- **Insert**
  - **insert into** *instructor* **values** ('10211', 'Smith', 'Biology', 66000);
- **Delete**
  - Remove all tuples from the *student* relation 变为空表
    - **delete from** *student*
- **Drop Table**
  - **drop table** *r* 删除表结构
- **Alter** 改变
  - **alter table** *r* **add** *A D*
    - where *A* is the name of the attribute to be added to relation *r* and *D* is the domain of *A.*
    - All exiting tuples in the relation are assigned *null* as the value for the new attribute.
  - **alter table** *r* **drop** *A*
    - where *A* is the name of an attribute of relation *r*
    - Dropping of attributes not supported by many databases.

©Silberschatz, Korth and Sudarshan



Basic Query Structure

- A typical SQL query has the form:

select A_1, A_2, ..., A_n
from r_1, r_2, ..., r_m
where P

  - A_i represents an attribute
  - R_i represents a relation
  - P is a predicate. 谓词条件

- The result of an SQL query is a relation.



The select Clause

- The **select** clause lists the attributes desired in the result of a query
  - corresponds to the projection operation of the relational algebra
- Example: find the names of all instructors:

  select *name*
  from *instructor*
- NOTE: SQL names are case insensitive (i.e., you may use upper- or lower-case letters.)
  - E.g., *Name* ≡ *NAME* ≡ *name*
  - Some people use upper case wherever we use bold font.

关系代数

大小写不敏感



The select Clause (Cont.)

允许重复

- SQL allows duplicates in relations as well as in query results.
- To force the elimination of duplicates, insert the keyword **distinct** after select.
- Find the department names of all instructors, and remove duplicates

```
select distinct dept_name
from instructor
```

- The keyword **all** specifies that duplicates should not be removed.

```
select all dept_name
from instructor
```



The select Clause (Cont.)

- An asterisk in the select clause denotes “all attributes” 查找所有属性

```
select *
from instructor
```

- An attribute can be a literal with no **from** clause

```
select '437'
```

  - Results is a table with one column and a single row with value “437”
  - Can give the column a name using:

```
select '437' as FOO
```

- An attribute can be a literal with **from** clause 子句

文字

```
select 'A'
from instructor
```

  - Result is a table with one column and *N* rows (number of tuples in the *instructors* table), each row with value “A”

©Silberschatz, Korth and Sudarshan



The select Clause (Cont.)

- The **select** clause can contain arithmetic expressions involving the operation, +, –, ∗, and /, and operating on constants or attributes of tuples.
  - The query:

    select *ID, name, salary/12*
    from *instructor*

    would return a relation that is the same as the *instructor* relation, except that the value of the attribute *salary* is divided by 12.
  - Can rename "s*alary/12"* using the **as** clause:

    select *ID, name, salary/12* **as** *monthly_salary*



The where Clause

- The **where** clause specifies conditions that the result must satisfy
  - Corresponds to the selection predicate of the relational algebra.
- To find all instructors in Comp. Sci. dept

```
select name
from instructor
where dept_name = 'Comp. Sci.'
```

- SQL allows the use of the logical connectives **and, or,** and **not**
- The operands of the logical connectives can be expressions involving the comparison operators <, <=, >, >=, =, and <>.
- Comparisons can be applied to results of arithmetic expressions
- To find all instructors in Comp. Sci. dept with salary > 80000

```
select name
from instructor
where dept_name = 'Comp. Sci.' and salary > 80000
```


©Silberschatz, Korth and Sudarshan



The from Clause

- The **from** clause lists the relations involved in the query
  - Corresponds to the Cartesian product operation of the relational algebra.
- Find the Cartesian product *instructor X teaches*

  select ∗
  from *instructor, teaches*

  - generates every possible instructor – teaches pair, with all attributes from both relations.
  - For common attributes (e.g., *ID*), the attributes in the resulting table are renamed using the relation name (e.g., *instructor.ID*)
- Cartesian product not very useful directly, but useful combined with where-clause condition (selection operation in relational algebra).



Examples

- Find the names of all instructors who have taught some course and the course_id
  - **select** *name, course_id*
    from *instructor , teaches*
    where *instructor.ID = teaches.ID*
- Find the names of all instructors in the Art department who have taught some course and the course_id
  - **select** *name, course_id*
    from *instructor , teaches*
    where *instructor.ID = teaches.ID* ***and*** *instructor. dept_name* = 'Art'

©Silberschatz, Korth and Sudarshan



The Rename Operation

- The SQL allows renaming relations and attributes using the **as** clause:

  old-name **as** *new-name*

- Find the names of all instructors who have a higher salary than some instructor in 'Comp. Sci'.

  - **select distinct** *T.name*
    from *instructor* **as** *T, instructor* **as** *S*
    where *T.salary* > *S.salary* **and** *S.dept_name* = *'Comp. Sci.'*

- Keyword **as** is optional and may be omitted

  instructor **as** *T* ≡ *instructor T*



Self Join Example

- Relation *emp-super*

person	*supervisor*
Bob	Alice
Mary	Susan
Alice	David
David	Mary

- Find the supervisor of “Bob”
- Find the supervisor of the supervisor of “Bob”
- Can you find ALL the supervisors (direct and indirect) of “Bob”?

©Silberschatz, Korth and Sudarshan



String Operations

- SQL includes a string-matching operator for comparisons on character strings. The operator **like** uses patterns that are described using two special characters:
  - percent (%). The % character matches any substring.
  - underscore (_). The _ character matches any character.
- Find the names of all instructors whose name includes the substring “dar”.

```
select name
from instructor
where name like '%dar%'
```

- Match the string “100%”

```
like '100 \%'  escape  '\'
```

in that above we use backslash (\) as the escape character.

转义字符



String Operations (Cont.)

- Patterns are case sensitive.
- Pattern matching examples:
  - 'Intro%' matches any string beginning with “Intro”.
  - '%Comp%' matches any string containing “Comp” as a substring.
  - '_ _ _' matches any string of exactly three characters.
  - '_ _ _ %' matches any string of at least three characters.
- SQL supports a variety of string operations such as
  - concatenation (using “||”)
  - converting from upper to lower case (and vice versa)
  - finding string length, extracting substrings, etc.

©Silberschatz, Korth and Sudarshan



Ordering the Display of Tuples

- List in alphabetic order the names of all instructors

排序

```
select distinct name
from    instructor
order by name
```

- We may specify **desc** for descending order or **asc** for ascending order, for each attribute; ascending order is the default.
  - Example: **order by** *name* **desc**
- Can sort on multiple attributes
  - Example: **order by** *dept_name, name*

©Silberschatz, Korth and Sudarshan



Where Clause Predicates

- SQL includes a **between** comparison operator
- Example: Find the names of all instructors with salary between \$90,000 and \$100,000 (that is, $\geq$ \$90,000 and $\leq$ \$100,000)
  - **select** *name*
    from *instructor*
    where *salary* **between** 90000 **and** 100000
- Tuple comparison
  - **select** *name*, *course_id*
    from *instructor*, *teaches*
    where (*instructor.ID*, *dept_name*) = (*teaches.ID*, 'Biology');



Set Operations

- Find courses that ran in Fall 2017 or in Spring 2018

  (**select** *course_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2017)
  union
  (**select** *course_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2018)

- Find courses that ran in Fall 2017 and in Spring 2018

  (**select** *course_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2017)
  intersect
  (**select** *course_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2018)

- Find courses that ran in Fall 2017 but not in Spring 2018

  (**select** *course_id* **from** *section* **where** *sem* = 'Fall' **and** *year* = 2017)
  except
  (**select** *course_id* **from** *section* **where** *sem* = 'Spring' **and** *year* = 2018)

©Silberschatz, Korth and Sudarshan



Set Operations (Cont.)

- Set operations **union**, **intersect**, and **except**
  - Each of the above operations automatically eliminates duplicates
- To retain all duplicates use the
  - **union all**,
  - **intersect all**
  - **except all**.



Null Values

- It is possible for tuples to have a null value, denoted by **null**, for some of their attributes
- **null** signifies an unknown value or that a value does not exist.
- The result of any arithmetic expression involving **null** is **null**
  - Example: 5 + **null** returns **null**
- The predicate **is null** can be used to check for null values.
  - Example: Find all instructors whose salary is null.

    select *name*
    from *instructor*
    where *salary* **is null**
- The predicate **is not null** succeeds if the value on which it is applied is not null.



Null Values (Cont.)

- SQL treats as **unknown** the result of any comparison involving a null value (other than predicates **is null** and **is not null**).
  - Example*: 5* < **null** or **null** <> **null** or **null** = **null**
- The predicate in a **where** clause can involve Boolean operations (**and**, **or**, **not**); thus the definitions of the Boolean operations need to be extended to deal with the value **unknown**.
  - **and** : *(true* **and** *unknown)* = *unknown,*
    (false **and** *unknown)* = *false,*
    (unknown **and** *unknown)* = *unknown*
  - **or:** (*unknown* **or** *true*) = *true*,
    (*unknown* **or** *false*) = *unknown*
    (*unknown* **or** *unknown)* = *unknown*
- Result of **where** clause predicate is treated as *false* if it evaluates to *unknown*



Aggregate Functions

聚合函数

- These functions operate on the multiset of values of a column of a relation, and return a value

avg: average value
min: minimum value
max: maximum value
sum: sum of values
count: number of values

©Silberschatz, Korth and Sudarshan



Aggregate Functions Examples

- Find the average salary of instructors in the Computer Science department
  - **select avg** (*salary*)
    from *instructor*
    where *dept_name*= 'Comp. Sci.';
- Find the total number of instructors who teach a course in the Spring 2018 semester
  - **select count** (**distinct** *ID*)
    from *teaches*
    where *semester* = 'Spring' **and** *year* = 2018;
- Find the number of tuples in the *course* relation
  - **select count** (*)
    from *course*;



Aggregate Functions – Group By

- Find the average salary of instructors in each department
  - **select** *dept_name*, **avg** (*salary*) **as** *avg_salary*
    from *instructor*
    group by *dept_name*;

分组

ID	*name*	*dept_name*	*salary*
76766	Crick	Biology	72000
45565	Katz	Comp. Sci.	75000
10101	Srinivasan	Comp. Sci.	65000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000
12121	Wu	Finance	90000
76543	Singh	Finance	80000
32343	El Said	History	60000
58583	Califieri	History	62000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
22222	Einstein	Physics	95000

dept_name	*avg_salary*
Biology	72000
Comp. Sci.	77333
Elec. Eng.	80000
Finance	85000
History	61000
Music	40000
Physics	91000

©Silberschatz, Korth and Sudarshan



Aggregation (Cont.)

- Attributes in **select** clause outside of aggregate functions must appear in **group by** list
  - /* erroneous query */
    select *dept_name*, *ID*, **avg** (*salary*)
    from *instructor*
    group by *dept_name*;

聚合函数之外的select子句中的属性必须出现在group by列表中



Aggregate Functions – Having Clause

- Find the names and average salaries of all departments whose average salary is greater than 42000

  select *dept_name*, **avg** (*salary*) **as** *avg_salary*
  from *instructor*
  group by *dept_name*
  having avg (*salary*) > 42000;

- Note: predicates in the **having** clause are applied after the formation of groups whereas predicates in the **where** clause are applied before forming groups

having子句中的谓语在组形成之后使用，而where子句中的谓语在组形成之前使用

筛选作用



Nested Subqueries
嵌套

- SQL provides a mechanism for the nesting of subqueries. A **subquery** is a **select-from-where** expression that is nested within another query.
- The nesting can be done in the following SQL query

  select A_1, A_2, ..., A_n
  from r_1, r_2, ..., r_m
  where P

  as follows:

  - **From clause:** r_i can be replaced by any valid subquery 对应
  - **Where clause:** P can be replaced with an expression of the form:

    B <operation> (subquery)

    B is an attribute and <operation> to be defined later.
  - **Select clause:**

    A_i can be replaced be a subquery that generates a single value.

©Silberschatz, Korth and Sudarshan



Set Membership



Set Membership

- Find courses offered in Fall 2017 and in Spring 2018

```
select distinct course_id
from section
where semester = 'Fall' and year= 2017 and
        course_id in (select course_id
                      from section
                      where semester = 'Spring' and year= 2018);
```

- Find courses offered in Fall 2017 but not in Spring 2018

```
select distinct course_id
from section
where semester = 'Fall' and year= 2017 and
        course_id  not in (select course_id
                           from section
                           where semester = 'Spring' and year= 2018);
```


©Silberschatz, Korth and Sudarshan



Set Membership (Cont.)

- Name all instructors whose name is neither “Mozart” nor Einstein”

```
select distinct name
from instructor
where  name not in ('Mozart', 'Einstein')
```

- Find the total number of (distinct) students who have taken course sections taught by the instructor with *ID* 10101

```
select count (distinct ID)
from takes
where (course_id, sec_id, semester, year) in
                    (select course_id, sec_id, semester, year
                     from teaches
                     where teaches.ID= 10101);
```

- Note: Above query can be written in a much simpler manner. The formulation above is simply to illustrate SQL features



Set Comparison



Set Comparison – “some” Clause

找出工资高于生物系某些(至少一个)教师的姓名。

- Find names of instructors with salary greater than that of some (at least one) instructor in the Biology department.

```
select distinct T.name
from instructor as T, instructor as S
where T.salary > S.salary and S.dept name = 'Biology';
```

- Same query using > **some** clause

```
select name
from instructor
where salary > some (select salary
                     from instructor
                     where dept name = 'Biology');
```



Definition of "some" Clause

- F <comp> **some** $r \Leftrightarrow \exists\, t \in r$ such that (F <comp> t)
  Where <comp> can be: $<,\ \leq,\ >,\ =,\ \neq$

(5 < **some** | 0 / 5 / 6 |) = true (read: 5 < some tuple in the relation)

(5 < **some** | 0 / 5 |) = false

(5 = **some** | 0 / 5 |) = true

(5 ≠ **some** | 0 / 5 |) = true (since 0 ≠ 5)

(= **some**) ≡ **in**
However, (≠ **some**) ≢ **not in**



Set Comparison – “all” Clause

查找工资高于生物系所有教师工资的所有教师的姓名。

- Find the names of all instructors whose salary is greater than the salary of all instructors in the Biology department.

```
select name
from instructor
where salary > all (select salary
                    from instructor
                    where dept name = 'Biology');
```


©Silberschatz, Korth and Sudarshan



Definition of "all" Clause

- F <comp> **all** $r \Leftrightarrow \forall\ t \in r$ (F <comp> t)

(5 < **all** {0, 5, 6}) = false

(5 < **all** {6, 10}) = true

(5 = **all** {4, 5}) = false

(5 ≠ **all** {4, 6}) = true (since 5 ≠ 4 and 5 ≠ 6)

(≠ **all**) ≡ **not in**

However, (= **all**) ≠ **in**



Test for Empty Relations

- The **exists** construct returns the value **true** if the argument subquery is nonempty.
- **exists** $r \Leftrightarrow r \neq \emptyset$
- **not exists** $r \Leftrightarrow r = \emptyset$

©Silberschatz, Korth and Sudarshan



Use of "exists" Clause

- Yet another way of specifying the query "Find all courses taught in both the Fall 2017 semester and in the Spring 2018 semester"

```
select course_id
from section as S
where semester = 'Fall' and year = 2017 and
        exists  (select *
                 from section as T
                 where semester = 'Spring' and year= 2018
                       and S.course_id = T.course_id);
```

- **Correlation name** – variable S in the outer query
- **Correlated subquery** – the inner query



Use of "not exists" Clause

找到所有修过生物系所有课程的学生

- Find all students who have taken all courses offered in the Biology department.

```
select distinct S.ID, S.name
from student as S
where not exists ( (select course_id
                    from course
                    where dept_name = 'Biology')
                   except
                    (select T.course_id
                     from takes as T
                     where S.ID = T.ID));
```

第一个嵌套查询列出了生物学提供的所有课程

  - First nested query lists all courses offered in Biology
  - Second nested query lists all courses a particular student took

- Note that $X - Y = \emptyset \Leftrightarrow X \subseteq Y$

第二个嵌套查询列出了特定学生所修的所有课程

- Note: Cannot write this query using = all and its variants



Test for Absence of Duplicate Tuples

- The **unique** construct tests whether a subquery has any duplicate tuples in its result.
- The **unique** construct evaluates to “true” if a given subquery contains no duplicates . 如果子查询不包含重复项，则构造的计算结果为" true "。
- Find all courses that were offered at most once in 2017

```
select T.course_id
 from course as T
 where unique ( select R.course_id
                  from section as R
                  where T.course_id= R.course_id
                        and R.year = 2017);
```



Subqueries in the From Clause



Subqueries in the Form Clause

- SQL allows a subquery expression to be used in the **from** clause
- Find the average instructors' salaries of those departments where the average salary is greater than $42,000."

```
select dept_name, avg_salary
from ( select dept_name, avg (salary) as avg_salary
          from instructor
          group by dept_name)
where avg_salary > 42000;
```

- Note that we do not need to use the **having** clause
- Another way to write above query

```
select dept_name, avg_salary
from ( select dept_name, avg (salary)
          from instructor
          group by dept_name)
          as dept_avg (dept_name, avg_salary)
where avg_salary > 42000;
```



With Clause

临时的

- The **with** clause provides a way of defining a temporary relation whose definition is available only to the query in which the **with** clause occurs.
- Find all departments with the maximum budget

```
with max_budget (value) as
        (select max(budget)
         from department)
select department.name
from department, max_budget
where department.budget = max_budget.value;
```



Complex Queries using With Clause

- Find all departments where the total salary is greater than the average of the total salary at all departments

```
with dept _total (dept_name, value) as
        (select dept_name, sum(salary)
         from instructor
         group by dept_name),
dept_total_avg(value) as
       (select avg(value)
       from dept_total)
select dept_name
from dept_total, dept_total_avg
where dept_total.value > dept_total_avg.value;
```



Scalar Subquery

标量子查询是在需要单个值的地方使用的查询

- Scalar subquery is one which is used where a single value is expected
- List all departments along with the number of instructors in each department

```
select dept_name,
        ( select count(*)
          from instructor
          where department.dept_name = instructor.dept_name)
        as num_instructors
from department;
```

- Runtime error if subquery returns more than one result tuple

©Silberschatz, Korth and Sudarshan



Modification of the Database

- Deletion of tuples from a given relation.
- Insertion of new tuples into a given relation
- Updating of values in some tuples in a given relation

©Silberschatz, Korth and Sudarshan



Deletion

- Delete all instructors

  delete from *instructor*

- Delete all instructors from the Finance department

  delete from *instructor*
  where *dept_name*= 'Finance';

- *Delete all tuples in the instructor relation for those instructors associated with a department located in the Watson building.*

  delete from *instructor*
  where *dept name* **in** (**select** *dept name*
  from *department*
  where *building* = 'Watson');



Deletion (Cont.)

- Delete all instructors whose salary is less than the average salary of instructors

  delete from *instructor*
  where *salary* < (**select avg** (*salary*)
  from *instructor*);

  - Problem: as we delete tuples from *instructor*, the average salary changes
  - Solution used in SQL:
    1. First, compute **avg** (salary) and find all tuples to delete
    2. Next, delete all tuples found above (without recomputing **avg** or retesting the tuples)

©Silberschatz, Korth and Sudarshan



Insertion

- Add a new tuple to *course*

  insert into *course*
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);

- or equivalently

  insert into *course* (*course_id*, *title*, *dept_name*, *credits*)
  values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);

- Add a new tuple to *student* with *tot_creds* set to null

  insert into *student*
  values ('3003', 'Green', 'Finance', *null*);

©Silberschatz, Korth and Sudarshan



Insertion (Cont.)

- Make each student in the Music department who has earned more than 144 credit hours an instructor in the Music department with a salary of $18,000.

```
insert into instructor
    select ID, name, dept_name, 18000
    from   student
    where  dept_name = 'Music' and total_cred > 144;
```

- The **select from where** statement is evaluated fully before any of its results are inserted into the relation.

Otherwise queries like

```
insert into table1 select * from table1
```

would cause problem 主键的唯一性、



Updates

- Give a 5% salary raise to all instructors

```
update instructor
  set salary = salary * 1.05
```

- Give a 5% salary raise to those instructors who earn less than 70000

```
update instructor
  set salary = salary * 1.05
  where salary < 70000;
```

- Give a 5% salary raise to instructors whose salary is less than average

```
update instructor
 set salary = salary * 1.05
 where salary <  (select avg (salary)
                  from instructor);
```



Updates (Cont.)

- Increase salaries of instructors whose salary is over $100,000 by 3%, and all others by a 5%
  - Write two **update** statements:

```
update instructor
    set salary = salary * 1.03
    where salary > 100000;
update instructor
    set salary = salary * 1.05
    where salary <= 100000;
```

  - The order is important
  - Can be done better using the **case** statement (next slide)



Case Statement for Conditional Updates

- Same query as before but with case statement

```
update instructor
    set salary = case
                    when salary <= 100000 then salary * 1.05
                    else salary * 1.03
                 end
```


©Silberschatz, Korth and Sudarshan



Updates with Scalar Subqueries

标量查询

- Recompute and update tot_creds value for all students

```
update student S
set tot_cred = (select sum(credits)
                from takes, course
                where takes.course_id = course.course_id  and
                      S.ID= takes.ID.and
                      takes.grade <> 'F' and
                      takes.grade is not null);
```

- Sets *tot_creds* to null for students who have not taken any course
- Instead of **sum**(*credits*), use:

```
case
    when sum(credits) is not null then sum(credits)
    else 0
end
```


©Silberschatz, Korth and Sudarshan



End of Chapter 3