

V1  
12AX7A

V2  
12AX7A

V5  
12AX7A

NOTE  
J4 ISOLATED  
FROM CHASSIS

6CA7 (4)

EXT  
J4  
SPKR  
J3

\* 6RS20SP7B7  
OR  
1RCKZ70PM  
\*\* 6RS20SP20B20  
OR  
1RCKZ20DPM

4. ADJUST R8A TO ALLOW 8V D.C. DROP ACROSS  
R30(1K) SCREEN RESISTOR.

NOTE:  
1. ALL CAPACITANCE VALUES ARE IN MFD. UNLESS  
OTHERWISE SPECIFIED.  
2. ALL RESISTANCE VALUES ARE IN  $\Omega$  AT  $\pm 10\%$  UNLESS  
OTHERWISE SPECIFIED.  
3. TWO IN5061 CONTROLLED AVALANCHE TYPE  
RECTIFIERS IN EACH LEG MAY BE SUBSTITUTED  
FOR THE 3 PH204 IN EACH LEG.



YORKVILLE SOUND LTD.

DESIGN: P. TRAYNOR  
DATE: JAN 13/67  
SCALE:  
APPROVED:

YBA-3  
CUSTOM SPECIAL  
ALL DIMENSIONS IN INCHES  
80 NOT SCALE

REVISION NO.	DATE	BY
0543	NOV 20, 70	AK
0541	DEC 2/70	AK
0547	DEC 9/70	AK
PC A1319	JULY 18, 71	S. J.
A1322	AUG 5, 71	S. J.
A1332	FEB 17, 72	R.M.
A1336	MAY 17, 72	S.M.K.S.
16/2352	OCT. 5/72	S.M.K.S. / AK

LAST CAPACITOR C35 LAST RESISTOR NO 52