

# Greedy Algorithms: Fractional Knapsack

Michael Levin

Higher School of Economics

Algorithmic Toolbox  
Data Structures and Algorithms

# Outline

- 1 Long Hike
- 2 Fractional Knapsack
- 3 Pseudocode and Running Time

# Long Hike



# Long Hike



# Long Hike



# Outline

- 1 Long Hike
- 2 Fractional Knapsack
- 3 Pseudocode and Running Time


## Fractional knapsack

**Input:** Weights  $w_1, \dots, w_n$  and values  $v_1, \dots, v_n$  of  $n$  items; capacity  $W$ .

**Output:** The maximum total value of fractions of items that fit into a bag of capacity  $W$ .

# Example

\$20



\$18



\$14





7




knapsack





# Example





## Example



# Example



# Example



# Safe move

## Lemma

There exists an optimal solution that uses as much as possible of an item with the maximal value per unit of weight.

## Proof

\$20

4

\$5/*unit*

\$18

3

\$6/*unit*


\$14

2

\$7/*unit*

## Proof

\$20



\$5/*unit*

\$18



\$6/*unit*

\$14



\$7/*unit*

\$20



\$18



total: \$38

## Proof

\$20



\$5/unit

\$18



\$6/unit

\$14




\$7/unit

$\$20/2$

$\$20/2$




\$18



total: \$38



## Proof



# Greedy Algorithm

- While knapsack is not full

# Greedy Algorithm

- While knapsack is not full
- Choose item  $i$  with maximum  $\frac{v_i}{w_i}$

# Greedy Algorithm

- While knapsack is not full
- Choose item  $i$  with maximum  $\frac{v_i}{w_i}$
- If item fits into knapsack, take all of it

# Greedy Algorithm

- While knapsack is not full
- Choose item  $i$  with maximum  $\frac{v_i}{w_i}$
- If item fits into knapsack, take all of it
- Otherwise take so much as to fill the knapsack

# Greedy Algorithm

- While knapsack is not full
- Choose item  $i$  with maximum  $\frac{v_i}{w_i}$
- If item fits into knapsack, take all of it
- Otherwise take so much as to fill the knapsack
- Return total value and amounts taken

# Outline

- 1 Long Hike
- 2 Fractional Knapsack
- 3 Pseudocode and Running Time

# Greedy Algorithm

- While knapsack is not full
- Choose item  $i$  with maximum  $\frac{v_i}{w_i}$
- If item fits into knapsack, take all of it
- Otherwise take so much as to fill the knapsack
- Return total value and amounts taken



## Knapsack( $W, w_1, v_1, \dots, w_n, v_n$ )

$A \leftarrow [0, 0, \dots, 0], V \leftarrow 0$

repeat  $n$  times:

    if  $W = 0$ :

        return  $(V, A)$

    select  $i$  with  $w_i > 0$  and  $\max \frac{v_i}{w_i}$

$a \leftarrow \min(w_i, W)$

$V \leftarrow V + a \frac{v_i}{w_i}$

$w_i \leftarrow w_i - a, A[i] \leftarrow A[i] + a, W \leftarrow W - a$

return  $(V, A)$

## Lemma

The running time of Knapsack is  $O(n^2)$ .

## Lemma

The running time of Knapsack is  $O(n^2)$ .

## Proof

- Select best item on each step is  $O(n)$

## Lemma

The running time of Knapsack is  $O(n^2)$ .

## Proof

- Select best item on each step is  $O(n)$
- Main loop is executed  $n$  times

## Lemma

The running time of Knapsack is  $O(n^2)$ .

## Proof

- Select best item on each step is  $O(n)$
- Main loop is executed  $n$  times
- Overall,  $O(n^2)$



# Optimization

- It is possible to improve asymptotics!

# Optimization

- It is possible to improve asymptotics!
- First, sort items by decreasing  $\frac{v}{w}$

Assume  $\frac{v_1}{w_1} \geq \frac{v_2}{w_2} \geq \dots \geq \frac{v_n}{w_n}$

Knapsack( $W, w_1, v_1, \dots, w_n, v_n$ )

$A \leftarrow [0, 0, \dots, 0], V \leftarrow 0$

for  $i$  from 1 to  $n$ :

    if  $W = 0$ :

        return  $(V, A)$

$a \leftarrow \min(w_i, W)$

$V \leftarrow V + a \frac{v_i}{w_i}$

$w_i \leftarrow w_i - a, A[i] \leftarrow A[i] + a, W \leftarrow W - a$

return  $(V, A)$



# Asymptotics

- Now each iteration is  $O(1)$
- Knapsack after sorting is  $O(n)$
- Sort + Knapsack is  $O(n \log n)$