LDR and STR Addressing Modes

Mode	Pseudo-code Operation *	Example				
Offset modes – the base address register is not modified						
[Rn]	EA = Rn	LDR R0, [R1]				
[Rn, #offset]	EA = Rn + offset	LDR R0, [R1, #4]				
[Rn, Rm]	EA = Rn + Rm	LDR R0, [R1, R2]				
[Rn, Rm, LSL #shift]	EA = Rn + (Rm << shift)	LDR RO, [R1, R2, LSL #2]				
[Rn, Rm, LSR #shift]	EA = Rn + (Rm >> shift)	LDR RO, [R1, R2, LSR #2]				
Pre-indexed modes – the base address register is modified before accessing memory						
[Rn, #offset]!	Rn = Rn + offset	LDR R0, [R1, #4]!				
	EA = Rn					
[Rn, Rm]!	Rn = Rn + Rm	LDR R0, [R1, R2]!				
	EA = Rn					
[Rn, Rm, LSL #shift]!	Rn = Rn + (Rm << shift)	LDR R0, [R1, R2, LSL #2]!				
	EA = Rn					
[Rn, Rm, LSR #shift]!	Rn = Rn + (Rm >> shift)	LDR R0, [R1, R2, LSR #2]!				
	EA = Rn					
	pase address register is modified after a					
[Rn], #offset	EA = Rn	LDR RO, [R1], #4				
	Rn = Rn + offset					
[Rn], Rm	EA = Rn	LDR R0, [R1], R2				
	Rn = Rn + Rm					
[Rn], Rm, LSL #shift	EA = Rn	LDR R0, [R1], R2, LSL #2				
	Rn = Rn + (Rm << shift)					
[Rn], Rm, LSR #shift	EA = Rn	LDR R0, [R1], R2, LSR #2				
	Rn = Rn + (Rm >> shift)					

^{*} EA is the *Effective Address*, which is the memory address to which the load or store operation is applied.

Note: only a subset of the above addressing modes can be used to load or store halfwords, signed-halfwords or signed-bytes. See ARM Architecture Reference Manual section A5.3.

STM and LDM – STore and LoaD Multiple

Instruction	Example			
Base register Rn is not modified (no !)				
STMmode Rn, {list}	STMIA R12, {R0-R3}	Store the contents of R0-R3 in memory at the address contained in R12		
LDMmode Rn, {list}	LDMIA R12, {R5,R7,R10}	Load R5, R7 and R10 with the contents of memory at the address contained in R12		
Base register Rn is modified (Rn!)				
STMmode Rn!, {list}	STMFD SP!, {R4-R12,R14}	Push R4-R12 and R14 on to the system stack, updating the system stack pointer		
LDMmode Rn!, {list}	LDMFD SP!, {R4-R12,R14}	Pop 10 words off the top of the system stack into R4-R12 and R14, updating the system stack pointer		

mode

STM – STore Multiple		LDM - LoaD Multiple	
Instruction	Stack-Oriented Synonym	Instruction	Stack-Oriented Synonym
STMDB (decrement before)	STMFD (full descending)	LDMIA (increment after)	LDMFD (full descending)
STMIB (increment before)	STMFA (full ascending)	LDMDA (decrement after)	LDMFA (full ascending)
STMDA (decrement after)	STMED (empty decending)	LDMIB (increment before)	LDMED (empty decending)
STMIA (increment after)	STMEA (empty ascending)	LDMDB (decrement before)	LDMEA (empty ascending)