

# Personalized Prognostic Models for Oncology: A Machine Learning Approach

David Dooling<sup>1</sup>, Angela Kim<sup>1</sup>, Barbara McAneny<sup>1</sup>, Jennifer Webster<sup>1</sup>

**1 Innovative Oncology Business Solutions, Albuquerque, NM, USA**

\* ddooling@innovativeobs.com

## Abstract

We have applied a little-known data transformation to subsets of the Surveillance, Epidemiology, and End Results (SEER) publically available data of the National Cancer Institute (NCI) to make it suitable input to standard machine learning classifiers. This transformation properly treats the right-censored data in the SEER data and the resulting Random Forest and Multi-Layer Perceptron models predict full survival curves. Treating the 6, 12, and 60 months points of the resulting survival curves as 3 binary classifiers, the 18 resulting classifiers have AUC values ranging from .765 to .885. Further evidence that the models have generalized well from the training data is provided by the extremely high levels of agreement between the random forest and neural network models predictions on the 6, 12, and 60 month binary classifiers.

## Introduction

Opportunities are emerging in many industries today to develop and deploy services that cater to individual needs and preferences. Music aficionados can create their own radio stations from Pandora [1], bibliophiles can receive book recommendations from goodreads.com [2], and Google will provide directions between any two points with warnings of delays in real-time, as well as allowing users to choose mode of transportation [3]. These individualized services leverage large databases to learn and extract information relevant to individuals. A class of techniques that transforms data into actionable information goes by the name of Machine Learning (ML) [4]. ML has recently become a popular method to answer questions and solve problems that are too complex to solve via traditional methods.

The primary objective of this study is to show how ML models can be trained using publically available data to produce personalized survival prognosis curves. The methods presented below can be applied to any type of temporal outcome data, including survival, cost, complication and toxicity data. Traditionally, cancer survival curves have been estimated using Kaplan-Meier methods [5]. Kaplan-Meier methodology also uses large datasets to make predictions, but the resulting curves are summaries for a population and not necessarily relevant or particularly accurate for any given individual. This property of Kaplan-Meier methods is exacerbated when dealing with heterogeneous populations [6]. This capability to provide individualized survival curve prognoses is a direct result of recent advances in computing power and ML algorithms. Similar methodology is becoming commonplace in many industries. These techniques are now infiltrating the healthcare industry.

The Surveillance, Epidemiology, and End Results (SEER) Program of the National Cancer Institute (NCI) program is the most recognized authoritative source of information on cancer incidence and survival in the United States and is the primary data source for this study. SEER currently collects and publishes cancer incidence and survival data from population-based cancer registries covering approximately 28 percent of the US population. The SEER Program has been collecting data since 1973. Intuitively researchers feel confident that this data will surface information crucial to patients and providers, including the relationships between the collected data (demographics, staging, treatment and disease characteristics) and survival outcomes. Though these relationships evade capture by traditional methods, it is possible to surface them with two machine learning techniques known as random forests and neural networks.

One challenge of the SEER data that is shared by many survival datasets is the inclusion of censored data. Observations are labeled censored when the survival information is incomplete. The SEER data contains the number of months each patient survived, as well as the vital status. Traditional methods to deal effectively with this kind of "right-censored data" include Kaplan-Meier curves and Cox Proportional Hazard models [5].

Previous work applying machine learning methods to subsets of the SEER data include creative attempts to deal with the problems presented by right-censored data. Shin et al. [8] use semi-supervised learning techniques to predict 5 year survival, essentially imputing values for SEER records where the survival information is censored at a value less than 5 years. Zolbanin et al. [9] remove all records corresponding to patients who were living but censored within the 60 month study window. This treatment biases the predictions and leads to overly pessimistic predictions.

Previous work applying machine learning methods based on decision trees to survival data in general have a long history, starting with Gordon et al. [10]. A summary of more recent developments concerning survival trees is provided by Bou-Hamad et al. [11]. These methods focus on altering the splitting criteria used in decision tree growth to account for the censoring, and use Kaplan-Meier methods at the resulting nodes for prediction purposes. These methods do not generalize to non-tree-based machine learning algorithms, though Ishwaran et al. have extended the methodology to random survival forests, ensembles of survival trees [12].

Instead of modifying existing learning algorithms, we focus attention on the input data. This approach allows us to take advantage of powerful and rapidly improving machine learning derived discrete classifiers without modification. The essential idea is to recast the problem as a discrete classification problem (predicting the likelihood that a patient is alive in any given month) instead of a regression problem (predicting survival months). Treating months after diagnosis as a discrete feature, the SEER data (or any other right-censored data) can be transformed to make predictions for the hazard function (the probability of dying in the next month, given that the patient has not yet died). The survival function can then be derived from the hazard function.

## Materials and Methods

### Data preparation and preprocessing

For this study we use the publically available 1973-2012 SEER incidence data files corresponding to colon, breast and lung cancer. These files are listed in subsection Raw SEER datafiles in the Supporting Information Appendix. A great deal of data munging is necessary before using these SEER incidence files as input into machine learning algorithms. The input data was recoded and reshaped to comply with the requirements

of the analysis program. Details are included in subsection Data Preparation Details in the Supporting Information Appendix. Briefly, we transformed the location variables that are given as categorical State and County code pairs to (latitude, longitude, elevation) triples using the Google Maps API, as well as one-hot encoded all categorical variables.

In the SEER data, there is a record for each primary tumor. If multiple records exist for a given patient, only the first chronologically was included. The full set of conditions defining the subsets of the SEER data used in this study is included in the appendix Supporting Information.

Before applying machine learning models trained with these datasets, we describe in detail a method that takes full advantage of all the data, including the right-censored data, and which involves a simple and intuitive transformation, culminating in the full set of features and target variable listed in the appendix Supporting Information.

## Transformation of Censored Data for Machine Learning

In this section we describe an intuitive way to transform right-censored data appropriately so that it may be used as input to machine learning algorithms that learn the hazard function. The full details of this transformation, and a large inspiration for this study, can be found in this blog post [19].

The key observation is to note that the hazard function at any given time point can be directly learned via standard machine learning methods. It can be rewritten as

$$\lambda(\mathbf{X}_i, t_j) = P(Y = t_j | Y \geq t_j, \mathbf{X}_i), \quad (1)$$

the probability that, if someone has survived up until month  $t_j$ , they will die in that month.  $j$  runs from 0 to 107, and  $\mathbf{X}_i$  corresponds to the single row corresponding to patient  $i$  in the original untransformed dataset. 107 months was the maximum value of survival months in all three of the cancer datasets, and is a consequence of the data subsets chosen for this study.  $Y$  represents the true, uncensored number of survival months of the patient. What is actually provided in the SEER data is the related variable `SURVIVAL MONTHS`  $T$  (how long each subject was in the study), and whether they exited by dying or being censored ( $D$ ), `VITAL STATUS RECODE`.  $D$  is a Boolean variable, so  $D = 1$  if  $T = Y$ , and  $D = 0$  if  $T < Y$ .

It follows directly from equation 1 that

$$P(Y = t_j | \mathbf{X}_i) = \lambda(\mathbf{X}_i, t_j) \prod_{k=1}^{j-1} (1 - \lambda(\mathbf{X}_i, t_k)) \quad (2)$$

Knowing  $P(Y = t_j | \mathbf{X}_i)$  for all  $t_j$  gives the full probability distribution of dying at time  $Y$  [19]. The survival function is then readily derived from this distribution as

$$S(\mathbf{X}_i, t_k) = 1 - CDF(\mathbf{X}_i, t_k) \quad (3)$$

where  $CDF(\mathbf{X}_i, t_k) = \sum_{j=1}^k P(Y = t_j | \mathbf{X}_i)$  is the cumulative density function corresponding to the probability mass function in equation [20].

Treating  $T$  as just another covariate is the key to the transformation. Each datapoint in the hidden classification problem is the combination of an  $\mathbf{X}_i$  in the original dataset plus some month  $t_j$ , and the classification problem is "did point  $\mathbf{X}_i$  die in month  $t_j$ ." We will call this new variable  $D_{ij}$  (`newtarget`). We can transform our original data set into a new one, with one row for each month that each  $\mathbf{X}_i$  is in the sample; train a standard classifier on this new dataset with  $D_{ij}$  as the target, and derive a survival model from the original dataset. Pseudocode for this transformation is found in the appendix Supporting Information.

Explicit examples will help make this transformation clear. The untransformed records represented in Table (1) are transformed to the multiple records shown in Table (2).

Table 1. Example of four columns in the untransformed dataset.

	cs_tumor_size	year_of_birth	survival_months	vital_status_recode_Death
newindex				
205	60	1951	3	1
306	40	1950	3	0

Table 2. Example of four columns in the transformed dataset.

	cs_tumor_size	year_of_birth	month	newtarget
newindex				
205	60	1951	0	0
205	60	1951	1	0
205	60	1951	2	0
205	60	1951	3	1
306	40	1950	0	0
306	40	1950	1	0
306	40	1950	2	0
306	40	1950	3	0

One obvious side effect of this transformation is that it increases the length of the dataset. For this study, the original, untransformed colon cancer DataFrame has shape (113072, 103), and the total transformed colon cancer DataFrame has shape (4165251, 103). Similarly, the original, untransformed lung cancer DataFrame has shape (177089, 115), and the total transformed lung cancer DataFrame has shape (3079931, 115). The biggest increase in dataset size occurred with the breast cancer data, which is a consequence of the relatively high survival rates in breast cancer. A subject who is censored with a recorded survival months of 48 will contribute 49 rows to the transformed dataset. The original, untransformed breast cancer DataFrame has shape (329949, 67), and the total transformed breast cancer DataFrame has shape (15085711, 67). Training machine learning algorithms on such large datasets, even after splitting into training and testing sets described below, requires large RAM. All computations for this study were performed on a Dell XPS 8700 Desktop with 32GB of RAM. The training times involved in the classification task of learning the hazard function  $\lambda(\mathbf{X}_i, t_j)$  for the chosen model parameters were on the order of a few hours or less, but the evaluation of the AUC performance metrics associated with the 6, 12, and 60 month binary survival classifiers took more than 24 hours for the random forest models. These AUC performance metrics provided the feedback mechanism to adjust the model hyperparameters.

## Training and Test Partitions

The datasets were split into training and test sets at the patient level, with 97% of patients assigned to the training set, and the remaining 3% of patients assigned to the test set. All records corresponding to a given patient were assigned exclusively to either the training or test set. This choice of an unusually low percentage of data in the test set was made for two reasons. The performance metrics described in sec Performance

Metrics for the given choice of training and test partition of the data took well over 24 hours for the random forest models; choosing the convention 80/20 split would have resulted in a prohibitively long times for the training-performance metric feedback loop. Because of the large size of the data set, this choice of training and test partition still leads to an acceptably large test set for the purposes of model evaluation. An additional characteristic of this transformed data that requires careful treatment involves balancing. The transformation results in many new records with the target variable `newtarget == 0`. The training and test sets must be chosen such that the ratio of the number of records with `newtarget == 0` to that of the number of records with `newtarget == 1` is the same in the training and test datasets. This ratio turns out to be  $\approx 396$  for the breast cancer data,  $\approx 99$  for the colon cancer data, and  $\approx 22.75$  for the lung cancer data. The shapes of the training and testing datasets for breast cancer used in this study are (14936862, 67) and (148849, 67), respectively. For lung cancer, the corresponding datasets have shapes (2988768, 115) and (91163, 115). Finally, for colon cancer the partition into training and test datasets of the transformed data have the shapes (3958008, 103) and (207243, 103). Multiple rows correspond to the same test patient in these datasets. The colon cancer test dataset represents 5654 distinct subjects; the breast cancer test dataset represents 3300 distinct subjects; and the lung test dataset contains data for 5313 distinct subjects.

The models described below are trained to learn the values of `newtarget`, which is a binary variable: a value of '0' indicating that the subject is still alive at the given month, while a value of '1' indicates that the patient died at that particular value of `months`. The random forests and neural networks described below are binary classifiers with the target `newtarget`. Both the random forests and neural networks are capable of not only performing strict class prediction, i.e. predicting whether `newtarget` is '0' or '1', but are also able to predict the *probability* of `newtarget` being '0' or '1', and are thus able to learn the hazard function.

## Prediction Models

With the datasets transformed as described above, we are now able to use them to train and evaluate machine learning classifiers. The classifier models described in this section are learning the hazard function: given all of the data given in the appendix Supporting Information for each cancer type, which includes the field `months` (the months after diagnosis), the models predict the target variable `newtarget`, which is a binary class label equal to 1 if the subject died in that month and 0 otherwise.

From the hazard function for each unique patient, we can construct the survival function as in Equation 3. The relevant python code is available at the github repository containing supplemental material for this study [18]. For each subject  $i$ , all input data minus `months` and `newtarget` is represented by  $\mathbf{X}_i$ . After the classifier models have trained with target `newtarget` on the (very large) training set, each subject's survival function is computed in the corresponding (much smaller) test set. These functions are computed by using the model to predict  $\lambda(\mathbf{X}_i, t_j)$  for  $j$  running from 0 to 107 months, and  $\mathbf{X}_i$  corresponds to the single row corresponding to subject  $i$  in the original untransformed dataset. 107 months was the maximum value of survival months in all three of the cancer datasets, and is a consequence of the data subsets chosen for this study.

**Decision Trees and Random Forests** *Decision tree* classifiers are attractive models because they can be interpreted easily. Like the name decision tree suggests, we can think of this model as breaking down our data by making decisions based on asking

a series of questions. Based on the features in our training set, the decision tree model learns a series of questions to infer the class labels of the samples.

*Random forests* have gained huge popularity in applications of machine learning during the last decade due to their good classification performance, scalability, and ease of use. Intuitively, a random forest can be considered as an *ensemble of decision trees*. The idea behind ensemble learning is to combine *weak learners* to build a more robust model, a *strong learner*, that has a better generalization error and is less susceptible to overfitting.

The goal behind *ensemble methods* is to combine different classifiers into a meta-classifier that has a better generalization performance than each individual classifier alone. For example, assuming that we collected predictions from 10 experts, ensemble methods would allow us to strategically combine these predictions by the 10 experts to come up with a prediction that is more accurate and robust than the predictions by each individual expert. The individual decision trees that make an ensemble are called base learners, and as long as the error rate of each base learner is less than .50, the combined random forest will benefit from the affects of combining predictions to achieve a far greater accuracy.


A big advantage of random forests is that honing in on suitable hyperparameter values (the number of trees in the forest, the depth of each decision tree, the specific measure of information gain used to choose the node splitting, etc) is not very difficult. The ensemble method is robust to noise from the individual decision trees, which helps to prevent overfitting (memorizing the training dataset targets instead of generalizing from learned rules to perform successfully on unseen data). The only parameter that has a clearly noticeable effect on performance is the number of trees to include in the forest; in general, the more trees the better the performance, but there is a price to pay in terms of computational cost. The number of trees for the forests trained in this study was relatively small, 20 trees for breast cancer and 25 for both the lung and colon cancer models. We have used the Python scikit-learn implementation of the Random Forest machine learning classifier [24]. Random Forests are frequent winners of the Kaggle machine learning competitions [25]. The model parameters for each cancer type are given in the appendix Supporting Information.

**Multi-Layer Perceptron Neural Networks** Neural networks are a biologically-inspired programming paradigm that enable computers to learn from observational data [26]. Neural networks are a hot topic not only in academic research, but also in big technology companies such as Facebook, Microsoft, and Google who invest heavily in artificial neural networks and deep learning research. As of today, complex neural networks powered by deep learning algorithms are considered to be the state-of-the-art when it comes to complex problem solving such as image and voice recognition. In addition, the pharmaceutical industry recently started to use deep learning techniques for drug discovery and toxicity prediction, and research has shown that these novel techniques substantially exceed the performance of traditional methods for virtual screening [27].

We have used the Multi-Layer Perceptron Neural Network (MLP neural network) implementation Keras developed at MIT. Keras was initially developed as part of the research effort of project ONEIROS (Open-ended Neuro-Electronic Intelligent Robot Operating System) [28]. Keras is a minimalist, highly modular neural networks library, written in Python and capable of running on top of either TensorFlow or Theano. The model architecture for each cancer type are given in the appendix Supporting Information.

## Results

In order to evaluate the performance of the models, we first construct three binary classifiers corresponding to whether or not a subject survived 6, 12, or 60 months after diagnosis. We iterate over all distinct patient indices in the test set, compute the predicted survival function, and capture the values corresponding to 6, 12, and 60 months. If the survival function evaluated at 6 months is greater than or equal to .5 for a given patient, then the 6 months binary classifier predicts that that patient will be alive 6 months after diagnosis. Similarly, if the survival function evaluated at 12 months is less than .5, then the 12 months binary classifier predicts that that subject will be dead 12 months after diagnosis. Figure (1) illustrates the method; in this case the 6-month and 12-month classifiers predict survival, while the 60-month classifier predicts death.



**Figure 1.** Example of the construction of the binary classifiers for 6, 12, and 60 months survival. A patient's hazard curve  $\lambda(\mathbf{X}_i, t_j)$  is predicted by the model for times out to 107 months. The survival curve is then readily computed as in Equation (3). For this example, the 6-month and 12-month classifiers predict survival, while the 60-month classifier predicts death.

Because of censoring it is necessary to apply some Boolean filters to the data in order to correctly assess the resulting classifiers. To construct AUC curves for the 6 month classifier, we restrict ourselves to considering subjects in the test data where either of the following mutually exclusive conditions holds:

- `survival_months >= 6 AND vital_status_recode == 0`
- `vital_status_recode == 1`

That is, we restrict ourselves to subsets of the data where we know for certain whether or not the subject survived at least 6 months. Similarly for the 12 and 60 months survival classifiers.

**Survival Curve Error Estimates** The following bootstrap method was used to calculate the upper and lower bounds corresponding to 95% confidence intervals. From



equation 3, we can obtain the cumulative distribution function (CDF) associated with each individual survival curve. We then sample from this CDF in a way that reflects the underlying data used to produce the model. The training data used to create the model has an underlying distribution of survival months. In the transformed training dataset, each subject contributes as many rows as the number of survival months plus one (patients with zero survival months still contribute one row to the training data). A patient that survived 50 months contributes 51 "points" to the training of the model. If all patients lived out to 107 months, the model would contain less uncertainty. This observation leads to the following algorithm for determining the error estimates to the predicted survival curves:

- compute the CDF associated with the survival curve
- use the underlying training data CDF of survival months to choose the number of points to draw from the survival curve CDF, and compute a new survival curve
- Repeat the previous step 10,000 times and collect the curves into a list. Changing the number of curves affects how smooth the upper and lower bounds are, but does not affect the interval size between for each month.
- extract for each month from the list of curves the .975 and .025 percentiles to record the values for the upper and lower curves

The process is somewhat analogous to the following hypothetical situation. Imagine a patient going to an expert to get a survival prognosis. After collecting data on the patient and keeping records, the expert predicts the central, single survival curve. The patient then seeks multiple "second opinions." These second opinions are generated not from independent examinations of the patient, but by outside experts sampling from the data already collected by the first expert. Then the predictions of 95% of these 10,000 experts all fall within the band determined by the upper and lower curves.

## Performance Metrics

**AUC scores** The AUC scores for each of the 18 different binary classifiers are listed in Table (3). The lowest AUC in Table 3 is .765, corresponding to the lung neural network model predictions for 6 months survival, while the highest AUC in Table 3 is .885, corresponding to the breast random forest model predictions for 12 months survival.

**Table 3. AUC values for the Random Forest and Neural Networks model binary classifiers derived from the full survival curve predictions; see text for details. The number of subjects that were used in the calculation of a given AUC score are given in parenthesis after the score.**

Model	6 Months AUC	12 Months AUC	60 Months AUC
Breast RF	.846 (3035)	.885 (2797)	.844 (1392)
Breast NN	.855 (3035)	.867 (2797)	.836 (1392)
Colon RF	.804 (5281)	.806 (5003)	.828 (3232)
Colon NN	.797 (5281)	.804 (5003)	.841 (3232)
Lung RF	.772 (5019)	.796 (4860)	.874 (4143)
Lung NN	.765 (5019)	.796 (4860)	.875 (4143)

**Model Agreement** An additional means of validating the predictions of these models is by comparing their predictions to each other for the same set of input data. Table 4 shows the strong agreement between the random forest and neural network classifiers for each cancer type. Python code showing how the values in Table 4 are



computed is available in the files `NewPatientBreastCF.html` ,  
`NewPatientColonCF.html` , and `NewPatientLung.html` in the GitHub repository  
containing supplemental material for this study [18]. Table 4 is computed as follows.  
For each cancer type (breast,colon, and lung), do the following:

- use the corresponding Random Forest and Neural Network models to compute the survival curves for all of the test subjects
- extract the values of the survival curve evaluated for 6, 12, and 60 months for both models
- if both models predict less than .5 or both models predict greater than or equal to .5, that counts as agreement
- otherwise, the models disagree

The high level of agreement between two models lends confidence to the notion that they have both learned from the training data and are generalizing well. Figures (3, 2, 4) show box plots of the value of the random forest prediction subtracted from the neural network prediction. We emphasize that when evaluating the model agreement, we put no restrictions on the distinct subjects in the respective test datasets; we are confronting the models against each other, not some known ground truth as in the AUC performance metric calculations. The number of distinct subjects in all three of the colon cancer survival binary classifiers (6, 12, and 60 month survival) was 5654; for lung cancer the number of subjects entering into the calculation of Table (4) was 5313; and for breast cancer it was 3300. Exploring the outlier cases, for example where the difference between the neural network and random forest predictions for 5 year survival in breast cancer exceed .4, can reveal patterns indicating where the models need careful interpretation. The distribution of year of birth for patients where the neural network model prediction for 5 year survival exceeded the random forest prediction by more than .4 has a mode around 1930, a good 20 years earlier than the distribution for the remaining patients. The outliers in Figs. (3, 2, 4) corresponding to patients whose distributions for certain features are also outliers compared to the rest of the population used in training.

**Table 4. Percentage agreement for the Random Forest and Neural Network classifiers for 6, 12, and 60 month survival predictions on the test data for each cancer type.**


Cancer Type	% agreement 6 months	% agreement 12 months	% agreement 60 months
Colon	.981	.971	.915
Breast	.994	.984	.938
Lung	.861	.883	.900

## Survival Curve Prediction Apps


The six models have their full hyperparameter and architecture presented in the appendix section Supporting Information. Python code for all six model training and evaluation is available at the github repository containing supplemental material for this study [18].

Using the popular Flask microframework for web applications [29], we have made web applications corresponding to the six models. The list of web applications below will allow readers to freely experiment with the models.


1. breast cancer



**Figure 2.** Box plots showing the distributions of the signed difference between the MLP model's prediction for the probability of surviving 6 months and the Random Forest model's prediction of the same quantity for breast cancer. The plot shows the same quantity for the 12 and 60 months classifiers. It is apparent from the figures that the outliers are due to the neural network models predicting higher survival probabilities than the random forest for some few cases. These differences were evaluated for the 3300 test patients in the breast cancer data.



**Figure 3.** Box plots showing the distributions of the signed difference between the MLP model's prediction for the probability of surviving 6 months and the Random Forest model's prediction of the same quantity for colon cancer. The plot shows the same quantity for the 12 and 60 months classifiers. It is apparent from the figures that the outliers are due to the neural network models predicting higher survival probabilities than the random forest for some few cases. These differences were evaluated for the 5654 test patients in the colon cancer data.



**Figure 4.** Box plots showing the distributions of the signed difference between the MLP model's prediction for the probability of surviving 6 months and the Random Forest model's prediction of the same quantity for lung cancer. The plot shows the same quantity for the 12 and 60 months classifiers. These differences were evaluated for the 5313 test patients in the lung cancer data. The Interquartile Ranges for lung cancer are visibly larger than those for breast cancer and colon cancer shown in fig 2 and fig 3.

- (a) random forest: 334  
<https://github.com/doolingdavid/breast-cancer-rf-errors.git> 335
- (b) neural network: 336  
<https://github.com/doolingdavid/breast-cancer-nn-errors.git> 337
2. lung cancer 338
- (a) random forest: 339  
<https://github.com/doolingdavid/lung-cancer-rf-errors.git> 340
- (b) neural network: 341  
<https://github.com/doolingdavid/lung-cancer-nn-errors.git> 342
3. colon cancer 343
- (a) random forest: 344  
<https://github.com/doolingdavid/colon-cancer-rf-errors.git> 345
- (b) neural network: 346  
<https://github.com/doolingdavid/colon-cancer-nn-errors.git> 347

After downloading the .zip file associate with one of the above web applications, and assuming python is installed on your system, you can launch the application by running 348 349

```
>python hello.py 350
```

and pointing the browser to the local server: <http://127.0.0.1:5000> , or 351

<http://localhost:5000> . 352

These machine learning models are used to predict survival curves for a given set of 353 input data. The resulting survival curves predict the probability that a patient with the 354 given input data will survive at least up to month  $x$ . 355

For example, using the Colon Cancer neural network app, and inputting the values listed in Table (5) results in the survival curve depicted in Figure (5); the predicted probabilities of living at least 6, 12, and 60 months are .89, .83, and .50, respectively.

**Table 5. Example input data to the Colon Cancer neural network app**  
<https://github.com/doolingdavid/colon-cancer-nn-errors.git>.

Variable	Value
What is the tumor size (mm)	300
What is the patient's address?	boston massachusetts
Grade	moderately differentiated
Histology	adenomas and adenocarcinomas
Laterality	not a paired site
Marital Status at Dx	Single, never married
Month of Diagnosis	Jan
How many primaries	1
Race_ethnicity	White
seer_historic_stage_a	Regional
Gender	Male
spanish_hispanic_origin	Non-spanish/Non-hispanic
Year of Birth	1940
Year of Diagnosis	2010

Changing the data in Table 5 so that the address field is changed from Boston, Massachusetts to Denver, Colorado but keeping all other variables are unchanged results in the predicted probabilities of living at least 6, 12, and 60 months: .945, .902, .665. Behind the scenes, the apps use the input to the address field to make a call to the Google Maps API to convert the address into a latitude, longitude and elevation. These probabilities are noticeably higher and reflect the documented effects of both longitude and elevation on cancer treatment and prognosis in the United States [30].

A similar example of how changing the inputs to the models affects the predicted survival curves in interesting ways can be seen with the random forest model for lung cancer. Changing the data in Table 6 by toggling between the male/female, and married/single four possible permutations results in the following prediction probabilities for 6, 12, and 60 month survival:

- male/married: .53, .27, .01
- male/single: .35, .18, .009
- female/married: .55, .31, .01
- female/single: .50, .27, .01

Inputting the same combinations of data into the lung cancer neural network app <https://github.com/doolingdavid/lung-cancer-nn-errors.git> yields the following probabilities:

- male/married: .42, .24, .04
- male/single: .40, .22, .03
- female/married: .44, .26, .04
- female/single: .42, .24, .04


It is interesting to note that both the random forest and neural network lung cancer models predict greater 6 month survival rates for married people, with a slightly greater benefit for males than females. The effect is greater in the random forest model, but is also visible in the neural network model.

# Colon Cancer Survival Curve Prediction

## Prediction:

1. Probability of Surviving 6 months is **0.897**
2. Probability of Surviving 12 months is **0.831**
3. Probability of Surviving 60 months is **0.504**

## Predicted Survival Curve from Model



**Figure 5.** Colon Cancer Survival Curve predicted from the data in Table (5) using the neural network web app  
<https://github.com/doolingdavid/colon-cancer-nn-errors.git>.

## Discussion

The purpose of this study has been twofold; to develop a general methodology of data transformation to survival data with censored observations so that machine learning algorithms can be applied and to help further the cause of PPPM medicine by developing models of personalized survival curve prognosis. To help further refine the methodology, we would like to apply it to different survival datasets [31], not necessarily within the healthcare domain. In particular, the methods presented in this paper do not take into account time varying features. For example, the `cs.tumor_size` variable that has been a part of this study is kept fixed at the value measured at diagnosis for all records corresponding to a given subject. Clearly, the actual tumor size varies along with time and a sophisticated model can be developed to take this into account, given available datasets.

The SEER database has been linked with claims data in the SEER-Medicare Linked Database [32]. This linkage allows for the identification of additional clinical data for each record in the SEER database and allows for an enrichment of the models presented

**Table 6. Example input data to the Lung Cancer random forest app**  
<https://github.com/doolingdavid/lung-cancer-rf-errors.git>.

Variable	Value
What is the tumor size (mm)	500
What is the patient's address?	newark new jersey
Grade	well differentiated
Histology	acinar cell neoplasms
Laterality	bilateral involvement, lateral origin unknown; stated to be single primary
Marital Status at Dx	Married including common law
Month of Diagnosis	Jan
How many primaries	1
Race_ethnicity	White
seer_historic_stage_a	Distant
Gender	Female
spanish_hispanic_origin	Non-spanish/Non-hispanic
Year of Birth	1970
Year of Diagnosis	2011

in this study, and is an avenue for further investigation.

An additional avenue of research concerns the broad concept of causality. As demonstrated in section Survival Curve Prediction Apps, there appears to be a correlation between marital status and survival prognosis. Does this mean that if a single person in Boston, Massachusetts is diagnosed with cancer, that they should immediately get married and move to Denver? Of course not. But personal discussions with providers has confirmed for one of the authors (D.D.) that married males tend to be much more diligent in following instructions than their single counterparts. What appears to be in effect is that some of the SEER data is providing an identifiable signature of underlying causes not directly represented by the data. Latent variables not directly seen in the data are still providing echos of patterns in the data and the sheer volume allows us to see glimpses of these patterns. Marital status is in some instances a surrogate for the presence of a strong social structure and support group surrounding a patient, which presence presumably leads to more desirable survival prognosis. The daunting and exciting task of teasing out actual causality relationships within machine learning contexts has been pioneered by Judea Pearl of the University of California, Los Angeles <sup>1</sup> and seems particularly relevant and applicable to censored survival data. Combining the methodology presented in this study with that of the pioneering work of Judea Pearl on causality will be a fruitful avenue for future research.

## Supporting Information

### Raw SEER datafiles

- incidence\yr1973\_2012.seer9\COLRECT.txt
- incidence\yr1973\_2012.seer9\BREAST.txt
- incidence\yr1973\_2012.seer9\RESPIR.txt
- incidence\yr1992\_2012.sj\_la\_rg\_ak\COLRECT.txt
- incidence\yr1992\_2012.sj\_la\_rg\_ak\BREAST.txt

<sup>1</sup>Judea Pearl homepage at the University of California, Los Angeles, [http://bayes.cs.ucla.edu/jp\\_home.html](http://bayes.cs.ucla.edu/jp_home.html), accessed 11 Jan 2016.

- incidence\yr1992\_2012.sj\_la\_rg\_ak\RESPIR.txt 427
- incidence\yr2000\_2012.ca\_ky\_lo\_nj\_ga\COLRECT.txt 428
- incidence\yr2000\_2012.ca\_ky\_lo\_nj\_ga\BREAST.txt 429
- incidence\yr2000\_2012.ca\_ky\_lo\_nj\_ga\RESPIR.txt 430
- incidence\yr2005.lo\_2nd\_half\COLRECT.txt 431
- incidence\yr2005.lo\_2nd\_half\BREAST.txt 432
- incidence\yr2005.lo\_2nd\_half\RESPIR.txt 433

## Data Preparation Details 434

A preprocessing step common to each of the three cancer types studied involves the SEER STATE-COUNTY RECODE variable. The STATE-COUNTY RECODE field is a state-county combination where the first two characters represent the state FIPS code and the last three digits represent the FIPS county code. The FIPS code is a five-digit Federal Information Processing Standard (FIPS) code which uniquely identifies counties and county equivalents in the United States, certain U.S. possessions, and certain freely associated states. This particular field illustrates an important characteristic of machine learning, that is, the difference between *categorical features* and *numeric features*. All input into a machine learning algorithm must be numeric, but real numbers carry with them the usually extremely useful property known as the well-ordering property. Machine learning algorithms use the well-ordering property of the real numbers to learn. But if one is tasked with encoding a categorical feature into suitable numeric format for machine learning, it is necessary to do so in a way that removes the well-ordering property. Categorical variables are commonly encoded using one-hot encoding, in which the explanatory variable is encoded using one binary feature for each of the variable's possible values [14]. 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450

One-hot encoding needs to be applied to all of the nominal categorical variables in the SEER data that we wish to include in our predictive models. In particular, in order to include the geophgraphical information contained in the SEER categorical variable STATE-COUNTY RECODE , it becomes necessary to create a new feature variable for each of the distinct (state,county) pairs in the data. In the United States, there are approximately 3,000 counties. Clearly, transforming the STATE-COUNTY RECODE data representation into distinct (state\_county) columns will explode the dataset to become wider than is optimal for machine learning. Adding extra columns to your dataset, making it wider, requires more data rows (making it taller) in order for machine learning algorithms to effectively learn [14]. Because one-hot coding STATE-COUNTY RECODE would cause such drastic shape changes in our data, we wish to avoid doing so. Fortunately, this variable, though given as a categorical variable, is actually a recode for three ordinal variables. There is an ordering among the (state\_county) columns, namely longitude, latitude, and elevation. We can transform the data in STATE-COUNTY RECODE into three new numerical columns: `lat` , `lng` , and `elevation` . 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466

For example, Table (7) shows how five entries of STATE-COUNTY RECODE corresponding to counties within New Mexico can be represented by the `elevation` , `lat` , and `lng` features. 467 468 469

It is a simple exercise to construct the full lookup table from the SEER STATE-COUNTY RECODE variable to the corresponding three values `elevation` , `lat` , and `lng` . We use the publically available datafile from the United States Census Bureau [15] to map the state FIPS and county FIPS codes to query strings like those in the `address` field in Table (7). It is then possible to programmatically query the Google Maps Geocoding API for the latitude and longitude [16], and the Google Maps Elevation API for the corresponding elevation [17]. An added benefit of this shift from 470 471 472 473 474 475 476



Table 7. Example of the transformation of STATE-COUNTY RECODE to elevation, lat, and lng.

STATE-COUNTY RECODE	address	elevation	lat	lng
35001	Bernalillo+county+NM	5207.579772	35.017785	-106.629130
35003	Catron+county+NM	8089.242628	34.151517	-108.427605
35005	Chaves+county+NM	3559.931671	33.475739	-104.472330
35006	Cibola+county+NM	6443.415570	35.094756	-107.858387
35007	Colfax+county+NM	6147.749089	36.579976	-104.472330

the single categorical variable `STATE-COUNTY RECODE` to the three continuous numerical variables `lat`, `lng`, and `elevation` is that input into the web applications described later are not restricted to the states and counties covered in the SEER registries; in fact, the input to the models can be any address you would enter into Google Maps and calls to the Google Maps Geocoding API and the Google Maps Elevation API provide the conversion from the address string to the input variables `lat`, `lng`, and `elevation`. The full lookup table analogous to Table (7) is available from a GitHub repository containing supplemental information for this study [18].

## Data Subsets

The four COLRECT.txt files were imported into a pandas DataFrame object. This data was then filtered according to the conditions in Table (8). The RESPIR.txt and BREAST.txt files were imported into separate dataframes in similar fashion and filtered according to the conditions in Table (9) and Table (10), respectively. The SEER variable `CS TUMOR SIZE` records the tumor size in millimeters if known. But if not known, `CS TUMOR SIZE` is given as '999', to indicate that the tumor size is "Unknown; size not stated; not stated in pateint record." In this study, we discard those records, as indicated in Tables (10, 8, 9).

Table 8. Filters applied to the Colon Cancer data.

Column	Filter
SEQUENCE NUMBER-CENTRAL	≠ "Unspecified"
AGE AT DIAGNOSIS	≠ "Unknown age"
BIRTHDATE-YEAR	≠ "Unknown year of birth"
YEAR OF DIAGNOSIS	≥ 2004
SURVIVAL MONTHS FLAG	= "1"
CS TUMOR SIZE EXT/EVAL	≠ ""
CS TUMOR SIZE	≠ 999
SEER RECORD NUMBER	= 1
PRIMARY SITE	= "LARGE INTESTINE, (EXCL. APPENDIX)"
SEQUENCE NUMBER-CENTRAL	= 0

The following categorical features were one-hot encoded for each of the three datasets:

- SEX,
- MARITAL STATUS AT DX,
- RACE/ETHNICITY,

Table 9. Filters applied to the Lung Cancer data.

Column	Filter
SEQUENCE NUMBER-CENTRAL	≠ "Unspecified"
AGE AT DIAGNOSIS	≠ "Unknown age"
BIRTHDATE-YEAR	≠ "Unknown year of birth"
YEAR OF DIAGNOSIS	≥ 2004
SURVIVAL MONTHS FLAG	= "1"
CS TUMOR SIZE EXT/EVAL	≠ ""
CS TUMOR SIZE	≠ 999
SEER RECORD NUMBER	= 1
PRIMARY SITE	= "LUNG & BRONCHUS"
SEQUENCE NUMBER-CENTRAL	= 0

Table 10. Filters applied to the Breast Cancer data.

Column	Filter
SEQUENCE NUMBER-CENTRAL	≠ "Unspecified"
AGE AT DIAGNOSIS	≠ "Unknown age"
BIRTHDATE-YEAR	≠ "Unknown year of birth"
YEAR OF DIAGNOSIS	≥ 2004
SURVIVAL MONTHS FLAG	= "1"
CS TUMOR SIZE EXT/EVAL	≠ " "
CS TUMOR SIZE	≠ 999
SEER RECORD NUMBER	= 1
SEQUENCE NUMBER-CENTRAL	= 0

- SPANISH/HISPANIC ORIGIN , 499
  - GRADE , 500
  - PRIMARY SITE , 501
  - LATERALITY , 502
  - SEER HISTORIC STAGE A , 503
  - HISTOLOGY RECODE--BROAD GROUPINGS , 504
  - MONTH OF DIAGNOSIS , 505
  - VITAL STATUS RECODE , 506

and the STATE-COUNTY RECODE variable was dropped and replaced with the elevation , lat , and lng variables for all three datasets as illustrated in Table (7). 507 508

## Colon Cancer Feature Selection 509

The feature set used as input into both the Random Forest and Neural Network models, 510 after the transformation described in section Transformation of Censored Data for 511 Machine Learning is given below and also available in full detail in the file 512 NewPatientColonML.html . 513

- cs\_tumor\_size 514
  - elevation 515

• grade_cell type not determined	516
• grade_moderately differentiated	517
• grade_poorly differentiated	518
• grade_undifferentiated; anaplastic	519
• grade_well differentiated	520
• histology_recode_broad_groupings_acinar cell neoplasms	521
• histology_recode_broad_groupings_adenomas and adenocarcinomas	522
• histology_recode_broad_groupings_blood vessel tumors	523
• histology_recode_broad_groupings_complex epithelial neoplasms	524
• histology_recode_broad_groupings_complex mixed and stromal neoplasms	525
• histology_recode_broad_groupings_cystic, mucinous and serous neoplasms	526
• histology_recode_broad_groupings_ductal and lobular neoplasms	527
• histology_recode_broad_groupings_epithelial neoplasms, NOS	528
• histology_recode_broad_groupings_fibromatous neoplasms	529
• histology_recode_broad_groupings_germ cell neoplasms	530
• histology_recode_broad_groupings_lipomatous neoplasms	531
• histology_recode_broad_groupings_miscellaneous bone tumors	532
• histology_recode_broad_groupings_myomatous neoplasms	533
• histology_recode_broad_groupings_neuroepitheliomatous neoplasms	534
• histology_recode_broad_groupings_nevi and melanomas	535
• histology_recode_broad_groupings_paragangliomas and glomus tumors	536
• histology_recode_broad_groupings_soft tissue tumors and sarcomas, NOS	537
• histology_recode_broad_groupings_squamous cell neoplasms	538
• histology_recode_broad_groupings_synovial-like neoplasms	539
• histology_recode_broad_groupings_transistional cell papillomas and carcinomas	540
• histology_recode_broad_groupings_unspecified neoplasms	541
• lat	542
• laterality_Left: origin of primary	543
• laterality_Not a paired site	544
• laterality_Only one side involved, right or left origin unspecified	545
• laterality_Paired site, but no information concerning laterality; midline tumor	546
• laterality_Right: origin of primary	547
• lng	548
• marital_status_at_dx_Divorced	549
• marital_status_at_dx_Married (including common law)	550
• marital_status_at_dx_Separated	551
• marital_status_at_dx_Single (never married)	552
• marital_status_at_dx_Unknown	553
• marital_status_at_dx_Unmarried or domestic partner	554
• marital_status_at_dx_Widowed	555
• month_of_diagnosis_Apr	556
• month_of_diagnosis_Aug	557
• month_of_diagnosis_Dec	558
• month_of_diagnosis_Feb	559
• month_of_diagnosis_Jan	560
• month_of_diagnosis_Jul	561
• month_of_diagnosis_Jun	562
• month_of_diagnosis_Mar	563
• month_of_diagnosis_May	564
• month_of_diagnosis_Nov	565
• month_of_diagnosis_Oct	566
• month_of_diagnosis_Sep	567

- number\_of primaries 568
- race\_ethnicity\_Amerian Indian, Aleutian, Alaskan Native or Eskimo 569
- race\_ethnicity\_Asian Indian 570
- race\_ethnicity\_Asian Indian or Pakistani 571
- race\_ethnicity\_Black 572
- race\_ethnicity\_Chinese 573
- race\_ethnicity\_Fiji Islander 574
- race\_ethnicity\_Filipino 575
- race\_ethnicity\_Guamanian 576
- race\_ethnicity\_Hawaiian 577
- race\_ethnicity\_Hmong 578
- race\_ethnicity\_Japanese 579
- race\_ethnicity\_Kampuchean 580
- race\_ethnicity\_Korean 581
- race\_ethnicity\_Laotian 582
- race\_ethnicity\_Melanesian 583
- race\_ethnicity\_Micronesian 584
- race\_ethnicity\_New Guinean 585
- race\_ethnicity\_Other 586
- race\_ethnicity\_Other Asian 587
- race\_ethnicity\_Pacific Islander 588
- race\_ethnicity\_Pakistani 589
- race\_ethnicity\_Polynesian 590
- race\_ethnicity\_Samoan 591
- race\_ethnicity\_Thai 592
- race\_ethnicity\_Tongan 593
- race\_ethnicity\_Unknown 594
- race\_ethnicity\_Vietnamese 595
- race\_ethnicity\_White 596
- seer\_historic\_stage\_a\_Distant 597
- seer\_historic\_stage\_a\_In situ 598
- seer\_historic\_stage\_a\_Localized 599
- seer\_historic\_stage\_a\_Regional 600
- seer\_historic\_stage\_a\_Unstaged 601
- sex\_Female 602
- spanish\_hispanic\_origin\_Cuban 603
- spanish\_hispanic\_origin\_Dominican Republic 604
- spanish\_hispanic\_origin\_Mexican 605
- spanish\_hispanic\_origin\_Non-Spanish/Non-hispanic 606
- spanish\_hispanic\_origin\_Other specified Spanish/Hispanic origin (excludes Dominican Repuclic) 607
- spanish\_hispanic\_origin\_Puerto Rican 608
- spanish\_hispanic\_origin\_South or Central American (except Brazil) 609
- spanish\_hispanic\_origin\_Spanish surname only 610
- spanish\_hispanic\_origin\_Spanish, NOS; Hispanic, NOS; Latino, NOS 611
- spanish\_hispanic\_origin\_Uknown whether Spanish/Hispanic or not 612
- year\_of\_birth 613
- year\_of\_diagnosis 614
- month 615

and **newtarget** is the target variable, indicating whether or not the subject died in month given by the value of the **month** variable. 617

## Lung Cancer Feature Selection

The feature set used as input into both the Random Forest and Neural Network models, after the transformation described in section Transformation of Censored Data for Machine Learning is given below and also available in full detail in the file `NewPatientLungML.html`.

- `cs.tumor_size`
- `elevation`
- `grade_cell type not determined`
- `grade_moderately differentiated`
- `grade_poorly differentiated`
- `grade_undifferentiated; anaplastic`
- `grade_well differentiated`
- `histology_recode_broad_groupings_acinar cell neoplasms`
- `histology_recode_broad_groupings_adenomas and adenocarcinomas`
- `histology_recode_broad_groupings_blood vessel tumors`
- `histology_recode_broad_groupings_complex epithelial neoplasms`
- `histology_recode_broad_groupings_complex mixed and stromal neoplasms`
- `histology_recode_broad_groupings_cystic, mucinous and serous neoplasms`
- `histology_recode_broad_groupings_ductal and lobular neoplasms`
- `histology_recode_broad_groupings_epithelial neoplasms, NOS`
- `histology_recode_broad_groupings_fibroepithelial neoplasms`
- `histology_recode_broad_groupings_fibromatous neoplasms`
- `histology_recode_broad_groupings_germ cell neoplasms`
- `histology_recode_broad_groupings_gliomas`
- `histology_recode_broad_groupings_granular cell tumors & alveolar soft part sarcomas`
- `histology_recode_broad_groupings_lipomatous neoplasms`
- `histology_recode_broad_groupings_miscellaneous bone tumors`
- `histology_recode_broad_groupings_miscellaneous tumors`
- `histology_recode_broad_groupings_mucoepidermoid neoplasms`
- `histology_recode_broad_groupings_myomatous neoplasms`
- `histology_recode_broad_groupings_myxomatous neoplasms`
- `histology_recode_broad_groupings_nerve sheath tumors`
- `histology_recode_broad_groupings_neuroepitheliomatous neoplasms`
- `histology_recode_broad_groupings_nevi and melanomas`
- `histology_recode_broad_groupings_osseous and chondromatous neoplasms`
- `histology_recode_broad_groupings_paragangliomas and glomus tumors`
- `histology_recode_broad_groupings_soft tissue tumors and sarcomas, NOS`
- `histology_recode_broad_groupings_squamous cell neoplasms`
- `histology_recode_broad_groupings_synovial-like neoplasms`
- `histology_recode_broad_groupings_thymic epithelial neoplasms`
- `histology_recode_broad_groupings_transitional cell papillomas and carcinomas`
- `histology_recode_broad_groupings_trophoblastic neoplasms`
- `histology_recode_broad_groupings_unspecified neoplasms`
- `lat`
- `laterality_Bilateral involvement, lateral origin unknown; stated to be single primary`
- `laterality_Left: origin of primary`
- `laterality_Not a paired site`
- `laterality_Only one side involved, right or left origin unspecified`
- `laterality_Paired site, but no information concerning laterality; midline tumor`

• laterality_Right: origin of primary	670
• lng	671
• marital_status_at_dx_Divorced	672
• marital_status_at_dx_Married (including common law)	673
• marital_status_at_dx_Separated	674
• marital_status_at_dx_Single (never married)	675
• marital_status_at_dx_Unknown	676
• marital_status_at_dx_Unmarried or domestic partner	677
• marital_status_at_dx_Widowed	678
• month_of_diagnosis_Apr	679
• month_of_diagnosis_Aug	680
• month_of_diagnosis_Dec	681
• month_of_diagnosis_Feb	682
• month_of_diagnosis_Jan	683
• month_of_diagnosis_Jul	684
• month_of_diagnosis_Jun	685
• month_of_diagnosis_Mar	686
• month_of_diagnosis_May	687
• month_of_diagnosis_Nov	688
• month_of_diagnosis_Oct	689
• month_of_diagnosis_Sep	690
• number_of primaries	691
• race_ethnicity_Amerian Indian, Aleutian, Alaskan Native or Eskimo	692
• race_ethnicity_Asian Indian	693
• race_ethnicity_Asian Indian or Pakistani	694
• race_ethnicity_Black	695
• race_ethnicity_Chamorroan	696
• race_ethnicity_Chinese	697
• race_ethnicity_Fiji Islander	698
• race_ethnicity_Filipino	699
• race_ethnicity_Guamanian	700
• race_ethnicity_Hawaiian	701
• race_ethnicity_Hmong	702
• race_ethnicity_Japanese	703
• race_ethnicity_Kampuchean	704
• race_ethnicity_Korean	705
• race_ethnicity_Laotian	706
• race_ethnicity_Melanesian	707
• race_ethnicity_Micronesian	708
• race_ethnicity_New Guinean	709
• race_ethnicity_Other	710
• race_ethnicity_Other Asian	711
• race_ethnicity_Pacific Islander	712
• race_ethnicity_Pakistani	713
• race_ethnicity_Polynesian	714
• race_ethnicity_Samoan	715
• race_ethnicity_Thai	716
• race_ethnicity_Tongan	717
• race_ethnicity_Unknown	718
• race_ethnicity_Vietnamese	719
• race_ethnicity_White	720
• seer_historic_stage_a_Distant	721

- seer\_historic\_stage\_a\_In situ 722
- seer\_historic\_stage\_a\_Localized 723
- seer\_historic\_stage\_a\_Regional 724
- seer\_historic\_stage\_a\_Unstaged 725
- sex\_Female 726
- spanish\_hispanic\_origin\_Cuban 727
- spanish\_hispanic\_origin\_Dominican Republic 728
- spanish\_hispanic\_origin\_Mexican 729
- spanish\_hispanic\_origin\_Non-Spanish/Non-hispanic 730
- spanish\_hispanic\_origin\_Other specified Spanish/Hispanic origin (excludes Dominican Repuclic) 731
- spanish\_hispanic\_origin\_Puerto Rican 732
- spanish\_hispanic\_origin\_South or Central American (except Brazil) 733
- spanish\_hispanic\_origin\_Spanish surname only 734
- spanish\_hispanic\_origin\_Spanish, NOS; Hispanic, NOS; Latino, NOS 735
- spanish\_hispanic\_origin\_Uknown whether Spanish/Hispanic or not 736
- year\_of\_birth 737
- year\_of\_diagnosis 738
- month 739

and `newtarget` is the target variable, indicating whether or not the subject died in month given by the value of the `month` variable. 741

## Breast Cancer Feature Selection 743

The feature set used as input into both the Random Forest and Neural Network models, after the transformation described in section Transformation of Censored Data for Machine Learning is given below and also available in full detail in the file `NewPatientBreastML.html` . 744

- cs\_tumor\_size 748
- elevation 749
- grade\_moderately differentiated 750
- grade\_poorly differentiated 751
- grade\_ndifferentiated; anaplastic 752
- grade\_well differentiated 753
- histology\_recode\_broad\_groupings\_adenomas and adenocarcinomas 754
- histology\_recode\_broad\_groupings\_adnexal and skin appendage neoplasms 755
- histology\_recode\_broad\_groupings\_basal cell neoplasms 756
- histology\_recode\_broad\_groupings\_complex epithelial neoplasms 757
- histology\_recode\_broad\_groupings\_cystic, mucinous and serous neoplasms 758
- histology\_recode\_broad\_groupings\_ductal and lobular neoplasms 759
- histology\_recode\_broad\_groupings\_epithelial neoplasms, NOS 760
- histology\_recode\_broad\_groupings\_nerve sheath tumors 761
- histology\_recode\_broad\_groupings\_unspecified neoplasms 762
- lat 763
- laterality\_Bilateral involvement, lateral origin unknown; stated to be single primary 764
- laterality\_Paired site, but no information concerning laterality; midline tumor 765
- laterality\_Right: origin of primary 766
- lng 767
- marital\_stats\_at\_dx\_Divorced 768
- marital\_stats\_at\_dx\_Married (includng common law) 769



• marital_stats_at_dx_Separated	771
• marital_stats_at_dx_Single (never married)	772
• marital_stats_at_dx_Unknown	773
• marital_stats_at_dx_Unmarried or domestic partner	774
• marital_stats_at_dx_Widowed	775
• month_of_diagnosis_Apr	776
• month_of_diagnosis_Aug	777
• month_of_diagnosis_Dec	778
• month_of_diagnosis_Feb	779
• month_of_diagnosis_Jan	780
• month_of_diagnosis_Jul	781
• month_of_diagnosis_Jun	782
• month_of_diagnosis_Mar	783
• month_of_diagnosis_May	784
• month_of_diagnosis_Nov	785
• month_of_diagnosis_Oct	786
• month_of_diagnosis_Sep	787
• race_ethnicity_Amerian Indian, Aletian, Alaskan Native or Eskimo	788
• race_ethnicity_Asian Indian	789
• race_ethnicity_Black	790
• race_ethnicity_Chinese	791
• race_ethnicity_Japanese	792
• race_ethnicity_Melanesian	793
• race_ethnicity_Other	794
• race_ethnicity_Other Asian	795
• race_ethnicity_Pacific Islander	796
• race_ethnicity_Thai	797
• race_ethnicity_Unknown	798
• race_ethnicity_Vietnamese	799
• race_ethnicity_White	800
• seer_historic_stage_a_Distant	801
• seer_historic_stage_a_In sit	802
• seer_historic_stage_a_Localized	803
• seer_historic_stage_a_Unstaged	804
• sex_Female	805
• spanish_hispanic_origin_Cuban	806
• spanish_hispanic_origin_Mexican	807
• spanish_hispanic_origin_Non-Spanish/Non-hispanic	808
• spanish_hispanic_origin.Other specified Spanish/Hispanic origin (excldes Dominican Republic)	809
• spanish_hispanic_origin.Spanish surname only	810
• spanish_hispanic_origin.Spanish, NOS; Hispanic, NOS; Latino, NOS	811
• year_of_birth	812
• year_of_diagnosis	813
• month	814
	815

and `newtarget` is the target variable, indicating whether or not the subject died in month given by the value of the `month` variable.

## Pseudocode for the Data Transformation

```
def train(X, T, D)
    // X, T, D are the original dataset
```

```

X' = []
D' = []

// the transformation
for each index i in X:
    for t=1 to T[i]:
        new_D = (0 if t < T[i], else D[i])
        append new_D to D'
        new_X = (X[i], t)
        append new_X to X'

return a decision tree trained on (X', D')

def pmf(h, X)
    // X is a single datapoint
    // returns an array A where A[i] = P(Y = i | X)
    A = []
    p_so_far = 1 // this is p(T >= t | X)
    for t = 1 to (the last month where h has any data):
        // h knows p(T = t | T >= t, X), we call this p_cur
        p_cur = h's prediction for (X, t)
        append (p_so_far * p_cur) to A
        p_so_far *= (1 - p_cur)

```

### Breast Random Forest Model Hyperparameters

```

f = RandomForestClassifier(n_estimators=20,min_samples_split=3,
                           max_depth = 15,
                           max_features = .8,
                           n_jobs=5,verbose=2,random_state=33)

```

### Colon Random Forest Model Hyperparameters

```

rf = RandomForestClassifier(n_estimators=25,min_samples_split=3,
                           max_depth = 10,
                           max_features = .5,
                           n_jobs=5,verbose=2,random_state=3)

```

### Lung Random Forest Model Hyperparameters

```

rf = RandomForestClassifier(n_estimators=25,min_samples_split=3,
                           max_depth = 11,
                           max_features = .8,
                           n_jobs=5,verbose=2,random_state=3)

```

### Breast Neural Network Model Architecture

The architecture of the Keras multilayer perceptron neural network model trained on the breast cancer data is given explicitly below:

```

modelbreast = Sequential()
modelbreast.add(Dense(114, input_shape=(66,) ,init='normal'))

```

```

modelbreast.add(Activation('relu'))
modelbreast.add(Dropout(0.05))
modelbreast.add(Dense(50, init='normal'))
modelbreast.add(Activation('relu'))
modelbreast.add(Dropout(0.05))

modelbreast.add(Dense(36, init='normal'))
modelbreast.add(Activation('relu'))
modelbreast.add(Dropout(0.05))

modelbreast.add(Dense(2, init='normal'))
modelbreast.add(Activation('softmax'))

rms = RMSprop(lr=0.001)

modelbreast.compile(loss='binary_crossentropy',
                    optimizer=rms, class_mode="binary")

```

and trained with a batch size of 1500 for 200 epochs.

## Colon Cancer Neural Network Model Architecture

The architecture of the Keras multilayer perceptron neural network model trained on the colon cancer data is given explicitly below:

```

modelcolon = Sequential()
modelcolon.add(Dense(114, input_shape=(102,) ,init='normal'))
modelcolon.add(Activation('relu'))
modelcolon.add(Dropout(0.05))
modelcolon.add(Dense(50, init='normal'))
modelcolon.add(Activation('relu'))
modelcolon.add(Dropout(0.05))

modelcolon.add(Dense(35, init='normal'))
modelcolon.add(Activation('relu'))
modelcolon.add(Dropout(0.05))

modelcolon.add(Dense(2, init='normal'))
modelcolon.add(Activation('softmax'))

rms = RMSprop(lr=0.001)

modelcolon.compile(loss='binary_crossentropy',
                  optimizer=rms, class_mode="binary")

```

and trained with a batch size of 1500 for 200 epochs.

## Lung Cancer Neural Network Model Architecture

The architecture of the Keras multilayer perceptron neural network model trained on the lung cancer data is given explicitly below:

```
modellung = Sequential()
modellung.add(Dense(114, input_shape=(114,) ,init='normal'))
modellung.add(Activation('relu'))
modellung.add(Dropout(0.1))
modellung.add(Dense(80, init='normal'))
modellung.add(Activation('relu'))
modellung.add(Dropout(0.1))
modellung.add(Dense(40, init='normal'))
modellung.add(Activation('relu'))
modellung.add(Dropout(0.1))
```

```
modellung.add(Dense(2, init='normal'))
modellung.add(Activation('softmax'))
```

```
rms = RMSprop(lr=0.001)
```

```
modellung.compile(loss='binary_crossentropy',
                  optimizer=rms, class_mode="binary")
```

and trained with a batch size of 2000 for 50 epochs.

## Acknowledgments

Cras egestas velit mauris, eu mollis turpis pellentesque sit amet. Interdum et malesuada fames ac ante ipsum primis in faucibus. Nam id pretium nisi. Sed ac quam id nisi malesuada congue. Sed interdum aliquet augue, at pellentesque quam rhoncus vitae.

## References

1. Pandora Media, Inc . Pandora Internet Radio - Listen to Free Music You'll Love; 2016 (accessed 12 Feb 2016). <http://www.pandora.com/>.
2. Goodreads Inc. Share Book Recommendations With Your Friends, Join Book Clubs, Answer Trivia; 2016 (accessed 12 Feb 2016). <http://www.goodreads.com/>.
3. Google Maps. 4901 Lang Ave NE to Albuquerque Sunport, Albuquerque, NM - Google Maps; 2016 (accessed 17 Feb 2016). <https://goo.gl/1D7Jwf>.
4. Sebastian Raschka. Python Machine Learning Essentials. Packt Publishing; 2015.
5. Cam Davidson-Pilon. Quickstart – lifelines 0.8.0.1 documentation; 2016 (accessed 14 Jan 2016). <http://lifelines.readthedocs.org/en/latest/Quickstart.html>.

6. Kumbasar U, Raubenheimer H, Sahaf MA, Asadi N, Cufari ME, Proli C, et al. Selection for adjuvant chemotherapy in completely resected stage I non-small cell lung cancer: External validation of a Chinese prognostic risk model. *Journal of Thoracic Disease*. 2016;8(1):140–144. Cited By 0. Available from: <http://www.scopus.com/inward/record.url?eid=2-s2.0-84957096795&partnerID=40&md5=be331b5dc81ff3f73fd9e30aed8c00e0>.
7. Van Poucke S, Zhang Z, Schmitz M, Vukicevic M, Laenen MV, Celi LA, et al. Scalable predictive analysis in critically ill patients using a visual open data analysis platform. *PLoS ONE*. 2016;11(1). Cited By 0. Available from: <http://www.scopus.com/inward/record.url?eid=2-s2.0-84953931466&partnerID=40&md5=7a0cad7137c03146e4b75f3295f84cc6>.
8. Shin, Hyunjung and Nam, Yonghyun; ISCB Asia. A coupling approach of a predictor and a descriptor for breast cancer prognosis [Article; Proceedings Paper]. *BMC MEDICAL GENOMICS*. 2014 MAY 8;7(1). 3rd Annual Translational Bioinformatics Conference (TBC) / ISCB-Asia, Seoul, SOUTH KOREA, OCT 02-04, 2013.
9. Zolbanin, Hamed Majidi and Delen, Dursun and Zadeh, Amir Hassan. Predicting overall survivability in comorbidity of cancers: A data mining approach [Article]. *DECISION SUPPORT SYSTEMS*. 2015 JUN;74:150–161.
10. Gordon L, Olshen RA. Tree-structured survival analysis. *Cancer Treatment Reports*. 1985;69(10):1065–1068. Cited By 97. Available from: <http://www.scopus.com/inward/record.url?eid=2-s2.0-0021875130&partnerID=40&md5=9e112ed840960f801b6260b23bf6811d>.
11. Bou-Hamad I, Larocque D, Ben-Ameur H. A review of survival trees. *Statistics Surveys*. 2011;5:44–71. Cited By 15. Available from: <http://www.scopus.com/inward/record.url?eid=2-s2.0-84857308440&partnerID=40&md5=f8af82017ade68e335fd258c6857bf49>.
12. Ishwaran H, Kogalur UB. Consistency of random survival forests. *Statistics and Probability Letters*. 2010;80(13-14):1056–1064. Cited By 26. Available from: <http://www.scopus.com/inward/record.url?eid=2-s2.0-77953020220&partnerID=40&md5=1e4478c51150f0159fdc6c1cb631968b>.
13. National Cancer Institute, the Surveillance, Epidemiology, and End Results Program. Documentation for ASCII Text Data Files - SEER Datasets; 2016 (accessed 15 Jan 2016). <http://seer.cancer.gov/data/documentation.html>.
14. Michael Bowles. *Machine Learning in Python: Essential Techniques for Predictive Analysis*. Wiley; 2015.
15. United States Census Bureau. 2010 FIPS Code Files for Counties - Geography - U.S. Census Bureau; 2016 (accessed 18 Jan 2016). <https://www.census.gov/geo/reference/codes/cou.html>.
16. Google Developers. The Google Maps Geocoding API — Google Maps Geocoding API — Google Developers; 2016 (accessed 18 Jan 2016). <https://developers.google.com/maps/documentation/geocoding/intro>.
17. Google Developers. The Google Maps Elevation API — Google Maps Elevation API — Google Developers; 2016 (accessed 18 Jan 2016). <https://developers.google.com/maps/documentation/elevation/intro?hl=en>.

18. IOBS. Supplemental Material — PAPERDATA; 2016 (accessed 18 Jan 2016). <https://github.com/doolingdavid/PAPERDATA.git>.
19. Ben Kuhn. Decision trees for survival analysis; 2016 (accessed 14 Jan 2016). <http://www.benkuhn.net/survival-trees>.
20. Allen Downey. Think Stats. O'Reilly Media; 2014.
21. James Surowiecki. The Wisdom of Crowds. Doubleday; 2004.
22. John Cassidy. What killed Intrade?; 13 Mar 2013 (accessed 25 Jan 2016). <http://www.newyorker.com/news/john-cassidy/what-killed-intrade>.
23. Malcolm Gladwell. Outliers. Back Bay Books; 2011.
24. scikit-learn developers. 3.2.4.3.1. sklearn.ensemble.RandomForestClassifier; 2014 (accessed 25 Jan 2016). <http://scikit-learn.org/stable/modules/generated/sklearn.ensemble.RandomForestClassifier.html>.
25. Kaggle Inc . Random Forests — Kaggle; 2015 (accessed 25 Jan 2016). <https://www.kaggle.com/wiki/RandomForests>.
26. Michael Nielsen. Neural Networks and Deep Learning; Jan 2016 (accessed 25 Jan 2016). <http://neuralnetworksanddeeplearning.com/>.
27. T Unterthiner, A Mayr, G Klambauer, and S Hochreiter. Toxicity Prediction using deep learning; 4 Mar 2015 (accessed 25 Jan 2016). <http://arxiv.org/abs/1503.01445>.
28. F Chollet. Keras Documentation; 2015 (accessed 25 Jan 2016). <http://keras.io/>.
29. Armin Roncaher. Welcome — Flask (A Python Microframework; 2014 (accessed 29 Jan 2016). <http://flask.pocoo.org>.
30. Kai Porter, KOB Eyewitness News 4. Study links higher elevation with lower lung cancer risk; 26 Jan 2016 (accessed 27 Jan 2016). <http://www.kob.com/article/stories/s4029233.shtml#.VqlUafkrJhF>.
31. Statistical Software Information, University of Massachusetts Amherst. Software - Statistical Consulting Center - UMass Amherst; 2004 (accessed 29 Jan 2016). <https://www.umass.edu/statdata/statdata/stat-survival.html>.
32. National Cancer Institute, Division of Cancer Control and Population Sciences. SEER-Medicare Linked Database; 2015 (accessed 10 Feb 2016). <http://healthcaredelivery.cancer.gov/seermedicare/>.