




ECE 364

Software Engineering Tools Lab

Lecture 8
Python: Advanced I



Lecture Summary

- Python Variables
- Namespaces and Scope
- Modules
- Exceptions



More on Python Variables



- All variables in Python are actually pointers

```
>>> A = [10, 80, -3]
```

```
>>> B = "Foobar"
```

```
>>> C = A
```


- This is represented in memory like this:



More on Python Variables

- Whenever you use `=`, you are **reassigning a pointer**, not making a copy or altering a value.
- This can lead to side effects
- Example:



```
>>> A = [10, 80, -3]
>>> B = A
>>> B.append('Z')
>>> print(A)
[10, 80, -3, 'Z']
```



Making Copies

- The assignment $B = A$ only points B to A



$A = \{ "foo": 1024, 10: "qwerty", -7.2: 42 \}$



Making Copies (Shallow)

- Use the `copy()` function
- A shallow copy only duplicates the keys!



```
B = A.copy()
```



Making Copies (Deep)


- The copy module provides `deepcopy()`
- Copies keys and values

```
import copy  
B = copy.deepcopy(A)
```




Namespaces

- A namespace is “a mapping from names to objects”
 - e.g. “`x`” maps to the value 5 or “`A`” maps to [1, 2, 3]
- Python creates namespaces at different times
 - The built-in namespace is created when Python starts and is never deleted
 - A namespace is created for a function when the function is called and deleted when the function returns



Scope

- A scope is "a textual region of a Python program where a namespace is directly accessible"
- A new local namespace is created whenever a function is called
- Python resolves identifiers by searching their current scope in the following order
 1. Local namespace
 2. Global namespace within the module
 3. "Built-in" namespace
 4. If the name can not be resolved a NameError exception is raised



Scope (2)

```
Y=0                                # X and Y are part of the __global__ namespace
X=0

def foo():
    X = 10                        # X and Y are part of a new namespace
    Y = 40                        # __global__.foo, and are distinct from
    print("{} {}".format(X, Y))  # X and Y in the global namespace

def bar():
    X = 30                        # Python will search for names within
    print("{} {}".format(X, Y))  # the local namespace upwards to the
                                # __global__ namespace. Y is found _
                                # _global__


print("{} {}".format(X, Y))      # prints 0 0
foo()                            # prints 10 40
print("{} {}".format(X, Y))      # prints 0 0
bar()                            # prints 30 0
print("{} {}".format(X, Y))      # prints 0 0
```



Comparison: Scope in C

- Scope in C is defined by blocks
 - Created using curly braces

```
void foo(void *bar) {  
    int i = 0;  
    while (bar[i] != '\0') {  
        i++;  
    }  
    return i;  
}
```



Global Variables

- To write to a variable that is in any namespace other than the current, local namespace you must declare it as **global** in the current namespace

```
def ChangeA():  
    global A  
    A = 25
```


```
A = 404  
ChangeA ()  
print(A)
```

```
>>> 25
```

```
def ChangeA():  
    A = 25
```


```
A = 404  
ChangeA ()  
print(A)
```

```
>>> 404
```




Modules

- A python module is a file containing function definitions and statements that enables **code reuse** and provides **modular structure** to your programs
 - See `Pro_Set.py` in the example scripts
- An `import` statement loads the module and makes it's functions and variables visible to the current namespace
 - `sys` and `os` are commonly used modules
- A module's name is specified by it's file name
 - e.g. The module `Pro_Set` exists in the file `Pro_Set.py`




Modules (2)

- A module must be imported into the current namespace using an `import` statement
 - `import mod_name`
- When accessing a function or variable from the module you must prepend the module name
 - e.g. `os.access(...)` or `sys.argv`



Modules (3)


- You can omit the module name when referring to functions or variables defined in the module when using an alternative import style
 - `from mod_name import func_name`
- The `from` style import makes the function or variable name directly visible to the current name space



Modules (4)

```
from sys import argv, stderr
if len(argv) != 2:
    stderr.write("usage: script.py <arg1>\n")
```

- `argv` and `stderr` do not have a `sys.` prefix because they are directly imported from the `sys` module into the current namespace




Modules (5)

- An asterisk in the `from` style import allows you to import all functions and variables in the module into the current namespace

```
from sys import *  
if len(argv) != 2:  
    stderr.write("usage: script.py <arg1>\n")
```

- You should avoid using this **for more than one module**
 - It clutters the namespace and may cause name conflicts




Modules (6)

- Modules can be imported almost anywhere within a python program
 - Typically done at the very beginning of a file
 - But can be done elsewhere...

```
def print_usage():  
    import sys # sys only visible in print_usage()  
    sys.stdout.write("usage: %s\n" % (sys.argv[0],))
```

- When importing into a lower namespace the module is only accessible from within that namespace



What is an Exception?

- An exception is a **program branch** executed when an invalid operation or state is detected
- Each statement in a python program may cause an exception to occur, immediately changing the execution path
- Exceptions are used in many other high level languages
 - C++, Java, C# etc.
- In C there are no exceptions
 - Programmer must resort to using error codes and other mechanisms




What is an Exception?

- **An exception is the error**
 - Python is literally throwing the error at you
 - You can either catch it or let it knock you out
- Exceptions contain helpful details about what went wrong in the program
 - Error messages, function name, argument values etc.
 - Much more useful than error code
- Not as simple as an error code but the number 10 does not tell much about what went wrong



Built-In Exceptions


- `ValueError` – indicates a value is not properly formed
- `IOError` – indicates a problem when performing I/O
- `OSError` – indicates an error raised by the operating system
- `IndexError` – indicates an index lookup failed or was out of bounds
- `KeyError` – indicates an lookup by key failed or the key was not found
- `TypeError` – indicates an function or operation is applied to a type that does not support it



Handling Exceptions

- There are two things a program can do with exceptions
 - Ignore them – will result in early termination
 - **Catch** them – examine the exception and perform some action to correct the problem
- It is not always possible to correct errors at runtime
 - But you can display a user friendly error message and possibly log the error


```
try:  
    ... statements ...  
except:  
    ... exception handling statements ...
```



Handling Exceptions (2)


- There are many different types of exceptions.
- Many times you will want to handle them in a different way depending on the type.

```
try:
    ... statements that may raise an exception ...
except (IOError, ValueError):
    ... handle IO errors or value errors ...
except <ExType> as e:
    ... handle <ExType> error referenced as the variable e...
except:
    ... handle all other errors ...
else:
    ... statements to run if no exception was raised ...
finally:
    ... Always run after handling error ...
```



Handling Exceptions (4)

- `except IOError:`
 - No reference to the `IOError` exception is available.
- `except IOError as e:`
 - The `IOError` exception and its details are available in the local variable `e`.
 - Newer syntax that is preferred for new programs.
- `except IOError, e:` (In Python 2)
 - Equivalent to the above statement.



Handling Exceptions (5)

```
import sys
```

```
file_name = raw_input('Enter a file name: ')
```

Take branch if exception raised

```
fp = open(file_name, "r") # possible exception
```

```
sum = 0.0
```

Take branch if exception raised

```
for line in fp: # possible exception
```

```
    values = line.split(',') # possible exception
```

```
    for v in values:
```

Take branch if exception raised

```
        fv = float(v) # possible exception
```

```
        sum += fv
```

```
fp.close()
```

```
print "Sum = %f" % (sum,)
```

```
sys.exit(0)
```

Built-in Exception Handler:

```
import sys, traceback
```

```
t, v, tb = sys.exc_info()
```

```
traceback.print_exception(t, v, tb, limit=2, file=sys.stderr)
```

```
sys.exit(-1)
```

Handling Exceptions (6)

```
file_name = raw_input('Enter a file name: ')
```

```
try:
```

```
    fp = open(file_name, "r") # possible exception
```

Take branch if exception raised

```
except:
```

```
    print "Could not open %s" (file_name,)
```

```
    sys.exit(1)
```

```
sum = 0.0
```

```
for line in fp: # possible exception
```

Take branch if exception raised

```
    values = line.split(',')
```

```
    for v in values:
```

```
        try:
```

Take branch if exception raised

```
            fv = float(v) # possible exception
```

```
            sum += fv
```

```
        except ValueError as e:
```

```
            print "Unknown value %s: %s" % (v,e)
```

```
fp.close()
```

```
print "Sum = %f" % (sum,)
```

```
sys.exit(0)
```

Built-in Exception Handler:

```
t, v, tb = sys.exc_info()
```

```
traceback.print_exception(t, v, tb, limit=2, file=sys.stderr)
```

```
sys.exit(-1)
```



Handling Exceptions (7)

```
value = raw_input('Prompt: ')

try:
    # int() Raises a ValueError exception
    result = proc_integer(int(val))
except ValueError:
    result = proc_other(val)

print(value)
```




Handling Exceptions (8)

- To ignore an exception the `pass` statement can be used to indicate no action is taken

```
value = raw_input('Prompt: ')

try:
    result = proc_integer(int(val))
except ValueError:
    pass # do nothing...

print(value)
```




Handling Exceptions (9)

```
import sys

try:
    fp = open(sys.argv[1], "r")
except IOError as e:
    sys.stderr.write("Reason: %s\n" % (e,))
    sys.exit(1)


for line in fp:
    print(line)

fp.close()
sys.exit(0)
```



Raising Exceptions

- There are often many times when you want to signal an error to your program
- Typically you will raise exceptions from your own modules and functions to indicate errors or malformed arguments
- Exceptions are “raised” by the program using the `raise <Exception>` statement



Raising Exceptions (2)

```
def dotProduct(row, column):  
    if type(row) is not list or type(column) is not list:  
        raise TypeError("Row & Column must be lists.")  
  
    if ((len(row) == len(column)) and (len(row) > 0)):  
        raise ValueError("Row & Column must be of the same size.")  
  
    # Continue execution.  
    ...  
  
row2 = [3, 7, 1, 8]; column2 = [2, 5, 6]  
  
# These will raise an exception.  
dotProduct(row2, column2)  
dotProduct(9, column2)
```

