

1 Gamifying Judgments of Associative Memory

2 Erin M. Buchanan¹ & Abigail Van Nuland¹

3 ¹ Missouri State University

4 Author Note

5 Erin M. Buchanan is a Professor of Cognitive Analytics at Harrisburg University of
6 Science and Techonology, and Abigail Van Nuland is a Masters Degree candidate at Missouri
7 State Univeristy.

8 Correspondence concerning this article should be addressed to Erin M. Buchanan, 326
9 S. Market St., Harrisburg, PA, 17101. E-mail: ebuchanan@harrisburgu.edu

Abstract

One or two sentences providing a **basic introduction** to the field, comprehensible to a scientist in any discipline.

Two to three sentences of **more detailed background**, comprehensible to scientists in related disciplines.

One sentence clearly stating the **general problem** being addressed by this particular study.

One sentence summarizing the main result (with the words “**here we show**” or their equivalent).

Two or three sentences explaining what the **main result** reveals in direct comparison to what was thought to be the case previously, or how the main result adds to previous knowledge.

One or two sentences to put the results into a more **general context**.

Two or three sentences to provide a **broader perspective**, readily comprehensible to a scientist in any discipline.

Keywords: judgments, word association, metacognition

Gamifying Judgments of Associative Memory

We are going to write an introduction here about JAM, association, and stuff.

- 1) In a traditional free association task, people guess the words. . . would the numbers help? (a v b)
- 2) In a JAM task with multiple guesses, they would normally see the words, would expect them to be able to guess better if they know it's descending order, so the D condition would match the normal JAM slope and C should be better (this answers the bounded question).
- 3) For the non-numbers condition, see if singles or groups are better. Shouldn't more heads be better than one?
- 4) For the normal JAM task, see if groups are better than singles at guessing the numbers.

Judgments of associative memory are notoriously poor (Buchanan, 2009; Maki, 2007), where participants over estimate the relationship between word pairs. In the judgment task, participants are given two words (LOST-FOUND) and asked to rate how many people out of a 100 would list the second word if given the first word. Participants cannot tell the difference between low and high frequency pairs and tend to judge pairs higher than they should. The psycholinguistics lab has tried to correct these memory judgments by giving participants various instructions (Buchanan & Maki, in preparation), changing the scales for judgments (Buchanan, data analysis), changing the judgment type (Maki & Buchanan, in preparation), and having participants judge their own ratings over time (Buchanan, data collection). These manipulations have shown a small effect on judgment ability, mainly to reduce the overall bias to select very large numbers. The current protocol will examine if judgments are more accurate when the experimental task is more interesting and engaging. We will be using the game show Family Feud as the experimental procedure because the game show closely matches the judgments of memory paradigm currently used.

Method

Participants

Participants were recruited from the Psychology Department at a large Midwestern university using an online participant management system. They were given course credit for their participation in the study. Participants were assigned to work alone (247) or in groups (184 groups, 418) with a total of 431 sessions and 665 completing the study. No other demographic information was collected.

Materials

Stimuli were selected from the University of South Florida Free Association Database (???). Free association norms were created by asking participants to list the first word that comes to mind given a cue word. For example, when shown the cue *lost*, many participants will then list the target word *found*. These responses were collected over many participants and used to create a probability of eliciting the target word given a cue word called forward strength (FSG). The purpose of this study was to examine free association and judgments of associative memory over multiple cues, and therefore, cues with at least four matching target words were selected. For example, when given the cue *conditioner*, participants might list *shampoo* (FSG = .455), *hair* (FSG = .325), and *air* (FSG = .110). Cues with at least one target in each of the forward strength ranges of .40-.60, .20-.40, and <.20 were selected. Eight cue words were selected with an average of 5.00 target words paired with each cue ($SD = 0.93$). The average forward strength for high strength targets was 0.44 ($SD = 0.03$), medium strength targets 0.26 ($SD = 0.04$), and low strength targets 0.06 ($SD = 0.05$). The complete materials can be found online at <https://osf.io/83bkt/>.

73 Procedure

74 The eight cue-target lists were assembled into a powerpoint document that emulated a
75 game of Family Feud. Family Feud is a game show that gives contestants category labels and
76 asks them to list the ...

77 An experimenter will be with the participant at all times to keep score and be the
78 game show host. The rules of the game will be explained to the participant as follows: "You
79 will be playing Family Feud for your experimental credit today. We asked 100 people to say
80 the first thing they thought of when given each category you are going to see today. For
81 example, when we gave people the word "steak" many of them listed "sauce, cow, sirloin". In
82 the following rounds, you will guess what words people listed. (OR you will guess the
83 number of people who listed each word) You will receive points for your correct guesses. Try
84 to beat the high lab score!"

85 four different versions two of the versions included single participants versus groups of
86 participants (a and d)

87 **Version A.** guess the words, no numbers present three guesses wrong and we moved
88 on most matches a traditional free association task

89 **Version B.** guess the words, numbers were present three guesses wrong and we
90 moved on

91 **Version C.** guess the numbers, words were in numerical order 1 guess to get it right
92 and they were considered right if it was within five points

93 **Version D.** guess the numbers, words were NOT in numerical order 1 guess to get it
94 right and they were considered right if it was within five points most matches a JAM task

95 Participants will be in one of three conditions: • Regular Family Feud: This condition

is played like the game show. Participants are given the category label and asked to guess four words that people listed. They are given three strikes at guessing before moving onto the next round. When they guess a correct word, they are shown the word and points on a computer screen. The experimenter will keep score. • Numbered Family Feud: This condition is the same as above, with one exception. Participants will be able to see the number of people who listed each word next to the ? on each category label. This condition will examine if participants have an easier or harder time guessing with the scores listed. • Reverse Family Feud: This condition is played where participants are required to guess the number of people who listed each word under a category, mirroring the judgments of associative memory task previously used by the researcher. They will be told to guess within 10-20 people of the words (this number will be pilot tested by the lab assistants to find the range that allows participants to “win”).

The research assistants will pilot test all three conditions to come up with high scores for the game. The scores will be biased lower, so that participants can almost always score in the high score range. These scores will be posted in the lab for participants to try to beat. The first experiment will test participants individually, to eliminate any social facilitation and create a control group. The second experiment will test participants in pairs/threes to analyze judgments in groups.

Data analysis

Going to talk here about MLM and Log regression as the analyses of choice because they are the most appropriate.

Results

Hypothesis 1

- Version A versus B – would answer if the number helped them guess or not o Multilevel log regression o Random: participant, word? o IVs: Version, Points (sort of L, M, H words) o DV: correct (1) versus incorrect (0)

Hypothesis 2

- Version C versus D – would answer if we are better if they are in order or not o Multilevel regression o Random: participant, word? o IVs: Version, Points (sort of L, M, H words) o DV: Score they guessed

Hypothesis 3

- Version A singles versus Groups o Multilevel log regression o Random: participant, word? o IVs: Singles/Groups, Points (sort of L, M, H words) o DV: correct (1) versus incorrect (0)

Hypothesis 4

- Version D singles versus Groups o Multilevel regression o Random: participant, word? o IVs: Singles/groups, Points (sort of L, M, H words) o DV: Score they guessed

Discussion

References

Table 1

HEADER

Model	Predictor	\$b\$	\$SE\$	\$z\$	\$p\$
Main Effects	A vs B	0.19	0.09	2.18	.029
Main Effects	Points	0.08	0.01	8.29	< .001
Interactions	A vs B	0.11	0.12	0.93	.351
Interactions	Points	0.08	0.01	7.81	< .001
Interactions	Group:Points	0.00	0.00	1.03	.305
Simple Slope A	Points	0.07	0.01	8.25	< .001
Simple Slope B	Points	0.08	0.01	7.89	< .001

Note. STUFF