

Investigating the Interaction between Associative, Semantic, and Thematic Database Norms
for Memory Judgments and Retrieval

Nicholas P. Maxwell^{1,2} & Erin M. Buchanan¹

¹ Missouri State University

² University of Southern Mississippi

Author Note

Nicholas P. Maxwell received his masters degree at Missouri State University and is now a Ph.D. candidate at the University of Southern Mississippi. Erin M. Buchanan is an Associate Professor of Psychology at Missouri State University.

Correspondence concerning this article should be addressed to Erin M. Buchanan, 901 S. National Ave, Springfield, MO, 65897. E-mail: erinbuchanan@missouristate.edu

Abstract

This study examined the interactive relationship between semantic, thematic, and associative word pair strength in the prediction of item judgments and cued-recall performance. Participants were recruited from Amazon’s Mechanical Turk and were given word pairs of varying relatedness to judge for their semantic, thematic, and associative strength. After completing a distractor task, participants then completed a cued recall task. First, we sought to expand previous work on judgments of associative memory (JAM) to include semantic and thematic based judgments, while also replicating bias and sensitivity findings. Next, we tested for an interaction between the three database norms (FSG, COS, and LSA) when predicting participant judgments and also extended previous work to test for interactions between the three database norms when predicting recall. Significant three-way interactions were found between FSG, COS, and LSA when predicting judgments and recall. For low semantic feature overlap, thematic and associative strength were competitive; as thematic strength increased, associative predictiveness decreased. However, this trend reversed for high semantic feature overlap, wherein thematic and associative strength were complementary as both set of simple slopes increased together. Overall, our findings indicate the degree to which the processing of associative, semantic, and thematic information impacts cognitive processes such as retrieval and item judgments, while also examining the underlying, interactive relationship that exists between these three types of information.

Keywords: judgments, memory, association, semantics, thematics

Investigating the Interaction between Associative, Semantic, and Thematic Database Norms
for Memory Judgments and Retrieval

The study of cognition has a rich history of exploring the role of association in human memory. One key finding is that elements of cognitive processing play a critical role in how well an individual retains learned information. Throughout the mid-20th century, researchers investigated this notion, particularly through the use of paired-associate learning (PAL). In this paradigm, participants are presented with a pair of items and are asked to make connections between them so that the presentation of one item (the cue) will in turn trigger the recall of the other (the target). Early studies of this nature focused primarily on the effects of meaning and imagery on recall performance. For example, Smythe and Paivio (1968) found that noun imagery played a crucial role in PAL performance; subjects were much more likely to remember word-pairs that were low in meaning similarity if imagery between the two was high. Subsequent studies in this area focused on the effects of mediating variables on PAL tasks as well as the effects of imagery and meaningfulness on associative learning (Richardson, 1998), with modern studies shifting their focus towards a broad range of applied topics such as how PAL is affected by aging (Hertzog, Kidder, Powell-Moman, & Dunlosky, 2002), its impacts on second language acquisition (Chow, 2014), and even in evolutionary psychology (Schwartz & Brothers, 2013).

Early PAL studies routinely relied on stimuli generated from word lists that focused extensively on measures of word frequency, concreteness, meaningfulness, and imagery (Paivio, 1969). However, the word pairs in these lists were typically created due to their apparent relatedness or frequency of occurrence in text. While lab self-generation appears face valid, one finds that this method of selection lacks a decisive method of defining the underlying relationships between the pairs (Buchanan, 2010), as these variables only capture psycholinguistic measurements of an individual concept (i.e., how concrete is *cat* and word occurrence). PAL is, by definition, used on word pairs, which requires examining concept

relations in a reliable manner. As a result, free association norms have become a common means of indexing associative strength between word pairs.

As we will use several related variables, it is important to first define association as the context-based relation between concepts, usually found in text or popular culture (Nelson, McEvoy, & Dennis, 2000). These word associations may arise in several different ways. Such associations may develop through their co-occurrence together in language. The terms *peanut* and *butter* have become associated over time through their joint use to depict a particular type of food, though separately, the two concepts share very little overlap in terms of meaning. However, associations can also come about through shared meaning. For example, they capture the knowledge that fish live in water and that dogs and cats share many similar features. To generate these norms, participants engage in a free association task, in which they are presented with a cue word and are asked to list the first related target word that comes to mind. The probability of producing a given response to a particular cue word, or forward strength, can then be determined by dividing the number of participants who produced the response in question by the total number of responses generated for that word (FSG; Nelson et al., 2000). Thus, the free association process can be thought of as generating an index that contains the relative accessibility of related words in memory (Nelson, McEvoy, & Schreiber, 2004). Using this technique, researchers have developed databases of associative word norms that can be used to generate stimuli with a high degree of reliability. Many of these databases are now readily available online, with the largest one consisting of over 72,000 associates generated from more than 5,000 cue words (Nelson et al., 2004). More recently, the Small World of Words project (SWOW; ???) has sought to capture associations between Dutch words by employing a multiple response technique in contrast to the traditional single response free association task used by Nelson et al. (2004). These norms are now being collected for English words (De Deyne, Navarro, Perfors, Brysbaert, & Storms, 2018).

Similar to association norms, semantic word norms provide researchers with another option of constructing stimuli for use in word-pair tasks. These norms measure the underlying concepts represented by words and allow researchers to tap into aspects of semantic memory. Semantic memory is best described as an organized collection of our general knowledge and contains information regarding a concept's meaning (Hutchison, 2003). Models of semantic memory broadly fall into one of two categories. Connectionist models (e.g., Rogers & McClelland, 2006; Rumelhart, McClelland, & Group, 1986) portray semantic memory as a system of interconnected units representing concepts, which are linked together by weighted connections representing knowledge. By triggering the input units, activation will then spread throughout the system activating or suppressing connected units based on the weighted strength of the corresponding unit connections (Jones, Willits, & Dennis, 2015). On the other hand, distributional models of semantic memory posit that semantic representations are created through the co-occurrences of words together in a body of text and suggest that words with similar meanings will appear together in similar contexts (Riordan & Jones, 2011). Popular distributional models of semantic memory include Latent Semantic Analysis (LSA; Landauer & Dumais, 1997) and the Hyperspace Analogue to Language (HAL; Lund & Burgess, 1996).

Feature production tasks are a common means of producing semantic word norms (Buchanan, Holmes, Teasley, & Hutchison, 2013; McRae, Cree, Seidenberg, & McNorgan, 2005; Vinson & Vigliocco, 2008). In such tasks, participants are shown the name of a concept and are asked to list what they believe the concept's most important features to be (McRae et al., 2005). Several statistical measures have been developed which measure the degree of feature overlap between concepts. Similarity between any two concepts can be measured by representing them as vectors and calculating the cosine value (COS) between them (Maki, McKinley, & Thompson, 2004). Cosine values range from 0 (unrelated) to 1 (perfectly related). For example, the pair *hornet* - *wasp* has a COS of .88, indicating a high degree of overlap between the two concepts. Feature overlap can also be measured by JCN, which

involves calculating the information content value of each concept and the lowest super-ordinate shared by each concept using an online dictionary, such as WordNET (Miller, 1995). The JCN value is then computed by summing together the difference of each concept and its lowest super-ordinate (Jiang & Conrath, 1997; Maki et al., 2004). The advantage to using COS values over JCN values is the limitation of JCN being tied to a somewhat static dictionary database, while a semantic feature production task can be used on any concept to calculate COS values. However, JCN values are less time consuming to obtain if both concepts are in the database (Buchanan et al., 2013).

Semantic relations can be broadly described as being taxonomic or thematic in nature. Whereas taxonomic relationships focus on the connections between features and concepts within categories (e.g., *bird - pigeon*), thematic relationships center around the links between concepts and an overarching theme or scenario (e.g., *bird - nest*; Jones & Golonka, 2012). Jouravlev and McRae (2016) provide a list of 100 thematic relatedness production norms, which were generated through a task similar to feature production in which participants were presented with a concept and were asked to list names of other concepts they believed to be related. Distributional models of semantic memory also lend themselves well to the study of thematic word relations. Because these models are text-based and score word pair relations in regard to their overall context within a document, they assess thematic knowledge as well as semantic knowledge. Additionally, text-based models such as LSA are able to account for both the effects of context and similarity of meaning, bridging the gap between associations and semantics (Landauer, Foltz, Laham, Folt, & Laham, 1998).

Discussion of these measures then leads to the question of whether each one truly assesses some unique concept or if they simply tap into our overall linguistic knowledge. Taken at face value, word pair associations and semantic word relations appear to be vastly different, yet the line between semantics/associations and thematics is much more blurred. While thematic word relations are indeed an aspect of semantic memory and include word

co-occurrence as an integral part of their creation, themes also appear to be indicative of a separate area of linguistic processing. Previous research by Maki and Buchanan (2008) appears to confirm this theory. Using clustering and factor analysis techniques, they analyzed multiple associative, semantic, and text-based measures of associative and semantic knowledge. First, their findings suggested associative measures to be separate from semantic measures. Additionally, semantic information derived from lexical measures (e.g., COS, JCN) was found to be separate from measures generated from analysis of text corpora, suggesting that text-based measures may be more representative of thematic information.

While it is apparent that these word relation measures are assessing different domains of our linguistic knowledge, care must be taken when building experimental stimuli through the use of normed databases, as many word pairs overlap on multiple types of measurements. For example, some of the first studies on semantic priming used association word norms for stimuli creation (Lucas, 2000; Meyer & Schvaneveldt, 1971; Meyer, Schvaneveldt, & Ruddy, 1975). This observation becomes strikingly apparent when one desires the creation of word pairs related on only one dimension. One particular difficulty faced by researchers comes when attempting to separate association strength from feature overlap, as highly associated items tend to be semantically related as well. Additionally, a lack of association strength between two items may not necessarily be indicative of a total lack of association, as traditional norming tasks typically do not produce a large enough set of responses to capture all available associations between items. Some items with extremely weak associations may inevitably slip through the cracks (Hutchison, 2003). As such, the present study seeks to provide further insight by examining how different levels of associative overlap (measured in FSG), semantic overlap (feature overlap measured with COS), and thematic overlap (measured with LSA) affect cognitive tasks such as short term item retrieval and item relatedness judgments. Instead of focusing solely on one variable or trying to create stimuli that represent only one form of relatedness, we included a range of each of these variables to explore their potential interaction.

Specifically, this research was conceptualized within the framework of a three-tiered view of the interconnections between these systems as it relates to processing concept information. The three-tiered view is inspired by models of reading and naming, particularly the triangle models presented by Seidenberg and McClelland (1989) and Plaut (1995). These models explored the nature of reading as bidirectional relations between semantics, orthography, and phonology. In this research, we examine if the associative, semantic, and thematic systems are interactive for judgment and recall processes, much like the proposed interactive nature of phonology, orthographics, and semantics for reading and naming processes. Potentially, association, semantic, and thematic facets of word relation each provide a unique contribution that can be judged and used for memory, thus, suggesting three separate networks of independent information. This view seems unlikely, in that research indicates that there is often overlap in the information provided by each measure of word-pair relatedness. Instead, dynamic attractor networks, as proposed by Hopfield (1982) and McLeod, Shallice, and Plaut (2000) may better represent the interplay between these representations of concepts, as these models posit a similar feedback relationship between concepts in a network. Using these models as a theoretical framework for our study, we sought to understand how these three types of word-pair information may interact when judgment and recall processes were applied to concept networks, and use it as a framework for exploring how associative, semantic, and thematic memory networks share interconnections. Therefore, this study provides evidence of the structure and interplay between different forms of network relations for two cognitive tasks of judgment and retrieval and will shed light on the underlying processing for each task.

Application to Judgment Studies

Traditional judgment of learning tasks (JOL) can be viewed as an application of the PAL paradigm; participants are given pairs of items and are asked to judge how accurately

they would be able to correctly respond with the target with the cue on a recall task. Judgments are typically made out of 100, with a participant response of 100 indicating full confidence in recall ability. In their 2005 study, Koriat and Bjork examined overconfidence in JOLs by manipulating associative relations (FSG) between word-pairs and found that subjects were more likely to overestimate recall for pairs with little or no associative relatedness. Additionally, this study found that when accounting for associative direction, subjects were more likely to overestimate recall for pairs that were high in backwards strength but low in forward strength. To account for this finding, the authors suggested that JOLs may rely more heavily on overlap between cue and target with the direction of the associative relationship being secondary. Take for example the pair *feather - bird*, which has a FSG of .051 and a BSG of .359. This item pair also has a cosine value of .272 (suggesting low to moderate feature overlap) and an LSA score of .517 (suggesting moderate thematic overlap). As such, some of the overconfidence in JOLs may be attributed to more than just item associations. Paired items may also be connected by similar themes or share certain features, resulting in inflated JOLs.

Expanding upon this research, the traditional judgment of learning task (JOL) can be manipulated to investigate perceptions of word pair relationships by having participants judge how related they believe the cue and target items to be (Maki, 2007a, 2007b). The judged values generated from this task can then be compared to the normed databases to create a similar accuracy function or correlation as is created in JOL studies. When presented with the item pair, participants are asked to estimate the number of people out of 100 who would provide the target word when shown only the cue (Maki, 2007b), which mimics how association word norms are created through free association tasks. Maki (2007a) investigated such judgments within the context of associative memory by having participants rate how much associative overlap was shared between normed item pairs and found that responses were greatly overestimated relative to the actual normed overlap strength for pairs that were weak associates, while underestimated for strong associates, thus replicating the

Koriat and Bjork (2005) findings for relatedness judgments based upon associative memory, rather than judgments based on learning.

This discrepancy between free association strength and JAM ratings is noteworthy because on the surface, the two tasks should each be tapping into the concept of associative overlap. One explanation for this provided by Maki (2007a) is that judgment tasks are more easily influenced by outside factors such as the availability heuristic. Alternatively, it may be that viewing the cue-target pair together at the time of judgment interferes with individuals' ability to consider other target words that are related to the cue, thereby inflating (or reducing) the perceived relatedness between the items (Maki, 2007a). Indeed, work by (Nelson & Dunlosky, 1991) has shown this to be the case when eliciting judgments of learning, as JOLs made after a delay tend to be more accurate relative to those made immediately in the presence of the studied information.

The judgment of associative memory (JAM) function provides one means of visualizing the influence various cognitive biases have on associative memory judgments. By plotting the judged values against the word pair's normed associative strength, a fit line can be calculated which displays the calibration of JAM ratings relative to normed associative strength. This JAM function characteristically has a high intercept (bias) with a shallow slope (sensitivity). Figure 1 illustrates this function. Overall, the JAM function has been found to be highly reliable and generalized well across multiple variations of the study, with item characteristics such as word frequency, cue set size (QSS), and semantic similarity all having a minimal influence on it (Maki, 2007b). Furthermore, an applied meta-analysis of more than ten studies on JAM indicated that bias and sensitivity are nearly unchangeable, often hovering around 40-60 points for the intercept and .20-.30 for the slope (Valentine & Buchanan, 2013). Additionally, Valentine and Buchanan (2013) extended this research to include judgments of semantic memory with the same results.

The present study combined the paradigms of PAL, JOLs, and JAM to examine item

recall and judgments for three types of judgments of relatedness (JORs) with the goal of exploring the underlying memory network that is used for each of these cognitive processes as described above. To date, no study has examined the effects of these three types of information on cognitive processes like judgments and recall within the context of one unified study. As such, we tested four hypotheses based on previous research on JAM and semantic memory models.

First, we sought to expand previous Maki (2007b), Maki (2007a), Buchanan (2010), and Valentine and Buchanan (2013) research to include three types of JORs in one experiment, while replicating JAM bias and sensitivity findings. We used the three database norms for association, semantics, and thematics to predict each type of JOR and calculated average slope and intercept values for each participant. We expected to find slope and intercept values that were significantly different from zero. Though the three types of word relations are distinct from one another, we should expect to find slopes and intercepts for semantic and thematic JORs to be within the range of previous JAM findings if these memory systems are interconnected. We also examined the frequency of each predictor being the strongest variable to predict its own judgment condition (i.e., how often association was the strongest predictor of associative JORs, etc.). Thus, we are interested in exploring whether judgment findings replicate across a range of variables and covariates (rather than each individually, as tested in previous JOL and JAM publications), which expands our knowledge on how the judgment process taps into the underlying memory network.

Next, we explored the predictions from semantic network models that the relation between association, semantics, and thematics would be bidirectional in nature (i.e., the three-tiered hypothesis of each type of knowledge interconnected in memory). Therefore, we expected to find an interaction between database norms when predicting JORs. We used multilevel modeling to examine the interaction of database norms for association, semantics, and thematics in relation to participant judgments.

We then extended these analyses to include recall as the dependent variable of interest. We tested for the interaction of database norms in predicting recall by using a multilevel logistic regression, while controlling for judgment condition and rating. We expected to find that database norms would show differences in recall based on the levels of other variables (the interaction would be significant), and that ratings would also positively predict recall (i.e., words that participants thought were more related would be remembered better). Because judgment and recall are different cognitive processes, we used this hypothesis to examine how memory networks may be differently interactive for memory in comparison to judgment.

Finally, we examined if the judgment slopes from Hypothesis 1 would be predictive of recall. Whereas the recall model examined the direct relationship of word relatedness on recall, the goal of this hypothesis was to explore whether participant sensitivity to word relatedness was could also predict recall. For this analysis, we used a multilevel logistic regression to control for multiple judgment slope conditions. This hypothesis combines both cognitive processes into one analysis, to explore how judgment ability (i.e., slopes) would impact the memory process.

Method

Participants

A power analysis was conducted using the *simR* package in *R* (Green & MacLeod, 2016). This package uses simulations to generate power estimates for mixed linear models created from the *lme4* package in *R* (Bates, Mächler, Bolker, & Walker, 2015). The results of this analyses suggested a minimum of 35 participants would be required to detect an effect. However, because power often tends to be underestimated, we extended participant recruitment as funding permitted. In total, 112 participants took part in this study.

Participants were recruited from Amazon’s Mechanical Turk, which is a website that allows individuals to host projects and connects them with a large pool of respondents who complete them for small amounts of money (Buhrmester, Kwang, & Gosling, 2011). Participant responses were screened for a basic understanding of the study’s instructions. Responses were rejected for participants who entered related words when numerical judgment responses were required, and for participants who responded to the cue words during the recall phase with sentences or phrases instead of individual words. Those that completed the study correctly were compensated \$1.00 for their participation.

Materials

The stimuli used were sixty-three words pairs of varying associative, semantic, and thematic relatedness which were created from the Buchanan et al. (2013) word norm database and website. Associative relatedness was measured with Forward Strength (FSG), which is the probability that a cue word will elicit a desired target word (Nelson et al., 2004). This variable ranges from zero to one wherein zero indicates no association, while one indicates that participants would always give a target word in response to the cue word. Semantic relatedness was measured with cosine (COS), which is a measure of semantic feature overlap (Buchanan et al., 2013; McRae et al., 2005; Vinson & Vigliocco, 2008). This variable ranges from zero to one where zero indicates no shared semantic features between concepts and higher numbers indicate more shared features between concepts. Thematic relatedness was calculated with Latent Semantic Analysis (LSA), which generates a score based upon the co-occurrences of words within a document (Landauer & Dumais, 1997; Landauer et al., 1998). LSA values also range from zero to one, indicates no co-occurrence at the low end and higher co-occurrence with higher values. These values were chosen to represent these categories based on face validity and previous research on how word pair psycholinguistic variables overlap (Maki & Buchanan, 2008).

The selected stimuli included a range of values for each variable. Table 1 displays stimuli averages, *SD*, and ranges. A complete list of stimuli can be found at <http://osf.io/y8h7v>. The stimuli were arranged into three blocks for each judgment condition described below wherein each block contained 21 word pairs. Due to limitations of the available stimuli, blocks were structured so that each one contained seven word pairs of low (0-.33), medium (.34-.66), and high (.67-1.00) COS relatedness. Because of this selection process, FSG and LSA strengths are contingent upon the selected stimuli's COS strengths. We selected stimuli within the cosine groupings to cover a range of FSG and LSA values, but certain combinations are often difficult to achieve. For example, there are only four word-pairs that are both high COS and high FSG, thus limiting the ability to manipulate LSA. The study was built online using Qualtrics, and three surveys were created to counter-balance the order in which judgment conditions appeared. Each word pair appeared counter-balanced across each judgment condition, and stimuli were randomized within each block.

Procedure

The present study was divided into three phases. In the first phase, JORs were elicited by presenting participants with word pairs and asking them to make judgments of how related they believed the words in each pair to be. This judgment phase consisted of three blocks of 21 word pairs which corresponded to one of three types of word pair relationships: associative, semantic, or thematic. Each block was preceded by a set of instructions explaining one of the three types of relationships, and participants were provided with examples which illustrated the type of relationship to be judged. Participants were then presented with the word pairs to be judged. The associative block began by explaining associative memory and the role of free association tasks. Participants were provided with examples of both strong and weak associates. For example, *lost* and *found* and were

presented as an example of a strongly associated pair, while *article* was paired with *newspaper*, *the*, and *clothing* to illustrate that words can have many weak associates. The semantic judgment block provided participants with a brief overview of how words are related by meaning and showed examples of concepts with both high and low feature overlap. *Tortoise* and *turtle* were provided as an example of two concepts with significant overlap. Other examples were then provided to illustrate concepts with little or no overlap. For the thematic judgments, participants were provided with an explanation of thematic relatedness. *Tree* is explained to be related to *leaf*, *fruit*, and *branch*, but not *computer*. Participants were then given three concepts (*lost*, *old*, *article*) and were asked to come up with words that they feel are thematically related.

After viewing the examples at the start of the block, participants completed the JOR task. Each block contained a set of instructions which were contingent upon the type of JOR being elicited. For example, instructions in the associative block asked participants to estimate how many individuals out of 100 they expect would respond to the cue word with a given target, instructions for semantic JORs asked participants to indicate the percent of features shared between two concepts, and instructions for the thematic JOR task asked participants to base ratings on how likely to words would be used together in the same story. The complete experiment can be found at <http://osf.io/y8h7v>, which contains the exact instructions given to participants for each block and displays the structure of the study. All instructions were modeled after Buchanan (2010) and Valentine and Buchanan (2013).

In accordance with previous work on JOLs and JAM, participants made JOR ratings using a scale of zero to one hundred, with zero indicating no relationship, and one hundred indicating a perfect relationship. Participants typed their responses into the survey. Once completed, participants then completed the remaining judgment blocks in the same manner. Each subsequent judgment block changed the type of JOR being made. Three versions of the study were created, which counter-balanced the order in which the judgment blocks

appeared, and participants were randomly assigned to a survey version. This resulted in each word pair receiving a relatedness judgments on each of the three types relationships.

After completing the judgment phase, participants were then presented with a short distractor task to account for recency effects. In this section, participants were presented with a randomized list of the fifty U.S. states and were asked to arrange them in alphabetical order. This task was timed to last two minutes. Once time had elapsed, participants automatically progressed to the final phase, which consisted of a cued-recall task. Participants were presented with each of the 63 cue words from the judgment phase and were asked to complete each word pair by responding with the correct target word. Participants were informed that they would not be penalized for guessing. The cued-recall task included all stimuli in a random order.

Results

Data Processing and Descriptive Statistics

First, the results from the recall phase of the study was coded as zero for incorrect responses, one for correct responses, and NA for participants who did not complete the recall section (all or nearly all responses were blank). All word responses to judgment items were deleted and set to missing data. The final dataset was created by splitting the initial data file into six sections (one for each of the three experimental blocks and their corresponding recall scores). Each section was individually melted using the *reshape* package in *R* (Wickham, 2007) and was written as a csv file. The six output files were then combined to form the final dataset. Code is available on our OSF page embedded inline with the manuscript in an *R* markdown document written with the *papaja* package (Aust & Barth, 2017). With 112 participants, the dataset in long format included 7,056 rows of potential data (i.e., 112 participants * 63 JORs). One out of range JOR data point (> 100) was

corrected to NA. Missing data for JORs or recall were then excluded from the analysis, which included word responses to judgment items (i.e., responding with *cat* instead of a number when prompted to provide a JOR). These items usually excluded a participant from receiving Amazon Mechanical Turk payment, but were included in the datasets found online. In total, 787 data points were excluded (188 JOR only, 279 recall only, 320 both), leading to a final N of 105 participants and 6,269 observations. Recall and JOR values were then screened for outliers using Mahalanobis distance at $p < .001$, and no outliers were found (Tabachnick & Fidell, 2012). To screen for multicollinearity, we examined correlations between judgment items, COS, LSA, and FSG. All correlations were $r_s < .50$.

```
## [1] 13.81551
```

```
## [1] 2
```

```
##      Mode      TRUE      NA's
```

```
## logical    6269      787
```

```
## [1] 32
```

```
## [1] 32
```

```
##
```

```
## Associative      Semantic      Thematic
```

```
##           1533           1533           1533
```

```
##
```

```
## Associative      Semantic      Thematic
```

```
##           1533           1533           1533
```

```
## Warning: Converting "Partno" to factor for ANOVA.
```

```
## Warning: Collapsing data to cell means. *IF* the requested effects are a
```

```

415 ## subset of the full design, you must use the "within_full" argument, else
416 ## results may be inaccurate.

417 ## $ANOVA
418 ##           Effect DFn DFd           F           p p<.05           ges
419 ## 2 Judgment.Type    2 144 21.91932 4.893106e-09      * 0.09835317
420 ##
421 ## `$Mauchly's Test for Sphericity`
422 ##           Effect           W           p p<.05
423 ## 2 Judgment.Type 0.8788522 0.01020967      *
424 ##
425 ## `$Sphericity Corrections`
426 ##           Effect      GGe      p[GG] p[GG]<.05      HFe      p[HF]
427 ## 2 Judgment.Type 0.891943 2.669709e-08      * 0.9130645 1.915619e-08
428 ##      p[HF]<.05
429 ## 2      *

430 ##
431 ## Pairwise comparisons using t tests with pooled SD
432 ##
433 ## data: judge2$Score and judge2$Judgment.Type
434 ##
435 ##           Associative Semantic
436 ## Semantic 4.3e-16      -
437 ## Thematic < 2e-16      0.0015
438 ##
439 ## P value adjustment method: bonferroni

440 ##           Associative Semantic

```

```

441 ## Semantic      8.29354      NA
442 ## Thematic      11.78035 3.486807

443 ## Warning: Converting "Partno" to factor for ANOVA.
444
445 ## Warning: Collapsing data to cell means. *IF* the requested effects are a
446 ## subset of the full design, you must use the "within_full" argument, else
447 ## results may be inaccurate.

448 ## $ANOVA
449 ##           Effect DFn DFd      F      p p<.05      ges
450 ## 2 Judgment.Type    2 144 2.21907 0.1124147      0.006311687
451 ##
452 ## $`Mauchly's Test for Sphericity`
453 ##           Effect      W      p p<.05
454 ## 2 Judgment.Type 0.9891635 0.6792297
455 ##
456 ## $`Sphericity Corrections`
457 ##           Effect      GGe      p[GG] p[GG]<.05      HFe      p[HF] p[HF]<.05
458 ## 2 Judgment.Type 0.9892797 0.1130234      1.01708 0.1124147

```

459 The mean JOR for the associative condition ($M = 58.74$, $SD = 30.28$) was lower than
 460 the semantic ($M = 66.98$, $SD = 28.31$) and thematic ($M = 71.96$, $SD = 27.80$) conditions.
 461 Recall averaged over 60% for all three conditions: associative $M = 63.40$, $SD = 48.18$;
 462 semantic $M = 68.02$, $SD = 46.65$; thematic $M = 64.89$, $SD = 47.74$. To confirm these
 463 patterns, two one-way ANOVAs were used to test for differences between mean JOR rates
 464 and mean correct percent recall for each of the three judgment conditions. Overall, a
 465 significant main effect of judgment type was detected for JORs ($F(2, 144) = 21.92$), $p <$
 466 $.001$, $\eta p^2 = 0.10$), and a post-hoc pairwise t -test indicated that all comparisons were

significant ($ts > 3.48$, $ps < .002$) No significant difference was found between groups for mean correct recall ($F(2, 144) = 2.22$, $p = .112$, $\eta p^2 = 0.01$).

JAM Slope Bias and Sensitivity

First, we sought to replicate bias and sensitivity findings from previous research while expanding the JAM function to include judgments based on three types of memory. FSG, COS, and LSA were used to predict each type of relatedness judgment. JOR values were divided by 100, so as to place them on the same scale as the database norms. Slopes and intercepts were then calculated for each participant's ratings for each of the three JOR conditions, as long as they contained at least nine data points out of the twenty-one that were possible. Single sample t -tests were then conducted to test if slope and intercept values significantly differed from zero. See Table 2 for means and standard deviations. Slopes were then compared to the JAM function, which is characterized by high intercepts (between 40 and 60 on a 100 point scale) and shallow slopes (between 20 and 40). Because of the scaling of our data, to replicate this function, we should expect to find intercepts ranging from .40 to .60 and slopes in the range of 0.20. to 0.40. Intercepts for associative, semantic, and thematic JORs were each significant, and all fell within or near the expected range. Overall, thematic JORs had the highest intercept at .656, while JORs elicited in the associative condition had the lowest intercept at .511.

The JAM slope was successfully replicated for FSG in the associative JOR condition, with FSG significantly predicting association, although the slope was slightly higher than expected at .491. COS and LSA did not significantly predict association. For semantic judgments, each of the three database norms were significant predictors. However, JAM slopes were not replicated for this judgment type, as FSG had the highest slope at .118, followed by LSA .085, and then COS .059. These findings were mirrored for thematic JORs, as each database norm was a significant predictor, yet slopes for each predictor fell below

range of the expected JAM slopes. Again, FSG had the highest slope, this time just out of range at .192, followed closely by LSA at .188. Interestingly, COS slopes were found to be negative for this judgment condition, -.081. Overall, although JAM slopes were not successfully replicated in each JOR condition, the high intercepts and shallow slopes present across conditions are still indicative of overconfidence and insensitivity in participant JORs.

Additionally, we examined the frequency that each predictor variable was the strongest predictor for each of the three JOR conditions. For the associative condition, FSG was the strongest predictor for 64.0% of the participants, with COS and LSA being the strongest for only 16.0% and 20.0% of participants respectively. These differences were less distinct when examining the semantic and thematic JOR conditions. In the semantic condition, FSG was highest at 44.1% of participants, LSA was second at 32.4%, and COS was least likely at 23.5%. Finally, in the thematic condition, LSA was most likely to be the strongest predictor with 44.6% of participants, with FSG being the second most likely at 36.6%, and COS again being least likely at 18.8%. Interestingly, in all three conditions, COS was least likely to be the strongest predictor, even in the semantic condition. Therefore, these results provide evidence of the nature of judgments on the memory network as each judgment type appeared to tap each tier differently, suggesting a three-part system, rather than one large, encompassing memory network.

Interaction between Norms when Predicting Judgments of Relatedness

The goal of next analysis was to test for an interaction between the three overlap norms when predicting participant JORs to examine the bidirectional network model. First, the database norms were mean centered to control for multicollinearity. The *nlme* package and *lme* function were used to calculate these analyses (Pinheiro, Bates, Debroy, Sarkar, & Team, 2017). A maximum likelihood multilevel model was used to test the interaction between FSG, COS, and LSA when predicting JOR values, with participant number used as

the random intercept factor. The type of JOR being elicited was controlled for, so as to better assess the impact of each word overlap measure regardless of JOR condition. Multilevel models were used to retain all data points (rather than averaging over items and conditions) while controlling for correlated error due to participants, which makes these models advantageous for multiway repeated measures designs (Gelman, 2006). This analysis resulted in a significant three-way interaction between FSG, COS, and LSA ($\beta = 3.324$, $p < .001$), which is examined below in a simple slopes analysis. Table 3 includes values for main effects, two-way, and three-way interactions.

To investigate this interaction, simple slopes were calculated for low, average, and high levels of COS. This variable was chosen for two reasons: first, it was found to be the weakest of the three predictors in hypothesis one, and second, manipulating COS would allow us to track changes across FSG and LSA. Significant two-way interactions were found between FSG and LSA at both low COS ($\beta = -1.492$, $p < .001$), average COS ($\beta = -0.569$, $p < .001$), and high COS ($\beta = 0.355$, $p = .013$). A second level was then added to the analysis in which simple slopes were created for each level of LSA, allowing us to assess the effects of LSA at different levels of COS on FSG. When both COS and LSA were low, FSG significantly predicted JOR values ($\beta = 0.663$, $p < .001$). At low COS and average LSA, FSG decreased but still significantly predicted JORs ($\beta = 0.375$, $p < .001$). However, when COS was low and LSA was high, FSG was not a significant predictor ($\beta = 0.087$, $p = .079$). A similar set of results was found at the average COS level. When COS was average and LSA was LOW, FSG was a significant predictor, ($\beta = 0.381$, $p < .001$). As LSA increased at average COS levels, FSG decreased in strength: average COS, average LSA FSG ($\beta = 0.355$, $p = .013$) and average COS, high LSA FSG ($\beta = 0.161$, $p < .001$). This finding suggests that at low COS, LSA and FSG create a seesaw effect in which increasing levels of thematics is counterbalanced by decreasing importance of association when predicting JORs. FSG was not a significant predictor when COS was high and LSA was low ($\beta = 0.099$, $p = .088$). At high COS and average LSA, FSG significantly predicted JORs ($\beta = 0.167$, $p < .001$), and finally

when both COS and LSA were high, FSG increased and was a significant predictor of JOR values ($\beta = 0.236, p < .001$). Thus, at high levels of semantic overlap, associative and thematic overlap are complementary when predicting JOR ratings, increasing together as semantic strength increases. Figure 2 displays the three-way interaction wherein the top row of figures indicates the seesaw effect, as thematic strength increases, the predictive ability of associative overlap decreases in strength. The bottom row indicates the complementary effect where increases in LSA occur with increases in FSG predictor strength. Therefore, the cognitive process of judgment appears to be interactive in nature across these three types of memory information.

Interaction between Norms when Predicting Recall

Given the results of Hypothesis 2, we then sought to extend the analysis to participant recall scores. A multilevel logistic regression was used with the *lme4* package and *glmer()* function (Pinheiro et al., 2017), testing the interaction between FSG, COS, and LSA when predicting participant recall. As with the previous hypothesis, we controlled for JOR condition and, additionally, covaried JOR ratings. Participants were used as a random intercept factor. Judged values were a significant predictor of recall, ($\beta = 0.686, p < .001$) where increases in judged strength predicted increases in recall. A significant three-way interaction was detected between FSG, COS, and LSA ($\beta = 24.571, p < .001$). See Table 4 for main effects, two-way, and three-way interaction values.

The same moderation process used in Hypothesis 2 was then repeated, with simple slopes first calculated at low, average, and high levels of COS. This set of analyses resulted in significant two-way interactions between LSA and FSG at low COS ($\beta = -7.845, p < .001$) and high COS ($\beta = 5.812, p = .009$). No significant two-way interaction was found at average COS ($\beta = -1.017, p = .493$). Following the design used when predicting JORs, simple slopes were then calculated for low, average, and high levels of LSA at the low and

high levels of COS, allowing us to assess how FSG affects recall at varying levels of both COS and LSA. When both COS and LSA were low, FSG was a significant predictor of recall ($\beta = 4.116, p < .001$). At low COS and average LSA, FSG decreased from both low levels, but was still a significant predictor ($\beta = 2.601, p < .001$), and finally, low COS and high LSA, FSG was the weakest predictor of the three ($\beta = 1.086, p = .030$). As with Hypothesis 2, LSA and FSG counterbalanced one another, wherein the increasing levels of semantics led to a decrease in the importance of association in predicting recall. At high COS and low LSA, FSG was a significant predictor ($\beta = 2.447, p = .004$). When COS was high and LSA was average, FSG increased as a predictor and remained significant ($\beta = 3.569, p < .001$). This finding repeated when both COS and LSA were high, with FSG increasing as a predictor of recall ($\beta = 4.692, p < .001$). Therefore, at high levels of semantics, semantics, semantics and association are complementary predictors of recall, increasing together and extending the findings of Hypothesis 2 to participant recall. Figure 3 displays the three-way interaction. The top left figure indicates the counterbalancing effect of recall of LSA and FSG, while the top right figure shows no differences in simple slopes for average levels of cosine. The bottom left figure indicates the complementary effects where LSA and FSG increase together as predictors of recall at high COS levels.

Predicting Recall with JAM Slopes

In our fourth and final hypothesis, we investigated whether the JOR slopes and intercepts obtained in Hypothesis 1 would be predictive of recall ability. Whereas Hypothesis 3 indicated that word relatedness was directly related to recall performance, this hypothesis instead looked at whether or not participants' sensitivity and bias to word relatedness could be used as a predictor of recall (Maki, 2007b). This analysis was conducted with a multilevel logistic regression, as described in Hypothesis 3, where each database slope and intercept was used as predictors of recall using participant as a random intercept factor. These analyses

were separated by judgment condition, so that each set of JOR slopes and intercepts were used to predict recall. The separation controlled for the number of variables in the equation, as all slopes and intercepts would have resulted in overfitting. These values were obtained from Hypothesis 1 where each participant's individual slopes and intercepts were calculated for associative, semantic, and thematic JOR conditions. Table 2 shows average slopes and intercepts for recall for each of the three types of memory, and Table 5 portrays the regression coefficients and statistics. In the associative condition, FSG slope significantly predicted recall ($b = 0.898$, $p = .008$), while COS slope ($b = 0.314$, $p = .566$) and LSA slope ($b = 0.501$, $p = .278$) were non-significant. In the semantic condition, COS slope ($b = 2.039$, $p < .001$) and LSA slope ($b = 1.061$, $p = .019$) were both found to be significant predictors of recall. FSG slope was non-significant in this condition ($b = 0.380$, $p = .187$). Finally, no predictors were significant in the thematic condition, though LSA slope was found to be the strongest ($b = 0.896$, $p = .090$). This analysis indicated the extent to which the cognitive processes are related to each other as part of the memory network (i.e., judgment sensitivity predicting recall), furthering the previous two analyses, which illustrated the nature of those cognitive processes' relationship with the underlying memory network.

Discussion

This study investigated the relationship between associative, semantic, and thematic word relations and their effect on participant JORs and recall performance through the testing of four hypotheses. In our first hypothesis, we show that bias and sensitivity findings first proposed by Maki (2007a) successfully replicated in the associative condition, with slope and intercept values falling within the expected range. While these findings were not fully replicated when extending the analysis to include semantic and thematic JORs (as slopes in these conditions did not fall within the appropriate range), participants still displayed high intercepts and shallow slopes, suggesting overconfidence in judgment making and an

insensitivity to changes in strength between pairs. Additionally, when looking at the frequency that each predictor was the strongest in making JORs, FSG was the best predictor for both the associative and semantic conditions, while LSA was the best predictor in the thematic condition. In each of the three conditions, COS was the weakest predictor, even when participants were asked to make semantic judgments. This finding suggests that associative relationships seem to take precedence over semantic relationships when judging pair relatedness, regardless of what type of JOR is being elicited. Additionally, this finding may be taken as further evidence of a separation between associative information and semantic information, in which associative information is always processed, while semantic information may be suppressed due to task demands (Buchanan, 2010; Hutchison & Bosco, 2007).

Our second hypothesis examined the three-way interaction between FSG, COS, and LSA when predicting participant JORs. At low semantic overlap, a seesaw effect was found in which increases in thematic strength led to decreases in associative predictiveness. This finding was then replicated in Hypothesis 3 when extending the analysis to predict recall. By limiting the semantic relationships between pairs, an increased importance is placed on the role of associations and thematics when making relatedness judgments or retrieving pairs. In such cases, increasing the amount of thematic overlap between pairs results in thematic relationships taking precedent over associative relationships. However, when semantic overlap was high, a complementary relationship was found in which increases in thematic strength in turn led to increases in the strength of FSG as a predictor. This result suggests that at high semantic overlap, associations and thematic relations build upon one another. Because thematics is tied to both semantic overlap and item associations, the presence of strong thematic relationships between pairs during conditions of high semantic overlap boosts the predictive ability of associative word norms for both recall and JORs.

Finally, our fourth hypothesis used the JOR slopes and intercepts calculated in

Hypothesis 1 to investigate if participants' bias and sensitivity to word relatedness could be used to predict recall. For the associative condition, the FSG slope significantly predicted recall. In the semantic condition, recall was significantly predicted by both the COS and LSA slopes, with COS being the strongest. However, for the thematic condition, although the LSA slope was the strongest, no predictors were significant. One explanation for this finding is that thematic relationships between item pairs act as a blend between associations and semantics. As such, LSA faces increased competition from the associative and semantic database norms when predicting recall in this manner. Additionally, the dominance of FSG when predicting recall in the associative condition may be attributed to word associations being more accessible (and, thus, easier to process) than semantic or thematic relations between pairs.

Overall, our findings indicated the degree to which the processing of associative, semantic, and thematic information impacts retrieval and judgment making tasks and the interactive relationship that exists between these three types of lexical information. While previous research has shown that memory networks are divided into separate systems which handle storage and processing for meaning and association (see ??? for a review), the presence of these interactions suggests that connections exist between these individual memory networks, linking them to one another. As such, we suggest that these memory systems may be connected in such a way as to form a three-tiered, interconnected system. Within this framework, information enters the semantic memory network, which processes features of concepts and provides a means of categorizing items based on the similarity of their features. The associative network adds information for items based on contexts generated by reading or speech. The thematic network then pulls in information based on semantic and associative input to create a mental representation of both the item and its place in the world relative to other concepts.

While this study did not explore the timing or order of information input from each of

these systems of concept information, it may be similar to a dual-route model of reading and naming, in that each system runs in parallel when contributing to the judgment and recall process (Coltheart, Curtis, Atkins, & Haller, 1993). Alternatively, previous research on early linguistic access suggests that these three systems may not be operating completely in unison. For example, The Language and Situated Simulation Theory (LASS, see Barsalou, Santos, Kyle Simmons, and Wilson (2008) for a review) proposes that meaning is derived from the concurrent processing of both linguistic information (e.g., visual stimuli) and modal simulations (i.e., mental imagery related to the stimulus object). According to this theory, when an object is read, both systems become immediately engaged, though the linguistic system is assumed to be faster, because mental representations of linguistic forms are more accessible in memory relative to simulations (Barsalou et al., 2008, Tulving and Thomson (1973)). As the linguistic system becomes activated, it in turn activates related linguistic forms (i.e., associated words). Because word associations play a key role within this linguistic system, associative information may then come online first relative to semantic concept information.

Viewing this model purely through the lens of semantic memory, it draws comparison to dynamic attractor models (Hopfield, 1982; Jones et al., 2015; McLeod et al., 2000). One of the defining features of dynamic attractor models is that they allow for some type of bidirectionally or feedback between connections in the network. In the study of semantic memory, these models are useful for taking into account multiple restraints such as links between semantics and the orthography of the concept in question. Our hypothesis extends this notion as a means of framing how these three memory systems are connected. The underlying meaning of a concept is linked with both information pertaining to its co-occurrences in everyday language and information relating to the general contexts in which it typically appears.

How then does this hypothesis lend itself towards the broader context of

psycholinguistic research? One application of this hypothesis may be models of word recognition. One popular class of models are those based upon Seidenberg and McClelland (1989) “triangle model” (see Harley, 2008 for a review). The key feature of these models is that they recognize speech and reading based upon the orthography, phonology, and meaning of words in a bidirectional manner, similar to the models described above. Harm and Seidenberg (2004) developed a version which included a focus on semantics, with word meaning being related to input from the orthography and phonology components of the model. Our findings from the present study further suggest that thematic and associative knowledge is incorporated with meaning. One way of framing our results within this literature is to consider the semantic section of the triangle model as being comprised of this interconnected system, and that concept information is processed to some degree on each of these domains. One area for future studies of this nature may be investigating how aspects of orthography and phonology impact these memory networks.

Finally, future studies may wish to consider elements of thematic and associative knowledge when examining semantic based tasks, such as word recognition and reading, as thematic and associative information is interconnected with the semantic network. Finally, to fully understand the the interplay of associatitive, semantic, and thematic networks, it will be necessary to control to for several types of word properties (e.g., item frequency, concreteness, etc.) as these properties have been shown to influence judgments and recall. Ultimately, our findings show that these three lexical networks are highly related suggest they are individual components of an interconnected system.

Compliance with Ethical Standards

The authors declare that they have no conflict of interest. The study was approved by the Institutional Review Board at Missouri State University. Participants filled out an informed consent at the beginning of the study, after accepting the HIT on Mechanical Turk.

⁷²² The complete study with consent form can be found on our OSF page: <http://osf.io/y8h7v>.

References

- Aust, F., & Barth, M. (2017). papaja: Create APA manuscripts with R Markdown. Retrieved from <https://github.com/crsh/papaja>
- Barsalou, L. W., Santos, A., Kyle Simmons, W., & Wilson, C. D. (2008). Language and simulation in conceptual processing BT - Symbols and Embodiment: Debates on Meaning and Cognition. Retrieved from papers2://publication/uuid/7F8373D8-9080-4456-A964-4E8066D74753
- Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, 67(1), 1–48. doi:10.18637/jss.v067.i01
- Buchanan, E. M. (2010). Access into memory: Differences in judgments and priming for semantic and associative memory. *Journal of Scientific Psychology*, March, 1–8.
- Buchanan, E. M., Holmes, J. L., Teasley, M. L., & Hutchison, K. A. (2013). English semantic word-pair norms and a searchable Web portal for experimental stimulus creation. *Behavior Research Methods*, 45(3), 746–757. doi:10.3758/s13428-012-0284-z
- Buhrmester, M., Kwang, T., & Gosling, S. D. (2011). Amazon’s Mechanical Turk. *Perspectives on Psychological Science*, 6(1), 3–5. doi:10.1177/1745691610393980
- Chow, B. W.-Y. (2014). The differential roles of paired associate learning in Chinese and English word reading abilities in bilingual children. *Reading and Writing*, 27(9), 1657–1672. doi:10.1007/s11145-014-9514-3
- Coltheart, M., Curtis, B., Atkins, P., & Haller, M. (1993). Models of reading aloud: Dual-route and parallel-distributed-processing approaches. *Psychological Review*,

100(4), 589–608. doi:10.1037/0033-295X.100.4.589

De Deyne, S., Navarro, D. J., Perfors, A., Brysbaert, M., & Storms, G. (2018). *Measuring the associative structure of English: The “Small World of Words” norms for word association.*

Gelman, A. (2006). Multilevel (hierarchical) modeling: What it can and cannot do. *Technometrics*, 48(3), 432–435. doi:10.1198/0040170050000000661

Green, P., & MacLeod, C. J. (2016). SIMR: an R package for power analysis of generalized linear mixed models by simulation. *Methods in Ecology and Evolution*, 7(4), 493–498. doi:10.1111/2041-210X.12504

Harley, T. (2008). *The psychology of language: From data to theory* (Third.). New York: Psychology Press.

Harm, M. W., & Seidenberg, M. S. (2004). Computing the meanings of words in reading: Cooperative division of labor between visual and phonological processes. *Psychological Review*, 111(3), 662–720. doi:10.1037/0033-295X.111.3.662

Hertzog, C., Kidder, D. P., Powell-Moman, A., & Dunlosky, J. (2002). Aging and monitoring associative learning: Is monitoring accuracy spared or impaired? *Psychology and Aging*, 17(2), 209–225. doi:10.1037/0882-7974.17.2.209

Hopfield, J. J. (1982). Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the National Academy of Sciences*, 79(8), 2554–2558. doi:10.1073/pnas.79.8.2554

Hutchison, K. A. (2003). Is semantic priming due to association strength or feature overlap? A microanalytic review. *Psychonomic Bulletin & Review*, 10(4), 785–813.

doi:10.3758/BF03196544

Hutchison, K. A., & Bosco, F. A. (2007). Congruency effects in the letter search task: Semantic activation in the absence of priming. *Memory & Cognition*, 35(3), 514–525.

doi:10.3758/BF03193291

Jiang, J. J., & Conrath, D. W. (1997). Semantic similarity based on corpus statistics and lexical taxonomy. *Proceedings of International Conference Research on Computational Linguistics (ROCLING X)*. Retrieved from <http://arxiv.org/abs/cmp-lg/9709008>

Jones, L. L., & Golonka, S. (2012). Different influences on lexical priming for integrative, thematic, and taxonomic relations. *Frontiers in Human Neuroscience*, 6(July), 1–17. doi:10.3389/fnhum.2012.00205

Jones, M. N., Willits, J., & Dennis, S. (2015). Models of semantic memory. In Ames T. Townsend & Jerome R. Busemeyer (Eds.), *Oxford handbook of mathematical and computational psychology* (pp. 232–254). Oxford University Press. doi:10.1093/oxfordhb/9780199957996.013.11

Jouravlev, O., & McRae, K. (2016). Thematic relatedness production norms for 100 object concepts. *Behavior Research Methods*, (October 2015), 1349–1357. doi:10.3758/s13428-015-0679-8

Koriat, A., & Bjork, R. A. (2005). Illusions of competence in monitoring one's knowledge during study. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, 31(2), 187–194. doi:10.1037/0278-7393.31.2.187

Landauer, T. K., & Dumais, S. T. (1997). A solution to Plato's problem: The latent semantic analysis theory of acquisition, induction, and representation of knowledge.

Psychological Review, 104(2), 211–240. doi:10.1037//0033-295X.104.2.211

Landauer, T. K., Foltz, P. W., Laham, D., Folt, P. W., & Laham, D. (1998). An introduction to latent semantic analysis. *Discourse Processes*, 25(2), 259–284. doi:10.1080/01638539809545028

Lucas, M. (2000). Semantic priming without association: a meta-analytic review. *Psychonomic Bulletin & Review*, 7(4), 618–630. doi:10.3758/BF03212999

Lund, K., & Burgess, C. (1996). Producing high-dimensional semantic spaces from lexical co-occurrence. *Behavior Research Methods, Instruments, & Computers*, 28(2), 203–208. doi:10.3758/BF03204766

Maki, W. S. (2007a). Judgments of associative memory. *Cognitive Psychology*, 54(4), 319–353. doi:10.1016/j.cogpsych.2006.08.002

Maki, W. S. (2007b). Separating bias and sensitivity in judgments of associative memory. *Journal of Experimental Psychology. Learning, Memory, and Cognition*, 33(1), 231–237. doi:10.1037/0278-7393.33.1.231

Maki, W. S., & Buchanan, E. M. (2008). Latent structure in measures of associative, semantic, and thematic knowledge. *Psychonomic Bulletin & Review*, 15(3), 598–603. doi:10.3758/PBR.15.3.598

Maki, W. S., McKinley, L. N., & Thompson, A. G. (2004). Semantic distance norms computed from an electronic dictionary (WordNet). *Behavior Research Methods, Instruments, & Computers*, 36(3), 421–431. doi:10.3758/BF03195590

McLeod, P., Shallice, T., & Plaut, D. C. (2000). Attractor dynamics in word recognition: converging evidence from errors by normal subjects, dyslexic patients and a

connectionist model. *Cognition*, 74(1), 91–114. doi:10.1016/S0010-0277(99)00067-0

McRae, K., Cree, G. S., Seidenberg, M. S., & McNorgan, C. (2005). Semantic feature production norms for a large set of living and nonliving things. *Behavior Research Methods*, 37(4), 547–559. doi:10.3758/BF03192726

Meyer, D. E., & Schvaneveldt, R. W. (1971). Facilitation in recognizing pairs of words: Evidence of a dependence between retrieval operations. *Journal of Experimental Psychology*, 90(2), 227–234. doi:10.1037/h0031564

Meyer, D. E., Schvaneveldt, R. W., & Ruddy, M. G. (1975). Loci of contextual effects on visual word-recognition. In P. M. A. Rabbitt (Ed.), *Attention and performance v*. London, UK: Academic Press.

Miller, G. A. (1995). WordNet: a lexical database for English. *Communications of the ACM*, 38(11), 39–41. doi:10.1145/219717.219748

Nelson, D. L., McEvoy, C. L., & Dennis, S. (2000). What is free association and what does it measure? *Memory & Cognition*, 28(6), 887–899. doi:10.3758/BF03209337

Nelson, D. L., McEvoy, C. L., & Schreiber, T. A. (2004). The University of South Florida free association, rhyme, and word fragment norms. *Behavior Research Methods, Instruments, & Computers*, 36(3), 402–407. doi:10.3758/BF03195588

Nelson, T. O., & Dunlosky, J. (1991). When people’s judgments of learning (JOLs) are extremely accurate at predicting subsequent recall: The delayed-JOL effect. *Psychological Science*, 2(4), 267–270. doi:10.1111/j.1467-9280.1991.tb00147.x

Paivio, A. (1969). Mental imagery in associative learning and memory. *Psychological Review*, 76(3), 241–263. doi:10.1037/h0027272

Pinheiro, J., Bates, D., Debroy, S., Sarkar, D., & Team, R. C. (2017). nlme: Linear and

833 nonlinear mixed effects models. Retrieved from

834 <https://cran.r-project.org/package=nlme>

835 Plaut, D. C. (1995). Semantic and associative priming in a distributed attractor network.

836 *Proceedings of the 17th Annual Conference of the Cognitive Science Society*, 37–42.

837 Retrieved from

838 http://books.google.com/books?hl=en&lr=&id=CSU{_}Mj07G7UC{\\&}oi=fnd{\\&}pg=P

839 Richardson, J. T. E. (1998). The availability and effectiveness of reported mediators in

840 associative learning: A historical review and an experimental investigation.

841 *Psychonomic Bulletin & Review*, 5(4), 597–614. doi:10.3758/BF03208837

842 Riordan, B., & Jones, M. N. (2011). Redundancy in perceptual and linguistic experience:

843 Comparing feature-based and distributional models of semantic representation.

844 *Topics in Cognitive Science*, 3(2), 303–345. doi:10.1111/j.1756-8765.2010.01111.x

845 Rogers, T. T., & McClelland, J. L. (2006). *Semantic cognition*. Cambridge, MA: MIT Press.

846 Rumelhart, D. E., McClelland, J. L., & Group, P. R. (1986). *Parallel distributed processing:*

847 *Explorations in the microstructure of cognition. Volume 1*. Cambridge, MA: MIT

848 Press.

849 Schwartz, B. L., & Brothers, B. R. (2013). Survival Processing Does Not Improve

850 Paired-Associate Learning. In B. L. Schwartz, M. L. Howe, M. P. Toglia, & H. Otgaar

851 (Eds.), *What is adaptive about adaptive memory?* (pp. 159–171). Oxford University

852 Press. doi:10.1093/acprof:oso/9780199928057.003.0009

853 Seidenberg, M. S., & McClelland, J. L. (1989). A distributed, developmental model of word

854 recognition and naming. *Psychological Review*, 96(4), 523–568.

doi:10.1037//0033-295X.96.4.523

Smythe, P. C., & Paivio, A. (1968). A comparison of the effectiveness of word Imagery and
meaningfulness in paired-associate learning of nouns. *Psychonomic Science*, 10(2),
49–50. doi:10.3758/BF03331401

Tabachnick, B. G., & Fidell, L. S. (2012). *Using multivariate statistics* (Sixth.). Boston, MA:
Pearson.

Tulving, E., & Thomson, D. M. (1973). Encoding specificity and retrieval processes in
episodic memory. *Psychological Review*, 80(5), 352–373. Retrieved from
<http://gureckislab.org/courses/fall15/lhc/readings/TulvingThompson1973.pdf>

Valentine, K. D., & Buchanan, E. M. (2013). JAM-boree: An application of observation
oriented modelling to judgements of associative memory. *Journal of Cognitive
Psychology*, 25(4), 400–422. doi:10.1080/20445911.2013.775120

Vinson, D. P., & Vigliocco, G. (2008). Semantic feature production norms for a large set of
objects and events. *Behavior Research Methods*, 40(1), 183–190.
doi:10.3758/BRM.40.1.183

Wickham, H. (2007). Reshaping data with the reshape package. *Journal of Statistical
Software*, 21(12). doi:10.18637/jss.v021.i12

Table 1

Summary Statistics for Stimuli

Variable	COS Low			COS Average			COS High		
	<i>N</i>	<i>M</i>	<i>SD</i>	<i>N</i>	<i>M</i>	<i>SD</i>	<i>N</i>	<i>M</i>	<i>SD</i>
COS	21	.115	.122	21	.461	.098	21	.754	.059
FSG Low	18	.062	.059	18	.122	.079	17	.065	.067
FSG Average	3	.413	.093	2	.411	.046	2	.505	.175
FSG High	NA	NA	NA	1	.697	NA	2	.744	.002
LSA Low	16	.174	.090	8	.220	.074	7	.282	.064
LSA Average	5	.487	.126	10	.450	.111	12	.478	.095
LSA High	NA	NA	NA	3	.707	.023	2	.830	.102

Note. COS: Cosine, FSG: Forward Strength, LSA: Latent Semantic Analysis.

Table 2

Summary Statistics for Hypothesis 1 t-Tests

Variable	<i>M</i>	<i>SD</i>	<i>t</i>	<i>df</i>	<i>p</i>	<i>d</i>	95% <i>CI</i>
Associative Intercept	.511	.245	20.864	99	< .001	2.086	1.734 - 2.435
Associative COS	-.030	.284	-1.071	99	.287	-0.107	-0.303 - 0.090
Associative FSG	.491	.379	12.946	99	< .001	1.295	1.027 - 1.559
Associative LSA	.035	.317	1.109	99	.270	0.111	-0.086 - 0.307
Semantic Intercept	.587	.188	31.530	101	< .001	3.122	2.649 - 3.592
Semantic COS	.059	.243	2.459	101	.016	0.244	0.046 - 0.440
Semantic FSG	.118	.382	3.128	101	.002	0.310	0.110 - 0.508
Semantic LSA	.085	.304	2.816	101	.006	0.279	0.080 - 0.476
Thematic Intercept	.656	.186	35.475	100	< .001	3.530	3.002 - 4.048
Thematic COS	-.081	.239	-3.405	100	< .001	-0.339	-0.539 - -0.137
Thematic FSG	.192	.306	6.290	100	< .001	0.626	0.411 - 0.838
Thematic LSA	.188	.265	7.111	100	< .001	0.708	0.488 - 0.924

Note. Confidence interval for *d* was calculated using the non-central *t*-distribution.

Table 3

MLM Statistics for Hypothesis 2

Variable	<i>beta</i>	<i>SE</i>	<i>t</i>	<i>p</i>
Intercept	0.603	0.014	43.287	< .001
Semantic Judgments	0.079	0.008	9.968	< .001
Thematic Judgments	0.127	0.008	16.184	< .001
ZCOS	-0.103	0.017	-6.081	< .001
ZLSA	0.090	0.022	4.196	< .001
ZFSG	0.271	0.029	9.420	< .001
ZCOS:ZLSA	-0.141	0.085	-1.650	.099
ZCOS:ZFSG	-0.374	0.111	-3.364	< .001
ZLSA:ZFSG	-0.569	0.131	-4.336	< .001
ZCOS:ZLSA:ZFSG	3.324	0.490	6.791	< .001
Low COS ZLSA	0.129	0.033	3.934	< .001
Low COS ZFSG	0.375	0.049	7.679	< .001
Low COS ZLSA:ZFSG	-1.492	0.226	-6.611	< .001
High COS ZLSA	0.051	0.031	1.647	.100
High COS ZFSG	0.167	0.034	4.878	< .001
High COS ZLSA:ZFSG	0.355	0.143	2.484	.013
Low COS Low LSA ZFSG	0.663	0.078	8.476	< .001
Low COS High LSA ZFSG	0.087	0.049	1.754	.079
Avg COS Low LSA ZFSG	0.381	0.047	8.099	< .001
Avg COS High LSA ZFSG	0.161	0.027	5.984	< .001
High COS Low LSA ZFSG	0.099	0.058	1.707	.088
High COS High LSA ZFSG	0.236	0.023	10.263	< .001

Note. Database norms were mean centered. The table shows main effects and interactions for database norms at low, average, and high levels of COS and LSA when predicting participant judgments.

Table 4

MLM Statistics for Hypothesis 3

Variable	<i>beta</i>	<i>SE</i>	<i>z</i>	<i>p</i>
Intercept	0.301	0.138	2.188	.029
Semantic Judgments	0.201	0.074	2.702	.007
Thematic Judgments	-0.001	0.075	-0.020	.984
Judged Values	0.686	0.115	5.956	< .001
ZCOS	0.594	0.180	3.300	< .001
ZLSA	-0.350	0.204	-1.714	.087
ZFSG	3.085	0.302	10.207	< .001
ZCOS:ZLSA	2.098	0.840	2.497	.013
ZCOS:ZFSG	1.742	1.315	1.325	.185
ZLSA:ZFSG	-1.017	1.481	-0.686	.493
ZCOS:ZLSA:ZFSG	24.571	6.131	4.008	< .001
Low COS ZLSA	-0.933	0.300	-3.108	.002
Low COS ZFSG	2.601	0.470	5.539	< .001
Low COS ZLSA:ZFSG	-7.845	2.169	-3.617	< .001
High COS ZLSA	0.233	0.317	0.737	.461
High COS ZFSG	3.569	0.470	7.589	< .001
High COS ZLSA:ZFSG	5.812	2.231	2.605	.009
Low COS Low LSA ZFSG	4.116	0.745	5.525	< .001
Low COS High LSA ZFSG	1.086	0.501	2.169	.030
High COS Low LSA ZFSG	2.447	0.838	2.920	.004
High COS High LSA ZFSG	4.692	0.388	12.091	< .001

Note. Database norms were mean centered. The table shows main effects and interactions for database norms at low, average, and high levels of COS and LSA when predicting recall.

Table 5

MLM Statistics for Hypothesis 4

Variable	<i>b</i>	<i>SE</i>	<i>z</i>	<i>p</i>
(Intercept)	-0.432	0.438	-0.986	.324
ACOS	0.314	0.548	0.573	.566
ALSA	0.501	0.462	1.084	.278
AFSG	0.898	0.336	2.670	.008
AIntercept	1.514	0.602	2.514	.012
(Intercept)	-0.827	0.462	-1.791	.073
SCOS	2.039	0.517	3.942	< .001
SLSA	1.061	0.454	2.339	.019
SFSG	0.380	0.288	1.320	.187
SIntercept	2.292	0.680	3.371	< .001
(Intercept)	0.060	0.596	0.101	.920
TCOS	0.792	0.564	1.404	.160
TLSA	0.896	0.528	1.696	.090
TFSG	-0.394	0.440	-0.895	.371
TIntercept	1.028	0.753	1.366	.172

Note. Each judgment-database bias and sensitivity predicting recall for corresponding judgment block. A: Associative, S: Semantic, T: Thematic.




Figure 1. JAM slope findings from Maki (2007a). JAM is characterized by a high intercept (between 40 and 60) and a shallow slope (between 0.20 and 0.40). The solid line shows expected results if judgment ratings are perfectly calibrated with association norms.




Figure 2. Simple slopes graph displaying the slope of FSG when predicting JORs at low, average, and high LSA split by low, average, and high COS. All variables were mean centered.




Figure 3. Simple slopes graph displaying the slope of FSG when predicting recall at low, average, and high LSA split by low, average, and high COS. All variables were mean centered.