

# Supplementary materials for EFOMS: Effective, Efficient, and Environmentally Friendly Out-of-Model-Scope Detection Methodology

ANONYMOUS AUTHORS, Institution, Anonymous

## ACM Reference Format:

Anonymous authors. 2018. Supplementary materials for EFOMS: Effective, Efficient, and Environmentally Friendly Out-of-Model-Scope Detection Methodology. *Proc. ACM Meas. Anal. Comput. Syst.* 37, 4, Article 111 (August 2018), 10 pages.  
<https://doi.org/XXXXXX.XXXXXXX>

## 1 Supplementary Material

### 1.1 Image examples and image classes for the CIFAR-10 dataset

The image classes of the CIFAR-10 dataset are displayed in Tbl. 1, and some image examples for illustrating the CIFAR-10 and its OMS datasets are displayed in Fig. 1. The correspondence for the images in each column exists only for the first three rows.

Table 1. CIFAR-10 Image Classes

Label	Description	Label	Description	Label	Description
0	Airplane	1	Automobile	2	Bird
3	Cat	4	Deer	5	Dog
6	Frog	7	Horse	8	Ship
9	Truck				

### 1.2 Image examples for the Tiny-Imagenet dataset

A few image examples for illustrating the Tiny-Imagenet and the Tiny-Imagenet-C are shown in Fig. 2, and there is no correspondence between the images displayed in each column.

### 1.3 Additional accuracy results for the CIFAR-10 dataset using CPND with $tc_{OMS} = 1$

In Fig. 3, 4 and 5, We display the additional accuracy-related results on the distribution shift dataset of CIFAR10 (i.e., CIFAR-10-C) using CPND with  $tc_{OMS} = 1$ . These supplementary results help to justify the choice of  $tc_{OMS}$  described in the paper.

---

Author's Contact Information: Anonymous authors, Institution, Anonymous, Anonymous.

---

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.


© 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM 2476-1249/2018/8-ART111

<https://doi.org/XXXXXX.XXXXXXX>




(a) CIFAR-10 image examples



(b) CIFAR-10-c image examples, the displayed transformations are motion blur s3, fog s4, frost s2 and gaussian noise s5



(c) Adversarial attack examples generated on ResNet34, the displayed attack order is FGSM, DeepFool, Carlini&Wagner and JSMA




(d) Novelty image examples, they are respectively from SVHN, SVHN, DTD, and Places365.

Fig. 1. Image examples of CIFAR-10 and its OMS datasets




(a) Tiny-Imagenet image examples




(b) Tiny-Imagenet-C image examples, the displayed transformations are shot noise s3, defocus blur s4, elastic transform s2, snow s5

Fig. 2. Image examples of Tiny-Imagenet and Tiny-Imagenet-C

1.4 Additional accuracy results for the CIFAR-10 dataset using CPND and deep-KNN with  $tc_{OMS} = 2$ . In Fig. 6-9, We display the additional accuracy-related results on the distribution shift dataset of CIFAR10 (i.e., CIFAR-10-C) using CPND and deep-KNN with  $tc_{OMS} = 2$ .




(a) OMS, Total, and IMS Accuracy using  $CPND_{mc}$  on the CIFAR-10 and CIFAR-10-C datasets for ResNet18





(b) Comparison of accuracy improvements  $Acc_{imp}$  between all the tested methods for CPND (i.e.,  $CPND$ ,  $CPND_{me}$  and  $CPND_{mc}$ ) on the CIFAR-10 and CIFAR-10-C datasets for ResNet18

Fig. 3. ResNet18 Accuracy results on the CIFAR-10 and CIFAR-10-C datasets for CPND with  $tc_{OMS} = 1$











(a) OMS, Total, and IMS Accuracy using  $CPND_{mc}$  on the CIFAR-10 and CIFAR-10-C datasets for ResNet50




(b) Comparison of accuracy improvements  $Acc_{imp}$  between all the tested methods for CPND (i.e.,  $CPND$ ,  $CPND_{me}$  and  $CPND_{mc}$ ) on the CIFAR-10 and CIFAR-10-C datasets for ResNet50

Fig. 7. ResNet50 Accuracy results on the CIFAR-10 and CIFAR-10-C datasets for CPND with  $tc_{OMS} = 2$



(a) OMS, Total, and IMS Accuracy using  $deep-KNN_{mc}$  on the CIFAR-10 and CIFAR-10-C datasets for ResNet18



(b) Comparison of accuracy improvements  $Acc_{imp}$  between all the tested methods for deep-KNN (i.e.,  $deep-KNN$ ,  $deep-KNN_{me}$  and  $deep-KNN_{mc}$ ) on the CIFAR-10 and CIFAR-10-C datasets for ResNet18

Fig. 8. ResNet18 Accuracy results on the CIFAR-10 and CIFAR-10-C datasets for deep-KNN with  $t_{COMS} = 2$



(b) Comparison of accuracy improvements  $Acc_{imp}$  between all the tested methods for deep-KNN (i.e.,  $deep-KNN$ ,  $deep-KNN_{me}$  and  $deep-KNN_{mc}$ ) on the CIFAR-10 and CIFAR-10-C datasets for ResNet34

Fig. 9. ResNet34 Accuracy results on the CIFAR-10 and CIFAR-10-C datasets for deep-KNN with  $tc_{OMS} = 2$