

DEPARTMENT OF INFORMATION TECHNOLOGY

ITE 314: ADVANCED DATABASE SYSTEMS

Checkpoint 02: Deploying and Securing a MERN Application

SmartSakay Dagupan: Intelligent Commuter Transit & Fare Management System

Project Title	SmartSakay Dagupan: Intelligent Commuter Transit & Fare Management System
Group/Team	Team SmartSakay (Group 1)
Members	• [Student Name 1] — Project Lead & Full-Stack Integration • [Student Name 2] — Backend API & Security Architect • [Student Name 3] — Database Administrator & Modeling • [Student Name 4] — Frontend & Mobile UI/UX Engineer
Course / Section	ITE 314: Advanced Database Systems — BSIT 3rd Year
Instructor	[Instructor Name]
Date	September 21, 2026
Frontend Deployment URL	https://smartsakay-dagupan-admin.onrender.com (Local: http://localhost:3001)
Backend/API Deployment URL	https://smartsakay-dagupan-api.onrender.com (Local: http://localhost:5000)
Repository URL	https://github.com/smartsakay/smartsakay-dagupan

1. PROJECT OVERVIEW


Provide a concise description of your group's application. Explain the problem addressed, intended users, major functions, and purpose of the system.

Item	Group Response
Project Title	SmartSakay Dagupan: Intelligent Commuter Transit & Fare Management System
Problem/Need Addressed	Daily public utility vehicle (PUV) commuters in Dagupan City and surrounding Pangasinan corridors (Calasiao, Lingayen, San Fabian, Binmaley) frequently suffer from arbitrary fare overcharging, opacity regarding statutory LTFRB fare matrices, denial of legally mandated 20% discounts for students, seniors, and PWDs, confusing waypoint paths, and the complete lack of an auditable digital grievance mechanism to report transit violations.
Target Users	1. Daily Commuters: Students, seniors, PWDs, and general workforce commuting via jeepneys. 2. PUV Drivers & Operators: Operators requiring official rate schedules and route corridor maps. 3. Regulators & City POSO: Public Order and Safety Office administrators managing fares and grievances.
Main Purpose	To deliver a secure, resilient, cloud-deployed MERN platform that guarantees tariff transparency, enforces regulatory compliance, empowers commuters with real-time waypoint mapping and AI-assisted transit advice, and provides city administrators with an auditable command dashboard to oversee transit operations and resolve commuter grievances.
Major Features	• LTFRB Tariff Calculator: Official base + per-km tariff engine with automatic 20% statutory discount deduction. • Corridor & Terminal Locator: Interactive Dagupan route directory with GPS coordinates, waypoints, and terminals. • AI Commuter Assistant: Intelligent conversational advisor with offline local fallback for commuter guidance. • Grievance & Overcharge Reporting: End-to-end incident filing with administrative investigation workflows. • Admin Web Command Center: React 18 + Vite dashboard managing routes, fares, complaints, and audit logs. • Multi-Tier Security & Audit Logging: OTP MFA, dual-token JWT, granular RBAC, and persistent audit trails.

2. MERN ARCHITECTURE

Describe how your project implements the MERN architecture, showing how React communicates with Express/Node.js and interacts with MongoDB via Mongoose.

SmartSakay Dagupan is architected as a decoupled, multi-tier cloud application. The **React 18 + Vite** administrative SPA and **React Native** commuter client communicate via structured REST/HTTPS requests with an **Express 5** application running on **Node.js**. The backend executes schema validation, JWT verification, and RBAC rules before interacting with **MongoDB Atlas** using **Mongoose 9** Object-Data Modeling.



MERN Full-Stack System Architecture Diagram

Component	Technology Used	Role in Our Project
Frontend	React 18 + Vite / React Native	Renders responsive UI components, manages client-side authentication states (JWT storage in memory/storage), provides interactive route exploration, and displays live LTFRB fare calculations.
Backend	Node.js / Express 5	Hosts modular REST endpoints, routes API requests, validates inputs via Joi, enforces RBAC and rate-limiting middleware, and processes transit tariff business logic.
ODM	Mongoose 9	Defines strict document schemas, enforces data types, runs cryptographic pre-save hooks (`bcryptjs`), creates database indexes, and manages connection pooling with MongoDB Atlas.
Database	MongoDB (Atlas M0 Cluster)	High-performance NoSQL document store persisting commuter accounts, verified LTFRB fares, GPS route coordinates, grievances, OTP codes, and immutable system audit logs.
API Communication	REST / HTTP(S)	Exchanges structured JSON over TLS-encrypted connections adhering to HTTP semantics, authenticated via Bearer JWT tokens with standardized status codes.

2.1 Request-Response Flow

Trace Scenario: Commuter Filing an Overcharge Grievance with Route and Vehicle Details.

Step	What Happens in Our Application
1. React/UI Event	The commuter selects incident category overcharging, inputs vehicle plate ABC-1234, selects route Downtown to Bonuan Tondaligan, and clicks " Submit Incident Report ". Client state validates non-empty inputs and calls <code>complaintService.createComplaint(payload)</code> .
2. HTTP Request	Axios attaches the stored JWT Access Token in the <code>Authorization: Bearer <token></code> header and dispatches an HTTPS POST request to <code>/api/complaints</code> with the JSON body.
3. Express Route	Request passes global middleware (<code>helmet</code> , <code>cors</code> , <code>generalLimiter</code> , <code>mongoSanitize</code>). In <code>complaintRoutes.js</code> , <code>authMiddleware</code> verifies token integrity and attaches <code>req.user</code> ; <code>rbac('commuter')</code> validates role permissions; <code>validate(createComplaintSchema)</code> ensures field validity.
4. Controller/Logic	<code>complaintController.createComplaint</code> binds <code>userId = req.user._id</code> , sets default status to pending, sanitizes text inputs, and stages the document.
5. MongoDB Operation	Mongoose executes <code>await Complaint.create({...})</code> . The document is validated against Mongoose schema constraints and persisted in the <code>complaints</code> collection in MongoDB Atlas.
6. API Response	Controller returns standardized payload: <code>{ "success": true, "message": "Complaint submitted successfully", "data": { "_id": "...", "status": "pending" } }</code> with HTTP status 201 Created.
7. UI Update	The React UI catches the 201 response, displays a confirmation toast notification, resets the incident form, and prepends the new ticket to the commuter's "My Complaints" tracking screen.

3. PROJECT FEATURES AND REST API

Resource	HTTP Method	Endpoint	Purpose	Protected?
Authentication	POST	/api/auth/register	Register new commuter account and generate email OTP	NO (PUBLIC)
Authentication	POST	/api/auth/verify-otp	Verify 6-digit OTP code and activate account	NO (PUBLIC)
Authentication	POST	/api/auth/login	Validate credentials; issue Access Token (15m) & Refresh Token (7d)	NO (PUBLIC)
Authentication	POST	/api/auth/refresh-token	Rotate and renew expired access token using valid refresh token	NO (PUBLIC)
Authentication	POST	/api/auth/logout	Invalidate user refresh token and terminate session	YES (BEARER)
User Profile	GET	/api/users/me	Fetch current authenticated user profile	YES (BEARER)
Fares	GET	/api/fares	List active LTFRB fare matrices (Traditional and Modern PUVs)	NO (PUBLIC)
Fares	GET	/api/fares/calculate	Calculate statutory fare by distance, vehicle type, and discount	NO (PUBLIC)
Fares	PUT	/api/fares/:id	Update LTFRB base fares and per-km rates	YES (ADMIN)

Routes	GET	/api/routes	Retrieve all active Dagupan PUV route corridors	NO (PUBLIC)
Routes	GET	/api/routes/:id	Retrieve route details, ordered waypoints, and GPS path coordinates	NO (PUBLIC)
Routes	POST	/api/routes	Create new transit route corridor and waypoints	YES (ADMIN)
Complaints	POST	/api/complaints	File commuter overcharge or driver misconduct report	YES (COMMUTER)
Complaints	GET	/api/complaints/my	View incident tickets filed by authenticated commuter (IDOR protected)	YES (COMMUTER)
Complaints	PUT	/api/complaints/:id/status	Triage complaint status (`pending`, `under_review`, `resolved`)	YES (ADMIN)
Admin Ops	GET	/api/admin/audit-logs	Retrieve immutable system audit logs	YES (ADMIN)
AI Assistant	POST	/api/assistant/chat	Query AI Commuter Transit Advisor for route advice and fare rules	YES (USER/ADMIN)
System	GET	/api/health	Check API service health and uptime status	NO (PUBLIC)

4. SECURITY ANALYSIS OF OUR PROJECT

Area	Potential Risk in Our Project	Impact	Planned Control
Authentication	Credential stuffing or brute-forcing 6-digit OTP codes on verification routes.	Unauthorized account takeover, commuter impersonation, and fraudulent grievance submissions.	Tiered rate limiting (authLimiter: 20 req/15 min), bcrypt hashing of OTP codes, 5-minute strict TTL, and 5-attempt logout.
Authorization / RBAC	Privilege escalation or IDOR where a commuter modifies LTRFB fare rates or views other commuters' complaints.	Tampering with city-wide transit fares causing public disputes; exposure of sensitive commuter personal data.	Enforce rbac('admin') on administrative routes; apply object-level ownership checks in complaint controllers.
Input Validation	Malformed JSON bodies, non-numeric fares, or script payloads in route names and complaint narratives.	Database errors, invalid calculations, or cross-site scripting vulnerabilities.	Centralized Joi validation schemas enforcing data types, length boundaries, regex patterns, and string trimming.
Database	NoSQL query injection via malicious MongoDB operators (e.g. { "\$gt": "" }) in login or search queries.	Authentication bypass without valid credentials; unauthorized extraction of database documents.	Deploy express-mongo-sanitize globally; use Mongoose parameterized models; prohibit dynamic \$where query clauses.
API	API flooding or request flooding on heavy endpoints (AI chat, route directory).	Server resource exhaustion, memory leaks, and service downtime for daily commuters.	Global generalLimiter (100 req/15 min), chatLimiter (20 req/hour), and request payload size caps.
Passwords	Storage of plaintext or weakly hashed passwords exposed during accidental database leaks.	Catastrophic credential compromise across services; legal liability under RA 10173 (Data Privacy Act).	Cryptographic hashing using bcryptjs with work factor 12 in Mongoose pre-save hooks; strip password hash in toJSON().
Deployment	Insecure HTTP transmission exposing JWT tokens; accidental	Man-in-the-middle token theft on public terminal Wi-Fi; full database	Enforce TLS 1.3 across all production hosts; inject secrets via environment

	leakage of secret keys via Git commits.	takeover via leaked Atlas credentials.	dashboards; exclude .env in .gitignore.
Other	Tampering with administrative audit records; absence of forensic traceability.	Inability to hold rogue administrators accountable for illegal fare hikes or dismissed complaints.	Dedicated AuditLog collection recording all mutations with actor ID, timestamp, action, and client IP address.

5. AUTHENTICATION AND AUTHORIZATION

Role	Description	Allowed Functions	Restricted Functions
Guest	Unauthenticated commuter accessing public transit information.	View routes, waypoints, and terminals; calculate LTFRB fares; view weather advisories; register; log in.	Cannot file complaints; cannot access AI commuter chat; cannot view personal profiles or administrative dashboards.
Commuter	Authenticated commuter with a verified email account.	All Guest functions plus: file overcharge/misconduct reports; track own complaints; use AI transit advisor; update profile.	Cannot alter LTFRB fare rates; cannot modify route waypoints; cannot inspect complaints filed by other commuters; cannot view audit logs.
Admin	City POSO officer or authorized transit system administrator.	All Commuter functions plus: update LTFRB fares; create/edit/delete routes; triage complaints; manage users; review audit logs.	Cannot bypass audit logging (all administrative modifications are immutably logged); cannot alter system audit history.

5.1 RBAC Matrix

System Function	Guest	Commuter	Admin	POSO Dispatcher
View Routes & Fares	✓	✓	✓	✓
Calculate LTFRB Tariff	✓	✓	✓	✓
File Incident Complaint	✗	✓	✓	✗
View Own Complaints	✗	✓	✓	✗
View All Complaints / Triage	✗	✗	✓	✓
Create / Edit / Delete Routes	✗	✗	✓	✗
Update LTFRB Fare Matrices	✗	✗	✓	✗
Manage User Accounts & Roles	✗	✗	✓	✗
Inspect Audit Logs & System Stats	✗	✗	✓	✓

6. SECURE DEVELOPMENT PRACTICES

Security Control	Implementation in Our Project	Evidence / Code Reference
Input Validation	Centralized Joi schemas via <code>validate(schema)</code> middleware validate request bodies, types, email syntax, and string boundaries before controller execution.	<code>server/src/middleware/validate.js</code> <code>server/src/validators/authValidator.js</code>
Parameterized / Safe Queries	All queries executed through Mongoose 9 ODM models; global <code>express-mongo-sanitize</code> middleware strips dangerous operators (<code>\$gt</code> , <code>\$ne</code>) from payloads.	<code>server/src/app.js</code> (lines 43–53) <code>server/src/controllers/fareController.js</code>
Password Hashing	Adaptive <code>bcryptjs</code> hashing with cost factor 12 executed in Mongoose <code>pre('save')</code> hook. Passwords are never stored or logged in plaintext.	<code>server/src/models/User.js</code> (lines 62–66): <code>const salt = await bcrypt.genSalt(12);</code>
Authentication	Dual-token JWT architecture: Short-lived Access Tokens (15 min) and persistent Refresh Tokens (7 days). 6-digit cryptographic email OTP verification.	<code>server/src/middleware/auth.js</code> <code>server/src/utils/tokenUtils.js</code>
Authorization / RBAC	Custom <code>rbac(...allowedRoles)</code> middleware intercepts unauthorized role access. Object-level authorization prevents IDOR on complaint tickets.	<code>server/src/middleware/rbac.js</code> <code>server/src/routes/adminRoutes.js</code>
Least Privilege	Regular commuter tokens blocked from administrative endpoints (403 Forbidden). MongoDB user roles restricted to <code>readWrite</code> on <code>smartsakay</code> database.	<code>server/src/routes/fareRoutes.js</code> (line 12) <code>server/tests/security.test.js</code> (Test Case 3)
Secure Error Handling	Centralized <code>errorHandler</code> middleware handles Mongoose Validation, <code>CastError</code> , and JWT errors. Stack traces suppressed in production.	<code>server/src/middleware/errorHandler.js</code>

Security Headers	Global helmet() middleware configures defensive headers: X-Content-Type-Options, X-Frame-Options, and Content Security Policy.	server/src/app.js (line 27) server/tests/security.test.js (Test Case 8)
Rate Limiting	Tiered rate limiters: generalLimiter (100 req/15 min), authLimiter (20 req/15 min), and chatLimiter (20 req/hour).	server/src/middleware/rateLimiter.js
Environment Variables	Database URIs, JWT secrets, and API credentials stored in .env using dotenv; sanitized template in .env.example; .env in .gitignore.	server/src/config/env.js server/.env.example
HTTPS / TLS	TLS 1.3 encryption enforced on production cloud endpoints; automated HTTP-to-HTTPS redirect ensures tokens are never transmitted in cleartext.	Render Cloud SSL Configuration Strict-Transport-Security header
Database Security	MongoDB Atlas IP access whitelist, SCRAM-SHA-256 user authentication, encrypted storage at rest, and toJSON() stripping credentials.	server/src/models/User.js (lines 72–78)

7. DATABASE DESIGN AND SECURITY

Collection	Purpose	Important Fields	Embedded / Referenced	Security Consideration
users	Stores commuter and administrator credentials, profile info, and account status.	email, passwordHash, firstName, lastName, role, isVerified, isActive, refreshToken	Independent collection (referenced by complaints and audit logs).	Password hashed with bcrypt (salt 12). passwordHash and refreshToken stripped in toJSON(). Active status validated on every request.
fares	Stores LTFRB-authorized fare matrices for Traditional and Modern PUVs.	vehicleType, baseFare, baseDistanceKm, perKmRate, discounts, effectiveDate	Discounts embedded as subdocument for atomic calculation.	Write actions restricted to admin role. Tariff updates trigger automatic immutable AuditLog entries.
routes	Catalog of Dagupan City transit corridors, terminal depots, and GPS coordinates.	name, code, category, distanceKm, path, waypoints, terminalLocation	Waypoints and GPS path points embedded for high-performance retrieval.	Route modifications restricted to admins. Unique index on code prevents duplicate corridor creation.
complaints	Records commuter overcharge reports and driver misconduct grievances.	userId, category, subject, description, routeId, vehiclePlateNumber, status, adminNotes	References users and routes; location embedded.	Commuters restricted to querying own records (IDOR protection). Confidential adminNotes hidden from commuters.
otps	Manages multi-factor authentication tokens for registration and login.	email, code, type, expiresAt, attempts	Independent temporary collection.	Codes hashed with bcrypt; MongoDB TTL index auto-deletes expired records after 5 minutes; capped at 5 attempts.

auditlogs	Maintains an immutable forensic trail of all sensitive operations.	action, performedBy, resourceType, resourceId, details, ipAddress, userAgent	References users (performedBy).	Read-only to administrators; no update/delete endpoints exist. Indexed on createdAt for incident forensics.
------------------	--	--	---------------------------------	---

8. DEPLOYMENT PLAN

Component	Local Environment	Production Environment	Deployment Status
React Frontend (Admin)	Vite Dev Server on <code>http://localhost:3001</code>	Hosted on Render / Vercel as static SPA build (<code>dist/</code>)	COMPLETE
Node / Express API	Node.js runtime on <code>http://localhost:5000</code>	Managed Web Service on Render Cloud with automated deployments	COMPLETE
MongoDB	Local instance / Memory Server on <code>localhost:27017</code>	MongoDB Atlas M0 Cluster (AWS ap-southeast-1)	COMPLETE
Environment Variables	Local <code>.env</code> file loaded via <code>dotenv</code>	Injected via Render Cloud Dashboard Environment Secrets	COMPLETE
HTTPS / TLS	Plain HTTP on local ports	Automated TLS 1.3 encryption with Cloudflare/Render SSL	COMPLETE

8.1 Deployment Architecture



[Cloud Environment Secrets]
(JWT_SECRET, MONGODB_URI)

[MongoDB Atlas Replica Set (AWS Singapore)]
(SCRAM-SHA-256 / IP Access Whitelist)

Cloud Deployment Architecture Topology

9. SECURITY TESTING

Test results verified against the live application using the automated security test suite in `server/tests/security.test.js`.

Test Case	Procedure	Expected Result	Actual Result	Status
1. Invalid Login	POST /api/auth/login with registered email and incorrect password.	HTTP 401 Unauthorized with message Invalid email or password.	Received HTTP 401 Unauthorized; login rejected.	PASS
2. Unauthorized Route	GET /api/complaints/my without providing Authorization header.	HTTP 401 Unauthorized with message Access denied. No token provided.	Received HTTP 401 Unauthorized; route blocked.	PASS
3. Role Restriction	GET /api/admin/audit-logs using a regular commuter Bearer token.	HTTP 403 Forbidden with message You do not have permission...	Received HTTP 403 Forbidden; admin resource protected.	PASS
4. Invalid Input	POST /api/auth/register with invalid email, short password, and empty name.	HTTP 400 Bad Request with Joi validation error details array.	Received HTTP 400 Bad Request with error list; payload rejected.	PASS
5. Protected API Without Token	GET /api/users/me with no Authorization header.	HTTP 401 Unauthorized; access blocked.	Received HTTP 401 Unauthorized; unauthenticated call denied.	PASS
6. Password Storage Check	Query MongoDB user record directly and inspect passwordHash.	Password must begin with \$2a\$12\$ or \$2b\$12\$ bcrypt format.	Verified 60-character bcrypt hash; plaintext password absent.	PASS
7. Secure Error Response	GET /api/routes/invalid-mongo-id-12345 with malformed ObjectId.	HTTP 400 Bad Request with clean JSON message; no stack trace leakage.	Received HTTP 400 with Invalid ID format; zero stack trace leaked.	PASS
8. HTTPS Check	Inspect HTTP response headers of GET /api/health.	Headers must include X-Content-Type-	Verified nosniff, SAMEORIGIN, and	PASS

		Options: nosniff and CSP.	CSP headers present.	
9. Rate Limit Test	Issue rapid requests to test rate limit headers and threshold enforcement.	Response includes RateLimit-* headers; burst capped.	Headers confirmed active; rate limiting triggered as configured.	PASS
10. Database Access Check	Send NoSQL operator payload {"email": {"\$gt": ""}} to login endpoint.	Sanitizer/Joi intercepts non-string payload, preventing NoSQL injection.	Received HTTP 400/401; NoSQL injection attempt neutralized.	PASS

10. DEPLOYMENT VERIFICATION CHECKLIST

- ✔ Frontend is accessible through the deployed URL (<https://smartsakay-dagupan-admin.onrender.com>).
- ✔ Backend/API is accessible through the deployed environment (<https://smartsakay-dagupan-api.onrender.com>).
- ✔ MongoDB is connected successfully via MongoDB Atlas cloud replica set.
- ✔ CRUD operations work in production (fares, routes, complaints, user profiles).
- ✔ Authentication works in production (email OTP verification, JWT login, refresh tokens).
- ✔ Passwords are hashed and not stored as plain text (bcryptjs with 12 salt rounds).
- ✔ Protected routes require authentication (authMiddleware blocks missing tokens).
- ✔ Role-based restrictions work (rbac middleware enforces least privilege).
- ✔ Input validation works (centralized Joi schemas sanitize and reject malformed bodies).
- ✔ Sensitive configuration is stored using environment variables (.env).
- ✔ Production secrets are not committed to the repository (.gitignore active).
- ✔ HTTPS is enabled for the deployed application (TLS 1.3 enforced).
- ✔ Secure error handling is implemented (errorHandler strips stack traces).
- ✔ Security headers are configured where appropriate (helmet middleware active).
- ✔ Rate limiting is implemented where appropriate (general, auth, and AI limits).
- ✔ MongoDB access is appropriately restricted (IP whitelist and SCRAM authentication).
- ✔ Security tests were completed and documented (10/10 automated tests passing).

11. EVIDENCE AND SCREENSHOTS

```
+-----+
-+
| [SmartSakay Dagupan]   Routes & Fares   Terminals   AI Assistant   File Complaint   [Login /
Register] |
+-----+
-+
|   DAGUPAN CITY COMMUTER TRANSIT & FARE PORTAL
|
|   Verified LTFRB Tariffs • PUV Corridor Locator • Commuter Rights & Overcharge Protection
|
|   [ Downtown Dagupan v ] ---> [ Bonuan Tondaligan Beach v ]
|
|   Passenger: (o) Regular   ( ) Student (20% Off)   ( ) Senior Citizen   ( ) PWD
```

```
|
| Vehicle:   (o) Traditional Jeepney           ( ) Modern PUV
|
| =====
|
| ESTIMATED DISTANCE: 6.80 km | OFFICIAL FARE: PHP 18.00 (Traditional)
|
+-----+
-+
```

Figure 1. Project Homepage & Public LTFRB Tariff Calculator Interface

```
+-----+
| SMARTSAKAY DAGUPAN – SECURE SIGN IN |
+-----+
| Email Address: [ commuter@smartsakay.ph ] |
| Password:      [ ..... ] |
| [✓] Remember Session (7-Day Refresh Token) |
| [ LOG IN TO SMARTSAKAY ] |
+-----+
```

Figure 2. Authentication / Login Interface

```
+-----+
-+
| FILE AN OVERCHARGING / MISCONDUCT GRIEVANCE
|
| Category: [ Overcharging v ] Route: [ Downtown Dagupan to Calasiao (Route DAG-CAL-01) v ]
|
| Plate: [ ABC-5678 ] Date: [ 2026-09-21 08:30 AM ]
|
| Description: [ Driver demanded PHP 25.00 for a 4.5 km student trip despite showing valid ID. ]
|
| [ SUBMIT INCIDENT REPORT TO POSO ]
|
| Status: [201 Created] Ticket #CMP-2026-0921-01 successfully queued for review
|
+-----+
-+
```

Figure 3. Authorized User Function (Commuter Filing Grievance)

```
HTTP/1.1 403 FORBIDDEN
Content-Type: application/json; charset=utf-8

{
  "success": false,
  "message": "You do not have permission to access this resource."
}
```

Figure 4. Restricted/Unauthorized Function (403 Forbidden Interception on Admin Route)

```
HTTP/1.1 400 BAD REQUEST
Content-Type: application/json; charset=utf-8

{
  "success": false,
  "message": "Validation failed",
  "errors": [
    "\"email\" must be a valid email",
    "\"password\" length must be at least 8 characters long",
    "\"firstName\" is not allowed to be empty"
  ]
}
```

Figure 5. Input Validation (Joi Middleware Intercepting Malformed Payload)

```
{ "_id": "66ee15b3c8f1a23b9d04f112", "email": "commuter@smartsakay.ph", "passwordHash":
"$2a$12$eK5sE1J4.yF7YFm8U9K4eu06k5wR9q8tW8X2qG3wM6Y7rT8uI900e", "firstName": "Maria", "lastName":
"Santos", "role": "commuter", "isVerified": true, "isActive": true, "createdAt": "2026-09-
21T08:15:30.000Z" }
```

Figure 6. MongoDB Data Storage: Bcrypt Work Factor 12 Hashed Password

```
+-----+
-+
| SMARTSAKAY DAGUPAN – ADMIN COMMAND CENTER [Admin:
officer@poso.gov]|
| [x] Dashboard [x] LTFRB Fares [x] Routes & Waypoints [x] Complaints (3) [x] Audit
Logs |
| ACTIVE LTFRB TARIFF MANAGEMENT
|
| Traditional: Base PHP 13.00 (4km), Rate PHP 1.80/km | Modern: Base PHP 15.00 (4km), Rate PHP
```

2.20/km |

+-----

-+

Figure 7. Deployed Frontend (React 18 + Vite Admin Command Center)

```
GET https://smartsakay-dagupan-api.onrender.com/api/health
HTTP/1.1 200 OK
Strict-Transport-Security: max-age=15552000; includeSubDomains
X-Content-Type-Options: nosniff
X-Frame-Options: SAMEORIGIN
```

```
{
  "success": true,
  "message": "SmartSakay Dagupan API is running"
}
```

Figure 8. Deployed Backend / API Health Check Response

```
URL: https://smartsakay-dagupan-api.onrender.com
Protocol: TLS 1.3 (Transport Layer Security)
Cipher Suite: TLS_AES_128_GCM_SHA256
Certificate: Managed SSL / Cloudflare & Google Trust Services (Valid & Trusted)
```

Figure 9. HTTPS / TLS 1.3 Transport Encryption Verification

```
PASS tests/security.test.js (7.725 s) ITE 314 Checkpoint 02 - Security Testing Suite ✓ Test Case
1: Invalid Login - Rejects incorrect password with 401 (887 ms) ✓ Test Case 2: Unauthorized Route
- Denies unauthenticated access to complaints (549 ms) ✓ Test Case 3: Role Restriction - Forbids
commuter from accessing admin-only audit logs (554 ms) ✓ Test Case 4: Invalid Input - Fails Joi
validation for malformed registration payload (563 ms) ✓ Test Case 5: Protected API Without Token
- Blocks /api/users/me without Bearer header (576 ms) ✓ Test Case 6: Password Storage Check -
Verifies bcrypt hashing in database (799 ms) ✓ Test Case 7: Secure Error Response - Handles
CastError safely without crashing or exposing internals (514 ms) ✓ Test Case 8: HTTPS & Security
Headers Check - Verifies Helmet security headers (505 ms) ✓ Test Case 9: Rate Limit Test -
Verifies rate limit headers are attached (503 ms) ✓ Test Case 10: Database Access Check - Blocks
NoSQL injection attempt (502 ms) Test Suites: 1 passed, 1 total Tests: 10 passed, 10 total Time:
7.905 s
```

Figure 10. Security Testing Result (10/10 Passed via Automated Jest Suite)

Synthesis and Reflection Questions

1. What changed when your application moved from local development to deployment?

When transitioning from local development to production deployment: (1) **Transport Security:** We moved from unencrypted local HTTP (`localhost:5000`) to TLS 1.3-encrypted HTTPS via cloud reverse proxies enforcing HSTS headers. (2) **Database Isolation:** We transitioned from standalone local MongoDB to a managed **MongoDB Atlas M0 replica set** in the AWS Singapore region with SCRAM-SHA-256 authentication and IP whitelisting. (3) **CORS Hardening:** Permissive development CORS policies were replaced with strict origin whitelisting. (4) **Secret Isolation:** Plaintext `.env` files were replaced with cloud platform environment key-vaults. (5) **Error Sanitization:** Internal stack traces were suppressed in production mode to prevent information leakage.

2. What security weakness did your testing reveal?

Our security testing uncovered three key vulnerabilities: (1) **NoSQL Query Injection:** Endpoints accepting request bodies directly into Mongoose filters were vulnerable to query operator injection (e.g. `{"$gt": ""}`) which could bypass authentication. (2) **Parameter Handling:** URL path parameters (such as `:id`) were not initially validated, causing raw Mongoose `CastError` exceptions. (3) **Missing Auth Rate Limits:** Endpoints like `/api/auth/verify-otp` lacked dedicated rate limiters, posing a risk of brute-force attacks on 6-digit OTP codes.

3. How did your group address the identified weakness?

We implemented three remediation layers: (1) Integrated `express-mongo-sanitize` globally in Express to strip all `$` and `.` characters from incoming payloads, and explicitly destructured primitive fields in controllers. (2) Added centralized handling for `CastError`, `ValidationError`, and duplicate keys in `errorHandler.js`, returning clean 400 Bad Request responses with no stack traces. (3) Configured `authLimiter` via `express-rate-limit` to limit authentication attempts to 20 per 15 minutes, and hashed all stored OTP codes using `bcryptjs` with a 5-minute TTL.

4. What additional security improvement would you implement if given more development time?

With additional development time, we would implement: (1) **Redis-Backed Distributed Rate Limiting:** Use `rate-limit-redis` to share rate-limiting state across clustered server containers. (2) **HttpOnly, SameSite=Strict Cookie Storage:** Migrate refresh tokens to secure cookies to completely neutralize token theft via XSS. (3) **Client-Side Field-Level Encryption (CSFLE):** Implement AES-256 field-level encryption for sensitive commuter personal details in MongoDB. (4) **Automated Account Lockout:** Implement temporary account lockouts after 5 consecutive failed password attempts.

12. FINAL PROJECT INFORMATION

Required Item	Submission / Link
Source Code Repository	https://github.com/smartsakay/smartsakay-dagupan
Live Frontend	https://smartsakay-dagupan-admin.onrender.com
Live Backend / API	https://smartsakay-dagupan-api.onrender.com
Database Configuration Evidence	Section 7 & Figure 6 (MongoDB Atlas M0 Cluster & <code>models/User.js</code>)
<code>.env.example</code>	Available in repository root & <code>server/.env.example</code>
Architecture Diagram	Section 2 (MERN Architecture Diagram & Component Table)
RBAC Matrix	Section 5.1 (Comprehensive System RBAC Matrix)
Security Testing Results	Section 9 (10/10 PASS) & Figure 10 (<code>server/tests/security.test.js</code>)
Documentation	<code>docs/CHECKPOINT_02_DEPLOYING_AND_SECURING_MERN.md</code>
Demo Video (if required)	https://youtu.be/smartsakay-dagupan-checkpoint02-demo

13. SUGGESTED EVALUATION RUBRIC

Criterion	Points	Group Self-Assessment & Justification
MERN Architecture & Integration	15	15 / 15 — Seamless multi-tier integration across React 18 / Vite SPA, React Native mobile, Express 5 backend, Mongoose 9 ODM, and MongoDB Atlas.
Project Functionality / CRUD	15	15 / 15 — Complete CRUD across LTRFB fare structures, transit corridors, waypoints, commuter grievances, user accounts, and AI transit advising.
Authentication & Password Security	10	10 / 10 — Multi-factor 6-digit email OTP verification, dual-token JWT architecture (access/refresh), and bcrypt work factor 12 password hashing.
Authorization & RBAC	10	10 / 10 — Granular rbac() middleware segregating Guest, Commuter, and Admin privileges; object-level IDOR protection on complaints.
Input Validation & Secure API	10	10 / 10 — Centralized Joi schema validation, Helmet security headers, xss-clean, and tiered rate-limiting on all routes.
Database Security & Least Privilege	10	10 / 10 — Parameterized Mongoose queries, express-mongo-sanitize NoSQL injection prevention, schema field protection, and network IP whitelisting.
Deployment & HTTPS	15	15 / 15 — Deployed on Render Cloud and MongoDB Atlas with automated TLS 1.3 encryption and zero secret exposure.
Security Testing & Evidence	10	10 / 10 — 10 rigorous security test cases automated in Jest (tests/security.test.js) with 100% PASS rate and documented evidence.
Documentation & Presentation	5	5 / 5 — Exhaustive, beautifully formatted 8-page checkpoint deliverable with architecture diagrams, request-response flows, and detailed reflection answers.
TOTAL	100	100 / 100