

Recommended Configuration Maximums

9.0.0

Updated on June 17, 2025



You can find the most up-to-date technical documentation on the VMware website at:

<https://docs.vmware.com/>

If you have comments about this documentation, submit your feedback to

configmaxtool@vmware.com

VMware LLC
3401 Hillview Ave.
Palo Alto, CA 94304
www.vmware.com

Copyright © 2005-date(){return(new Date).getFullYear()} Broadcom. All Rights Reserved. The term “Broadcom” refers to Broadcom Inc. and/or its subsidiaries. [Copyright and trademark information.](#)

The VMware Configuration Maximums tool provides the officially supported configuration limits for VMware products. These limits define the maximum values that VMware has tested and validated to ensure reliable performance and support.

Disclaimer: The limits can be affected by other factors, such as hardware dependencies. For more information about the supported hardware, refer to the corresponding hardware compatibility guide. It might not be possible to maximize all configuration settings and expect your desired outcome. To ensure that you do not exceed supported configurations for your environment, consult individual solution limits. The recommended configuration limits do not represent the theoretical possibilities of your product.

Recommended Configuration Limits

Category		Limits	Description
Extra Small Deployment			
Configuration	vCPU	2	
Configuration	Memory (GB)	8	
Configuration	Datastore latency	10 ms	Consistently lower than 10 ms with possible occasional peaks up to 15 ms
Configuration	Network latency for data nodes	5 ms	
Configuration	vCPU - Physical core ratio for data nodes	1 vCPU to 1 physical core at scale maximums	It is critical to allocate enough CPU resources for environments running at scale maximums to avoid performance degradation. Refer to the vRealize Operations Manager Cluster Node Best Practices in the vRealize Operations Manager 6.6 Help for more guidelines regarding CPU allocation.
Configuration	Maximum Memory Configuration (GB)	16	
Configuration	Single-Node Maximum Objects	700	
Objects and Metrics	Single-Node Maximum Collected Metrics	140,000	Metric numbers reflect the total number of metrics that are collected from all adapter instances in vRealize Operations Manager. To get this number, you can go to the Cluster Management page in vRealize Operations Manager, and view the adapter instances of each node at the bottom of the page. You can get the number of metrics collected by each adapter instance. The sum of these metrics is what is estimated in this sheet. Note: The number shown in the overall metrics on the Cluster Management page reflects the metrics that are collected from different data sources and the metrics that vRealize Operations Manager creates.
Objects and Metrics	Maximum number of nodes in a cluster	1	
Objects and Metrics	Maximum number of nodes in a cluster	700	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of objects in a cluster	700	
Small Deployments			
Configuration	vCPU	4	
Configuration	Memory (GB)	16	
Configuration	Maximum Memory Configuration (GB)	32	
Configuration	Datastore latency	10 ms	Consistently lower than 10 ms with possible occasional peaks up to 15 ms
Configuration	Network latency for data nodes	5 ms	

Recommended Configuration Limits

Category		Limits	Description
Configuration	vCPU - Physical core ratio for data nodes	1 vCPU to 1 physical core at scale maximums	It is critical to allocate enough CPU resources for environments running at scale maximums to avoid performance degradation. Refer to the vRealize Operations Manager Cluster Node Best Practices in the vRealize Operations Manager 6.6 Help for more guidelines regarding CPU allocation.
Objects and Metrics	Maximum number of nodes in a cluster	2	
Objects and Metrics	Multi-Node Maximum Objects Per Node	6000	
Objects and Metrics	Multi-Node Maximum Metrics Per Node	1,400,000	
Objects and Metrics	Maximum number of objects in a cluster	12,000	
Objects and Metrics	Maximum number of Metrics in a Cluster	2,800,00	
Objects and Metrics	Maximum number of metrics in an extended cluster	3,080,000	
Medium Deployments			
Configuration	vCPU	8	
Configuration	Memory (GB)	32	
Configuration	Maximum Memory Configuration (GB)	64	
Configuration	Datastore latency	10 ms	Consistently lower than 10 ms with possible occasional peaks up to 15 ms
Configuration	Network latency for data nodes	5 ms	
Configuration	vCPU - Physical core ratio for data nodes	1 vCPU to 1 physical core at scale maximums	It is critical to allocate enough CPU resources for environments running at scale maximums to avoid performance degradation. Refer to the vRealize Operations Manager Cluster Node Best Practices in the vRealize Operations Manager 6.6 Help for more guidelines regarding CPU allocation.
Objects and Metrics	Single-Node Maximum Objects	30,000	
Objects and Metrics	Single-Node Maximum Collected Metrics	5,000,000	Metric numbers reflect the total number of metrics that are collected from all adapter instances in vRealize Operations Manager. To get this number, you can go to the Cluster Management page in vRealize Operations Manager, and view the adapter instances of each node at the bottom of the page. You can get the number of metrics collected by each adapter instance. The sum of these metrics is what is estimated in this sheet. Note: The number shown in the overall metrics on the Cluster Management page reflects the metrics that are collected from different data sources and the metrics that vRealize Operations Manager creates.

Recommended Configuration Limits

Category		Limits	Description
Objects and Metrics	Multi-Node Maximum Objects Per Node	17,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Multi-Node Maximum Collected Metrics Per Node	4,000,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of nodes in a cluster	8	
Objects and Metrics	Maximum Objects for the configuration with the maximum supported number of nodes	136,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of Metrics in a Cluster	32,000,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of objects in an extended cluster	149,600	
Continuous Availability	Maximum number of nodes in each Continuous Availability fault-domain	4	Each Continuous Availability cluster must have one Witness node which will require 2 vCPUs and 8 GB of Memory.
	Maximum number of metrics in an extended cluster	35,200,000	
Large Deployments			
Configuration	vCPU	16	
Configuration	Memory (GB)	48	
Configuration	Maximum Memory Configuration (GB)	96	
Configuration	Datastore latency	10 ms	Consistently lower than 10 ms with possible occasional peaks up to 15 ms
Configuration	Network latency for data nodes	5 ms	
Configuration	vCPU - Physical core ratio for data nodes	1 vCPU to 1 physical core at scale maximums	It is critical to allocate enough CPU resources for environments running at scale maximums to avoid performance degradation. Refer to the vRealize Operations Manager Cluster Node Best Practices in the vRealize Operations Manager 6.6 Help for more guidelines regarding CPU allocation.
Objects and Metrics	Single-Node Maximum Objects	44,000	

Recommended Configuration Limits

Category		Limits	Description
Objects and Metrics	Single-Node Maximum Collected Metrics	8,000,000	Metric numbers reflect the total number of metrics that are collected from all adapter instances in vRealize Operations Manager. To get this number, you can go to the Cluster Management page in vRealize Operations Manager, and view the adapter instances of each node at the bottom of the page. You can get the number of metrics collected by each adapter instance. The sum of these metrics is what is estimated in this sheet. Note: The number shown in the overall metrics on the Cluster Management page reflects the metrics that are collected from different data sources and the metrics that vRealize Operations Manager creates.
Objects and Metrics	Multi-Node Maximum Objects Per Node	36,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Multi-Node Maximum Collected Metrics Per Node	6,000,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of nodes in a cluster	16	
Objects and Metrics	Maximum number of objects in a cluster	576,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of Metrics in a Cluster	81,600,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of objects in an extended cluster	633,600	
Objects and Metrics	vCPU	89,760,000	
Continuous Availability	Maximum number of nodes in each Continuous Availability fault-domain	8	Each Continuous Availability cluster must have one Witness node which will require 2 vCPUs and 8 GB of Memory.
Extra Large Deployments			
Configuration	vCPU	24	
Configuration	Memory (GB)	128	
Configuration	Maximum Memory Configuration (GB)	256	
Configuration	Datastore latency	10 ms	Consistently lower than 10 ms with possible occasional peaks up to 15 ms
Configuration	Network latency for data nodes	5 ms	

Recommended Configuration Limits

Category		Limits	Description
Configuration	vCPU - Physical core ratio for data nodes	1 vCPU to 1 physical core at scale maximums	It is critical to allocate enough CPU resources for environments running at scale maximums to avoid performance degradation. Refer to the vRealize Operations Manager Cluster Node Best Practices in the vRealize Operations Manager 6.6 Help for more guidelines regarding CPU allocation.
Objects and Metrics	Single-Node Maximum Objects	100,000	
Objects and Metrics	Single-Node Maximum Collected Metrics	20,000,000	Metric numbers reflect the total number of metrics that are collected from all adapter instances in vRealize Operations Manager. To get this number, you can go to the Cluster Management page in vRealize Operations Manager, and view the adapter instances of each node at the bottom of the page. You can get the number of metrics collected by each adapter instance. The sum of these metrics is what is estimated in this sheet. Note: The number shown in the overall metrics on the Cluster Management page reflects the metrics that are collected from different data sources and the metrics that vRealize Operations Manager creates.
Objects and Metrics	Multi-Node Maximum Objects Per Node	88,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Multi-Node Maximum Collected Metrics Per Node	15,000,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of nodes in a cluster	12	
Objects and Metrics	Maximum Objects for the configuration with the maximum supported number of nodes	1,056,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum Metrics for the configuration with the maximum supported number of nodes	126,000,000	In large, 16-node configurations, note the reduction in maximum metrics to permit some head room. This adjustment is accounted for in the calculations.
Objects and Metrics	Maximum number of objects in an extended cluster	1,161,600	
vRealize Application Remote Collector telegraf agent	Maximum number of telegraf agents per node	4000	
	Maximum number of metrics in an extended cluster	138,600,000	
Small Deployments with Cloud Proxy			
Configuration	vCPU	2	
Configuration	Memory (GB)	8	

Recommended Configuration Limits

Category		Limits	Description
Configuration	vCPU - physical core ratio	1 vCPU to 1 physical core at scale maximums	
Configuration	Network latency	< 500 ms	
Configuration	Network packet loss	< 2%	
Configuration	Maximum number of cloud proxies in a cluster	1000	
Objects and Metrics	Maximum Objects	16,000	
Objects and Metrics	Maximum Collected Metrics	2,400,00	
Bandwidth	Minimum required bandwidth (Mbps)	15	
VCF Operations Application Monitoring (telegraf) agents	Maximum number of telegraf agents	500	
Standard Deployments with Unified Cloud Proxy Deployments with Cloud Proxy			
Configuration	vCPU	4	
Configuration	Memory (GB)	32	
Configuration	vCPU - physical core ratio	1 vCPU to 1 physical core at scale maximums	
Configuration	Network latency	< 500 ms	
Configuration	Network packet loss	< 2%	
Configuration	Maximum number of cloud proxies in a cluster	1000	
Objects and Metrics	Maximum Objects	80,000	
Objects and Metrics	Maximum Collected Metrics	12,000,000	
Bandwidth	Minimum required bandwidth (Mbps)	60	
VCF Operations Application Monitoring (telegraf) agents	Maximum number of telegraf agents	3000	
Small Deployments with Unified Cloud Proxy			
Configuration	vCPU	4	
Configuration	Memory (GB)	16	
Configuration	vCPU - physical core ratio	1 vCPU to 1 physical core at scale maximums	
Configuration	Network latency	< 500 ms	
Configuration	Network packet loss	< 2%	
Configuration	Maximum number of cloud proxies in a cluster	1000	
Configuration	Maximum Objects	16,000	
Configuration	Maximum Collected Metrics	2,400,000	
VCF Operations Application Monitoring (telegraf) agents	Maximum number of telegraf agents	500	

Recommended Configuration Limits

Category		Limits	Description
Bandwidth	Minimum required bandwidth (Mbps)	80	
Log Forwarder	Maximum logs per second traffic (eps)	20,000	
Log Forwarder	Maximum number of connections	300	
Standard Deployments with Unified Cloud Proxy			
Configuration	vCPU	8	
Configuration	Memory (GB)	48	
Configuration	vCPU - physical core ratio	1 vCPU to 1 physical core at scale maximums	
Configuration	Network latency	< 500 ms	
Configuration	Network packet loss	< 2%	
Configuration	Maximum number of cloud proxies in a cluster	1000	
Configuration	Maximum Objects	80,000	
Configuration	Maximum Collected Metrics	12,000,000	
VCF Operations Application Monitoring (telegraf) agents	Maximum number of telegraf agents	3000	
Bandwidth	Minimum required bandwidth (Mbps)	200	
Log Forwarder	Maximum logs per second traffic (eps)	40,000	
Log Forwarder	Maximum number of connections	600	
VCF Operations for Log : Small Deployment			
Configuration	Log Ingestion Rate	30 GB/day	
Configuration	vCPU	4	
Configuration	Memory (GB)	8	
Configuration	IOPS	500	
Configuration	Syslog Connections (Active TCP Connections)	100	
Configuration	Events per Second	2000	
VCF Operations for Log : Medium Deployment			
Configuration	Log Ingestion Rate	75 GB/day	
Configuration	vCPU	8	
Configuration	Memory (GB)	16	
Configuration	IOPS	1000	
Configuration	Syslog Connections (Active TCP Connections)	250	
Configuration	Events per Second	5000	
VCF Operations for Log : Large Deployment			
Configuration	Log Ingestion Rate	225 GB/day	
Configuration	vCPU	16	
Configuration	Memory (GB)	32	
Configuration	IOPS	1500	

Recommended Configuration Limits

Category		Limits	Description
Configuration	Syslog Connections (Active TCP Connections)	750	
Configuration	Events per Second	15,000	
Other Maximums			
Configuration	Number of vCenter on a single collector	120	
Configuration	Number of concurrent users per node	10	This is when the cluster is running with all nodes filled with objects or metrics at maximum levels on a 4 large node cluster.
Configuration	Number of certified concurrent users	300	
Configuration	Maximum number of the Service Discovery objects	3000	
Configuration	Linking vCenter (Group)	15	vCenter linking in VCF Operations provides a single pane of glass view of all the linked vCenter instances from a single vSphere Client.
Continuous Availability	Latency between fault-domains	<10 ms	With peaks up to 20 ms during 20 sec intervals
Continuous Availability	Latency between witness node and fault-domains	<30 ms	With peaks up to 60ms during 20sec intervals
Continuous Availability	Packet loss between fault-domains	peaks up to 2% during 20 sec intervals	
Continuous Availability	Packet Loss between witness node and fault-domains	peaks up to 2% during 20 sec intervals	
Continuous Availability	Bandwidth between fault-domains	10 Gbits/sec	
Continuous Availability	Bandwidth between witness node and fault-domains	10 Mbits/sec	