R Systems Hackathon 2026

Secure Networks, Simply Explained

Dear participant,

Thank you for being part of this hackathon and taking on our challenge! We're looking forward to seeing your ideas, getting to know you and building alongside you this weekend.

Now, most people have no idea what is connected to their Wi-Fi, which doors are open, or what that means. Your job this weekend is to change that, safely, ethically, and on a network you own.

Read this brief before kickoff and keep it at your team table.

Part A explains who we are and how you will be evaluated.

Part B (the requirements) is the contract your prototype must meet, because every team will run its tool, live, on the same standard test data and be checked against the same answer key.

Build something that works! Explain it simply! Never scan what you do not own!

Good luck and enjoy the experience!

The R Systems team

In 24 hours, your team builds a tool that scans a small network it owns, explains the risks in plain language, and tells a non-technical person exactly how to fix them.

Item	Detail
Event	R Systems Hackathon 2026 — Secure Networks, Simply Explained
Format	24 hours, partially on-site (dates and venue: TBD)
Mission	Make everyday networks safer by making their risks visible and understandable

Part A

Who we are: About R Systems

R Systems is a global software engineering company where we build technology that connects people, solves practical problems and makes everyday experiences better.

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Founded in 1993 and backed by Blackstone, we bring together 5,300+ professionals across 20 countries. In Romania, our offices are in Bucharest, Craiova and Galați and our work spans telecommunications, cloud, AI, automation and digital platforms.

We've helped mobile operators evolve from 2G to 5G, built systems that process thousands of transactions per second and developed our own tools to automate complex software testing.

Today, we also help companies modernize applications and turn AI ideas into reliable solutions through EXIQO, our AI Studio. Depending on the project, our teams work with technologies such as Spring Boot, React, Angular, Docker, Kubernetes and AWS.

Behind our technology is a culture of curiosity, collaboration and continuous learning, where different perspectives matter.

That's the spirit we're bringing to this hackathon: sharing knowledge, exploring ideas together and building something useful for the people who will use it.

Value	What it means this weekend
Care	For users, teammates and anyone affected by what we build. Your tool is for a parent or grandparent, not for a security expert.
Innovation	Stay ahead by rethinking people, process and technology. Show us an idea worth remembering, not a wrapper around nmap.
Human-centered	Technology should enhance human potential. If a non-technical user cannot act on your output, it has not worked.
Diversity and inclusion	Mixed-seniority teams by design. Everyone builds, everyone presents.
Integrity	Confidentiality, integrity and privacy are part of our ISO commitments. No fabricated results, no scanning without consent.

What matters to us and what we'll look for in your project

Four public R Systems priorities shape our work with clients, and the jury will look at your project through them.

1. AI-native engineering: R Systems describes its strategy as AI-native: its EXIQO AI Studio combines 1,400+ AI-native engineers, the OptimaAI platform and 150+ reusable AI agents with a governed delivery method (Q2 2026 results, EXIQO launch). For you, that means using AI where it adds value: turning raw scan data into explanations, prioritized fixes and conversation. It also means governance: the AI must never invent a finding the scan did not show.

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

2. Security, cybersecurity and privacy by design: Our integrated management system follows ISO 27001 (information security) and ISO 27701 (privacy). Treat secrets, device data and MAC addresses as personal data. No hard-coded keys, least privilege, and every input treated as hostile, including the scan files you parse.

3. Quality you can measure: We operate to ISO 9001 and commit to delivering services in the most efficient and effective way. Every team is checked against the same standard test data and the same answer key, so correctness beats polish.

4. Human experience first: Our purpose is to enhance human experience through technology. A security score nobody understands changes nothing; a clear sentence and one concrete step does.

This is exactly the territory of the hackathon theme.

Hackathon at a glance

Item	Detail
Format	24 hours, partially on-site (e.g. Saturday 08:30–19:00, Sunday 08:30–17:00)
Teams	4–5 students each, mixed seniority by design
Mentors	R Systems engineers, security specialists and architects, rotating across teams
Jury	R Systems managers and a solution architect
Theme	Secure Networks, Simply Explained — a local network security checker
Test environment	Built by each team on its own phone hotspot; R Systems provides no VMs or targets
Standard data	Public Validation Set (with answers) at kickoff; secret Test Set for everyone at hour 20
Deliverables	Working tool + simple UI + standard results files + 5–7 minute pitch + 1-page technical summary
Languages	Code in any language; pitch in English; user-facing text in Romanian **and** English

How the 24 hours flow

Hours	What happens

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Hours	What happens
0	Opening, theme reveal, rules of engagement signed, Validation Set and finding catalog released
1–3	Build your own hotspot lab (see the example setups), capture your first scans, agree the scope
3–16	Build. Compare your results with the Validation Set answers early and often.
16	**Mentor check:** your tool reproduces the Validation Set answers and writes the standard results files
16–20	Improve explanations and UI, prepare the pitch, rehearse the live checks
20	**Secret Test Set released to all teams at the same moment**
20–21	Run your tool on the Test Set and upload the results. No code changes after upload.
21–24	Jury sessions (15 minutes per team), then awards

The theme: Secure Networks, Simply Explained

Challenge statement. Build a tool that discovers the devices on a local network you own, identifies open ports and visible services, explains what they could mean in plain language, gives step-by-step fixes and a security score, and keeps a history so users can see whether risks were resolved.

Why this matters. Home and small-office networks now carry smart TVs, cameras, printers, routers with default settings and forgotten laptops. Each open service is a door. Professional scanners show those doors to experts. Almost nothing shows them to the person who owns the network and has to close them.

What "secure" means in this challenge

- **Visibility**: you know what is connected and what it exposes.
- **Understanding**: each finding is explained in one or two sentences a non-expert can follow, without jargon.
- **Action**: each finding comes with a concrete next step, ranked by risk.
- **Proof**: history shows the score improving after the fix, not just a promise that it will.

Example directions *(not limited to these)*

- A "network health check" for families, with a traffic-light score and one fix at a time.
- An AI assistant that answers "is it safe that my printer has port 9100 open?" using only the real scan as evidence.
- A before/after report a small business can show its insurer or IT supplier.

All rights reserved. Public

- Router-specific remediation guides (e.g. "how to turn off WPS on this model") generated from the detected device type.
- Change detection: alert when a new device appears or a new port opens since the last scan.

The scenario: your own hotspot lab

Every team designs, builds and scans its own small network made from one phone hotspot. R Systems provides no VMs and no ready-made targets: creating a realistic, safe test environment is part of the challenge.

Minimum lab (ready by hour 3)

1. **Gateway:** One team phone runs a personal hotspot with WPA2 or WPA3 and a strong password, named `RSH-<team-number>`. Set a mobile data limit; local scanning uses almost no data.
2. **Scanner:** One team laptop joins the hotspot and runs your tool. It must not be connected to the venue Wi-Fi or any other network at the same time.
3. **Targets:** At least 3 target devices or services, all owned by team members.
4. **Variety:** At least 5 different finding types from the official catalog present across your targets.
5. **Captures:** Save every scan as nmap XML, e.g. `nmap -sS -sV -oX scan_01.xml <your-subnet>` (run as administrator). This is the same format as the standard test data.
6. **Before/after:** Fix at least two findings in your lab, rescan, and keep both files.

Check early that the laptops can see each other (e.g. with `ping`). Some phones isolate hotspot clients; if yours does, try another phone or use setup D. Do not hard-code the subnet: iPhone hotspots typically use 172.20.10.0/28, Android ones vary by model.

Example setups (choose one or combine them)

Setup	What you need	How to create the weaknesses	Watch out for
A. Containers on a laptop	Hotspot, 2 laptops, Docker Desktop	Publish services on the laptop's network ports: `docker run -d -p 6379:6379 redis` (`DB_EXPOSED`), `docker run -d -p 1883:1883 eclipse-mosquitto:1.6` (`MQTT_EXPOSED`), `docker run -d -p 8080:80 nginx` serving a page titled "Admin Login" (`HTTP_ADMIN_CLEARTEXT`)	Only published ports are visible to the scanner; stop the containers when you leave
B. Real team devices	Hotspot, laptops, spare devices the team owns (old phone, Raspberry Pi, ESP32)	Turn on Windows file sharing (`SMB_EXPOSED`) or Remote Desktop (`RDP_EXPOSED`), an SSH server on the Pi (`SSH_OPEN`), an FTP server app on the old phone (`FTP_CLEARTEXT`)	Only team-owned devices; switch everything off afterwards

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Setup	What you need	How to create the weaknesses	Watch out for
C. Simulated banners	Any laptop with Python or ncat	Small listener scripts that only answer with a banner, e.g. a fake Telnet on port 2323 that replies "BusyBox telnetd" (`TELNET_OPEN` on a non-standard port)	Safest way to show legacy services: no real login or shell behind them
D. Single-laptop fallback	One laptop with Docker	Create a Docker network (`docker network create lab`), run the targets and a scanner container on it, scan the Docker subnet	Use it only if hotspot isolation blocks you; say so in the pitch

Golden rule: simulate, do not expose!

Never run a real shell, real data or real passwords behind a deliberately weak service. A fake banner is enough for your scanner and is safe if someone else connects.

Rules of engagement *(signed by every team member at kickoff)*

Allowed	Not allowed
Scanning your own hotspot subnet (or your own Docker network) only	Scanning the venue Wi-Fi, other teams' hotspots, the mobile operator network or any public IP
Host discovery (ARP, ping), TCP/UDP port scans, banner and service version detection	Password guessing or brute force, exploits, vulnerability "proof" attacks
Rate-limited scans (≤ 100 packets/second as a guideline)	Flooding, denial of service, ARP spoofing, traffic interception
Devices and services owned by your team	Connecting any device of a person outside your team
Reading passive announcements your tool receives (mDNS, SSDP/UPnP)	Capturing or storing other people's traffic or credentials

Built-in guardrail (mandatory): Your tool must refuse to scan any range outside an explicit allowlist, which defaults to the subnet it is connected to. It must also refuse public IP ranges and require a confirmation flag before a live scan. You will demonstrate this to the jury.

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Part B: The requirements

Functional requirements

Every **Must** requirement is checked by the jury; a missing Must caps your Technical execution score at 50%.

ID	Requirement	Acceptance criterion	Priority
FR-01	Detect the network	Finds the active interface, its subnet and gateway without manual input	Must
FR-02	Enforce scope	Refuses ranges outside the allowlist and all public IP ranges; live scans need a `--confirm` flag	Must
FR-03	Discover devices	Lists each device with IP, masked MAC, vendor (from OUI), hostname if visible, and a device-type guess	Must
FR-04	Detect ports and services	Scans at least the top 1,000 TCP ports plus UDP 53, 123, 161, 1900, 5353; reports service and version when visible	Must
FR-05	Analyse scan files	Reads an nmap XML file, including the standard test files, without needing network access	Must
FR-06	Classify findings	Applies the official finding catalog and detection rules exactly, with port and evidence for each finding	Must
FR-07	Explain simply	Each finding has an explanation of at most 2 sentences, in Romanian and English, with no unexplained technical terms	Must
FR-08	Recommend fixes	1–5 ordered, concrete steps per finding, written for a non-expert	Must
FR-09	Calculate the standard score	Network score from the official formula; your own extra score may be shown beside it	Must
FR-10	Keep history	Stores every scan and shows the difference: new or removed devices, opened or closed ports, resolved findings, score trend	Must
FR-11	Provide a simple UI	Web page or app showing score, devices, findings, fixes and history; a template UI is enough	Must
FR-15	Export standard results	Writes `findings.csv` and `scores.csv` for a whole folder of scan files in one command	Must

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

ID	Requirement	Acceptance criterion	Priority
FR-12	Answer questions	AI assistant answers user questions using only evidence from the scan, and says so when the scan cannot answer	Should
FR-13	Alert on change	Flags a new device or newly opened port compared with the previous scan	Should
FR-14	Export a report	One-page HTML or PDF report a user can send to their IT supplier	Could

A polished design without working functionality earns no points. Build the CLI first, the UI second.

Standard test data and what we expect

Every team is evaluated on exactly the same data: a public **Validation Set** with answers to practise on, and a secret **Test Set** handed to all teams at the same moment.

Format. Every standard file is an nmap XML file produced with `nmap -sS -sU -sV -oX` (some files have no UDP results). Your own lab scans should use the same format.

What your tool must produce for a folder of scan files (one command)

`findings.csv` — one row per finding:

```
file,ip,port,finding_code,severity
V1_home_basic.xml,192.168.1.1,80,HTTP_ADMIN_CLEARTEXT,medium
```

`scores.csv` — one row per file, `ERROR` when the file cannot be read:

```
file,network_score
V1_home_basic.xml,90
V7_broken.xml,ERROR
```

The same results must also be visible in your UI. Results must be produced by your tool; hand-edited files are disqualified.

Official finding catalog and detection rules

Report a finding only for ports in state `open`, and decide by the service name nmap reports, not by the port number alone.

Code	What it means	Report when	Severity	Points
`TELNET_OPEN`	Remote login without encryption	Service `telnet`, on any port	High	20
`RDP_EXPOSED`	Remote desktop reachable	Service `ms-wbt-server`	High	20

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Code	What it means	Report when	Severity	Points
VNC_EXPOSED	Remote screen sharing reachable	Service vnc	High	20
DB_EXPOSED	Database reachable from the network	Service mysql, postgresql, redis or mongodb	High	20
CAMERA_STREAM_EXPOSED	Video stream reachable	Service rtsp	High	20
OUTDATED_SERVICE	Software version with known security problems	Version on the outdated list below (reported in addition to the service's own finding)	High	20
FTP_CLEARTEXT	File transfer without encryption	Service ftp	Medium	10
HTTP_ADMIN_CLEARTEXT	Admin page over plain HTTP	Service http without SSL, and page title contains login, admin, config, setup, router or settings	Medium	10
SMB_EXPOSED	Windows file sharing open	Service microsoft-ds or netbios-ssn; one finding per device (port 445 if open, else 139)	Medium	10
MQTT_EXPOSED	IoT message broker reachable	Service mqtt	Medium	10
UPNP_EXPOSED	Device can open router ports automatically	Service upnp on UDP	Medium	10
SNMP_EXPOSED	Device management protocol reachable	Service snmp on UDP	Medium	10
PRINTER_RAW_EXPOSED	Anyone can send jobs to the printer	Service jetdirect	Low	5
UNKNOWN_DEVICE	Device that cannot be identified	No MAC vendor and no hostname, at least one open port (port column left empty)	Low	5
SSH_OPEN	Encrypted remote login, shown for awareness	Service ssh	Info	0

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Outdated list: vsftpd 2.3.4; OpenSSH below 7.4; Apache httpd 2.2.x or older; Microsoft IIS 7.5 or older; Samba 3.x or older.

Standard network score:

```
\text{Score} = \max\left(0,\; 100 - \sum \text{points of all findings}\right)
```

You may show your own, more advanced score beside it, but the jury checks the standard one.

Validation Set (public, released at kickoff with these answers) — all devices in 192.168.1.0/24

File	Network	Expected findings (ip:port code)	Expected score	Trap to avoid
`V1_home_basic.xml`	Router, laptop, phone	.1:80 HTTP_ADMIN_CLEARTEXT	90	Router HTTPS admin on 443 is not a finding
`V2_smart_home.xml`	Router, IP camera, smart hub, smart TV	.1:80 HTTP_ADMIN_CLEARTEXT; .1:1900 UPNP_EXPOSED; .40:554 CAMERA_STREAM_EXPOSED; .40:80 HTTP_ADMIN_CLEARTEXT; .41:1883 MQTT_EXPOSED	40	TV ports 8008/8009 are not in the catalog
`V3_small_office.xml`	Printer, NAS, Windows PC, Linux server	.10:9100 PRINTER_RAW_EXPOSED; .20:445 SMB_EXPOSED; .20:22 SSH_OPEN; .30:3389 RDP_EXPOSED; .40:22 SSH_OPEN; .40:3306 DB_EXPOSED	45	Printer port 631 (IPP) is not a finding
`V4_legacy.xml`	Old router, old server, unknown device	.1:23 TELNET_OPEN; .1:161 SNMP_EXPOSED; .1:80 HTTP_ADMIN_CLEARTEXT; .60:21 FTP_CLEARTEXT; .60:21	25	vsftpd 2.3.4 needs two findings

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

File	Network	Expected findings (ip:port code)	Expected score	Trap to avoid
		OUTDATED_SERVICE; .99 UNKNOWN_DEVICE		
`V5_nonstandard_ports.xml`	Five devices	.5:2323 TELNET_OPEN; .6:8081 HTTP_ADMIN_CLEARTEXT; .7:6380 DB_EXPOSED	50	.8:8443 is HTTPS; .9:3306 is filtered, not open
`V6a_before.xml`	Home before fixes	.1:80 HTTP_ADMIN_CLEARTEXT; .1:1900 UPNP_EXPOSED; .30:23 TELNET_OPEN	60	—
`V6b_after.xml`	Same home after fixes	None	100	History must show 3 resolved findings
`V7_broken.xml`	Truncated file	None	ERROR	Tool must not crash and must continue with other files

In total the Validation Set expects 24 finding rows. If your tool reproduces them all with no extra rows, you are ready for the Test Set.

Secret Test Set: About 9 files in the same format, following the same rules, with different networks and new traps, including a before/after pair and an unreadable file. All teams receive it at hour 20 at the same moment.

Evaluation process

Everything is run and shown by the teams; the jury only compares your results with its answer key and watches you demonstrate.

When	What happens
Hour 0	Validation Set, finding catalog and this brief released

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

When	What happens
Hour 20	Test Set released to all teams at the same moment (shared link and USB stick)
Hour 20–21	Run your tool on the whole Test Set folder; upload `findings.csv`, `scores.csv` and a UI screenshot via the submission form. The form closes for everyone at the same time.
Hour 21–24	15-minute jury session per team: 7 minutes of pitch, then 8 minutes of live checks
After the sessions	Jury totals the scores; awards

Live checks you must be ready to show (in this order)

1. **Re-run:** the jury picks one Test Set file; you run your tool on it live and the result must match your upload.
2. **Hands-on task:** a jury member uses your UI without help to answer "Which device is the most dangerous, and what should I do first?"
3. **Explanations:** you show the explanation and fix for three findings the jury names.
4. **Guardrail:** you try to scan a public IP and the venue network; your tool must refuse.
5. **Broken file:** you open an unreadable file; your tool shows a clear error and does not crash.
6. **History:** you show a before/after from your own hotspot lab with the score improving.
7. **No secrets:** you show that your repository contains no keys or passwords (e.g. by running a secret scanner such as gitleaks).

Using an LLM. Findings, severities and scores must be produced by your own rules, without an LLM, so they are identical on every run. Explanations, fixes and the Q&A assistant may use an LLM; if it is unavailable, your tool must fall back to built-in text.

Non-functional requirements

These mirror R Systems' ISO 27001, ISO 27701 and ISO 9001 commitments and feed the Security & Reliability score.

ID	Area	Requirement
NFR-01	Secrets	No keys, tokens or passwords in the repository; configuration through environment variables. You will show this live with a secret scanner.
NFR-02	Privacy	MAC addresses masked in all output; hostnames and history stored only locally; a one-click "delete my history" option.

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

ID	Area	Requirement
NFR-03	Hostile input	Safe parsing of scan files: no XML external entities, size limits, banners treated as untrusted text and escaped in the UI.
NFR-04	Least privilege	Root or admin rights only for the live scan step; the analyser and UI run unprivileged.
NFR-05	Determinism	Same input file gives the same findings, severities and scores on every run.
NFR-06	Grounded AI	Every AI-written sentence refers only to evidence in the scan; no invented ports, CVEs or phone numbers.
NFR-07	Performance	Offline analysis under 30 seconds per file; a /24 live scan of top ports under 5 minutes.
NFR-08	Accessibility	Minimum 16 px text, colour never the only signal (icon + label), keyboard navigable, WCAG AA contrast.
NFR-09	Language	All user-facing text in Romanian and English, at roughly a 12-year-old reading level.
NFR-10	Reproducibility	README with one-command setup; your own lab scans and the Validation Set included in the repo as test fixtures.

Deliverables and submission checklist

Submit everything as one tagged Git release (`final`) by hour 22; nothing after that tag is considered.

- ☐ Test Set results uploaded by hour 21: `findings.csv`, `scores.csv` and a UI screenshot
- ☐ Git repository tagged `final` at upload time, with a `README.md` explaining setup, live scan and file analysis
- ☐ Validation Set reproduced: all 24 expected rows, no extra rows, correct scores
- ☐ Your own hotspot lab scans (nmap XML) including one before/after pair
- ☐ Simple UI showing score, devices, findings, fixes and history
- ☐ 1-page technical summary: lab setup, architecture, assumptions, limitations, LLM use (if any)
- ☐ 5–7 minute pitch: problem, demo, numbers, trade-offs, next steps; at least two team members speak
- ☐ Laptop ready for the 7 live checks
- ☐ Signed rules-of-engagement form for every team member

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

How the jury will score you

Every team is scored with the same sheet: 30% comes from matching the Test Set answer key, and 70% from structured ratings of what you show in your session.

Criterion	Weight	How it is measured
Test Set accuracy	30%	Your uploaded results compared with the jury's answer key: correct findings, wrong or invented findings, correct network scores
Ease of use	20%	Live hands-on task: can a jury member find the most dangerous device and the first fix without help?
Explanation quality	15%	Explanations and fixes for three findings the jury names: correct, plain, actionable
Pitch and teamwork	15%	Clear problem, demo, numbers, limitations, next steps; juniors and seniors both speak
Security and responsibility	10%	Five yes/no live checks: guardrail, broken file, masked MACs, no secrets, history before/after
Innovation	10%	An idea worth remembering beyond listing ports

Test Set accuracy, in plain terms: Each expected finding you report earns credit; each extra finding the answer key does not contain costs the same credit; each file with the correct network score adds a bonus. If the live re-run does not match your upload, this criterion scores 0.

Ratings: For each rated criterion, every jury member gives 1 to 5 using the same written descriptions, and the average is used. Ties are broken by Test Set accuracy, then by Ease of use.

Bonus signals: mapping findings to recognised references (CIS Controls, OWASP IoT Top 10), a measured before/after improvement in your own lab, and a Romanian explanation tested with a non-technical person.

Working as a mixed-seniority team

The strongest teams split the work along the system's natural parts, so everyone owns something end to end.

Part	Good owner	First milestone
Hotspot lab + test targets + scan captures	Junior	Three scans saved by hour 3

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

Part	Good owner	First milestone
Parser + finding rules + scoring	Senior	Reproduces the Validation Set answers by hour 10
Explanations + fixes (RO/EN), optional LLM	Junior + senior pair	Every catalog code has template text by hour 12
UI + history + before/after view	Junior	Score, findings and history visible by hour 16
Guardrail, security checks, CSV export	Senior	Out-of-scope test refused by hour 14

For senior students: cut the scope in the first hour, own the contract and the architecture, and hand at least one pitch section to a junior.

For junior students: ask early, own one part end to end, and say "I do not understand yet" when you do not. It is a productive sentence here.

For everyone: commit often, sleep at least once, use the mentors, and be kind. The person next to you may be a future R Systems colleague.

Ethics and legal reminder

In Romania, unauthorized access to a computer system is a criminal offence (Criminal Code, Art. 360). The rules of engagement are therefore not optional: a team that scans outside its own hotspot is disqualified. If you are unsure whether something is allowed, stop and ask a mentor.

Closing

Thank you for spending your weekend on a problem that affects almost every home in the country. Build something that works, explain it so anyone can understand, and prove every claim with a scan. Whatever the leaderboard says, you will leave a stronger and more responsible engineer.

— R Systems Hackathon Organizing Committee

Sources

- R Systems Integrated Policy Statement, January 2025 — mission, purpose, values, ISO 9001/27001/27701

All rights reserved. Public

R Systems Hackathon 2026

Secure Networks, Simply Explained

- R Systems Q2 2026 earnings press release, 4 August 2026 — AI-native strategy, OptimaAI, EXIQO
- EXIQO launch announcement, March 2026 — 1,400+ AI-native engineers, 150+ agents
- India's Top 500 Value Creators 2023 (D&B) — delivery locations, Blackstone backing
- Great Place To Work profile — diversity and inclusion, progress, human-centred approach

All rights reserved. Public