

14B12785 藤森慶一郎

In [1]:

```
#問1
def calc(n):
    res = 0
    for i in range(n):
        for j in range(i):
            res+=j
    return res
#オーダーはn^2
```

In [2]:

```
import time

def timeck(n):
    t1 = time.time()
    calc(n)
    t2 = time.time()
    etime = t2-t1
    return etime
```

In [3]:

```
import scipy.optimize
import matplotlib.pyplot as plt
%matplotlib inline
l = []
m = [0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
for n in range(11):
    l.append(timeck(1000*n))
    n +=1
```

In [4]:

```
import numpy as np

def func(x, a, b, c):
    return a*x**2 + b*x + c

result, covariance=scipy.optimize.curve_fit(func,m, l)
print('a =', result[0])
print('b =', result[1])
print('c =', result[2])
x = np.arange(0, 10, 0.1)
y = (result[0] * x **2) + (result[1] * x) + result[2]
plt.scatter(m, l, alpha=0.5)
plt.plot(x, y)
```

```
a = 0.0209900087944
b = -0.000948987531727
c = -0.00553432711575
```

Out[4]:

[<matplotlib.lines.Line2D at 0x2af1900f208>]

