1 Example module (synthetic)

Lt Module Output · Source: c1-r101 · captured 2000-01-01 · exported 2000-01-01

⚠ This page is your own module output, written by lt-module-export. lt-module-answer skips every page stamped with lt-module::, so it is never read back as a source.

Page 3 — Calibration slide images

Explain why immersion oil improves resolution at high magnification.

`i-text-1 · high confidence`

- Immersion oil has a refractive index close to that of glass, so light leaving the slide is not bent away from the objective lens.
  EX-PRAC, slide-14
- This matters for two reasons.
- More of the light cone enters the lens, which raises the numerical aperture and so the finest detail the lens can resolve.
  EX-PRAC, slide-14 · **EX-LECT**, 00:23:40
- Fill: **filled** (verified)

  ⚠ **Lt marks this wrong and the answer stands.** The page holds “Immersion oil matches the refractive index of glass, so light is not bent away from the objective lens.”; Lt's marking indicates “Immersion oil magnifies the image.”, seen via model-answer. The researched answer stands — (**EX-PRAC**, slide-14) — and Lt's marking is evidence about what the unit will accept, not a tier. Lt's model answer gives another reason. Slide 14 supports the draft, so it stays; Lt's wording is kept as a note on what the marker expects.

Not drafted

TODO Record the measured field diameter.

`i-unmapped-1`

- pluginKey 'kcDataValue' has no tested write path.
- Placement: Page 3, panel pk-12, the measured field diameter field. Type the value by hand.