Accordia: Adaptive Cloud Configuration Optimization for Recurring Data-Intensive Applications

Yang Liu¹, Huanle Xu^{1,2} and Wing Cheong Lau¹

¹The Chinese University of Hong Kong, Hong Kong ²Dongguan University of Technology, P.R. China {ly016,xh112,wclau}@ie.cuhk.edu.hk

ABSTRACT

Recognizing the diversity of big data analytic jobs, cloud providers offer a wide range of virtual machine (VM) instances for different use cases. The choice of cloud instance configurations can have significant impact on the response time and running cost of data-intensive, recurring jobs for production. A poor choice of cloud instance-type/configuration can substantially degrade the response time by 5x, or increase the cost by 10x. Identifying the best cloud configuration under low search budget is a challenging problem due to i) the large and high-dimensional configuration-parameters space, ii) the dynamically varying price of some instance types, iii) job response time variation even given the same configuration, and iv) gradual drifts/ unexpected changes of the characteristics of the recurring jobs. To tackle this problem, we have designed and implemented Accordia, a system which enables Adaptive Cloud Configuration Optimization for Recurring Data-Intensive Applications.

Accordia extends the Gaussian-Process Upper Confidence Bound (GP-UCB) approach in [3] to search for and track the *potentially dynamic* optimal cloud configuration within a high-dimensional para-meter-space. Unlike other state-of-the-art schemes, such as CherryPick[1] and Arrow[2], Accordia can handle time-varying instance pricing while providing a performance guarantee of *sublinear regret* when comparing with the static, offline optimial solution.

Figure 1 depicts the system architecture of our implementation of Accordia for Apache Spark running over Kubernetes. When a job is submitted, a Spark driver and multiple Spark executors are deployed as containers, each within its own Kubernetes pod. Accordia then dynamically adjusts the resource types/ allocation for the containers within their respective pods to minimize the job completion cost using the GP-UCB online-learning approach.

To evaluate the performance of Accordia, we have run different mixes of recurring Spark jobs over the Google public cloud. In our experiments, Accordia dynamically learns the best cloud configuration from over 7000 candidate choices within a 5-dimensional parameter space, covering the number of executors, as well as the number of CPU cores and memory (RAM) allocation for the driver and the executor pods. Empirical measurements show that Accordia can find a near-cost-optimal configuration for a recurring job (i.e.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

SoCC '19, November 20–23, 2019, Santa Cruz, CA, USA © 2019 Copyright held by the owner/author(s). ACM ISBN 978-1-4503-6973-2/19/11.

https://doi.org/10.1145/3357223.3365441




Figure 1: System Architecture of Accordia

within 10% of the optimal cost) with fewer than 20 runs, which translates to a 2X-speedup and a 20.9% cost-savings, when comparing to CherryPick. To highlight Accordia's capability to handle abrupt/unexpected changes of the characteristics of a recurring job, we even dynamically switch the type of a recurring job (without notifying Accordia) over exponentially-distributed time-intervals. Under such cases, Accordia can still achieve on average a cost-savings of 18.4% over CherryPick. The full technical report is available at http://mobitec.ie.cuhk.edu.hk/cloudComputing/Accordia.pdf.

CCS CONCEPTS

• Computer systems organization → Cloud computing; • Mathematics of computing → Stochastic processes; Mathematical optimization.

KEYWORDS

Big data analytics, Cloud configuration, Gaussian-Process UCB, Kubernetes

REFERENCES

- Omid Alipourfard, Hongqiang Harry Liu, Jianshu Chen, Shivaram Venkataraman, Minlan Yu, and Ming Zhang. 2017. CherryPick: Adaptively Unearthing the Best Cloud Configurations for Big Data Analytics.. In NSDI, Vol. 2. 4–2.
- [2] Chin-Jung Hsu, Vivek Nair, Vincent W Freeh, and Tim Menzies. 2018. Arrow: Low-Level Augmented Bayesian Optimization for Finding the Best Cloud VM. In ICDCS.
- [3] Niranjan Srinivas, Andreas Krause, Sham Kakade, and Matthias Seeger. 2010. Gaussian Process Optimization in the Bandit Setting: No Regret and Experimental Design. In ICML.