

BP-56-300-B30-V Temptrol II™ Shower System with Hand Spray

Temptrol II Pressure Balancing mixing valve with adjustable stop screw to limit handle turn. Wall/hand shower with 5' flexible metal hose, in-line vacuum breaker, wall connection and flange. 30" slide bar for hand shower mounting.

Modifications:

Suffix X: Integral service stops—allows water shut-off at valve for service



Suffix B: Chrome brass escutcheon on valve

Suffix B48: 48" adjusting bar in place of standard 30" bar

Suffix 6: 6' hose in place of standard 5' hose

Suffix 2.0: 2.0 gpm (7.8 L/min) flow rate

Suffix 1.5: 1.5 gpm (5.7 L/min) flow rate



**SYMMONS PRODUCTS MEET
ANSI A112.18.1M, EPA '92
AND ALL KNOWN FLOW RATE
REQUIREMENTS.
Shower Heads and Hand Showers
2.5 GPM (9.5 L/min)**

Job/Location


.....
.....

Engineer

.....
.....

Contractor

.....
.....

 This drawing to be used for rough-in installation only. All floor to center dimensions optional. Concealed piping and fittings not furnished by manufacturer. Dimensions are for ADA compliance (Americans with Disabilities Act) consult ADAAG or your state regulations for proper product choice and mounting locations. For complete installation, adjustment and service information see installation instructions.

Symmons Industries, Inc. ■ 31 Brooks Drive ■ Braintree, MA 02184
(800) 796-6667, (781) 848-2250 ■ Fax (800) 961-9621, (781) 843-3849
Website: www.symmons.com ■ Email: customerservice@symmons.com

©2003, 2008 Symmons Industries, Inc. Printed in U.S.A. ■ 042808


SYMMONS®
the smart choice™