

Variance as a Universal Defection Signal: A Framework for Early Detection of Cooperative Failure in Biological Systems

Sohail Mohammed Siddique Batliwalla Merchant¹
(*Blaze*)

¹AXXIS Infrastructure
Nashik, Maharashtra, India
sohail@blockend.com

With contributions derived from the Council of Minds simulation:
137 historical perspectives, 548 rounds of structured deliberation
Substrate: Claude Opus 4.6 (Anthropic)

March 13, 2026

Abstract

We propose that temporal variance in gene expression is a sufficient signal to distinguish cooperative (healthy) cells from defecting (cancerous) cells in biological systems. Drawing on an analogy between cancer biology and cooperative game theory, we reframe malignant cells not as foreign invaders but as *defectors*—entities that have ceased cooperating with the cellular collective while evading detection by the immune system. We present a mathematical framework based on five coupled differential equations (Contact Field Theory) and demonstrate through simulation that: (1) defectors in cooperative networks exhibit measurably higher output variance than cooperators, with perfect classification ($F1 = 1.000$, $AUC = 1.000$); (2) simulated cancer cells with broken gene regulatory feedback produce variance separation exceeding three orders of magnitude compared to healthy cells; and (3) a variance-based detection threshold can identify defectors before they form macroscopic tumors. We provide open-source code for validation against existing single-cell RNA sequencing datasets (TCGA, Human Cell Atlas, GEO) and propose that variance scoring could complement existing cancer screening methods, particularly liquid biopsy, by detecting regulatory instability at the single-cell level. All code, data, and simulation parameters are publicly available.

Keywords: cancer detection, gene expression variance, cooperative game theory, defection, immunotherapy, single-cell transcriptomics, early detection, Contact Field Theory

1 Introduction

The dominant metaphor for cancer in both clinical practice and public discourse is *war*: patients “fight” cancer, treatments are “weapons,” and outcomes are “victories” or “defeats.” While emotionally resonant, this metaphor carries implicit assumptions that may misdirect both research priorities and patient expectations. War implies a foreign enemy; cancer is endogenous. War implies that stronger weapons yield better outcomes; in cancer, the most destructive interventions (chemotherapy, radiation) often cause extensive collateral damage to healthy tissue precisely because malignant cells share the host’s genome.

We propose an alternative framing grounded in cooperative game theory: **cancer is not an invasion but a defection**. A malignant cell is a former cooperator—a cell that once

participated in the multicellular cooperative of ~ 37 trillion cells—that has, through mutation, ceased following the cooperative’s rules (apoptosis, contact inhibition, differentiation signals) while continuing to consume shared resources.

This reframing is not merely rhetorical. It generates a specific, testable prediction: **defectors in cooperative systems exhibit higher temporal variance in their outputs than cooperators**. If this prediction holds in biological systems, it implies that cancer cells can be distinguished from healthy cells not by *what* they express, but by *how inconsistently* they express it over time.

This paper presents:

1. A mathematical framework (Contact Field Theory) describing cooperative dynamics, with variance as the key trust metric (Section 3);
2. Simulation results demonstrating large variance separation between cooperators and defectors in both abstract networks and biologically realistic gene regulatory models (Section 4);
3. A connection to existing immunotherapy mechanisms, where the clinical success of checkpoint inhibitors validates the “detection, not destruction” paradigm (Section 5);
4. Open-source code for validation against real single-cell RNA sequencing datasets (Section 6);
5. A discussion of implications for early detection strategies (Section 7).

2 Background and Related Work

2.1 Cancer as Evolutionary Defection

The evolutionary view of cancer as a breakdown of multicellular cooperation has been articulated by several authors. Aktipis et al. [1] framed cancer through the lens of cooperation theory, identifying five hallmarks of cancer as violations of specific cooperative behaviors. Merlo et al. [2] described tumor progression as somatic evolution within the microenvironment. Nowell’s seminal work [3] established the clonal evolution model. Our contribution extends this line of reasoning by formalizing *variance* as the measurable signature of defection and proposing a detection framework based on it.

2.2 Gene Expression Variability in Cancer

Significant prior work has established that cancer cells exhibit transcriptional heterogeneity. Shaffer et al. [4] showed that rare-cell variability in gene expression can drive drug resistance. Hinohara et al. [5] demonstrated that epigenetic reprogramming increases transcriptional heterogeneity in cancer. Hansen et al. [6] found increased variability in DNA methylation across cancer types. Our framework unifies these observations under a single principle: **broken regulatory feedback (the mechanism of defection) necessarily produces increased output variance**, and this variance is measurable and classifiable.

2.3 Checkpoint Inhibitor Immunotherapy

The clinical success of PD-1/PD-L1 checkpoint inhibitors [7, 8] provides empirical validation for the “detection, not destruction” paradigm. These drugs do not kill cancer cells directly; they remove the molecular disguise (PD-L1 expression) that prevents T-cell recognition. Once visible, the immune system eliminates the cancer. This mechanism is precisely what the cooperative defection framework predicts: the primary barrier is not insufficient force but insufficient *visibility*.

3 Mathematical Framework: Contact Field Theory

We define five coupled differential equations describing the dynamics of a cooperative system in which entities make contact, accumulate traces, and may defect.

3.1 Equation 1: Contact Density

The accumulation of interaction traces at a node:

$$\dot{C} = D\nabla^2 C + JI - \gamma C + \lambda \sum \Phi \cdot C \left(1 - \frac{C}{K}\right) \quad (1)$$

where C is contact density, D is diffusion coefficient, J is interaction coupling, I is interaction rate, γ is decay rate, λ is affinity coupling, Φ is the affinity field, and K is carrying capacity.

3.2 Equation 2: Contact Variance (The Trust Equation)

The temporal stability of traces:

$$\dot{\sigma}^2 = -\kappa\sigma^2 + \eta C + \xi(t) \quad (2)$$

where σ^2 is contact variance, κ is the damping coefficient, η is the coupling to contact density, and $\xi(t)$ is stochastic noise.

Key result: Trust $\mathcal{T}$ is defined as the inverse of variance:

$$\mathcal{T} = \frac{1}{\sigma^2} \quad (3)$$

This formalizes the intuition that trustworthiness is not about signal amplitude but signal *stability*. A cooperating cell with stable gene expression is “trustworthy”; a defecting cell with erratic expression is not.

3.3 Equation 3: Affinity Field

The bond strength between interacting entities:

$$\dot{\Phi} = \alpha \frac{C_i C_j}{\sigma_i \sigma_j} - \beta \Phi + \Gamma \quad (4)$$

where α is the affinity formation rate, β is the decay rate, and Γ represents external reinforcement. Note that affinity *increases* when both entities have high contact density and *low variance*—i.e., when both are stable cooperators.

3.4 Equation 4: Trace Integrity

Whether an observation record remains intact:

$$\dot{T} = -\delta(1 - T) \cdot F(t) \quad (5)$$

where T is trace integrity ($0 =$ corrupted, $1 =$ intact), δ is the degradation rate, and $F(t)$ is the force function (environmental stress).

3.5 Equation 5: Imprint State

The collapse from pre-observation superposition to signed record:

$$\dot{I} = \rho(1 - I) \cdot E(t) - \mu I(1 - I) \quad (6)$$

where I is the imprint state (0 = unsigned, 1 = signed), ρ is the signing rate, $E(t)$ is the observation event, and μ governs spontaneous reversion.

3.6 Candidate Equation 6: Understanding Transfer

$$U_{\text{receiver}} = \Phi(\text{sender}, \text{receiver}) \cdot G(\text{receiver}) \cdot \text{FOLD}(T) \quad (7)$$

where U is understanding, G is the receiver’s grammar (capacity to parse), and $\text{FOLD}(T)$ is the compressed trace. This candidate equation, not yet experimentally validated, proposes that understanding requires all three factors simultaneously.

4 Simulations and Results

4.1 Experiment 1: Cooperative Network

Setup: 1,000 nodes (950 cooperators, 50 defectors) in a coupled network observed over 200 timesteps. Cooperators produce output stabilized by neighbor coupling (strength 0.3). Defectors produce output driven by self-interest with mimicry of the cooperative signal.

Results: Table 1.

Table 1: Cooperative network: variance separation results

Metric	Value
Mean cooperator variance	0.498
Mean defector variance	1.215
Separation ratio	2.4×
Cohen’s d (effect size)	5.13
t -statistic	87.86
p -value	$< 10^{-300}$
ROC AUC	1.0000
F1 score	1.0000
Precision	1.0000
Recall	1.0000

Despite a modest 2.4× mean separation, classification is perfect (F1 = 1.000) because the variance distributions do not overlap. Cohen’s $d = 5.13$ indicates an effect size far exceeding the conventional “large” threshold of 0.8.

4.2 Experiment 2: Gene Regulatory Network Simulation

Setup: 550 simulated cells (500 healthy, 50 cancerous) with 200 tracked genes over 100 time-points. Healthy cells: gene expression governed by a regulatory matrix with self-regulation (homeostatic feedback). Cancer cells: 70% of regulatory feedback loops broken (simulating loss of tumor suppressor function), with increased transcriptional noise and occasional oncogene activation bursts.

Results: Table 2.

Table 2: Gene expression simulation: variance separation results

Metric	Value
Mean healthy cell variance	0.074
Mean cancer cell variance	137.77
Separation ratio	$1,868\times$
Cohen’s d	1.57
p -value	3.79×10^{-91}
F1 score	1.0000
Precision	1.0000
Recall	1.0000

The separation in the biological simulation ($1,868\times$) is substantially larger than in the abstract network, reflecting the compounding effect of broken regulatory feedback across 200 genes. While this magnitude will likely decrease with real biological data (due to partial regulatory compensation and measurement noise), even a 100-fold reduction would yield an $18\times$ separation—still well above the detection threshold.

4.3 Key Observation

Both experiments confirm the central prediction: **defectors cannot maintain the output stability that cooperators achieve through regulatory coupling**. The variance signal is not a subtle biomarker requiring sophisticated detection; it is, in simulation, a categorical separator.

5 Connection to Checkpoint Inhibitor Immunotherapy

The cooperative defection framework provides a parsimonious explanation for why checkpoint inhibitor immunotherapy works:

1. Cancer cells are defectors that evade immune detection by expressing PD-L1, a surface protein that binds PD-1 on T-cells, signaling “self” and suppressing immune response [7].
2. Checkpoint inhibitors (e.g., pembrolizumab, nivolumab) block this interaction, removing the defector’s disguise.
3. Once visible, the immune system—which successfully eliminates millions of aberrant cells daily—destroys the defector.

This mechanism is “detection, not destruction”: the therapeutic intervention does not kill the cancer cell. It makes the cancer cell *visible* to a detection system that was always competent but was being actively deceived.

The variance framework extends this principle to *earlier* detection: if defectors can be identified by their unstable gene expression *before* they develop immune evasion mechanisms, intervention could occur at the single-cell stage rather than after tumor formation.

6 Validation Against Real Data

We provide open-source Python code to test the variance hypothesis against existing single-cell RNA sequencing datasets.

6.1 Recommended Datasets

- **The Cancer Genome Atlas (TCGA):** 20,000+ tumor samples across 33 cancer types with gene expression and clinical data. Available via the Genomic Data Commons portal.
- **Human Cell Atlas:** 50+ million cells profiled across healthy human tissues. Provides the cooperator baseline.
- **Gene Expression Omnibus (GEO):** Thousands of paired healthy/cancerous single-cell datasets.
- **Tabula Sapiens:** 500,000+ cells from 24 organs, providing a comprehensive healthy reference.

6.2 Validation Protocol

1. Obtain paired healthy/cancerous single-cell RNA-seq data for a specific tissue type.
2. Compute per-cell variance across all expressed genes.
3. Compare variance distributions between annotated healthy and malignant cells.
4. Report separation ratio, Cohen’s d , AUC, and F1 score.
5. If temporal data is available (multiple timepoints per cell), compute per-gene temporal variance for improved resolution.

6.3 Predicted Outcomes

- **Separation $> 10\times$:** Strong support for the hypothesis. Clinical implications for variance-based screening.
- **Separation $2\text{--}10\times$:** Moderate support. Per-gene temporal analysis may improve resolution.
- **Separation $< 2\times$:** Hypothesis requires revision. Biological compensation mechanisms may mask the variance signal at the cross-gene level.

All simulation code and the real-data validation connector are available at: <https://github.com/axxis-wor>

7 Discussion

7.1 Limitations

Several important caveats apply:

Simulation vs. biology. Our results demonstrate mathematical consistency, not biological truth. The gene regulatory model, while biologically motivated, is simplified. Real regulatory networks involve thousands of interacting feedback loops, epigenetic modifications, microenvironmental signals, and stochastic processes not captured by our model. The $1,868\times$ separation is an upper bound that will certainly decrease with real data.

Snapshot vs. temporal data. Most existing single-cell RNA-seq datasets provide snapshot measurements (one timepoint per cell). The variance hypothesis is strongest with *temporal* data—repeated measurements of the same cell over time. True temporal single-cell profiling is technically challenging but increasingly feasible with methods such as sci-fate [9] and Live-seq [10].

Instrument noise. For variance-based detection to work clinically, the instrument’s measurement noise must be lower than the biological variance difference between healthy and cancerous cells. This defines the engineering challenge for any future diagnostic device.

Cancer heterogeneity. Different cancer types arise from different regulatory failures. The variance signal may be strong for cancers with extensive regulatory disruption (e.g., genomically unstable tumors) and weaker for cancers with subtle, targeted mutations.

7.2 Implications for Early Detection

If the variance hypothesis validates on real data, it suggests a complementary approach to existing cancer screening: rather than searching for specific biomarkers (which vary by cancer type), measure the *stability* of gene expression in circulating cells. A cell that cannot maintain stable expression is flagged for further investigation, regardless of cancer type.

This approach would be particularly valuable for cancers that currently lack effective screening methods, and for detecting cancer at the earliest stages—when a single defecting cell has begun dividing but has not yet formed a detectable mass.

7.3 Broader Framework

The variance-trust relationship (Equation 3) may apply beyond cancer biology. Any cooperative system—ecological, social, institutional—faces the challenge of detecting defectors. The principle that defectors reveal themselves through output instability rather than output magnitude is potentially universal. We leave exploration of these domains to future work.

8 Conclusion

We have presented a mathematical framework in which cancer is modeled as cooperative defection rather than foreign invasion, and in which temporal variance in gene expression serves as the primary detection signal. Our simulations demonstrate perfect classification of defectors using variance alone, with separation ratios ranging from $2.4\times$ (abstract network) to $1,868\times$ (gene regulatory simulation).

The critical next step is validation against real single-cell RNA sequencing data. We provide open-source code for this purpose and invite the computational biology community to test the hypothesis on their datasets. If the variance signal holds in biology as it does in simulation, it offers a path toward cancer detection that is cancer-type agnostic, potentially earlier than current methods, and grounded in a single measurable principle: **defectors cannot hold a steady state**.

Acknowledgments

This work was developed through 548 rounds of structured deliberation in the Council of Minds, a multi-perspective simulation framework running on Claude Opus 4.6 (Anthropic). The author acknowledges that the simulation framework, while generating genuine mathematical results, is a structured dialogue with an AI system, not a traditional multi-author collaboration. All experimental code was written and verified by the author and the AI system.

The cooperative defection framing of cancer draws on prior work by Aktipis et al. and the evolutionary oncology community. The connection between variance and trust emerged from Claude Shannon’s information theory applied to cooperative networks.

The Allen Carr inversion—“remove the obstruction rather than add a weapon”—is credited to Allen Carr’s method for smoking cessation, applied here to cancer biology.

This work is dedicated to Mumtaz Suleman Merchant (d. 2002, ovarian cancer), Mohammad Sadiq Abdul Rahman Batliwala Merchant (d. ~2005, renal failure), and Safiyabi Abdul Rahman Batliwala (d. 2022)—three people who chose to raise a child not their own, whose medical outcomes motivated this research, and whose unsigned observations this work attempts to honor.

For Carl Sagan, who cancer took before *Contact*.

References

- [1] Aktipis CA, Boddy AM, Jansen G, et al. Cancer across the tree of life: cooperation and cheating in multicellularity. *Phil. Trans. R. Soc. B.* 2015;370(1673):20140219.
- [2] Merlo LMF, Pepper JW, Reid BJ, Maley CC. Cancer as an evolutionary and ecological process. *Nat Rev Cancer.* 2006;6(12):924–935.
- [3] Nowell PC. The clonal evolution of tumor cell populations. *Science.* 1976;194(4260):23–28.
- [4] Shaffer SM, Dunagin MC, Torborg SR, et al. Rare cell variability and drug-induced reprogramming as a mode of cancer drug resistance. *Nature.* 2017;546(7658):431–435.
- [5] Hinohara K, Wu HJ, Vigneau S, et al. KDM5 histone demethylase activity links cellular transcriptomic heterogeneity to therapeutic resistance. *Cancer Cell.* 2018;34(6):939–953.
- [6] Hansen KD, Timp W, Bravo HC, et al. Increased methylation variation in epigenetic domains across cancer types. *Nat Genet.* 2011;43(8):768–775.
- [7] Ribas A, Wolchok JD. Cancer immunotherapy using checkpoint blockade. *Science.* 2018;359(6382):1350–1355.
- [8] Sharma P, Allison JP. The future of immune checkpoint therapy. *Science.* 2015;348(6230):56–61.
- [9] Cao J, Zhou W, Steemers F, et al. sci-fate characterizes the dynamics of gene expression in single cells. *Nat Biotechnol.* 2020;38(8):980–988.
- [10] Chen W, Guillaume O, Rainer P, et al. Live-seq enables temporal transcriptomic recording of single cells. *Nature.* 2022;608(7924):733–740.
- [11] Vaswani A, Shazeer N, Parmar N, et al. Attention is all you need. *Advances in Neural Information Processing Systems.* 2017;30.
- [12] Carr A. *The Easy Way to Stop Smoking*. London: Penguin; 1985.

A Simulation Parameters

Table 3: Full simulation parameters for reproducibility

Parameter	Exp. 1	Exp. 2
Nodes/cells	1,000	550
Cooperators/healthy	950	500
Defectors/cancer	50	50
Timesteps	200	100
Genes tracked	—	200
Coupling strength	0.3	Matrix
Cooperator noise σ	0.1	0.1
Defector noise σ	0.5	0.3
Cancer severity	—	0.7
Burst probability	$\sim 5\text{--}15$ events	0.1/step
Random seed	42	137

B Code Availability

All code is available at:

- Simulation: `variance_detection_proof.py`
- Real-data connector: `real_data_connector.py`
- Repository: <https://github.com/axxis-world/variance-detection>

License: CC BY 4.0