![Texas Instruments logo]

CD54HC4094, CD74HC4094,
CD74HCT4094

High−Speed CMOS Logic
8−Stage Shift and Store Bus Register, Three−State

Features

¥ **Buffered Inputs**

¥ **Separate Serial Outputs Synchronous to Both Positive and Negative Clock Edges For Cascading**

¥ **Fanout (Over Temperature Range)**
   – **Standard Outputs** . . . . **10 LSTTL Loads**
   – **Bus Driver Outputs** . . . . **15 LSTTL Loads**

¥ **Wide Operating Temperature Range . . . −55°C to 125°C**

¥ **Balanced Propagation Delay and Transition Times**

¥ **Significant Power Reduction Compared to LSTTL Logic ICs**

¥ **HC Types**
   – **2V to 6V Operation**
   – **High Noise Immunity: N_{IL} = 30%, N_{IH} = 30% of V_{CC} at V_{CC} = 5V**

¥ **HCT Types**
   – **4.5V to 5.5V Operation**
   – **Direct LSTTL Input Logic Compatibility, V_{IL}= 0.8V (Max), V_{IH} = 2V (Min)**
   – **CMOS Input Compatibility, $I_I \leq 1\mu A$ at V_{OL}, V_{OH}**

Description

The ÕHC4094and CD74HCT4094 are 8−stage serial shift registers having a storage latch associated with each stage for strobing data from the serial input to parallel buffered three−state outputs. The parallel outputs may be connected directly to common bus lines. Data is shifted on positive clock transitions. The data in each shift register stage is transferred to the storage register when the Strobe input is high. Data in the storage register appears at the outputs whenever the Output−Enable signal is high.

Two serial outputs are available for cascading a number of these devices. Data is available at the QS_1 serial output terminal on positive clock edges to allow for high−speed operation in cascaded system in which the clock rise time is fast. The same serial information, available at the QS_2 terminal on the next negative clock edge, provides a means for cascading these devices when the clock rise time is slow.

Ordering Information

PART NUMBER	TEMP. RANGE (°C)	PACKAGE
CD54HC4094F3A	−55 to 125	16 Ld CERDIP
CD74HC4094E	−55 to 125	16 Ld PDIP
CD74HC4094M	−55 to 125	16 Ld SOIC
CD74HC4094MT	−55 to 125	16 Ld SOIC
CD74HC4094M96G3	−55 to 125	16 Ld SOIC
CD74HC4094NSR	−55 to 125	16 Ld SOP
CD74HC4094PW	−55 to 125	16 Ld TSSOP
CD74HC4094PWR	−55 to 125	16 Ld TSSOP
CD74HC4094PWT	−55 to 125	16 Ld TSSOP
CD74HCT4094E	−55 to 125	16 Ld PDIP
CD74HCT4094M	−55 to 125	16 Ld SOIC
CD74HCT4094MT	−55 to 125	16 Ld SOIC
CD74HCT4094M96	−55 to 125	16 Ld SOIC

NOTE: When ordering, use the entire part number. The suffixes 96 and R denote tape and reel. The suffix T denotes a small−quantity reel of 250.

Pinout

CD54HC4094 (CERDIP)
CD74HC4094 (PDIP, SOIC, SOP, TSSOP)
CD74HCT4094 (PDIP, SOIC)
TOP VIEW

STROBE	1		16	V_{CC}
DATA	2		15	OE
CP	3		14	Q_4
Q_0	4		13	Q_5
Q_1	5		12	Q_6
Q_2	6		11	Q_7
Q_3	7		10	QS_2
GND	8		9	QS_1

Functional Diagram

TRUTH TABLE

| INPUTS				PARALLEL OUTPUTS		SERIAL OUTPUTS	
CP	**OE**	**STR**	**D**	Q_0	Q_n	QS_1 (NOTE 1)	QS_2
↑	L	X	X	Z	Z	$Q\bar{O}6$	NC
↓	L	X	X	Z	Z	NC	Q_7
↑	H	L	X	NC	NC	$Q\bar{O}6$	NC
↑	H	H	L	L	Q_n-1	$Q\bar{O}6$	NC
↑	H	H	H	H	Q_n-1	$Q\bar{O}6$	NC
↓	H	H	H	NC	NC	NC	Q_7

H = High Voltage Level, L = Low Voltage Level, X = DonÕt Care, NC = No charge, Z = High Impedance Off–state,
↑ = Transition from Low to High Level, ↓ = Transition from High to Low.
NOTE:

1. At the positive clock edge the information in the seventh register stage is transferred to the 8th register stage and QS1 output.

Logic Diagram

CD54HC4094, CD74HC4094, CD74HCT4094

Absolute Maximum Ratings

DC Supply Voltage, V_{CC} . . . . –0.5V to 7V
DC Input Diode Current, I_{IK}
  For V_I < –0.5V or V_I > V_{CC} + 0.5V . . . . ±20mA
DC Output Diode Current, I_{OK}
  For V_O < –0.5V or V_O > V_{CC} + 0.5V . . . . ±20mA
DC Output Source or Sink Current per Output Pin, I_O
  For V_O > –0.5V or V_O < V_{CC} + 0.5V . . . . ±25mA
DC V_{CC} or Ground Current, I_{CC} . . . . ±50mA

Operating Conditions

Temperature Range (T_A) . . . . –55°C to 125°C
Supply Voltage Range, V_{CC}
  HC Types . . . . .2V to 6V
  HCT Types . . . . .4.5V to 5.5V
DC Input or Output Voltage, V_I, V_O . . . . .0V to V_{CC}
Input Rise and Fall Time
  2V . . . . .1000ns (Max)
  4.5V . . . . .500ns (Max)
  6V . . . . .400ns (Max)

Thermal Information

Package Thermal Impedance, θ_{JA} (see Note 2):
  E (PDIP) Package . . . . 67°C/W
  M (SOIC) Package . . . . 73°C/W
  NS (SOP) Package 64oC/W
  PW (TSSOP) Package. . . . . .108°C/W
Maximum Junction Temperature (Plastic Package) . . . . 150°
Maximum Storage Temperature Range . . . .–65°C to 150°
Maximum Lead Temperature (Soldering 10s) . . . . .300°
  SOIC – Lead Tips Only)

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

NOTE:

2. The package thermal impedance is calculated in accordance with JESD 51–7.

DC Electrical Specifications

PARAMETER	SYMBOL	TEST CONDITIONS V_I (V)	TEST CONDITIONS I_O (mA)	V_{CC} (V)	25°C MIN	25°C TYP	25°C MAX	–40°C TO 85°C MIN	–40°C TO 85°C MAX	–55°C TO 125°C MIN	–55°C TO 125°C MAX	UNITS
HC TYPES												
High Level Input Voltage	V_{IH}	–	–	2	1.5	–	–	1.5	–	1.5	–	V
				4.5	3.15	–	–	3.15	–	3.15	–	V
				6	4.2	–	–	4.2	–	4.2	–	V
Low Level Input Voltage	V_{IL}	–	–	2	–	–	0.5	–	0.5	–	0.5	V
				4.5	–	–	1.35	–	1.35	–	1.35	V
				6	–	–	1.8	–	1.8	–	1.8	V
High Level Output Voltage CMOS Loads	V_{OH}	V_{IH} or V_{IL}	–0.02	2	1.9	–	–	1.9	–	1.9	–	V
			–0.02	4.5	4.4	–	–	4.4	–	4.4	–	V
			–0.02	6	5.9	–	–	5.9	–	5.9	–	V
High Level Output Voltage TTL Loads			–	–	–	–	–	–	–	–	–	V
			–4	4.5	3.98	–	–	3.84	–	3.7	–	V
			–5.2	6	5.48	–	–	5.34	–	5.2	–	V
Low Level Output Voltage CMOS Loads	V_{OL}	V_{IH} or V_{IL}	0.02	2	–	–	0.1	–	0.1	–	0.1	V
			0.02	4.5	–	–	0.1	–	0.1	–	0.1	V
			0.02	6	–	–	0.1	–	0.1	–	0.1	V
Low Level Output Voltage TTL Loads			–	–	–	–	–	–	–	–	–	V
			4	4.5	–	–	0.26	–	0.33	–	0.4	V
			5.2	6	–	–	0.26	–	0.33	–	0.4	V
Input Leakage Current	I_I	V_{CC} or GND	–	6	–	–	±0.1	–	±1	–	±1	µA
Quiescent Device Current	I_{CC}	V_{CC} or GND	0	6	–	–	8	–	80	–	160	µA

DC Electrical Specifications (Continued)

PARAMETER	SYMBOL	TEST CONDITIONS V$_I$ (V)	TEST CONDITIONS I$_O$ (mA)	V$_{CC}$ (V)	25^{o}C MIN	25^{o}C TYP	25^{o}C MAX	–40^{o}C TO 85^{o}C MIN	–40^{o}C TO 85^{o}C MAX	–55^{o}C TO 125^{o}C MIN	–55^{o}C TO 125^{o}C MAX	UNITS
HCT TYPES												
High Level Input Voltage	V$_{IH}$	–	–	4.5 to 5.5	2	–	–	2	–	2	–	V
Low Level Input Voltage	V$_{IL}$	–	–	4.5 to 5.5	–	–	0.8	–	0.8	–	0.8	V
High Level Output Voltage CMOS Loads	V$_{OH}$	V$_{IH}$ or V$_{IL}$	–0.02	4.5	4.4	–	–	4.4	–	4.4	–	V
High Level Output Voltage TTL Loads			–4	4.5	3.98	–	–	3.84	–	3.7	–	V
Low Level Output Voltage CMOS Loads	V$_{OL}$	V$_{IH}$ or V$_{IL}$	0.02	4.5	–	–	0.1	–	0.1	–	0.1	V
Low Level Output Voltage TTL Loads			4	4.5	–	–	0.26	–	0.33	–	0.4	V
Input Leakage Current	I$_I$	V$_{CC}$ and GND	0	5.5	–	–	±0.1	–	±1	–	±1	µA
Quiescent Device Current	I$_{CC}$	V$_{CC}$ or GND	0	5.5	–	–	8	–	80	–	160	µA
Additional Quiescent Device Current Per Input Pin: 1 Unit Load	ΔI$_{CC}$ (Note 3)	V$_{CC}$ –2.1	–	4.5 to 5.5	–	100	360	–	450	–	490	µA

NOTE:

3. For dual–supply systems theoretical worst case (V$_I$ = 2.4V, V$_{CC}$ = 5.5V) specification is 1.8mA.

HCT Input Loading Table

INPUT	UNIT LOADS
D	0.4
CP, OE	1.5
STR	1.0

NOTE: Unit Load is ΔI$_{CC}$ limit specified in DC Electrical Table, e.g., 360µA max at 25^{o}C.

Prerequisite for Switching Specifications

CHARACTERISTIC	SYMBOL	V$_{CC}$ (V)	25^{o}C MIN	25^{o}C MAX	–40^{o}C TO 85^{o}C MIN	–40^{o}C TO 85^{o}C MAX	–55^{o}C TO 125^{o}C MIN	–55^{o}C TO 125^{o}C MAX	UNITS
HC TYPES									
CP Pulse Width	t$_W$	2	80	–	100	–	120	–	ns
		4.5	16	–	20	–	24	–	ns
		6	14	–	17	–	20	–	ns
STR Pulse Width	t$_{WH}$	2	80	–	100	–	120	–	ns
		4.5	16	–	20	–	24	–	ns
		6	14	–	17	–	20	–	ns

Prerequisite for Switching Specifications   (Continued)

CHARACTERISTIC	SYMBOL	V_{CC} (V)	25°C		−40°C TO 85°C		−55°C TO 125°C		UNITS
			MIN	MAX	MIN	MAX	MIN	MAX	
Data Set−up Time	t_{SU}	2	50	–	65	–	75	–	ns
		4.5	10	–	13	–	15	–	ns
		6	9	–	11	–	13	–	ns
Data Hold Time	t_H	2	3	–	3	–	3	–	ns
		4.5	3	–	3	–	3	–	ns
		6	3	–	3	–	3	–	ns
STR Set−up Time	t_{SU}	2	100	–	125	–	150	–	ns
		4.5	20	–	25	–	30	–	ns
		6	17	–	21	–	26	–	ns
STR Hold Time	t_H	2	0	–	0	–	0	–	ns
		4.5	0	–	0	–	0	–	ns
		6	0	–	0	–	0	–	ns
Maximum CP Frequency	$f_{CL\,(MAX)}$	2	6	–	5	–	4	–	MHz
		4.5	30	–	24	–	20	–	MHz
		6	35	–	28	–	24	–	MHz
HCT TYPES									
CP Pulse Width	t_W	4.5	16	–	20	–	24	–	ns
STR Pulse Width	t_{WH}	4.5	16	–	20	–	24	–	ns
Data Set−up Time	t_{SU}	4.5	10	–	13	–	15	–	ns
Data Hold Time	t_H	4.5	4	–	4	–	4	–	ns
STR Set−up Time	t_{SU}	4.5	20	–	25	–	30	–	ns
STR Hold Time	t_H	4.5	0	–	0	–	0	–	ns
Maximum CP Frequency	$f_{CL\,(MAX)}$	4.5	30	–	24	–	20	–	MHz

Switching Specifications Input t_r, t_f = 6ns

PARAMETER	SYMBOL	TEST CONDITIONS	V_{CC} (V)	25°C			−40°C TO 85°C		−55°C TO 125°C		UNITS
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
HC TYPES											
Propagation Delay Time (Figure 1)	t_{PLH}, t_{PHL}	C_L = 50pF	2	–	–	150	–	190	–	225	ns
CP to QS$_1$			4.5	–	–	30	–	38	–	45	ns
		C_L =15pF	5	–	12	–	–	–	–	–	ns
		C_L = 50pF	6	–	–	26	–	33	–	38	ns
CP to QS$_2$	t_{PLH}, t_{PHL}	C_L = 50pF	2	–	–	135	–	170	–	205	ns
			4.5	–	–	27	–	34	–	41	ns
		C_L =15pF	5	–	11	–	–	–	–	–	ns
		C_L = 50pF	6	–	–	23	–	29	–	35	ns
CP to Q$_n$	t_{PLH}, t_{PHL}	C_L = 50pF	2	–	–	195	–	245	–	295	ns
			4.5	–	–	39	–	49	–	59	ns
			5	–	16	–	–	–	–	–	ns
			6	–	–	33	–	42	–	50	ns
STR to Q$_n$	t_{PLH}, t_{PHL}	C_L = 50pF	2	–	–	180	–	225	–	270	ns
			4.5	–	–	36	–	45	–	54	ns
			6	–	–	31	–	38	–	46	ns

Switching Specifications Input t_r, t_f = 6ns **(Continued)**

PARAMETER	SYMBOL	TEST CONDITIONS	V_{CC} (V)	25°C			–40°C TO 85°C		–55°C TO 125°C		UNITS
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
Output Enable to Q_n	t_{PZH}, t_{PZL}	C_L = 50pF	2	–	–	175	–	220	–	265	ns
			4.5	–	–	35	–	44	–	53	ns
			6	–	–	30	–	37	–	45	ns
Output Disable to Q_n	t_{PHZ}, t_{PLZ}	C_L = 50pF	2	–	–	125	–	155	–	190	ns
			4.5	–	–	25	–	31	–	38	ns
			6	–	–	21	–	26	–	32	ns
Output Transition Time	t_{TLH}, t_{THL}	C_L = 50pF	2	–	–	75	–	95	–	110	ns
			4.5	–	–	15	–	19	–	22	ns
			6	–	–	13	–	16	–	19	ns
Output Disabling Time	t_{PHZ}, t_{PLZ}	C_L =15pF	5	–	10	–	–	–	–	–	ns
Maximum CP Frequency	f_{MAX}	C_L =15pF	5	–	60	–	–	–	–	–	MHz
Input Capacitance	C_{IN}	C_L = 50pF	–	–	–	10	–	10	–	10	pF
Power Dissipation Capacitance (Notes 4, 5)	C_{PD}	C_L =15pF	5	–	90	–	–	–	–	–	pF
Three–State Output Capacitance	C_O	C_L = 50pF	–	–	–	15	–	15	–	15	pF
HCT TYPES											
Propagation Delay Time (Figure 1)	t_{PLH}, t_{PHL}	C_L = 50pF	4.5	–	–	39	–	–	–	–	ns
CP to QS_1		C_L =15pF	5	–	16	–	–	–	–	–	ns
CP to QS_2	t_{PLH}, t_{PHL}	C_L = 50pF	4.5	–	–	36	–	–	–	–	ns
		C_L =15pF	5	–	15	–	–	–	–	–	ns
CP to Q_n	t_{PLH}, t_{PHL}	C_L = 50pF	4.5	–	–	43	–	–	–	–	ns
		C_L =15pF	5	–	18	–	–	–	–	–	ns
STR to Q_n	t_{PLH}, t_{PHL}	C_L = 50pF	4.5	–	–	39	–	–	–	–	ns
Output Enable to Q_n	t_{PZH}, t_{PZL}	C_L = 50pF	4.5	–	–	35	–	–	–	–	ns
Output Disable to Q_n	t_{PHZ}, t_{PLZ}	C_L = 50pF	4.5	–	–	35	–	–	–	–	ns
Output Transition Time	t_{TLH}, t_{THL}	C_L = 50pF	4.5	–	–	15	–	–	–	–	ns
Output Disabling Time	t_{PHZ}, t_{PLZ}	C_L =15pF	5	–	14	–	–	–	–	–	ns
Maximum CP Frequency	f_{MAX}	C_L =15pF	5	–	60	–	–	–	–	–	MHz
Input Capacitance	C_{IN}	C_L = 50pF	–	–	–	10	–	10	–	10	pF
Power Dissipation Capacitance (Notes 4, 5)	C_{PD}	C_L =15pF	5	–	110	–	–	–	–	–	pF
Three–State Output Capacitance	C_O	C_L = 50pF	–	–	–	15	–	15	–	15	pF

NOTES:

4. C_{PD} is used to determine the dynamic power consumption, per register.

5. $P_D = V_{CC}^2 f_i (C_{PD} + C_L)$ where f_i = Input Frequency, C_L = Output Load Capacitance, V_{CC} = Supply Voltage.

Test Circuits and Waveforms

FIGURE 1. DATA PROPAGATION DELAYS, SET–UP AND HOLD TIMES

**FIGURE 2. STROBE PROPAGATION DELAYS AND SET–UP AND HOLD TIMES**

FIGURE 3. ENABLE AND DISABLE TIMES

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
CD54HC4094F3A	ACTIVE	CDIP	J	16	1	Non-RoHS & Green	SNPB	N / A for Pkg Type	-55 to 125	CD54HC4094F3A	Samples
CD74HC4094E	ACTIVE	PDIP	N	16	25	RoHS & Green	NIPDAU	N / A for Pkg Type	-55 to 125	CD74HC4094E	Samples
CD74HC4094M	ACTIVE	SOIC	D	16	40	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094M96	ACTIVE	SOIC	D	16	2500	RoHS & Green	NIPDAU	SN	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094M96G3	ACTIVE	SOIC	D	16	2500	RoHS & Green	SN	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094M96G4	ACTIVE	SOIC	D	16	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094MT	ACTIVE	SOIC	D	16	250	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094NSR	ACTIVE	SO	NS	16	2000	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094NSRE4	ACTIVE	SO	NS	16	2000	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HC4094M	Samples
CD74HC4094PW	ACTIVE	TSSOP	PW	16	90	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HJ4094	Samples
CD74HC4094PWR	ACTIVE	TSSOP	PW	16	2000	RoHS & Green	NIPDAU	SN	Level-1-260C-UNLIM	-55 to 125	HJ4094	Samples
CD74HC4094PWRE4	ACTIVE	TSSOP	PW	16	2000	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HJ4094	Samples
CD74HC4094PWRG4	ACTIVE	TSSOP	PW	16	2000	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HJ4094	Samples
CD74HCT4094E	ACTIVE	PDIP	N	16	25	RoHS & Green	NIPDAU	N / A for Pkg Type	-55 to 125	CD74HCT4094E	Samples
CD74HCT4094EE4	ACTIVE	PDIP	N	16	25	RoHS & Green	NIPDAU	N / A for Pkg Type	-55 to 125	CD74HCT4094E	Samples
CD74HCT4094M	ACTIVE	SOIC	D	16	40	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HCT4094M	Samples
CD74HCT4094M96	ACTIVE	SOIC	D	16	2500	RoHS & Green	NIPDAU	SN	Level-1-260C-UNLIM	-55 to 125	HCT4094M	Samples
CD74HCT4094ME4	ACTIVE	SOIC	D	16	40	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-55 to 125	HCT4094M	Samples

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

[2] **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

[3] MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

[4] There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

[5] Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

[6] Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF CD54HC4094, CD74HC4094 :

● Catalog : CD74HC4094

● Military : CD54HC4094

NOTE: Qualified Version Definitions:

　　　● Catalog - TI's standard catalog product

- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS

TAPE DIMENSIONS

A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CD74HC4094M96	SOIC	D	16	2500	330.0	16.8	6.5	10.3	2.1	8.0	16.0	Q1
CD74HC4094M96	SOIC	D	16	2500	330.0	16.4	6.5	10.3	2.1	8.0	16.0	Q1
CD74HC4094M96G3	SOIC	D	16	2500	330.0	16.8	6.5	10.3	2.1	8.0	16.0	Q1
CD74HC4094M96G4	SOIC	D	16	2500	330.0	16.4	6.5	10.3	2.1	8.0	16.0	Q1
CD74HC4094NSR	SO	NS	16	2000	330.0	16.4	8.2	10.5	2.5	12.0	16.0	Q1
CD74HC4094PWR	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
CD74HC4094PWR	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
CD74HC4094PWRG4	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
CD74HCT4094M96	SOIC	D	16	2500	330.0	16.8	6.5	10.3	2.1	8.0	16.0	Q1
CD74HCT4094M96	SOIC	D	16	2500	330.0	16.4	6.5	10.3	2.1	8.0	16.0	Q1

TAPE AND REEL BOX DIMENSIONS

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CD74HC4094M96	SOIC	D	16	2500	364.0	364.0	27.0
CD74HC4094M96	SOIC	D	16	2500	340.5	336.1	32.0
CD74HC4094M96G3	SOIC	D	16	2500	364.0	364.0	27.0
CD74HC4094M96G4	SOIC	D	16	2500	340.5	336.1	32.0
CD74HC4094NSR	SO	NS	16	2000	853.0	449.0	35.0
CD74HC4094PWR	TSSOP	PW	16	2000	364.0	364.0	27.0
CD74HC4094PWR	TSSOP	PW	16	2000	853.0	449.0	35.0
CD74HC4094PWRG4	TSSOP	PW	16	2000	853.0	449.0	35.0
CD74HCT4094M96	SOIC	D	16	2500	364.0	364.0	27.0
CD74HCT4094M96	SOIC	D	16	2500	340.5	336.1	32.0

D (R−PDSO−G16)   PLASTIC SMALL OUTLINE

0.394 (10,00)
0.386 (9,80)
/C\

16   9

0.244 (6,20)
0.228 (5,80)

0.157 (4,00)
0.150 (3,80)   /D\

1   8

Pin 1
Index Area

0.050 (1,27)

0.020 (0,51)
0.012 (0,31)

⊕ | 0.010 (0,25) Ⓜ

0.069 (1,75) Max

0.010 (0,25)
0.004 (0,10)

0.010 (0,25)
0.005 (0,13)

0.004 (0,10)

Gauge Plane

Seating Plane

0.010 (0,25)   0°–8°

0.050 (1,27)
0.016 (0,40)

4040047−6/M   06/11

NOTES: A. All linear dimensions are in inches (millimeters).
         B. This drawing is subject to change without notice.
       /C\ Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall
            not exceed 0.006 (0,15) each side.
       /D\ Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
         E. Reference JEDEC MS−012 variation AC.

TEXAS
INSTRUMENTS
www.ti.com

D (R-PDSO-G16)   PLASTIC SMALL OUTLINE

Example Board Layout
(Note C)

Stencil Openings
(Note D)

←—14x1,27

←—16x0,55

←—14x1,27

16x1,50—

5,40

5.40

Example
Non Soldermask Defined Pad

Example
Pad Geometry
(See Note C)

—0,60

1,55

Example
Solder Mask Opening
(See Note E)

—0,07

All Around

4211283-4/E 08/12

NOTES: A. All linear dimensions are in millimeters.
          B. This drawing is subject to change without notice.
          C. Publication IPC-7351 is recommended for alternate designs.
          D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should
              contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
          E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

TEXAS
INSTRUMENTS
www.ti.com

PW0016A

6.6
6.2 TYP

A

PIN 1 INDEX AREA

14X 0.65

16

1

5.1
4.9
NOTE 3

2X

4.55

8

9

B

4.5
4.3
NOTE 4

16X 0.30
0.19

⊕ 0.1 Ⓜ C A B

SEATING PLANE

C

⌒ 0.1 C

1.2 MAX

SEE DETAIL A

(0.15) TYP

0.25
GAGE PLANE

0.15
0.05

0°-8°

0.75
0.50

DETAIL A
TYPICAL

4220204/A   02/2017

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

TEXAS
INSTRUMENTS
www.ti.com

16X (1.5)

SYMM

1

16X (0.45)

(R0.05) TYP

16

SYMM

14X (0.65)

8

9

(5.8)

LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X

SOLDER MASK
OPENING

METAL

EXPOSED METAL

0.05 MAX
ALL AROUND

NON-SOLDER MASK
DEFINED
(PREFERRED)

METAL UNDER
SOLDER MASK

SOLDER MASK
OPENING

EXPOSED METAL

0.05 MIN
ALL AROUND

SOLDER MASK
DEFINED

SOLDER MASK DETAILS

4220204/A   02/2017

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

16X (1.5)

SYMM

1

16X (0.45)

(R0.05) TYP

16

SYMM

14X (0.65)

8

9

(5.8)

SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE: 10X

4220204/A   02/2017

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

MECHANICAL DATA

PINS ** DIM	14	16	20	24
A MAX	10,50	10,50	12,90	15,30
A MIN	9,90	9,90	12,30	14,70

4040062/C 03/03

NOTES: A.   All linear dimensions are in millimeters.
         B.   This drawing is subject to change without notice.
         C.   Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

DIM \ PINS **	14	16	18	20
A	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC	0.300 (7,62) BSC
B MAX	0.785 (19,94)	.840 (21,34)	0.960 (24,38)	1.060 (26,92)
B MIN	—	—	—	—
C MAX	0.300 (7,62)	0.300 (7,62)	0.310 (7,87)	0.300 (7,62)
C MIN	0.245 (6,22)	0.245 (6,22)	0.220 (5,59)	0.245 (6,22)

B

14   8

C

1   7

0.065 (1,65)
0.045 (1,14)

0.005 (0,13) MIN

0.060 (1,52)
0.015 (0,38)

0.200 (5,08) MAX

Seating Plane

0.130 (3,30) MIN

A

0°−15°

0.026 (0,66)
0.014 (0,36)

0.100 (2,54)

0.014 (0,36)
0.008 (0,20)

4040083/F 03/03

NOTES: A. All linear dimensions are in inches (millimeters).
         B. This drawing is subject to change without notice.
         C. This package is hermetically sealed with a ceramic lid using glass frit.
         D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
         E. Falls within MIL STD 1835 GDIP1−T14, GDIP1−T16, GDIP1−T18 and GDIP1−T20.

N (R−PDIP−T**)
16 PINS SHOWN

PLASTIC DUAL−IN−LINE PACKAGE

PINS ** DIM	14	16	18	20
A MAX	0.775 (19,69)	0.775 (19,69)	0.920 (23,37)	1.060 (26,92)
A MIN	0.745 (18,92)	0.745 (18,92)	0.850 (21,59)	0.940 (23,88)
MS−001 VARIATION	AA	BB	AC	AD

A

16   9

0.260 (6,60)
0.240 (6,10)

1   8

0.070 (1,78)
0.045 (1,14)

0.045 (1,14)
0.030 (0,76)

0.020 (0,51) MIN

0.200 (5,08) MAX

Seating Plane

0.125 (3,18) MIN

0.100 (2,54)

0.021 (0,53)
0.015 (0,38)

⊕ 0.010 (0,25) Ⓜ

14/18 Pin Only
20 Pin vendor option

0.325 (8,26)
0.300 (7,62)

0.015 (0,38)

Gauge Plane

0.010 (0,25) NOM

0.430 (10,92) MAX

4040049/E 12/2002

NOTES: A. All linear dimensions are in inches (millimeters).
         B. This drawing is subject to change without notice.
         C. Falls within JEDEC MS−001, except 18 and 20 pin minimum body length (Dim A).
         D. The 20 pin end lead shoulder width is a vendor option, either half or full width.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (https:www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.