



AMMAR

INDUSTRIAL CORPORATION



PNEUMATICS | HYDRAULICS | INSTRUMENTATION

FITTINGS • VALVES • HOSES

Brass Compression Fittings (Ferrule Fittings)

Brass fittings are designed for pressure applications and are commonly used for gasoline, grease, oil, water, vacuum, air lines, L.P., and natural gas.



We deal in wide variety of pipe fittings and nipples. Nipples are available in a variety of lengths and thread sizes and fittings are offered in a number of configurations using both male and female pipe threads. Many popular pipe fittings are offered in both bar stock and cast materials. All tapered pipe threads are manufactured to the highest quality standards and tolerances. Used in process control, instrumentation, hydraulic and pneumatic applications, these fittings offer optimum results. Apart from this, these fittings also find application in chemicals & petrochemicals, fertilizers, offshore, power plants, automobile and varied other process industries. Our fittings can also be customized in different sizes and shapes, as per the specifications detailed by the clients.





One Touch Push-in Fittings

One Touch Push-in fittings allow rapid, reliable assembly of circuits to convey compressed air, various gases, or liquids at a wide range of pressures and temperatures. These fittings allow you to exert even greater control over your pneumatic installation. Compact, reliable and easy to install, these fittings can be used in various applications, including food and beverage manufacturing, automotive manufacturing, printing and textile industries.



Two Touch Push-on Fittings (aluminium)

We are professionals in providing an unmatched range of Two Touch Fittings that are used in various industries for different purposes.

- ❑ Quick fitting - the tube can be fitted and detached easily, so that workability is remarkably improved.
- ❑ Accurate jointing - pressure loss is reduced. A large volume of compressed air can be fed with least pressure loss/air leak.
- ❑ Long life-span made of Aluminium, excellent in anti-corrosion and anti-chemicals.
- ❑ Compact design is suited to the pneumatic systems necessary for automation and labor saving. Thus the joints will satisfy strict user's demands.



Air Filters | Air Regulators | Air Lubricators

Air Cylinders | Pneumatic Actuators

Solenoid Valves | Solenoid Coils | Manual Valves



AIR PREPARATION UNITS

We are offering a comprehensive range of Pneumatic FRL units, available with modular designs, filter regulator and lubricator units. Our FRL units are robust in design, construction and are ideal to be used in tough working conditions.

Applications :

Textile Industry | Auto Industry | Instrumentation | Medical equipment | Industrial Machinery
Pharmaceutical Industry | Assembly automation | Foundry | Paper and packaging industry |
Food processing industry



SOLENOID VALVES

Our Solenoid Valves offer fast and safe switching, high reliability, long service life, good medium compatibility of the materials used, low control power and compact design.



Sizes : It comes in various sizes from 1/8" upto 4"

Port Type : 2/2 way, 3/2 Way, 5/2 Way, 5/3 Way

Valve Type : Direct Acting, Diaphragm Operated, Pilot Operated, Poppet Type, Angle Type, NO & NC Type

Pressure : from 0 kg to 15 kg Voltages : 12V, 24V, 110V, 230V (AC/DC)

Material : PVC, Aluminium, Brass, SS 304/316

Coils : Single Coil Operated & Double Coil Operated

Medium : Air, Water, Gases, Oil, Steam



AMMAR INDUSTRIAL CORPORATION

SOLENOID COILS

We serve a variety of Solenoid Coils for various Solenoid Valves of different shape and sizes in different operating voltages and power consumption



MECHANICALLY OPERATED/ MANUAL VALVES

Manually operated valves have a wide variety of operators to satisfy most applications involving man-machine interface of pneumatics systems. Our range includes Push-Buttons, Toggle Valves, Knob Turn Valves, Hand Lever Valves, Hand Rotary Valves, Auto Drain Valves, Shuttle Valves, Flow Control Valves, Foot Peddle etc.



CYLINDERS/ACTUATORS

Model : Round Body in Al./SS , Tie Rod, DNC/ISO profile, Compact, ADVU/SDVU, Rodless etc.

Working : Single Acting , Double Acting

Material : Upon job specification, the material may be chosen. Material range from hard anodized Aluminium Alloy/nickel-plated brass to aluminum, and even steel and stainless steel. Depending on the level of loads, humidity, temperature, and stroke lengths specified, the appropriate material may be selected.

Mounting : Depending on the location of the application and machinability, there exist different kinds of mounts for attaching pneumatic cylinders, like : Clevis, Trunion, Flanged, Foot, Rod Fork, Rod Eye etc.

Size : Air cylinders are available in a variety of sizes and can typically range from a small 2.5 mm upto 1000mm.



Hydraulic Ferrule (OD) Fittings / Threaded pipe fittings

We offer our client a wide range of hydraulic fittings and accessories. We stock and supply a wide variety of hydraulic fittings in various sizes and even customize it to suit the needs of our clients.

They have a three piece structure that includes body, special case hardened ferrule and nut. These fitting are known for their strength for working precisely and preventing the nut to loosening under high pressure, strain and vibration.



Working Principle :

- ❑ On screwing the nut on to the body, the ferrule grips the pipe in position and the perceptibly bites into the pipe
- ❑ On being fully tightened, the ferrule bows slightly in the middle and acts as a spring
- ❑ The spring action of the ferrule keeps a constant tension between the body and nut

Size :

Our Hydraulic Fittings are available from 6mm OD of tube to 42mm OD of tube in low pressure series i.e. 'L' and 6mm OD to tube to 38mm OD of tube in high pressure series i.e. 'S'. These are also available for use with Nominal Bore of tube from 1/8" to 2" and OD of tube from 3/16" to 2".

Our wide range of fittings are as follows:

- ❑ Male Stud Couplings & Straight Couplings
- ❑ Equal Elbow Couplings & Male Elbow Couplings
- ❑ Equal Tee Couplings & Male Tee Couplings
- ❑ Swivel Fittings (Straight, Tee, Elbow)
- ❑ Hose Nozzles & Gauge Adaptors
- ❑ Hex Nipples & Plugs





SS Double Ferrule Tube Fittings/ SS OD Fittings

Double Ferrule Compression Tube Fittings provide leak proof torque free seals at all tubing connections. They eliminate hazardous leaks in instrumentation, process, pneumatic, hydraulic, gas and other applicable tubing system which could otherwise turn out to be costly to the installation. Apart from this, these fittings also find application in chemicals & petrochemicals, fertilizers, offshore, power plants, automobile and varied other process industries.

Standard specifications :

Tube : 1/8"OD to 2"OD , 4mmOD to 50mm OD

Threads : NPT, BSP, BSPT, UNF

MoC : SS 304, SS 316 from Bar Stock & Forged Body



Available Standard Configurations :

- ☐ Tube To Tube [Straight, Elbow, Tee, Cross, Bulk Head]
- ☐ Tube To Male [Male Connectors, Female Connectors, Male Elbow, Male Tee]
- ☐ Weld Nipples
- ☐ Nut & Ferrule Set.
- ☐ Manifold Valves
- ☐ Needle Valves



SS PIPE FITTINGS/ THREADED FITTINGS

- ☐ Stainless steel fittings are used because of very low general corrosion rate in water or where the use of heat would be a problem.
- ☐ High strength allows reduction in section diameter, wall thickness and weight, making it quick and easy to install.
- ☐ Stainless steel requires no additional coating or painting and can be left visible to the eye.
- ☐ No maintenance is required after installation, reducing system down time, replacement and maintenance costs over the life-cycle of the installation.
- ☐ At the end of its useful life, stainless steel is fully recyclable and retains a higher residual scrap value than ordinary steel.
- ☐ Stainless steel installations blend well with modern architecture and interior design.



Quick Release Couplings

Working Principle: Quick couplings are devices which permit easy, immediate connections and separation of fluid and pneumatic lines. When installed in a system quick couplings saves time by eliminating the necessity to close valves, bleed the system, recharge with fluid and purge entrapped air whenever an accessory is being replaced. These couplings serve virtually every industry in the control and flow of fluid power - Hydraulic / Pneumatic / Chemical / Petrochemical / Cryogenic.



Features:

- ❑ Quick Release Couplings eliminate valves and screw on fittings in many pneumatic, hydraulic and chemical systems.
- ❑ Permits easy, safe, quick & reliable connections between delivery lines, pressure hoses etc.
- ❑ Connection & disconnection of fluid systems is as easy as plugging in an electric gadget.

Material of Construction - As per Standards

- ❑ Body » Available in SS 304 / MS. - Chrome plated. Also available in S.S 316 / Brass
- ❑ Spring » Available in MS, S.S. - 304 / S.S. - 316 as required
- ❑ Ball » Available in MS, S.S. - 304 & S.S. - 316 as required
- ❑ Seal Materials » Available in Nitrile, Viton, Neoprene, Silicon Materials.

Sizes : Sizes are mainly from 1/8 inch up to 2 inch used by various industries & having end connections like pipe thread male / female, hose shank etc.

Selection of QRC : Functions or Need, Pressure Requirement, Type of coupling, Pipe and Thread size, Flow Characteristics Material, Seal, End Connections.

Types of Coupling : Three general types of quick couplings commonly recognized are:

1. One way check valve coupling (Single Check Valve)
2. Two way check valve coupling (Double Check Valve)
3. Straight through coupling. (No Check valve)

1. Single check valve : Type comes with one way sealing with one check valve build in to coupler only, where as plug do not have any check valve. The coupler body should be installed on the upstream (Supply) end of the line to shut off the fluid supply, when coupling is disconnected.



2. Double check valve: These are designed for connecting hydraulic lines. They are also extensively used where a variety of other fluids are involved. They are made to withstand pressure from 800 to 10000 PSI depending upon size and material. They contain valves in both the coupler and adaptor to prevent loss of fluid when the parts are disconnected.

3. StraightThrough : type quick release couplings have no check valves. These are ideal for maximum flow application. Their smooth, open bore offers the lowest pressure drop of any quick disconnected couplings and allows them to be through cleaned. Since there is no valve, fluid flow should be shut off before the coupling is disconnected.



HYDRAULIC COUPLINGS
ISO MODEL



SCREW TYPE
COUPLINGS for JACKS



DIN Series
COUPLINGS



FLAT FACE COUPLINGS





Camlock Couplings

We are one of the leading distributors and traders of a wide range of Camlock couplings, which is widely used for loading and unloading of tankers for water, petrol and chemical. Widely used in ships and atomic energy plants.

A Camlock coupling is in fact, a means of quick engaging or disengaging a hose connection from a system requiring transfer of fluid or gas. It consists of a COUPLER with cam arms and a slip in ADAPTOR. In order to connect the Arm of the coupler need to be lifted and the adaptor slipped into the coupler. The handles are then pressed down with normal hand pressure for a leak proof connection.

Types :

The Coupler & Adaptors are available in different configurations. With male threads, female threads and hose shanks

Seals : Nitrile, Viton, Teflon, Silicon Etc.

Features :

- ☐ Fastest and simplest tight connection.
- ☐ Interchangeability.
- ☐ Positive locking and greater resistance to vibration.
- ☐ Better flow characteristics.
- ☐ No ball bearings, threading, twisting springs, snaps tools, lugs, etc.
- ☐ Tightness under pressure and vacuum.
- ☐ Durable.

Sizes	1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3", 4", 5", 6"
Working Pressure	5 kg/cm ² to 20 kg/cm ² (working varies according to the size of coupling)
Material	S.S.304, Aluminium
Application	Cement, Fertilizers, Fire Fighting Equipment, Ink / Dye / Paint Industries, Petrochemical / Refineries, Process Industries, Mining, Oil Drilling Companies, (offshore / onshore), Railways, Steel Plants, Military, Applications, Pneumatic Conveyors, Oil Blending Plants, Automobile manufacturers, Chemical Industries and Furnaces



PU PIPES (POLYURETHANE HOSES)

Main advantages of using good polyurethane tubing with one-touch push-in fittings:

- ❑ High flexibility and small bend radius
- ❑ Large range of working temperatures and pressures
- ❑ Small pressure drop
- ❑ Constant rigidity, good ageing
- ❑ Good absorption of vibration
- ❑ Different colour Tubings available for easy identification of circuits
- ❑ 3mm to 16mm O.D.
- ❑ In 25 mtr rolls to 500 mtr rolls



HYDRAULIC HOSE (High Pressure rubber hose: RUBBER outside-Metal braiding in between)

It is mainly used to carry out the passing of the liquids at high temperature and pressure.

Tube - Oil resistant synthetic rubber.

Reinforcement Range - 1 to 6 high tensile steel wire braids.

Cover - Abrasion and weather resistant synthetic rubber

Temperature range: -400C to +1200C

Size range: range starts from 1/4" bore to 2" bore

Pressure range: start from 500 PSI to 10000 PSI



SS BELLOW HOSE (SS BRAIDING outside-SS BELLOW inside)



TEFLON HOSE (SS braiding outside-TEFLON inside)



PNEUMATIC RUBBER HOSE (RUBBER outside-NYLON braiding in between)



COOLANT PIPES

Made from high-tensile strength spring steel. STAY-PUT Coolant Nozzles convey soluble oils and cutting fluids through unrestricted full bore tubing. Hollow cone spray pattern, uniform distribution with fine atomization even at low pressure

Application:

Foam control, scrubbing, air & gas washing, industrial washing, cooling, wetting and degreasing, dust control settling dust in ash pits, bins, flue ducts, metal treatment & in chemical process.

Material:

Commonly made of Spring steel and Nylon.
On special order, in any machinable material.
Standard Length: 6", 12", 18", 24".
Can also be made as per client specifications

Thread Size:

1/8", 1/4", 3/8", 1/2", 3/4", and 1".
Can also be made as per client specifications.



SINTERED BRONZE FILTER ELEMENTS

Product Detail : Our silencers made from sintered bronze, can reduce the noise effectively in the pneumatic system or air discharge equipment, work as a filter and flow rate regulator, always directly mounting in the solenoid valve, cylinder and other pneumatic components. Our Filter elements comes with long service life, reliable working function, excellent performance. Any special size filter element is welcome to order.

Application:

Polymer Filtration, Gases Filtration, Compressors, Pneumatic Equipments, Mining Equipments, Steam & Gas Turbine

Other Application:

Sound Silencer, Flame Cutter, Fluidization



SEALS & WASHERS

Hydraulic Seals are soft, non metallic rings which are placed in a grouping of rings, forming a seal assembly. Seals traded by us are manufactured using various best quality raw materials including Nitrile, PU, Neoprene, EPDM and PTFE with Filler. Bonded Seals are sealing discs used to seal screwed and flanged connections. Copper washers have a wide range of sizes and applications.



BAKELITE KNOBS

We offer an impressive line of adjustment and control knobs, Handles and Hand wheels for use on equipment or appliances. Knobs, Handles and Hand wheels are available in a wide variety of styles and sizes with either threaded screw, blind inserts or thru-hole inserts.



Authorised Stockists & Dealers of

UflowTM
Solenoid Valve



AeroflexTM
FITTINGS & HOSES



PRAJ

Flexible Coolant Pipes & Accesories



AMMAR
INDUSTRIAL CORPORATION

83/85, Netaji Subhas Road, Shop No. A-33, Kolkata - 700 001

Ph.: +91 33 2231 6239 / 3985 5010

Fax : +91 33 2231 6239

e-mail : aicinfo@yahoo.co.in

website : www.ammarindustrial.in