

Email setup

[Debian TS-WXL](#)

Set up exim.
Basically the same as for [HS-DHGL](#) .
There is no local mail spool, and all mail is sent using ns.yamasita.jp as a smart host.

Confirm Installation

```
tswxl:~# dpkg -l exim
Desired=Unknown/Install/Remove/Purge/Hold
| Status=Not/Inst/Cfg-files/Unpacked/Failed-cfg/Half-inst/trig-aWait/Trig-pend
|/ Err?=(none)/Hold/Reinst-required/X=both-problems (Status,Err: uppercase=bad)
||/ Name Version Description
+++-+-----+-----+-----+
an exim (no description available)
tswxl:~# dpkg -l | grep exim
ii exim4 4.69-9 metapackage to ease Exim MTA (v4) installati
ii exim4-base 4.69-9 support files for all Exim MTA (v4) packages
ii exim4-config 4.69-9 configuration for the Exim MTA (v4)
ii exim4-daemon-light 4.69-9 lightweight Exim MTA (v4) daemon
odxl: ~ #
```

exim4 is installed.

setup

tswxl:~# dpkg-reconfigure exim4-config

Setting items	Set value
General type of mail configuration	mail sent by smarthost; no local mail
System mail name	tswxl.yamasita.jp
IP-addresses to listen on for incoming SMTP connections	127.0.0.1
Other destinations for which mail is accepted	tswxl.yamasita.jp
Visible domain name for local users	tswxl.yamasita.jp
IP address or host name of the outgoing smarthost	ns.yamasita.jp
Keep number of DNS-queries minimal (Dial-on-Demand)?	No
Split configuration into small files?	No
Root and postmaster mail recipient	yasunari @ yamasita.jp

Stopping MTA for restart: exim4_listener.
Restarting MTA: exim4.
odxl: ~ #

Verification

```
tswxl:~# mail yasunari@yamasita.jp
Subject: test from tswxl
test from tswxl
Cc:
odxl: ~ #
```

root @ Confirm that mail is sent from tswxl.yamasita.jp.

OK



TS-WXL

[Rakuten Ichiba](#)
[Amazon](#)
[Yahoo Shopping](#)
[Livedoor Department Store](#)

Copyright (C) 2003-2010 Yasunari Yamashita. All Rights Reserved. [Yasunari](#)
yama yamasita.jp [Yasunari Yamashita](#) 向 Mukoichi, Kyoto