

End processing by miconapl (2)

[Debian TS-WXL](#)

Check the processing required at shutdown.

/usr/local/sbin/miconapl -a Just execute shutdown_wait and if you do shutdown -h now, the LCD will remain displayed.

Read Standard Farm

When reading /usr/local/bin/change_notify.sh from /etc/init.d/rc.Down,

```
/usr/local/sbin/miconapl -a lcd_set_dispitem off
/usr/local/sbin/miconapl -a led_set_cpu_mcon off
/usr/local/sbin/miconapl -a led_set_on_off off
/usr/local/sbin/miconapl -a led_set_brink off
```

Running.

Manual execution

First, try to run it by hand.

```
odxl: ~ #
tswxl:~# /usr/local/sbin/miconapl -a shutdown_wait
tswxl:~# /usr/local/sbin/miconapl -a lcd_set_dispitem off
tswxl:~# /usr/local/sbin/miconapl -a led_set_cpu_mcon off
tswxl:~# /usr/local/sbin/miconapl -a led_set_on_off off
tswxl:~# /usr/local/sbin/miconapl -a led_set_brink off
tswxl:~# shutdown -h now
:
:
```

The power was turned off and the LCD went off.

After that, scripting



TS-WXL

[Rakuten Ichiba](#)
[Amazon](#)
[Yahoo Shopping](#)
[Livedoor Department Store](#)

Copyright (C) 2003-2010 Yasunari Yamashita. All Rights Reserved. [Yasunari](#)
yama yamasita.jp [Yasunari Yamashita](#)向 Mukoichi, Kyoto