

## Lab 8: GUI

### UNK CSIT 150 Object Oriented Programming

#### Objectives

- Familiarize yourself with designing & implementing a solution in GUI form
- Exercise good programming style
- Familiarize yourself with the Button listeners.
- Introduce programming of Data Validation with form, featuring intelligent error messages.

A sample application has been implemented as an example of a GUI interface that separates into two classes, the functionality of displaying data, with the actual class responsible for performing the logic of the program.

1. Download the two source code files and put them into a Java package named Lab8:
  - TheaterRevenues
  - TheaterRevenueWindow
2. Compile and run. A Window such as shown below should appear.

The screenshot shows a Java Swing window titled "Theater Revenue Calculator". The window is divided into two main sections. The left section, titled "Tickets sold", contains four input fields: "Adult ticket price" (with a value of 75.00), "Number adult tickets sold" (with a value of 0), "Child ticket price" (with a value of 25.00), and "Number child tickets sold" (with a value of 0). The right section, titled "Revenues", contains four input fields: "Gross Rev. Adult", "Net Rev. Adult", "Gross Revenues Child", and "Net Rev. Child". A "Clear" button is located at the top right of the "Revenues" section. At the bottom of the window, there is a "Calculate Revenues" button and two output fields: "Total Gross Rev:" and "Total Net Rev:". The "Calculate Revenues" button is located at the bottom left, and the "Total Gross Rev:" and "Total Net Rev:" fields are located at the bottom right.

Before we dissect the details of the lab assignment, we will discuss the responsibilities in general, for each class:

- **TheaterRevenueWindow:** This program's overall responsibility is to handle anything to do with the display (**view**) of data, entry of the data and **interface** with the user.
- **TheaterRevenues:** This program's overall responsibility is to handle all the theater data (**model**), along with its data calculations, such as the net and gross incomes for both adult and child ticket sales, given the ticket prices and the number of tickets. This class does not need modified for this lab assignment.
- **MyListener:** This class is a private internal class within TheaterRevenueWindow. This class provides the **controller**. It responds to the user's actions. Because it is a private class within the TheaterRevenueWindow class, it has access to all of the TheaterRevenueWindow's data members and methods.

Note: It is important to separate out the display of the data with the logic. [Model-View-Control software development](#) architecture.

There are several features to this application to be noticed. The first feature to be discussed are the event listeners. These are added to the code in the method **addButtonListener()**. This method creates an instance of the **MyListener** class and adds it to individual components we want to “listen” to. At this point, we are listening to two **JButtons**. It should be noticed that the actions to be performed for each of the individual buttons is determined by the method call within the **actionPerformed()** method of the new listener. We have discussed the action listener previously so the code to create one should be familiar to you.

3. Complete the program to respond to user action.

- Complete the **actionPerformed()** method, such that:
- When the user clicks the **calcButton**, call the **validateFields()** method and proceed to the calculations if all fields are all valid. The data validation methods have been provided for you for this lab. **You need to complete the calculation methods.**

So, what is a valid field? That is entirely dependent on the actual application and deciding what constitutes a valid field is all part of the design process. What are the questions to be asked? Look at both of these methods to determine what they do.

1) Is the data type restrictive? For instance in this application when it asks for the number of tickets sold, does it make sense to enter 10 ½ tickets or should the number be restricted to positive whole number. Since integers are more restrictive than decimal numbers, the field would have to be checked for both letters and decimal number. What about negative number. Should these be allowed? With numbers these decisions are fairly straight forward, but with text, the best choices are not so obvious.

2) Is it critical that there be a default value or can the field be empty? What happened if no adult tickets were sold? Does a 0 have to be entered or can the field be zero.

- When the user clicks the **clearButton**, call the **clearAllFields()** method and put the values back to the default values.
4. Run and test the program to verify that it works correctly.
5. Add a Menu Bar. Add two menus to the menu bar: File and Help. In the File menu, add two menu items, About and Exit. If the user selects “About”, open a dialog box that displays information about this program. If the user selects “Exit”, close the program. If the user selects the “Help” menu, open a dialog box that displays helpful information for this program.
6. Bonus: Remove the buttons, and move the control of user actions to menu items. You can choose the appropriate menus and menu items to add to do this.