


Predictive Analysis of Road Incidences

Exploratory Lines


BDigital

May 23, 2014



- Despite significant improvements in vehicle technology and road engineering over the last 40 years, on a world-wide scale road accidents are still one of the main accidental causes of death and injury (WHO, 2004).
- In a study regarding the relation between extreme weather events (e.g.: flash floods) and road accidents it was found that motorists account for 84 % of the totality of the victims [1].
- The assessment of the occurrence of road accidents has therefore attracted the attention of many researchers.

Introduction (cont.)



source: <http://www.geocurrents.info>

What do we want to predict?

Occurrence (0,1) and location (x,y) of incidents, as a function (pairwise or multivariate) of other variables;

- time of the day;
- weekday;
- traffic density;
- weather (rainfall, snowfall, visibility, winds, etc);
- traffic control devices (e.g.: traffic lights, stop signal, etc);
- roadway geometries (e.g.: steepness, intersection, degree of curvature, etc) ;
- roadway conditions (road surface, obstacles);
- vehicle type;

Some of these variables are continuous in space and most of them change over time.

Modelling Approaches: Classical Statistics

- The most common approach applied in early works is to model the interaction between each dependent variable and incidence frequencies by means of conventional (multiple) linear regression models [2]; these **do not take in account covariance between response variables**.

Modelling Approaches: Classical Statistics

- The most common approach applied in early works is to model the interaction between each dependent variable and incidence frequencies by means of conventional (multiple) linear regression models [2]; these **do not take in account covariance between response variables**.
- Most of these models use a Normal or Poisson distribution that is not well-suited to the scarce nature of incidence data. Accident data is often characterized by small observed mean values and a large number of zero counts leading to the well discussed phenomenon of **over-dispersion**: the presence of greater variability (statistical dispersion) in a data set than would be expected based on a given simple statistical model.

Modelling Approaches: Classical Statistics

- The most common approach applied in early works is to model the interaction between each dependent variable and incidence frequencies by means of conventional (multiple) linear regression models [2]; these **do not take in account covariance between response variables**.
- Most of these models use a Normal or Poisson distribution that is not well-suited to the scarce nature of incidence data. Accident data is often characterized by small observed mean values and a large number of zero counts leading to the well discussed phenomenon of **over-dispersion**: the presence of greater variability (statistical dispersion) in a data set than would be expected based on a given simple statistical model.
- None of these models addresses explicitly the question of **spatial autocorrelation**: the value of samples taken close to each other are more likely to have similar magnitude than by chance alone.

Modelling Approaches: Data Mining

Statistical models are particularly likely to be preferable when fairly simple models are adequate and the important variables can be identified before modeling. **This is not the case of the large and complex data set of road incidences.**

Data mining can be defined as the *nontrivial process of identifying valid, novel, potentially useful, and ultimately understandable patterns in large amounts of data* [3].

- Scale differences: data sets can be much larger than in statistics.

Modelling Approaches: Data Mining

Statistical models are particularly likely to be preferable when fairly simple models are adequate and the important variables can be identified before modeling. **This is not the case of the large and complex data set of road incidences.**

Data mining can be defined as the *nontrivial process of identifying valid, novel, potentially useful, and ultimately understandable patterns in large amounts of data* [3].

- Scale differences: data sets can be much larger than in statistics.
- Conceptual differences: compared with statistics, data mining pays less attention to the large-scale asymptotic properties of its inferences and more to the general philosophy of *learning*. For this fact, data mining has been criticized for being a "black box" [4].


Statistical models are particularly likely to be preferable when fairly simple models are adequate and the important variables can be identified before modeling. **This is not the case of the large and complex data set of road incidences.**

Data mining can be defined as the *nontrivial process of identifying valid, novel, potentially useful, and ultimately understandable patterns in large amounts of data* [3].

- Scale differences: data sets can be much larger than in statistics.
- Conceptual differences: compared with statistics, data mining pays less attention to the large-scale asymptotic properties of its inferences and more to the general philosophy of *learning*. For this fact, data mining has been criticized for being a "black box" [4].
- Dataset collection differences: it is generally a form of secondary data analysis, as very likely the datasets have been collected for other purpose than the one of answering the research question.

There are two major groups of tasks in Data Mining [3]:

- Description: affinity group and clustering;
- Prediction: classification and estimation;



DBSCAN clusters of tweets during MWC vs a *normal* day

Often Data Mining Techniques are combined together, or with traditional statistical methods, to yield better results:

- **Multivariate regression analysis + Bayesian Probabilistic Networks (BPN)** [2];
- Random Forest + Multivariate Adaptive Regression Splines (MARS) [7];
- Classification and Regression Trees (CART) [6];
- Genetic Mining Rule + Logit Model [2];
- **Frequent Item Sets** [3];
- Support Vector Machines (SVM);
- **Self Organizing Maps (SOM)**;

Bayesian Approach

In this case study[cite] it is used a mixed-model to predict the occurrence of road accidents:

The BPN is based on the regression model, but its parameters are updated by learning algorithms; the update *only replaces the response variables that have been observed in conjunction with the accident*. This approach allows to cope with different degrees of completeness of the dataset.

The methodology is illustrated using data of the Austrian rural motorway network (+/- 80 000 vehicles/day) and the quality of the prediction was found to be 73%.

Bayesian Approach

In this case study[cite] it is used a mixed-model to predict the occurrence of road accidents:

- Multivariate Poisson-lognormal regression analysis, which facilitates taking into account the covariance structure of the model response variables as well as over-dispersion effects.

The BPN is based on the regression model, but its parameters are updated by learning algorithms; the update *only replaces the response variables that have been observed in conjunction with the accident*. This approach allows to cope with different degrees of completeness of the dataset.

The methodology is illustrated using data of the Austrian rural motorway network (+/- 80 000 vehicles/day) and the quality of the prediction was found to be 73%.

In this case study[cite] it is used a mixed-model to predict the occurrence of road accidents:

- Multivariate Poisson-lognormal regression analysis, which facilitates taking into account the covariance structure of the model response variables as well as over-dispersion effects.
- Bayesian Probabilistic Networks (BPN) that take into account aleatory and epistemic uncertainties as well as possibly non-linear dependencies between the risk indicating variables and the response variables.

The BPN is based on the regression model, but its parameters are updated by learning algorithms; the update *only replaces the response variables that have been observed in conjunction with the accident*. This approach allows to cope with different degrees of completeness of the dataset.

The methodology is illustrated using data of the Austrian rural motorway network (+/- 80 000 vehicles/day) and the quality of the prediction was found to be 73%.

In this case study[cite] an association algorithm is used to obtain a descriptive analysis of accident high risk areas. This algorithm **identifies the accident circumstances that frequently occur together**. We are able to target the highest frequencies through a *minimum support value*.

This algorithm was applied to road accident data in Belgian (1997-1999). Some factors that were frequently linked to accidents:

- "Left" turns;
- Uneven views when approaching an intersection;
- Rainy conditions;
- Involvement of young pedestrians;

Some of these risk factors could be reduced with signing or roundabouts in these zones;

What About Space?




Figure: Heat map of road accidents in Moscow; source:
<http://mapsforhumans.com/2011/07/road-accidents-heat-map-of-moscow/>

What About Space? (cont.)

Road incidences happen in time and **space**. The contact with the spatial dimension of the phenomena starts with the input dataset. The most frequent approach to represent the road structure is to use networks. Networks represent lanes as *links* and intersections as *nodes*.




Figure: Road network in Hillsborough [cite]

For longer roads, it may be actually useful to split them into **homogeneous sections**.

What About Space? (cont.)

But the space dimension does not end up in the representation of the input variables (implicit). Space **relationships should also be explicitly stated in the model.**

- Spatial Auto correlation (as opposed to spatial independence) is an arrangement of the accidents where the locations are related to each other.
- Numerous studies have shown that accounting for spatial correlation among the analyzed observations is a big step toward a better safety assessment [cite].
- This is actually a *weakness* of many models; on the Bayesian Network model [cite], although acknowledged, spatial correlations were not considered in the development of the risk model; on conditionally autoregressive models (CAR) spatial effects are introduced as random.

Geographical Information Systems (GIS) can be a valuable tool for representing/integrating the different variables on a geographical space.

Considering Space: A Simple Example

Study of how circumstances affect people in episodes of bad weather [cite]. Data from newspapers was collected for a period of 10 yrs, in the region of Calabria.




Figure: Localisation of damage to people sorted according to the type of damaging agent. (1) Victims, (2) injured, and (3) involved people [cite]

Considering Space: A Simple Example (cont)




Figure: Localisation of damage to people along the Calabria road network [cite]

- Urban flooding and flash floods were found to be the most damaging events;
- Drivers accounted for 84% of the victims during these episodes.
- The mapping of damaging effects pointed out the regional sectors for which the high frequency of damaging events suggests planning further in-depth examinations;
- The identification of these critical points can support local regulator interventions, that might change damage incidences in the future.

Considering Space: A more complex example

The Self Organizing Map (SOM) is an artificial neural network based on an unsupervised learning process that performs a gradual and nonlinear mapping of high dimensional input data onto an ordered and structured array of nodes, generally of lower dimension [cite].

- The SOM compresses information and reduces dimensionality;

Considering Space: A more complex example

The Self Organizing Map (SOM) is an artificial neural network based on an unsupervised learning process that performs a gradual and nonlinear mapping of high dimensional input data onto an ordered and structured array of nodes, generally of lower dimension [cite].

- The SOM compresses information and reduces dimensionality;
- It transforms nonlinear statistical relationships in geometric relationships;

Considering Space: A more complex example

The Self Organizing Map (SOM) is an artificial neural network based on an unsupervised learning process that performs a gradual and nonlinear mapping of high dimensional input data onto an ordered and structured array of nodes, generally of lower dimension [cite].

- The SOM compresses information and reduces dimensionality;
- It transforms nonlinear statistical relationships in geometric relationships;
- It is a visualization method for multidimensional data;

Considering Space: A more complex example

The Self Organizing Map (SOM) is an artificial neural network based on an unsupervised learning process that performs a gradual and nonlinear mapping of high dimensional input data onto an ordered and structured array of nodes, generally of lower dimension [cite].

- The SOM compresses information and reduces dimensionality;
- It transforms nonlinear statistical relationships in geometric relationships;
- It is a visualization method for multidimensional data;
- Unlike other NN models, it **preserves topological relationships** units that are close in the output space, are also next to each other in the data space.

Considering Space: A more complex example

The Self Organizing Map (SOM) is an artificial neural network based on an unsupervised learning process that performs a gradual and nonlinear mapping of high dimensional input data onto an ordered and structured array of nodes, generally of lower dimension [cite].

- The SOM compresses information and reduces dimensionality;
- It transforms nonlinear statistical relationships in geometric relationships;
- It is a visualization method for multidimensional data;
- Unlike other NN models, it **preserves topological relationships** units that are close in the output space, are also next to each other in the data space.
- Unlike other models (e.g.: Support Vector Machines), as the training is unsupervised, it can prevent the analyst's arbitrary perspective.

Self Organizing Maps

The process of creating SOMs undergoes two main stages[cite]:




Figure: source: <http://www.mql5.com/en/articles/283>

Self Organizing Maps

The process of creating SOMs undergoes two main stages[cite]:

- training: vector quantitization; the neurons *adjust* their weights to the input vector;




Figure: source: <http://www.mql5.com/en/articles/283>

Self Organizing Maps

The process of creating SOMs undergoes two main stages[cite]:

- training: vector quantitization; the neurons *adjust* their weights to the input vector;
- mapping: vector projection; the network classifies a new input dataset;




Figure: source: <http://www.mql5.com/en/articles/283>

Self Organizing Maps (cont.)

Apart from the predictive capacity, the algorithm also works as a multidimensional clustering algorithm and a valuable visualization tool (U-Matrix and component planes).





Figure: source:

https://upload.wikimedia.org/wikipedia/commons/7/70/Synapse_Self-Organizing_Map.png

Self Organizing Maps (cont.)

When applied to geo-referenced data, this technique may allow the explanation of complex structures and phenomena in a spatial perspective [cite].

Going back to geographical space:



source: <http://www.ai-junkie.com/ann/som/som5.html>

Self Organizing Maps (cont.)

SOM's have been used for estimating:

- the risk for cancer patients (demonstrated accuracy in classification) [cite];
- underlying physical parameters from near infrared planetary spectra (83%-100% accuracy) [cite];
- the distance of an astronomic object based on its color (when compared to other techniques offer a competitive choice in terms of low-RMSE, and percentage of outliers) [cite];
- productivity of goat and sheep farms, based on herd management practices (the results are coherent with the animal science criteria that are common for this problem)[cite];

The approach has been showed to be an evidence-based predictive tool with high-knowledge-generation capabilities, very valuable to support decision-making [cite].

SOM's and Road Incidences

- Real-world road incidences are characterized by complicated multi-dimensionality mutual relationships.
- We want to propose a SOM to capture and extract the essence of these relationships by visualizing the results of incidence clustering.
- Moreover, we want to be able to predict these clusters of incidences, for a new set of input variables.

SOMs have been used in a study to estimate the effectiveness of Crash Avoidance technologies [cite]. They identified and characterized clusters of accidents, based on the relationships between (normalized) variables.

SOM's and Road Incidences

- Real-world road incidences are characterized by complicated multi-dimensionality mutual relationships.
- We want to propose a SOM to capture and extract the essence of these relationships by visualizing the results of incidence clustering.
- Moreover, we want to be able to predict these clusters of incidences, for a new set of input variables.

SOMs have been used in a study to estimate the effectiveness of Crash Avoidance technologies [cite]. They identified and characterized clusters of accidents, based on the relationships between (normalized) variables.

- 1 year of data (2010);

SOM's and Road Incidences

- Real-world road incidences are characterized by complicated multi-dimensionality mutual relationships.
- We want to propose a SOM to capture and extract the essence of these relationships by visualizing the results of incidence clustering.
- Moreover, we want to be able to predict these clusters of incidences, for a new set of input variables.

SOMs have been used in a study to estimate the effectiveness of Crash Avoidance technologies [cite]. They identified and characterized clusters of accidents, based on the relationships between (normalized) variables.

- 1 year of data (2010);
- 16,180 fatal passenger car drivers;

SOM's and Road Incidences

- Real-world road incidences are characterized by complicated multi-dimensionality mutual relationships.
- We want to propose a SOM to capture and extract the essence of these relationships by visualizing the results of incidence clustering.
- Moreover, we want to be able to predict these clusters of incidences, for a new set of input variables.

SOMs have been used in a study to estimate the effectiveness of Crash Avoidance technologies [cite]. They identified and characterized clusters of accidents, based on the relationships between (normalized) variables.

- 1 year of data (2010);
- 16,180 fatal passenger car drivers;
- 48 variables;






- What incidence dataset could we use? (e.g.: time and space dimensions, magnitude of incidence, type of incidence);
- Incidences vs Accidents;
- It would be useful to have two datasets: one for training and one for validation;
- What type of predictive dataset do we have (e.g.: road geometry, road characteristics, traffic density) ?
- How accurate are these datasets (measuring errors, etc)?

Targeting More Specific Aspects of Incidences:

- Identify and describe secondary crashes;
- Identify hot spots or "black zones", and model their behaviour;
- Model crashes at specific type of road entity (e.g.: unsignalised intersections);
- Classify road accidents;

Other Relevant Studies:

- Predict traffic levels in unmeasured locations (Kriging)[cite];
- Estimation of road traffic congestion (MCE, ANN)[cite];
- Traffic simulation model (CA)[cite];
- Traffic Forecast System[cite];
- Predict travel time [cite];

-  O. Petrucci and A. A. Pasqua *Damaging events along roads during bad weather periods: a case study in Calabria (Italy)*. Nat. Hazards Earth Syst. Sci., 12, 365-378, 2012.
-  Markus Deublein and Matthias Schubert and Bryan T. Adey and Jochen Kohler and Michael H. Faber *Prediction of road accidents: A Bayesian hierarchical approach* . Accident Analysis & Prevention 51, 274-291, 2013.
-  Karolien Geurts and Isabelle Thomas and Geert Wets *Understanding spatial concentrations of road accidents using frequent item sets*. Accident Analysis and Prevention 37, 787-799, 2005.
-  Qiang Zeng and Helai Huang *Bayesian spatial joint modeling of traffic crashes on an urban road network*. Accident Analysis & Prevention 67, 105-112, 2014.
-  Yu-Chiun Chiou and Lawrence W. Lan and Wen-Pin Chen *A two-stage mining framework to explore key risk conditions on*