Deep Demonstration Tracing: Learning Generalizable Imitator Policy for Runtime Imitation from a Single Demonstration

Xiong-Hui Chen [*1,2] Junyin Ye [*1,2] Hang Zhao [*3,2] Yi-Chen Li [1,2] Xu-Hui Liu [1,2] Haoran Shi [2] Yu-Yan Xu [2]
Zhihao Ye [1,2] Si-Hang Yang [1,2] Yang Yu [1,2] Anqi Huang [4,2] Kai Xu [3] Zongzhang Zhang [1]

Introduction [1]

The vision of Runtime One-shot imitation Learning [2]



Achieve any tasks directly "prompted" by corresponding demonstration. [11]

Popular paradigm: Transformer + behavior cloning [12]



Our focus: Generlization Challenges of runtime OSIL [14]



(a) Provided demonstration. [16]

(b) Policy trained by a traditional OSIL method. [18]

(c) Policy trained by DDT. [20]

(A) Valet Parking Assist in Maze (VPAM) [24]

Trained by DDT [26] Trained by traditional OSIL [28]

- ***Unseen demonstrations in unseen envirnoments.*** [21]
  - *-> incorrect representation caused by transformer.*
- ***Unforseen changes after demonstrations collection.***
  - *-> limitation of behavior cloning.*

Methodology [29]

KEY1: Inject the inductive bias of "how human make decisions in runtime OSIL" into the imitator policy network. [30]



An example of 3-stage OSIL of humans. [32]



- Stage 1: **Identify** relevant states within the trajectory based on the current state. [34]
- Stage 2: **Analyze** the expert's behavior patterns associated with these states.
- Stage 3: **Trace** the expert's demonstrations based on the relationship between the current state and the expert's behavior patterns in the demonstrations.

KEY2: Solve runtime one-shot imitation learning by context-based meta-RL, instead of supervised learning [35]



- The unforeseen changes will randomly apprear in the simulators ($\mathcal{M}$). [37]
- With meta-RL, the imitator policy will try to achieve *all of* the targets the same to the demonstration guided by 0-1 task rewards.
- In the process, the imitator policy will suffer from the unforseen changes and *have to handle them before achieve the targets.*

Major Experiments [38]

Q1: One-shot imitation ability in unseen situations [39]



Group results averged by 8 settings with 3 seeds (VPAM env). [41]



Table 4: Performance on unseen heterogeneous demonstrations.

Environment	Button Press	Door Close	Reach
Performance	0.78	1.00	0.75

Q2: Does DDT imitating via tracing the demos [54]

(a) Trajectory of DDT. [56]



(b) Attention score. [58]

Q3: The "Scaling Law" of DDT in the OSIL setting [60]



MORE VIDEO

https://osil-ddt.github.io/