



## SNx4HC138 3-Line To 8-Line Decoders/Demultiplexers

### 1 Features

- Targeted Specifically for High-Speed Memory Decoders and Data-Transmission Systems
- Wide Operating Voltage Range (2 V to 6 V)
- Outputs Can Drive Up To 10 LSTTL Loads
- Low Power Consumption, 80- $\mu$ A Maximum  $I_{CC}$
- Typical  $t_{pd} = 15$  ns
- $\pm 4$ -mA Output Drive at 5 V
- Low Input Current of 1- $\mu$ A Maximum
- Active Low Outputs ( Selected Output is Low)
- Incorporate Three Enable Inputs to Simplify Cascading or Data Reception

### 2 Applications

- LED Displays
- Servers
- White Goods
- Power Infrastructure
- Building Automation
- Factory Automation

### 3 Description


The SNx4HC138 devices are designed to be used in high-performance memory-decoding or data-routing applications requiring very short propagation delay times. In high-performance memory systems, these decoders can be used to minimize the effects of system decoding. When employed with high-speed memories using a fast enable circuit, the delay times of these decoders and the enable time of the memory are usually less than the typical access time of the memory. This means that the effective system delay introduced by the decoders is negligible.

**Device Information<sup>(1)</sup>**

| PART NUMBER | PACKAGE    | BODY SIZE (NOM)    |
|-------------|------------|--------------------|
| SN74HC138D  | SOIC (16)  | 9.90 mm x 3.90 mm  |
| SN74HC138DB | SSOP (16)  | 6.20 mm x 5.30 mm  |
| SN74HC138N  | PDIP (16)  | 19.32 mm x 6.35 mm |
| SN74HC138NS | SO (16)    | 10.20 mm x 5.30 mm |
| SN74HC138PW | TSSOP (16) | 5.00 mm x 4.40 mm  |
| SN54HC138J  | CDIP (16)  | 21.34 mm x 6.92 mm |
| SN54HC138W  | CFP (16)   | 10.16 mm x 6.73 mm |
| SN54HC138FK | LCCC (20)  | 8.89 mm x 8.89 mm  |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

**Logic Diagram (Positive Logic)**



Copyright © 2016, Texas Instruments Incorporated

Pin numbers shown are for the D, DB, J, N, NS, PW, and W packages.



An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

On products compliant to MIL-PRF-38535, all parameters are tested unless otherwise noted. On all other products, production processing does not necessarily include testing of all parameters.

## Table of Contents

|  |          |  |           |
|--|----------|--|-----------|
| <b>1 Features</b> .....                          | <b>1</b> | 8.1 Overview .....   | <b>9</b>  |
| <b>2 Applications</b> .....                      | <b>1</b> | 8.2 Functional Block Diagram .....                               | <b>9</b>  |
| <b>3 Description</b> .....                       | <b>1</b> | 8.3 Feature Description .....                                    | <b>9</b>  |
| <b>4 Revision History</b> .....                  | <b>2</b> | 8.4 Device Functional Modes .....                                | <b>10</b> |
| <b>5 Pin Configuration and Functions</b> .....   | <b>3</b> | <b>9 Application and Implementation</b> .....                    | <b>11</b> |
| <b>6 Specifications</b> .....                    | <b>4</b> | 9.1 Application Information .....                                | <b>11</b> |
| 6.1 Absolute Maximum Ratings .....               | <b>4</b> | 9.2 Typical Application .....                                    | <b>11</b> |
| 6.2 ESD Ratings: SN74HC138 .....                 | <b>4</b> | <b>10 Power Supply Recommendations</b> .....                     | <b>12</b> |
| 6.3 Recommended Operating Conditions .....       | <b>4</b> | <b>11 Layout</b> .....   | <b>12</b> |
| 6.4 Thermal Information: SN74HC138 .....         | <b>5</b> | 11.1 Layout Guidelines .....                                     | <b>12</b> |
| 6.5 Thermal Information: SN54HC138 .....         | <b>5</b> | 11.2 Layout Example .....  | <b>12</b> |
| 6.6 Electrical Characteristics .....             | <b>5</b> | <b>12 Device and Documentation Support</b> .....                 | <b>13</b> |
| 6.7 Electrical Characteristics: SN74HC138 .....  | <b>6</b> | 12.1 Documentation Support .....                                 | <b>13</b> |
| 6.8 Electrical Characteristics: SN54HC138 .....  | <b>6</b> | 12.2 Related Links .....   | <b>13</b> |
| 6.9 Switching Characteristics .....              | <b>6</b> | 12.3 Receiving Notification of Documentation Updates .....       | <b>13</b> |
| 6.10 Switching Characteristics: SN74HC138 .....  | <b>7</b> | 12.4 Community Resources .....                                   | <b>13</b> |
| 6.11 Switching Characteristics: SN54HC138 .....  | <b>7</b> | 12.5 Trademarks .....  | <b>13</b> |
| 6.12 Typical Characteristic .....                | <b>7</b> | 12.6 Electrostatic Discharge Caution .....                       | <b>13</b> |
| <b>7 Parameter Measurement Information</b> ..... | <b>8</b> | 12.7 Glossary .....  | <b>13</b> |
| <b>8 Detailed Description</b> .....              | <b>9</b> | <b>13 Mechanical, Packaging, and Orderable Information</b> ..... | <b>13</b> |


## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


| Changes from Revision E (September 2003) to Revision F  | Page     |
|---|----------|
| • Added ESD Ratings table, Feature Description section, Device Functional Modes, Application and Implementation section, Power Supply Recommendations section, Layout section, Device and Documentation Support section, and Mechanical, Packaging, and Orderable Information section ..... | <b>1</b> |
| • Deleted Ordering Information table; see POA at the end of the data sheet .....  | <b>1</b> |
| • Changed R <sub>θJA</sub> values from 73 to 87.3 (D), from 82 to 104.3 (DB), from 67 to 54.8 (N), from 64 to 91.1 (NS), and from 108 to 114.6 (PW) .....   | <b>5</b> |

## 5 Pin Configuration and Functions

**SOIC, SSOP, PDIP, SO, TSSOP, CDIP, or CFP Package**  
16-Pin D, DB, N, NS, PW, J or W  
Top View



**LCCC Package**  
20-Pin FK  
Top View



NC: No internal connection

### Pin Functions

| NAME             | PIN                                    |              | I/O | DESCRIPTION                            |
|------------------|--|--------------|-----|--|
|                  | SOIC, SSOP, PDIP, SO, TSSOP, CDIP, CFP | LCCC         |     |  |
| A                | 1                                      | 2            | I   | Select input A (least significant bit) |
| B                | 2                                      | 3            | I   | Select input B                         |
| C                | 3                                      | 4            | I   | Select input C (most significant bit)  |
| $\overline{G2A}$ | 4                                      | 5            | I   | Active low enable A                    |
| $\overline{G2B}$ | 5                                      | 7            | I   | Active low enable B                    |
| G1               | 6                                      | 8            | I   | Active high enable                     |
| GND              | 8                                      | 10           | —   | Ground                                 |
| NC               | —                                      | 1, 6, 11, 16 | —   | No internal connection                 |
| V <sub>CC</sub>  | 16                                     | 20           | —   | Supply voltage                         |
| Y0               | 15                                     | 19           | O   | Output 0 (least significant bit)       |
| Y1               | 14                                     | 18           | O   | Output 1                               |
| Y2               | 13                                     | 17           | O   | Output 2                               |
| Y3               | 12                                     | 15           | O   | Output 3                               |
| Y4               | 11                                     | 14           | O   | Output 4                               |
| Y5               | 10                                     | 13           | O   | Output 5                               |
| Y6               | 9                                      | 12           | O   | Output 6                               |
| Y7               | 7                                      | 9            | O   | Output 7 (most significant bit)        |

## 6 Specifications

### 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|  |                             | MIN  | MAX | UNIT |
|--|-----------------------------|------|-----|------|
| Supply voltage range, $V_{CC}$             |                             | −0.5 | 7   | V    |
| Input clamp current, $I_{IK}^{(2)}$        | $V_I < 0$ or $V_I > V_{CC}$ |      | ±20 | mA   |
| Output clamp current, $I_{OK}^{(2)}$       | $V_O < 0$ or $V_O > V_{CC}$ |      | ±20 | mA   |
| Continuous output current, $I_O$           | $V_O = 0$ to $V_{CC}$       |      | ±25 | mA   |
| Continuous current through $V_{CC}$ or GND |                             |      | ±50 | mA   |
| Junction temperature, $T_J$                |                             |      | 150 | °C   |
| Storage temperature, $T_{stg}$             |                             | −65  | 150 | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

### 6.2 ESD Ratings: SN74HC138

|                                     |  | VALUE | UNIT |
|-------------------------------------|--|-------|------|
| $V_{(ESD)}$ Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>              | ±2000 | V    |
|                                     | Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup> | ±1000 |      |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

### 6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                     |   | MIN              | NOM  | MAX      | UNIT |
|---------------------|---|------------------|------|----------|------|
| $V_{CC}$            | Supply voltage                          | 2                | 5    | 6        | V    |
| $V_{IH}$            | High-level input voltage                | $V_{CC} = 2$ V   | 1.5  |          | V    |
|                     |   | $V_{CC} = 4.5$ V | 3.15 |          |      |
|                     |   | $V_{CC} = 6$ V   | 4.2  |          |      |
| $V_{IL}$            | Low-level input voltage                 | $V_{CC} = 2$ V   |      | 0.5      | V    |
|                     |   | $V_{CC} = 4.5$ V |      | 1.35     |      |
|                     |   | $V_{CC} = 6$ V   |      | 1.8      |      |
| $V_I$               | Input voltage                           | 0                |      | $V_{CC}$ | V    |
| $V_O$               | Output voltage                          | 0                |      | $V_{CC}$ | V    |
| $\Delta t/\Delta v$ | Input transition rise or fall time      | $V_{CC} = 2$ V   |      | 1000     | ns   |
|                     |   | $V_{CC} = 4.5$ V |      | 500      |      |
|                     |   | $V_{CC} = 6$ V   |      | 400      |      |
| $C_{pd}$            | Power dissipation capacitance (no load) |                  | 85   |          | pF   |
| $T_A$               | Operating free-air temperature          | SN54HC138        | −55  | 125      | °C   |
|                     |   | SN74HC138        | −40  | 85       |      |

- (1) All unused inputs of the device must be held at  $V_{CC}$  or GND to ensure proper device operation. See TI application report, [Implications of Slow or Floating CMOS Inputs](#) (SCBA004).

## 6.4 Thermal Information: SN74HC138

| THERMAL METRIC <sup>(1)</sup> |  | SN74HC138 |           |          |         |            | UNIT |
|-------------------------------|--|-----------|-----------|----------|---------|------------|------|
|                               |  | D (SOIC)  | DB (SSOP) | N (PDIP) | NS (SO) | PW (TSSOP) |      |
|                               |  | 16 PINS   | 16 PINS   | 16 PINS  | 16 PINS | 16 PINS    |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance       | 87.3      | 104.3     | 54.8     | 91.1    | 114.6      | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance    | 45.8      | 54.7      | 42.1     | 49.5    | 49.5       | °C/W |
| $R_{\theta JB}$               | Junction-to-board thermal resistance         | 44.8      | 54.9      | 34.8     | 51.5    | 59.6       | °C/W |
| $\Psi_{JT}$                   | Junction-to-top characterization parameter   | 14.2      | 17.7      | 27       | 17.8    | 6.9        | °C/W |
| $\Psi_{JB}$                   | Junction-to-board characterization parameter | 44.5      | 54.4      | 34.7     | 51.2    | 59.1       | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

## 6.5 Thermal Information: SN54HC138

| THERMAL METRIC <sup>(1)</sup> |  | SN54HC138 <sup>(2)</sup> |         |           | UNIT |
|-------------------------------|--|--------------------------|---------|-----------|------|
|                               |  | J (CDIP)                 | W (CFP) | FK (LCCC) |      |
|                               |  | 16 PINS                  | 16 PINS | 20 PINS   |      |
| $R_{\theta JA}$               | Junction-to-ambient thermal resistance       | —                        | —       | —         | °C/W |
| $R_{\theta JC(top)}$          | Junction-to-case (top) thermal resistance    | 45.4                     | 68.1    | 49        | °C/W |
| $R_{\theta JB}$               | Junction-to-board thermal resistance         | —                        | 118.4   | 47.7      | °C/W |
| $\Psi_{JT}$                   | Junction-to-top characterization parameter   | —                        | —       | 7.2       | °C/W |
| $\Psi_{JB}$                   | Junction-to-board characterization parameter | 62.5                     | —       | —         | °C/W |
| $R_{\theta JC(bot)}$          | Junction-to-case (bottom) thermal resistance | 17.7                     | 9       | —         | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application report.

(2)  $R_{\theta JC}$  follows MIL-STD-883, and  $R_{\theta JB}$  follows JESD51.

## 6.6 Electrical Characteristics

$T_A = 25^\circ\text{C}$  (unless otherwise noted)

| PARAMETER       | TEST CONDITIONS  |  |                         | MIN  | TYP   | MAX  | UNIT |
|-----------------|--|--|-------------------------|------|-------|------|------|
| V <sub>OH</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OH</sub> = −20 μA                         | V <sub>CC</sub> = 2 V   | 1.9  | 1.998 | V    |      |
|                 |  |  | V <sub>CC</sub> = 4.5 V | 4.4  | 4.499 |      |      |
|                 |  |  | V <sub>CC</sub> = 6 V   | 5.9  | 5.999 |      |      |
|                 |  | I <sub>OH</sub> = −4 mA, V <sub>CC</sub> = 4.5 V |                         | 3.98 | 4.3   |      |      |
|                 |  | I <sub>OH</sub> = −5.2 mA, V <sub>CC</sub> = 6 V |                         | 5.48 | 5.8   |      |      |
| V <sub>OL</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OL</sub> = 20 μA                          | V <sub>CC</sub> = 2 V   |      | 0.002 | 0.1  | V    |
|                 |  |  | V <sub>CC</sub> = 4.5 V |      | 0.001 | 0.1  |      |
|                 |  |  | V <sub>CC</sub> = 6 V   |      | 0.001 | 0.1  |      |
|                 |  | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 4.5 V  |                         |      | 0.17  | 0.26 |      |
|                 |  | I <sub>OL</sub> = 5.2 mA, V <sub>CC</sub> = 6 V  |                         |      | 0.15  | 0.26 |      |
| I <sub>I</sub>  | V <sub>I</sub> = V <sub>CC</sub> or 0, V <sub>CC</sub> = 6 V                     |  |                         |      | ±0.1  | ±100 | nA   |
| I <sub>CC</sub> | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0, V <sub>CC</sub> = 6 V |  |                         |      |       | 8    | μA   |
| C <sub>i</sub>  | V <sub>CC</sub> = 2 V to 6 V   |  |                         |      | 3     | 10   | pF   |

**SN54HC138, SN74HC138**

SCLS107F – DECEMBER 1982 – REVISED SEPTEMBER 2016

[www.ti.com](http://www.ti.com)
**6.7 Electrical Characteristics: SN74HC138**

over operating free-air temperature range (unless otherwise noted)

| PARAMETER       | TEST CONDITIONS  |  |                         | MIN  | TYP | MAX   | UNIT |
|-----------------|--|--|-------------------------|------|-----|-------|------|
| V <sub>OH</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OH</sub> = −20 μA                         | V <sub>CC</sub> = 2 V   | 1.9  |     |       | V    |
|                 |  |  | V <sub>CC</sub> = 4.5 V | 4.4  |     |       |      |
|                 |  |  | V <sub>CC</sub> = 6 V   | 5.9  |     |       |      |
|                 |  | I <sub>OH</sub> = −4 mA, V <sub>CC</sub> = 4.5 V |                         | 3.84 |     |       |      |
|                 |  | I <sub>OH</sub> = −5.2 mA, V <sub>CC</sub> = 6 V |                         | 5.34 |     |       |      |
| V <sub>OL</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OL</sub> = 20 μA                          | V <sub>CC</sub> = 2 V   |      |     | 0.1   | V    |
|                 |  |  | V <sub>CC</sub> = 4.5 V |      |     | 0.1   |      |
|                 |  |  | V <sub>CC</sub> = 6 V   |      |     | 0.1   |      |
|                 |  | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 4.5 V  |                         |      |     | 0.33  |      |
|                 |  | I <sub>OL</sub> = 5.2 mA, V <sub>CC</sub> = 6 V  |                         |      |     | 0.33  |      |
| I <sub>I</sub>  | V <sub>I</sub> = V <sub>CC</sub> or 0, V <sub>CC</sub> = 6 V                     |  |                         |      |     | ±1000 | nA   |
| I <sub>CC</sub> | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0, V <sub>CC</sub> = 6 V |  |                         |      |     | 80    | μA   |
| C <sub>i</sub>  | V <sub>CC</sub> = 2 V to 6 V   |  |                         |      |     | 10    | pF   |

**6.8 Electrical Characteristics: SN54HC138**

over operating free-air temperature range (unless otherwise noted)

| PARAMETER       | TEST CONDITIONS  |  | V <sub>CC</sub>         | MIN | TYP | MAX   | UNIT |
|-----------------|--|--|-------------------------|-----|-----|-------|------|
| V <sub>OH</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OH</sub> = −20 μA                         | V <sub>CC</sub> = 2 V   | 1.9 |     |       | V    |
|                 |  |  | V <sub>CC</sub> = 4.5 V | 4.4 |     |       |      |
|                 |  |  | V <sub>CC</sub> = 6 V   | 5.9 |     |       |      |
|                 |  | I <sub>OH</sub> = −4 mA, V <sub>CC</sub> = 4.5 V |                         | 3.7 |     |       |      |
|                 |  | I <sub>OH</sub> = −5.2 mA, V <sub>CC</sub> = 6 V |                         | 5.2 |     |       |      |
| V <sub>OL</sub> | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                              | I <sub>OL</sub> = 20 μA                          | V <sub>CC</sub> = 2 V   |     |     | 0.1   | V    |
|                 |  |  | V <sub>CC</sub> = 4.5 V |     |     | 0.1   |      |
|                 |  |  | V <sub>CC</sub> = 6 V   |     |     | 0.1   |      |
|                 |  | I <sub>OL</sub> = 4 mA, V <sub>CC</sub> = 4.5 V  |                         |     |     | 0.4   |      |
|                 |  | I <sub>OL</sub> = 5.2 mA, V <sub>CC</sub> = 6 V  |                         |     |     | 0.4   |      |
| I <sub>I</sub>  | V <sub>I</sub> = V <sub>CC</sub> or 0, V <sub>CC</sub> = 6 V                     |  |                         |     |     | ±1000 | nA   |
| I <sub>CC</sub> | V <sub>I</sub> = V <sub>CC</sub> or 0, I <sub>O</sub> = 0, V <sub>CC</sub> = 6 V |  |                         |     |     | 160   | μA   |
| C <sub>i</sub>  | V <sub>CC</sub> = 2 V to 6 V   |  |                         |     |     | 10    | pF   |

**6.9 Switching Characteristics**
 $T_A = 25^\circ C$  and  $C_L = 50 \text{ pF}$  (unless otherwise noted; see [Parameter Measurement Information](#))

| PARAMETER | TEST CONDITIONS                           |                  |  | MIN | TYP | MAX | UNIT |
|-----------|---|------------------|--|-----|-----|-----|------|
| $t_{pd}$  | From A, B, or C (input) to any Y (output) | $V_{CC} = 2 V$   |  |     | 67  | 180 | ns   |
|           |   | $V_{CC} = 4.5 V$ |  |     | 18  | 36  |      |
|           |   | $V_{CC} = 6 V$   |  |     | 15  | 31  |      |
|           | From enable (input) to any Y (output)     | $V_{CC} = 2 V$   |  |     | 66  | 155 |      |
|           |   | $V_{CC} = 4.5 V$ |  |     | 18  | 31  |      |
|           |   | $V_{CC} = 6 V$   |  |     | 15  | 26  |      |
| $t_t$     | To any output                             | $V_{CC} = 2 V$   |  |     | 38  | 75  | ns   |
|           |   | $V_{CC} = 4.5 V$ |  |     | 8   | 15  |      |
|           |   | $V_{CC} = 6 V$   |  |     | 6   | 13  |      |

## 6.10 Switching Characteristics: SN74HC138

over recommended operating free-air temperature range and  $C_L = 50$  pF (unless otherwise noted; see [Parameter Measurement Information](#))


| PARAMETER | TEST CONDITIONS                           | MIN              | TYP | MAX | UNIT |
|-----------|---|------------------|-----|-----|------|
| $t_{pd}$  | From A, B, or C (input) to any Y (output) | $V_{CC} = 2$ V   |     | 225 | ns   |
|           |   | $V_{CC} = 4.5$ V |     | 45  |      |
|           |   | $V_{CC} = 6$ V   |     | 38  |      |
|           | From enable (input) to any Y (output)     | $V_{CC} = 2$ V   |     | 195 |      |
|           |   | $V_{CC} = 4.5$ V |     | 39  |      |
|           |   | $V_{CC} = 6$ V   |     | 33  |      |
| $t_t$     | To any output                             | $V_{CC} = 2$ V   |     | 95  | ns   |
|           |   | $V_{CC} = 4.5$ V |     | 19  |      |
|           |   | $V_{CC} = 6$ V   |     | 16  |      |

## 6.11 Switching Characteristics: SN54HC138

over recommended operating free-air temperature range and  $C_L = 50$  pF (unless otherwise noted; see [Parameter Measurement Information](#))


| PARAMETER | TEST CONDITIONS                           | MIN              | TYP | MAX | UNIT |
|-----------|---|------------------|-----|-----|------|
| $t_{pd}$  | From A, B, or C (input) to any Y (output) | $V_{CC} = 2$ V   |     | 270 | ns   |
|           |   | $V_{CC} = 4.5$ V |     | 54  |      |
|           |   | $V_{CC} = 6$ V   |     | 46  |      |
|           | From enable (input) to any Y (output)     | $V_{CC} = 2$ V   |     | 235 |      |
|           |   | $V_{CC} = 4.5$ V |     | 47  |      |
|           |   | $V_{CC} = 6$ V   |     | 40  |      |
| $t_t$     | To any output                             | $V_{CC} = 2$ V   |     | 110 | ns   |
|           |   | $V_{CC} = 4.5$ V |     | 22  |      |
|           |   | $V_{CC} = 6$ V   |     | 19  |      |

## 6.12 Typical Characteristic



**Figure 1. Typical Propagation Delay vs Supply Voltage**

## 7 Parameter Measurement Information



- NOTES:
- A.  $C_L$  includes probe and test-fixture capacitance.
  - B. Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1 \text{ MHz}$ ,  $Z_O = 50 \Omega$ ,  $t_r = 6 \text{ ns}$ ,  $t_f = 6 \text{ ns}$ .
  - C. The outputs are measured one at a time with one input transition per measurement.
  - D.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{pd}$ .

**Figure 2. Load Circuit and Voltage Waveforms**




## 8 Detailed Description

### 8.1 Overview

The SNx4HC138 devices are 3-to-8 decoders and demultiplexers. The three input pins, A, B, and C, select which output is active. The selected output is pulled LOW, while the remaining outputs are all HIGH. The conditions at the binary-select inputs at the three enable inputs select one of eight output lines. Two active-low and one active-high enable inputs reduce the requirement for external gates or inverters when expanding. A 24-line decoder can be implemented without external inverters, and a 32-line decoder requires only one inverter. An enable input can be used as a data input for demultiplexing applications.

### 8.2 Functional Block Diagram



Copyright © 2016, Texas Instruments Incorporated

Pin numbers shown are for the D, DB, J, N, NS, PW, and W packages.

**Figure 3. Logic Diagram (Positive Logic)**

### 8.3 Feature Description

This device features three binary inputs to select a single active-low output. Three enable pins are also available to enable or disable the outputs. One active high enable and two active low enable pins are available, and any enable pin can be deactivated to force all outputs high. All three enable pins must be active for the output to be enabled.

## SN54HC138, SN74HC138

SCLS107F – DECEMBER 1982 – REVISED SEPTEMBER 2016

[www.ti.com](http://www.ti.com)

### 8.4 Device Functional Modes

Table 1 lists the functions of the SNx4HC138 devices.

**Table 1. Function Table**

| INPUTS |                  |                  |        |   |   | OUTPUTS |    |    |    |    |    |    |    |
|--------|------------------|------------------|--------|---|---|---------|----|----|----|----|----|----|----|
| ENABLE |                  |                  | SELECT |   |   |         |    |    |    |    |    |    |    |
| G1     | $\overline{G2A}$ | $\overline{G2B}$ | C      | B | A | Y0      | Y1 | Y2 | Y3 | Y4 | Y5 | Y6 | Y7 |
| X      | H                | X                | X      | X | X | H       | H  | H  | H  | H  | H  | H  | H  |
| X      | X                | H                | X      | X | X | H       | H  | H  | H  | H  | H  | H  | H  |
| L      | X                | X                | X      | X | X | H       | H  | H  | H  | H  | H  | H  | H  |
| H      | L                | L                | L      | L | L | L       | H  | H  | H  | H  | H  | H  | H  |
| H      | L                | L                | L      | L | H | H       | L  | H  | H  | H  | H  | H  | H  |
| H      | L                | L                | L      | H | L | H       | H  | L  | H  | H  | H  | H  | H  |
| H      | L                | L                | L      | H | H | H       | H  | H  | L  | H  | H  | H  | H  |
| H      | L                | L                | H      | L | L | H       | H  | H  | H  | L  | H  | H  | H  |
| H      | L                | L                | H      | L | H | H       | H  | H  | H  | H  | L  | H  | H  |
| H      | L                | L                | H      | H | L | H       | H  | H  | H  | H  | H  | L  | H  |
| H      | L                | L                | H      | H | H | H       | H  | H  | H  | H  | H  | H  | L  |

## 9 Application and Implementation


### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 9.1 Application Information

The SN74HC138 is useful as a scanning column selector for an LED Matrix display as it can be used for the low side drive of the LED string. The decoder functionality ensures that no more than one output is pulled to a low-level logic voltage so that only a single column is enabled at any point in time.

### 9.2 Typical Application



Copyright © 2016, Texas Instruments Incorporated

**Figure 4. LED Matrix Driver Application**

#### 9.2.1 Design Requirements


These devices use CMOS technology and have balanced output drive. Take care to avoid bus contention because it can drive currents that would exceed maximum limits. The high drive also creates fast edges into light loads, so routing and load conditions must be considered to prevent ringing.

#### 9.2.2 Detailed Design Procedure

- Recommended Input Conditions
  - For switch time specifications, see propagation delay times in [Switching Characteristics](#).
  - For input voltage level specifications for control inputs, see  $V_{IH}$  and  $V_{IL}$  in [Electrical Characteristics](#).
- Recommended Output Conditions
  - Outputs must not be pulled above  $V_{CC}$  or below GND.

## Typical Application (continued)

### 9.2.3 Application Curve



**Figure 5. Input High and Input Low Thresholds vs Supply Voltage**

## 10 Power Supply Recommendations

The power supply can be any voltage between the minimum and maximum supply voltage rating located in the [Recommended Operating Conditions](#).


Each  $V_{CC}$  terminal must have a good bypass capacitor to prevent power disturbance. A 0.1- $\mu$ F bypass capacitor is recommended to be placed close to the  $V_{CC}$  terminal. It is acceptable to parallel multiple bypass capacitors to reject different frequencies of noise; 0.1- $\mu$ F and 1- $\mu$ F capacitors are commonly used in parallel. The bypass capacitor must be installed as close to the power terminal as possible for best results.

## 11 Layout

### 11.1 Layout Guidelines

Reflections and matching are closely related to loop antenna theory, but different enough to warrant their own discussion. When a PCB trace turns a corner at a 90° angle, a reflection can occur. This is primarily due to the change of width of the trace. At the apex of the turn, the trace width is increased to 1.414 times its width. This upsets the transmission line characteristics, especially the distributed capacitance and self-inductance of the trace (resulting in the reflection). It is a given that not all PCB traces can be straight, and so they have to turn corners. [Figure 6](#) shows progressively better techniques of rounding corners. Only the last example maintains constant trace width and minimizes reflections.

### 11.2 Layout Example



**Figure 6. Trace Example**

## 12 Device and Documentation Support

### 12.1 Documentation Support

#### 12.1.1 Related Documentation

For related documentation see the following:

[Implications of Slow or Floating CMOS Inputs](#) (SCBA004)

### 12.2 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

**Table 2. Related Links**

| PARTS     | PRODUCT FOLDER             | SAMPLE & BUY               | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|-----------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| SN54HC138 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| SN74HC138 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

### 12.3 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

### 12.4 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

**TI E2E™ Online Community** *TI's Engineer-to-Engineer (E2E) Community*. Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

### 12.5 Trademarks

E2E is a trademark of Texas Instruments.

All other trademarks are the property of their respective owners.

### 12.6 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

### 12.7 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 13 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)            | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|---------------------|--------------------------------------|----------------------|--------------|------------------------------------|-------------------------|
| 5962-8406201VEA  | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-8406201VE<br>A<br>SNV54HC138J | <a href="#">Samples</a> |
| 5962-8406201VFA  | ACTIVE        | CFP          | W                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 5962-8406201VF<br>A<br>SNV54HC138W | <a href="#">Samples</a> |
| 84062012A        | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | POST-PLATE                           | N / A for Pkg Type   | -55 to 125   | 84062012A<br>SNJ54HC<br>138FK      | <a href="#">Samples</a> |
| 8406201EA        | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8406201EA<br>SNJ54HC138J           | <a href="#">Samples</a> |
| 8406201FA        | ACTIVE        | CFP          | W                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8406201FA<br>SNJ54HC138W           | <a href="#">Samples</a> |
| JM38510/65802B2A | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | POST-PLATE                           | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65802B2A               | <a href="#">Samples</a> |
| JM38510/65802BEA | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65802BEA               | <a href="#">Samples</a> |
| M38510/65802B2A  | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | POST-PLATE                           | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65802B2A               | <a href="#">Samples</a> |
| M38510/65802BEA  | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | JM38510/<br>65802BEA               | <a href="#">Samples</a> |
| SN54HC138J       | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | SN54HC138J                         | <a href="#">Samples</a> |
| SN74HC138D       | ACTIVE        | SOIC         | D                  | 16   | 40             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |
| SN74HC138DBR     | ACTIVE        | SSOP         | DB                 | 16   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |
| SN74HC138DE4     | ACTIVE        | SOIC         | D                  | 16   | 40             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |
| SN74HC138DG4     | ACTIVE        | SOIC         | D                  | 16   | 40             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |
| SN74HC138DR      | ACTIVE        | SOIC         | D                  | 16   | 2500           | RoHS & Green        | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |
| SN74HC138DRE4    | ACTIVE        | SOIC         | D                  | 16   | 2500           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                              | <a href="#">Samples</a> |

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)     | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5)       | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|---------------------|--------------------------------------|----------------------|--------------|-------------------------------|-------------------------|
| SN74HC138DRG4    | ACTIVE        | SOIC         | D                  | 16   | 2500           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138DT      | ACTIVE        | SOIC         | D                  | 16   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138N       | ACTIVE        | PDIP         | N                  | 16   | 25             | RoHS & Green        | NIPDAU   SN                          | N / A for Pkg Type   | -40 to 85    | SN74HC138N                    | <a href="#">Samples</a> |
| SN74HC138NE4     | ACTIVE        | PDIP         | N                  | 16   | 25             | RoHS & Green        | NIPDAU                               | N / A for Pkg Type   | -40 to 85    | SN74HC138N                    | <a href="#">Samples</a> |
| SN74HC138NSR     | ACTIVE        | SO           | NS                 | 16   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138PW      | ACTIVE        | TSSOP        | PW                 | 16   | 90             | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138PWR     | ACTIVE        | TSSOP        | PW                 | 16   | 2000           | RoHS & Green        | NIPDAU   SN                          | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138PWRE4   | ACTIVE        | TSSOP        | PW                 | 16   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138PWRG4   | ACTIVE        | TSSOP        | PW                 | 16   | 2000           | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SN74HC138PWT     | ACTIVE        | TSSOP        | PW                 | 16   | 250            | RoHS & Green        | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | HC138                         | <a href="#">Samples</a> |
| SNJ54HC138FK     | ACTIVE        | LCCC         | FK                 | 20   | 1              | Non-RoHS<br>& Green | POST-PLATE                           | N / A for Pkg Type   | -55 to 125   | 84062012A<br>SNJ54HC<br>138FK | <a href="#">Samples</a> |
| SNJ54HC138J      | ACTIVE        | CDIP         | J                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8406201EA<br>SNJ54HC138J      | <a href="#">Samples</a> |
| SNJ54HC138W      | ACTIVE        | CFP          | W                  | 16   | 1              | Non-RoHS<br>& Green | SNPB                                 | N / A for Pkg Type   | -55 to 125   | 8406201FA<br>SNJ54HC138W      | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

- (3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.
- (4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.
- (5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.
- (6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN54HC138, SN54HC138-SP, SN74HC138 :**

- Catalog: [SN74HC138](#), [SN54HC138](#)
- Automotive: [SN74HC138-Q1](#), [SN74HC138-Q1](#)
- Military: [SN54HC138](#)
- Space: [SN54HC138-SP](#)

**NOTE: Qualified Version Definitions:**

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Military - QML certified for Military and Defense Applications
- Space - Radiation tolerant, ceramic packaging and qualified for use in Space-based application



**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74HC138DR    | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC138DR    | SOIC         | D               | 16   | 2500 | 330.0              | 16.8               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC138DRG4  | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| SN74HC138NSR   | SO           | NS              | 16   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74HC138PWR   | TSSOP        | PW              | 16   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC138PWR   | TSSOP        | PW              | 16   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC138PWRG4 | TSSOP        | PW              | 16   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| SN74HC138PWT   | TSSOP        | PW              | 16   | 250  | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74HC138DR    | SOIC         | D               | 16   | 2500 | 333.2       | 345.9      | 28.6        |
| SN74HC138DR    | SOIC         | D               | 16   | 2500 | 364.0       | 364.0      | 27.0        |
| SN74HC138DRG4  | SOIC         | D               | 16   | 2500 | 333.2       | 345.9      | 28.6        |
| SN74HC138NSR   | SO           | NS              | 16   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC138PWR   | TSSOP        | PW              | 16   | 2000 | 364.0       | 364.0      | 27.0        |
| SN74HC138PWR   | TSSOP        | PW              | 16   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC138PWRG4 | TSSOP        | PW              | 16   | 2000 | 853.0       | 449.0      | 35.0        |
| SN74HC138PWT   | TSSOP        | PW              | 16   | 250  | 853.0       | 449.0      | 35.0        |

FK (S-CQCC-N\*\*)

LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN



| NO. OF<br>TERMINALS<br>** | A                |                  | B                |                  |
|---------------------------|------------------|------------------|------------------|------------------|
|                           | MIN              | MAX              | MIN              | MAX              |
| 20                        | 0.342<br>(8,69)  | 0.358<br>(9,09)  | 0.307<br>(7,80)  | 0.358<br>(9,09)  |
| 28                        | 0.442<br>(11,23) | 0.458<br>(11,63) | 0.406<br>(10,31) | 0.458<br>(11,63) |
| 44                        | 0.640<br>(16,26) | 0.660<br>(16,76) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 52                        | 0.740<br>(18,78) | 0.761<br>(19,32) | 0.495<br>(12,58) | 0.560<br>(14,22) |
| 68                        | 0.938<br>(23,83) | 0.962<br>(24,43) | 0.850<br>(21,6)  | 0.858<br>(21,8)  |
| 84                        | 1.141<br>(28,99) | 1.165<br>(29,59) | 1.047<br>(26,6)  | 1.063<br>(27,0)  |




4040140/D 01/11

- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a metal lid.
  - Falls within JEDEC MS-004

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4040047-6/M 06/11

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AC.

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.



## PACKAGE OUTLINE

## TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE




1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT


PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4220204/A 02/2017

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0016A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220204/A 02/2017

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.



# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE


14-PINS SHOWN



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

W (R-GDFP-F16)

CERAMIC DUAL FLATPACK



- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - This package can be hermetically sealed with a ceramic lid using glass frit.
  - Index point is provided on cap for terminal identification only.
  - Falls within MIL STD 1835 GDFP2-F16

J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |



4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.

## DB (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

28 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150

N (R-PDIP-T\*\*)

16 PINS SHOWN

# PLASTIC DUAL-IN-LINE PACKAGE



| PINS **<br>DIM      | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



4040049/E 12/2002

NOTES:

- A. All linear dimensions are in inches (millimeters).  
B. This drawing is subject to change without notice.
-  Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).  
 The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2021, Texas Instruments Incorporated