



Splunk® Enterprise Security

Administer Splunk Enterprise Security 7.0.1

List correlation searches in Splunk Enterprise Security

Generated: 5/19/2022 1:01 am

List correlation searches in Splunk Enterprise Security

To obtain a list of correlation searches enabled in Splunk Enterprise Security, use a REST search to extract the information that you want in a table.

For example, create a table with the app, security domain, name, and description of all correlation searches in your environment.

```
| rest splunk_server=local count=0 /services/saved/searches | where  
match('action.correlationsearch.enabled', "1|[Tt]|[Tt][Rr][Uu][Ee]") | rename eai:acl.app as app, title as  
csearch_name, action.correlationsearch.label as csearch_label, action.notable.param.security_domain as  
security_domain | table csearch_name, csearch_label, app, security_domain, description
```

As another example, create a table with only the enabled correlation searches and the adaptive response actions associated with those searches in your environment. To see the adaptive response actions for all correlation searches, **remove** | where disabled=0.

```
| rest splunk_server=local count=0 /servicesNS/-/SplunkEnterpriseSecuritySuite/saved/searches | where  
match('action.correlationsearch.enabled', "1|[Tt]|[Tt][Rr][Uu][Ee]") | where disabled=0 | eval  
actions=split(actions, ",") | table title,actions
```