

Contents

| | |
|---|------------------|
| <i>Principal symbols, functions and operators</i> | <i>page</i> viii |
| <i>List of abbreviations</i> | x |
| <i>Foreword</i> | xii |
| <i>Preface</i> | xv |
| 1 Making fringes | 1 |
| 1.1 The need for angular resolution | 1 |
| 1.2 The resolution of a single telescope | 2 |
| 1.3 A long-baseline interferometer | 5 |
| 1.4 The interferometric measurement equation | 7 |
| 1.5 Spatial coherence | 21 |
| 1.6 Nomenclature | 23 |
| 1.7 Polychromatic interferometry | 25 |
| 1.8 Chromatic dispersion and group delay | 30 |
| 2 Basic imaging | 36 |
| 2.1 Fourier inversion | 36 |
| 2.2 Visibility functions of simple objects | 37 |
| 2.3 Sampling the Fourier plane | 44 |
| 2.4 The image-plane effects of Fourier-plane sampling | 47 |
| 3 Atmospheric seeing and its amelioration | 53 |
| 3.1 The wavefront perturbation model | 54 |
| 3.2 First-order effects on interferometers | 61 |
| 3.3 The effects of finite exposure time | 69 |
| 3.4 The effects of finite aperture size | 73 |
| 3.5 Adaptive optics | 76 |

| | | |
|----------|---|------------|
| 3.6 | Spatio-temporal effects | 81 |
| 3.7 | Spatial filtering | 82 |
| 3.8 | Fringe tracking | 87 |
| 3.9 | Wavelength dependence of atmospheric perturbations | 89 |
| 4 | Interferometers in practice | 91 |
| 4.1 | Interferometric facilities | 91 |
| 4.2 | Siting | 92 |
| 4.3 | Collectors | 94 |
| 4.4 | Beam relay | 97 |
| 4.5 | Array layout | 103 |
| 4.6 | Delay lines | 105 |
| 4.7 | Beam combiners | 108 |
| 4.8 | Detectors | 121 |
| 4.9 | Alignment | 122 |
| 4.10 | Aperture masking | 125 |
| 5 | Measurement noise | 129 |
| 5.1 | Atmospheric noise | 129 |
| 5.2 | Detection noise | 134 |
| 5.3 | Alternative fringe detection methods | 138 |
| 5.4 | The interferogram | 143 |
| 5.5 | Noise on fringe parameters | 144 |
| 5.6 | Comparison of noise levels | 151 |
| 6 | Interferometric observation of faint objects | 152 |
| 6.1 | The optimum exposure time | 153 |
| 6.2 | The optimum aperture size | 156 |
| 6.3 | AO on faint objects | 160 |
| 6.4 | Fringe-tracking limits | 164 |
| 6.5 | Faint-object limits for interferometry | 177 |
| 7 | Observation planning | 180 |
| 7.1 | Example proposal | 180 |
| 7.2 | Target selection | 181 |
| 7.3 | Wavelength and spectral resolution | 186 |
| 7.4 | Baseline selection | 188 |
| 7.5 | Calibrator selection | 189 |
| 7.6 | Surveys | 191 |
| 7.7 | Short-timescale phenomena | 192 |
| 7.8 | Complementary observations | 193 |

| | | |
|-------------------|---|-----|
| 8 | Data reduction | 194 |
| 8.1 | Scientific inference | 194 |
| 8.2 | The forward problem | 195 |
| 8.3 | The inverse problem | 198 |
| 8.4 | Flat fielding and background subtraction | 199 |
| 8.5 | Extracting the coherent flux | 200 |
| 8.6 | Coherent integration | 208 |
| 8.7 | Incoherent integration | 210 |
| 8.8 | Visibility calibration | 211 |
| 8.9 | OIFITS files | 216 |
| 9 | Model fitting and image reconstruction | 218 |
| 9.1 | Bayesian inference | 218 |
| 9.2 | The interferometric likelihood | 219 |
| 9.3 | Model-dependent priors | 222 |
| 9.4 | Model fitting in practice | 224 |
| 9.5 | Model-independent priors | 225 |
| 9.6 | Preconditions for imaging | 226 |
| 9.7 | Model-independent image reconstruction | 234 |
| 9.8 | Image quality | 239 |
| 9.9 | Practical case study: imaging and model-fitting on Betelgeuse | 243 |
| <i>Appendix A</i> | Fourier transforms | 248 |
| <i>Appendix B</i> | Supplementary online material | 255 |
| | <i>References</i> | 257 |
| | <i>Index</i> | 265 |