

))) B-Line

High Performance Subwoofers



))) AUDIOTECHNIK subwoofers of B-Line consistently distribute rich, clear, dynamic sound without unwanted distortion. With a broad range of sizes and capabilities, these subwoofers can be paired with other **)))** products to create full range scalable systems for portable applications or fixed installations of any size.

This product line expertly blends precision and power into one cohesive package. Designed using a sophisticated asymmetrical port technology, every subwoofer is built and tuned to the highest standards. Optimising the port airflow makes the sound consistent no matter the stress, while keeping a low amount of unwanted noise, distortion and extending the dynamics.



B15A rear view with built-in amplifier.

The B15A passive model speakOn connectors on the back and two additional speakON connectors located on the front increase wiring flexibility and ease of use cutting set-up time even in large configurations.

Key Features

-))) **Aerodynamic Port Design**
Reduces distortion and airflow noise.
-))) **Extended Connectivity**
Convenient multiple speakON sockets on passive models allows for easy set up ideal for live performances.
-))) **Octopus Feet**
Increased slip resistance and stability.
-))) **Flexibility**
Smaller, lighter, scalable.
Suitable for various configurations
-))) **Road-Ready**
Allows for optimal packing and easy transport on European Pallets.
-))) **Additional Accessories**
Dedicated dollyboards & raincovers

))) AUDIOTECHNIK

Contact

HEAD OFFICE

speaker trade Inh. Michael von Keitz
Neuenhofer Str. 42–44
42657 Solingen, Germany
+49 212 38226 - 10
info@se-audiotechnik.de
www.se-audiotechnik.de

Applications

- In- and Outdoor Concerts
- Touring
- Festivals
- Multi-Purpose Facilities
- Club
- Mobile DJ

Preliminary Specifications

	B15A	B15	B18	B21
Type	vented, powered	vented, passive	vented, passive	vented, passive
Transducer/ voice coil	15" / 3"	15" / 3"	18" / 4"	21" / 5"
Impedance	8 Ω	8 Ω	8 Ω	8 Ω
Coverage	Omni-directional	Omni-directional	Omni-directional	Omni-directional
Lowest cut-off freq. (-3 dB) (with/ without processing)	36 Hz/ 40 Hz	36 Hz/ 40 Hz	34 Hz/ 37 Hz	27 Hz/ 31 Hz
Lowest cut-off freq. (-10 dB) (with/ without processing)	33 Hz/ 33 Hz	33 Hz/ 33 Hz	26 Hz/ 28 Hz	21 Hz/ 25 Hz
Sensitivity SPL (1 m/ 1 W)	97.5 dB	97.5 dB	98.5 dB	99 dB
Max SPL* (Peak)	132 dB	132 dB	134 dB	137 dB
Power rating (Program/ RMS)	800 W/ 400 W	800 W/ 400 W	1600/ 800 W	3000 W/ 1500 W
Dimensions (W x H x D)	465 x 514 x 625 mm	465 x 514 x 625 mm	512 x 593 x 706 mm	585 x 700 x 910 mm
Weight	34 kg	30 kg	32 kg	38 kg
DSP	24-bit DSP, 48 kHz			

*Calculated values
All product specifications in this document are subject to change without prior notice.