

L 35

Specification Sheet

L 35 is an extremely compact passive two-way vented line array system with integrated crossover. It is equipped with two high-performance 3.5" neodymium drivers and a 1" compression driver.

Parameter	Value
Type	bass-reflex / closed-box
Frequency Response (-6dB)	90 - 19 kHz
Frequency Response (-3dB)	110 - 18 kHz
Nominal Impedance	16 Ω
High-Pass Frequency (min. 12 dB / oct.)	70 Hz (-6 dB) full range, 130 Hz (-6 dB) with L35 FS subwoofer
Sensitivity (dB SPL @ 1W/1m)	91 dB
Continuous Power Handling (AES)	100 W
Max. Continuous SPL	111 dB
Transducers	2 x 3.5" + 1 x 1" Compression driver
Dispersion (H x V)	100° x 20°
Controls	2-way Input Channel Switch (+1/-1 or +2/-2)
Audio Connectors	Neutrik Speakon® NL4 IN / LINK
Splay Angles	0°, 2.5°, 5°, 7.5°, 10°
Rigging	3-point rigging, 2x flat SE rigging pins with clip, 1x standard SE rigging pin
Cabinet	9-14mm plywood, black or white polyurea coating
Dimensions (W x H x D)	300 x 111 x 208 mm 312 x 133 x 230 mm with rigging
Weight	3,6 kg

*All product specifications in this document are subject to change without notice.