



AUDIOTECHNIK

L-Line

LA 804D

Specification Sheet

LA 804D is a dedicated L-Line system amplifier with built-in DSP, remote network control & Dante® inputs. Designed as the main workhorse for the L-Line array systems the amplifier can deliver either 4 x 1250 W or 2 x 2500W of power.

Parameter	Value
Type	Class D
Channels	4
Power Output	2 x 2500 W @ 2 Ohm / 2 x 2500 W @ 4 Ohm / 4 x 1250 W @ 2 Ohm / 4 x 800 W @ 4 Ohm
Minimum Load Impedance	2 Ω
Damping Factor	>100
Max. Line Input Level	+23 dBu
Input SNR	128 dB (A)
Output SNR (DSP + Amp)	112 dB (A)
Analog Line Input Impedance	Minimum 20 kΩ balanced
Controls	Control encoder with push-button, 4x channel MUTE, 4x channel SELECT, Power On
Indicators	4x4 Input sig. level LED, 4x4 Output sig. level LED, 4x4 Channel status (power, select, protect, mute), 1x Dante/1x LAN/1x Stand-By/1x Fault Status
Screen	3.5" TFT Color display with Touch Panel & 320 x RGB x 240 resolution
Analog Audio Connections	4x XLR Input / Link
Digital Audio Connections	2x AES/EBU (XLR)
Network Connectors	1x etherCON (LAN Control), 1x etherCON (Dante®)
Speaker Outputs	4x Speakon NL4
Dante®	Optional, Ultimo Chip, 4 Input Channel
DSP	32-bit SHARC CPU with floating point processing
DSP Sampling Frequency	48 / 96 kHz
DSP Features	Levels, Parametric EQ, Delay, Phase, RMS Limiter, Peak Limiter, FIR Filtering
Mains Input Voltage	85 - 265 VAC
Dimensions (W x H x D)	19" x 2 RU x 450mm

* max. SPL peak = Sensitivity + 10 x (log₁₀ RMS Power) + 12 dB crest factor

** All product specifications are subject to change without prior notice.

Dante® is registered trademark of Audinate Pty Ltd.

LA 804D Spec. Sheet v 1.0p